INCH-POUND

MIL-DTL-44484
28 MAY 1996

DETAIL SPECIFICATION

TRUSS ASSEMBLY, PLATFORM, TYPE V

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers 1 type of Truss Assembly used with the Type V Airdrop Platform.

1.2 Classification. The Trusses will be of the following sizes, and as specified (see 6.2).

Type I - 12 Foot	Type III - 20 Foot
Type II - 16 Foot	Type IV - 24 Foot

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:10Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are needed to meet the requirements specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents

2.2.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-3600 - Truss Assembly Installation, Airdrop

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SSCNC-MII, Natick, MA 01760-5017.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document,however,supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Materials. Materials and components shall be as specified on Drawing 11-1-3600 and all subsidiary drawings and parts lists and as specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:10Z
Check the source to verify that this is the current version before use.

3.3 Construction. Assemblies and components shall be constructed in accordance with the requirements of the Drawing 11-1-3600 and all subsidiary drawings and parts lists.

3.4 Workmanship. The end item shall conform to the quality of product established by this specification. All components and assemblies of the Truss Assembly shall be free of any rust or corrosion, dirt and other foreign matter. All surfaces shall be free from sharp edges or burrs. Components shall not be fractured, cracked, buckled, loose, dented, missing, malformed or misaligned.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.6 and 4.7. Any nonconformance shall be cause for the rejection of the first article.

4.3 Conformance Inspection. Conformance inspection shall include the examinations of 4.6 and 4.7.

4.4 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. Whenever nonconformance is noted, correction shall be made to affected items and process. Items that cannot be corrected shall be removed from the process. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.6 End item visual examination. The end items, defined as completely fabricated units of the Truss Assembly being purchased, shall be examined for the defects listed in table I. The lot size shall be expressed in units of Truss Assemblies. The sample unit shall be one Truss assembly. The finding of any defect shall be cause for the rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:10Z
Check the source to verify that this is the current version before use.

TABLE I End item visual defects

Examine	Defect
Final paint	Color not as specified Tacky (not dry to touch) Color separation Incomplete Blistered, peeling, flaking, or not adherent Embedded dirt or other foreign matter
Construction and workmanship	Any component missing, cracked, fractured, misaligned, or malformed (unless otherwise classified herein) Any component not assembled or joined as specified Any sharp edges, burrs, or metal slivers Any machine screw or rivet missing, loose or wrong type One rivet not properly set (i.e., head cracked, cocked, ringed or not flush) More than one rivet not properly set
Marking	Missing, incomplete, not legible, or otherwise not as specified

4.7 End item dimensional examination. Examination of the end items, defined as completely fabricated units of the Truss Assembly being purchased, shall be examined for conformance to the dimensions specified on the drawings. Any dimensions not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of Truss Assemblies. The sample unit shall be one Truss Assembly. The finding of any defect shall be cause for the rejection of the lot.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:10Z
Check the source to verify that this is the current version before use.

packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The intended use of the Trusses described in this document is to strengthen and link together several combinations of the Type V platform.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Type and size (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.3).
d. When first article is required (see 3.1, 4.2, and 6.3).
e Preservation and packing (see 5.1).
f. Palletization (see 5.2).
g. Marking,if required, see (5.3).

6.3 Subject term (key word) listing.

Airdrop System
Cargo loads
Modular assemblies
Parachute
Resupply
Platform

Custodians:
Army - GL
Navy - AS
Air Force - 99

Review Activities:
Army - AV

Preparing Activity:
Army -GL
(Project 1670-0827)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-DTL-44484 (GL)	1996 MAY 28

3. DOCUMENT TITLE

TRUSS ASSEMBLY, PLATFORM, TYPE IV

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER		
a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If applicable)*	7. DATE SUBMITTED *(YYMMDD)*

8. PREPARING ACTIVITY	
a. NAME U.S. Army Natick RD&E Center	b. TELEPHONE *(Include Area Code)* (1) Commercial: (508)233-4216 (2) AUTOVON/DSN: 256-4216
c. ADDRESS *(Include Zip Code)* Commander, U.S. Army Natick RD&E Center ATTN: SSCNC-UTE Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil - Downloaded: 2026-10-22T02:10Z
Check the source to verify that this is the current version before use.