MIL-B-60806C(MU)
6 May 1974
SUPERSEDING
MIL-B-60806B(MU)
25 May 1972

MILITARY SPECIFICATION

BOOSTER M125A1 ASSEMBLY LESS BOOSTER PELLET AND LEAD CUP CHARGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of booster for use with high explosive ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-331	- Fuze and Fuze Components Environmental and Performance Tests for
MIL-STD-1167	- Ammunition Data Card

DRAWINGS

Armament Command

F10520747	- Booster, M125A1, Assembly
F10520748	- Booster, M125A1, Sub-Assembly
A9277283	- Box, Packing Ammunition for Booster Assembly Details and Packing
LI-10520747	- Inspection Equipment List for Booster, M125A1

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

2.2 Other publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bids or request for proposal shall apply.

ANSI-B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, N.Y. 10018.)

3. REQUIREMENTS

3.1 General.-Materials, parts and assemblies shall comply with the requirements specified on applicable drawings, referenced standards and specifications except as provided in 6.1.

3.2 Environmental.

3.2.1 The booster shall comply with MIL-STD-331, Jolt, Test No. 101.

3.2.2 The booster shall comply with MIL-STD-331, Jumble, Test No. 102.

3.2.3 The booster shall comply with MIL-STD-331, Transportation-Vibration, Test No. 104.

3.3 Ballistics.-(See 6.3.2)

3.3.1 The booster shall not function prematurely. (See 6.3.1)

3.3.2 Target impact nonfunction distance.-The booster shall not detonate the round upon impact element function when fired in the 90MM Gun, Service Charge, (2400 feet per second, f.p.s.) on a target 160 plus 5 feet feet from the muzzle of the weapon.

3.3.3 Target impact function distance.-The booster shall detonate the round upon impact when fired in the 105MM Howitzer, Charge 7 (1550 f.p.s.) on a target 400 minus 5 feet from the muzzle of the weapon.

3.3.4 Ground or water impact.-The booster shall detonate the round upon impact when fired in the 155MM Howitzer, Charge 1 (680 f.p.s.) at an impact angle of 45 minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

3.4 Workmanship.-The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.4.1 Metal defects.-All components shall be free from cracks, splits, cold shuts, inclusions, porosity or any similar defects.

3.4.2 Surface finish.-The requirements for surface finish are as detailed on the applicable drawings.

3.4.3 Threads.-Threads shall be full and undamaged for the entire minimum length or depth as required by the applicable drawing.

3.4.4 Burr.-No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.4.5 Foreign matter.-No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter. The method and agents used in processing cleaning shall not adversely affect the finish or contaminate the parts.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.2 First article sample.

4.2.1 Initial production sample.-When required by the contract, the first units of production shall be submitted as an initial production sample. The samples shall consist of the following:

60 component parts as delineated in 4.2.2.
200 subassemblies as delineated in 4.2.3.
90 assemblies as delineated in 4.2.4 and 4.2.5.

The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.1.1 Examination and test.-After inspection by the contractor and provisional acceptance at source by the Government, 60 booster assemblies shall be forwarded to a designated proving ground as specified in the contract. Sixty (60) component parts, 200 subassemblies and 30 booster assemblies shall be inspected as provided herein at a Government laboratory or such other facility as specified in the contract.

4.2.2 Components.

4.2.2.1 Twenty (20) of each component shall be tested as in 4.3.2.1 (Hardness).

4.2.3 Subassemblies.

4.2.3.1 Fifty (50) of each subassembly shall be tested as in 4.3.2.3 and 4.3.2.5 (Static load).

4.2.3.1.1 Acceptance criteria.-Failure of any subassembly to comply with the requirements of the applicable drawing shall be cause for rejection of the initial production sample.

4.2.4 Booster assemblies.-Thirty (30) booster subassemblies assembled with test plug drawing 10555320 shall be subjected to the following MIL-STD tests:

Test	Quantity	Requirement	Test Method	Acceptance Criteria
Jolt	10	3.2.1	4.3.2.14.1	4.2.4.1.1
Jumble	10	3.2.2	4.3.2.14.2	4.2.4.1.1
Transportation-Vibration	10	3.2.3	4.3.2.14.3	4.2.4.1.2

4.2.4.1 Acceptance criteria.-Occurrence of any of the following in any booster shall be cause for rejection of the initial production sample.

4.2.4.1.1 Jolt and Jumble.

a. Rotor armed or partially armed. (See 6.2.1 and 6.2.2)
b. Failure of the booster to meet the non-arming requirements of the applicable drawing.
c. Broken, deformed or displaced parts which render the booster unsafe to handle or dangerous to use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.4.1.2 Transportation-Vibration.

a. Condition listed in 4.2.4.1.1.
b. Failure of the booster to meet the arming and non-arming requirements of the applicable drawing.

4.2.5 Ballistics.-Sixty (60) boosters, of the initial production sample, shall be subjected to the following ballistic test phases.

Phases	Quantity	Requirement	Test Method
Impact Nonfunction Distance	20	3.3.2	4.3.2.16.1
Impact Function Distance	20	3.3.3	4.3.2.16.2
Ground or Water Impact	20	3.3.4	4.3.2.16.3

4.2.5.1 Acceptance criteria.-The occurrence of the following shall be cause for rejection of the initial production sample:

a. A premature burst in any phase. (See 6.3.1)
b. Function of one or more rounds upon target impact in the Impact Nonfunction Phase.
c. Failure of more than one round total to function in the combined following phases:
(1) Target Impact Function Phase.
(2) Ground or Water Impact Phase.

4.3 Inspection provisions.

4.3.1 Submission of product.-The product shall be presented in accordance with MIL-STD-105.

4.3.1.1 Lot formation.-Each inspection lot of boosters shall be comprised of components (except explosive components) each produced by one manufacturer, by one process, in accordance with the same drawing and revision and specifications and revisions, as applicable, and assembled on one assembly line. Each explosive component within a lot of assembled boosters shall be limited to one manufacturer and one interfix number.

4.3.2 Inspection testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.2.1 Hardness (test samples destructive).-Twenty (20) samples from each lot of the following components shall be subjected to the hardness test. Failure of any component to comply with the requirements specified on the applicable drawing shall be cause for rejection of the lot.

Component	Drawing No.
Cup, Booster	C8595509
Wheel, Escapement	C8595539
Pin, Pallet	B11743965

4.3.2.2 Hardness (test method).-The test shall be performed using the value as specified on the applicable drawing. Samples shall be tested in an area which is solidly supported in order to obtain valid readings. The median value of three hardness readings taken on each sample unit shall be used as the individual reading. All tested samples shall be scrapped.

4.3.2.3 Static load (test samples destructive).-Fifty (50) samples from each lot of the following subassemblies shall be subjected to the static load test. Failure of any subassembly to comply with the requirement specified on the applicable drawing shall be cause for rejection of the lot of subassemblies, as applicable.

Pallet Assembly	D11743962
Wheel and Pinion Escapement Assembly	D11743967
No. 1 Gear and Pinion Assembly	D10523167

4.3.2.4 Static load (test method).-All units shall be tested to the value specified on the applicable drawing. All units subjected to the destructive load test shall be scrapped.

4.3.2.5 Load (test samples non-destructive).- Each setback mechanism assembly shall be subjected to the static load tests. Failure of any subassembly to comply with the load requirements on Drawing D10551357 shall be cause for rejection of the subassembly.

4.3.2.6 Load (test method).-All units shall be tested to the value specified on the applicable drawing. The load shall be applied gradually.

4.3.2.7 Arming - Booster assembly less setback mechanism assembly (non-destructive).-Each booster assembly less setback shall be subjected to the arming test. Failure of the rotor mechanism assembly to become locked in alignment with the flash hole, when spun at the Arming Spin Requirement on Drawing F10520748 shall be cause for rejection of the assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.2.8 Arming-Booster less setback mechanism assembly (test method).- The unarmed booster assembly prior to assembly of setback mechanism assembly shall be spun for a period of 10 seconds maximum in a counterclockwise direction when viewed from the top, at a constant r.p.m. as specified on drawing F10520748. After the test has been performed, the rotor shall be returned to the unarmed position (see 6.2.1 and 6.2.3).

4.3.2.9 Spin test - Setback mechanism assembly restricting movement of rotor (non-destructive).- Each booster assembly shall be subjected to this Spin Test. Failure of setback mechanism assembly to restrict movement of the rotor with both spring loaded blocks in the fully open position, shall be cause for rejection of that assembly.

4.3.2.10 Spin test (test method).-The unarmed booster (see 6.2.3) shall be spun for a period of 3 seconds minimum in a counterclockwise direction when viewed from the top at a constant 3,000 rpm + 50 rpm.

4.3.2.11 Non-arming.-Each booster assembly shall be subjected to a non-arming test. Failure of the rotor to remain locked in the unarmed position by either or both spring loaded blocks, when subjected to the Non-Arm Spin Requirement on Drawing F10520748 shall be cause for rejection of the assembly.

4.3.2.12 Non-arming (test method).-The unarmed booster (see 6.2.3) shall be spun for a period of 3 seconds minimum in a counterclockwise direction when viewed from the top, at a constant r.p.m. as specified on Drawing F10520748. The non-arming test shall be the last spin test to which the booster is subjected prior to packing.

4.3.2.13 Environmental tests (test samples destructive).-Thirty (30) booster subassemblies assembled with test plug, drawing 10555320 shall be subjected to the following MIL-STD tests.

Test	Quantity	Requirement	Test Method	Acceptance Criteria
Jolt	10	3.2.1	4.3.2.14.1	4.3.2.13.2
Jumble	10	3.2.2	4.3.2.14.2	4.3.2.13.2
Transportation-Vibration	10	3.2.3	4.3.2.14.3	4.3.2.13.3

4.3.2.13.1 Acceptance criteria.-Occurrence of any of the following in any booster shall be cause for rejection of the production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.2.13.2 Jolt and Jumble.-

a. Rotor armed or partially armed (see 6.2.1 and 6.2.2)

b. Broken, deformed or displaced parts which render the booster unsafe to handle or dangerous to use.

c. Failure of the booster to meet the non-arming requirements of the applicable drawing.

4.3.2.13.3 Transportation-Vibration.-

a. Conditions listed in 4.3.2.13.2

b. Failure of the booster to meet the arming and nonarming requirements of the applicable drawing.

4.3.2.14 Environmental test procedures.-The component parts of the booster, which have been disassembled and inspected following tests, shall be scrapped.

4.3.2.14.1 Jolt (test method).-The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 101. The booster shall be disassembled and inspected as follows:

a. Remove test plug check position of rotor
b. Subject the booster to the non-arming requirements of the applicable drawing

c. Remove top plate

d. Check for broken, deformed or displaced parts (that would render the booster unsafe to handle and dangerous to use.)

4.3.2.14.2 Jumble (test method).- The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 102. The booster shall be disassembled and inspected as follows:

a. Conditions listed in 4.3.2.14.1.

4.3.2.14.3 Transportation-Vibration (test method).-The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 104.

a. Remove test plug check position of rotor.
   (1) Spin for booster non-arming requirement.
   (2) Remove setback mechanism assembly
   (3) Spin for booster arming requirements

b. Conditions listed in 4.3.2.14.1 (c and d).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.2.15 Ballistics test samples (destructive).-Sixty (60) boosters from each lot shall be subjected to the following ballistic test phases:

Phases	Quantity	Requirement	Test Method
Impact Nonfunction Distance	20	3.3.2	4.3.2.16.1
*Impact Function Distance	20	3.3.3	4.3.2.16.2
Ground or Water Impact	20	3.3.4	4.3.2.16.3

* When ten (10) consecutive lots are fired with no duds occurring in this phase, the sample quantity will be reduced to ten (10) units in lieu of twenty (20). Acceptance criteria remains the same. Whenever a dud occurs within a sample quantity of ten (10), the sample quantity will revert to twenty (20) for subsequent lots until the above criteria for reduction is again statified.

4.3.2.15.1 Acceptance criteria.-The occurrence of the following shall be cause for rejection of the lot the ballistic sample represents:

a. A premature burst in any phase (see 6.3.1).

b. Function of one or more rounds upon target impact in the Impact Nonfunction Phase.

c. Failure of more than one round total to function in the combined following phases:
   (1) Target Impact Function Phase.
   (2) Ground or Water Impact Phase.

4.3.2.16 Ballistics (test method).-The booster assembly, Drawing F10520747, shall be assembled to Fuze, PD, M48A3 then assembled to a suitable projectile and fired as follows:

4.3.2.16.1 Impact nonfunction distance phase.-The test sample shall be fired as specified in 3.3.2 against a suitably supported one inch plywood screen of adequate size under the conditions delineated in 4.2.5 or 4.3.2.15 as appropriate. Observation of impact element function is required.

4.3.2.16.2 Impact function distance phase.-The test sample shall be fired as specified in 3.3.3 against a suitably supported one inch plywood screen of adequate size under conditions delineated in 4.2.5 or 4.3.2.15 as appropriate. Report of subsequent functioning, if a dud on the screen is observed, is required.

4.3.2.16.3 Ground or water impact phase.-The test sample shall be fired as specified in 3.3.4 under the conditions as delineated in 4.2.5 or 4.3.2.15 as appropriate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.2.16.4 Inspection equipment.-The examination and tests shall be made using equipment listed in LI-10520747. Equipment design shall be in accordance with the code designation on the applicable IEL.

4.3.3 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a single defect basis in accordance with MIL-STD-105. For the classification of defects contained herein, the AQL given shall be used. All nonconforming materials shall be rejected. The roughness comparison specimens prescribed by ANSI-B46.1 shall be used as a basis for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burrs and foreign matter.

4.3.3.1 Cup, Booster, Drawing B8595509, covering a detail of Drawing F10520747.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Inside radius, incorrect	Gage
102. Outside radius, incorrect	Gage
103. Chamfer, incorrect	Gage
104. Inside depth, improper	Gage
105. Pitch diameter of thread, improper	Gage
106. Minor diameter of thread exceeds max.	Gage
107. Outside diameter, improper	Gage
108. Effective length of thread, less than min.	Gage
109. Cut, score, or gouge on inside wall	Visual
110. Foreign matter	Visual

4.3.3.2 Cup, Closing, Drawing B8595508, covering a detail of Drawing F10520747.

CRITICAL	
1. Split, cut or crack	Visual
MAJOR AQL = 1.0%	
101. Length under flange, incorrect	Gage
102. Outside diameter exceeds max.	Gage
103. Thickness of base	Gage
104. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.3.3 Body, Drawing D11744006, covering a detail of Drawing F10520747.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Overall length exceeds max.	Gage
102. Diameter of closing cup hole improper	Gage
103. Pitch diameter of large external thread	Gage
104. Major diameter of large external thread	Gage
105. Pitch diameter of small external thread	Gage
106. Major diameter of small external thread	Gage
107. Pitch diameter of internal thread	Gage
108. Minor diameter of internal thread	Gage
109. Length from bottom surface to top of undercut shoulder, improper	Gage
110. Staking hole, (located on large external thread) missing	Visual
111. Metal defective	Visual
112. Foreign matter	Visual

4.3.3.4 Pallet Assembly Drawing D11743962 covering a detail of Drawing F10520747.

CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Perpendicularity of pallet, improper	Gage
102. Broken, deformed, or bent assembly	Visual
103. Pallet improperly seated (see 6.4)	Visual
104. Metal defective	Visual

4.3.3.5 Wheel and Pinion Escapement Drawing D11743967 covering a detail of Drawing F10520747.

CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.3.5 (Cont'd)

Defect	Method of Inspection
MAJOR AQL = 1.0%	
101. Circular runout of escape wheel and pinion, incorrect	Gage
102. Perpendicularity of escape wheel and pinion, incorrect	Gage
103. Broken or missing teeth, deformed or bent assembly	Visual
104. Escape wheel not seated properly (see 6.4)	Visual
105. Metal defective	Visual

4.3.3.6 No. 1 Gear and Pinion Assembly, Drawing D10523167, covering a detail of Drawing F10520747.

CRITICAL

None defined

MAJOR AQL - 1.0%	
101. Circular runout of gear and pinion, incorrect	Gage
102. Perpendicularity of gear and pinion, incorrect	Gage
103. Broken or missing teeth, deformed or bent assembly	Visual
104. Gear not seated properly (see 6.4)	Visual
105. Metal defective	Visual

4.3.3.7 Rotor Assembly, Drawing D10551356, covering a detail of Drawing F10520747.

CRITICAL

None defined

MAJOR AQL = 1.0%	
101. Circular runout of rotor assembly, incorrect	Gage
102. Perpendicularity of rotor assembly, incorrect	Gage
103. Broken or missing teeth, improper assembly	Visual
104. Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.3.8 Escape Wheel, Drawing C8595539, covering a detail of Drawing F10520747.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Escape wheel contour, incorrect	Gage
102. Metal defective	Visual

4.3.3.9 Setback Mechanism Assembly, Drawing D10551357, covering a detail of Drawing F10520747.

CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Crimp missing or inadequate	Gage
102. Thread damaged or not full	Visual

4.3.3.10 Booster M125A1 Subassembly, Drawing F10520748, covering a detail of Drawing F10520747.

CRITICAL	
None defined	
MAJOR AQL = .40%	
101. Disassembly torque of body screws	Gage
102. Length from base of body to top plate including all protrusions exceeds max.	Gage
103. Insecure, improper or incomplete assembly	Visual/Manual
104. Staking missing or inadequate	Visual
105. Metal defective	Visual
106. Threads damaged or not full	Visual
107. Burrs	Visual
108. Foreign matter	Visual
109. Nomeclature missing, incorrect, or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.3.11 Box, Packing, Drawing A9277283.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Board broken	Visual
102. Hardware missing, broken or illegible	Visual/Manual
103. Contents exposed	Visual
104. FSC symbol misleading, incorrect or illegible	Visual
105. Strapping missing, broken or loose	Visual/Manual
MINOR AQL = 2.5%	
201. Hardware improperly applied or engaged	Visual/Manual
202. Contents move when shaken	Manual
203. Car seal missing, unsealed or improperly positioned	Visual/Manual
204. Marking misleading, incorrect or illegible	Visual/Manual

4.3.3.12 Process control audit.-Periodic unscheduled monitoring shall be conducted for the process operations on the following assemblies to determine compliance with the requirements of the applicable drawings.

a. D.A.M. Movement Assembly, Drawing F10523008

(1) Application of lubricant
(2) Staking operation on movement plate screws

b. Booster, M125A1 Subassembly, Drawing F10520748

(1) Staking operation on assembly screws
(2) Staking operation on setback screw

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, labeling and marking.-Packaging, packing, labeling and marking shall be as specified on Drawing A9277283 with the following exception. Closing cups, Drawing B8595508 and booster cups, Drawing B8595509 may be shipped separately in accordance with best commercial practices as an alternate procedure.

5.2 Data cards.-Data card information shall be as specified in MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Dimensions

6.1.1 Compliance with tests (proving ground, ballistic performance and shop) required by the specifications and drawings is mandatory. The contractor will not assume, nor does the Government guarantee, that all possible combinations permitted by the tolerance limits of the specifications and drawings will consistently satisfy the test requirements. Therefore, the manufacturer is obligated to choose those combinations of tolerances and fits within the limits of the specifications and drawings that best suit his process needs and still satisfy the testing requirements.

6.1.2 Dimensions which are specifically referred to in the classification of defects, as listed in Section 4, are mandatory. Pertaining to other dimensions, it is recognized that current mass production methods may occasionally produce parts which are not in full compliance with all dimensional requirements, but which may provide adequate booster performance. Therefore, the contractor, at his own risk, may utilize these parts provided there is no adverse effect on booster functionability. This relaxation of requirements applies to "after the fact" deviations only, to dimensions only, and does not constitute authority to establish new dimensions or to relax efforts to achieve the required sizes within the specified limits. The procedure for accomplishing dimensional changes is available under the established engineering change system. Nothing above is to be construed as relieving the contractor of any responsibility in connection with performance of the booster.

6.1.3 The contractor shall maintain records showing deviations from dimensional requirements, the extent of such deviations, the amount of material involved, and the date the material is introduced into the assembly line. Copies of these records shall be forwarded to the agency assigned custody of the technical data on a monthly basis.

6.2 Armed/Unarmed boosters.

6.2.1 Armed.-Rotor is locked by the spring loaded detent pin in the position in which the detonator is fully visible through the flash hole.

6.2.2 Partially armed.-One or both spring-loaded safety blocks not fully seated in the rotor slots and locking the rotor.

6.2.3 Unarmed.-Rotor locked by both spring loaded safety blocks with the detonator not at all visible through the flash hole.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

6.3 Ballistic parameters.

6.3.1 Premature burst.-Shall be defined as the occurrence of any of the following:

a. If the round detonates in the bore of the weapon.
b. If the round detonates in flight within 160 feet from the muzzle of the weapon.

6.3.2 Muzzle velocities mentioned in this specification are nominal only and are given for the guidance of the proving ground in selecting appropriate weapons and rounds.

6.4 Adequate seating.-The gear or pallet shall be seated on at least one portion of the pinion or shaft shoulder and be within the drawing perpendicularity requirements.

6.5 Ordering data.-Procurement documents should specify the title, number and date of this specification.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1390-A158

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.