MILITARY SPECIFICATION

CASE, OPTICAL BORE SIGHT: 8587581

1. SCOPE

1.1 This specification covers performance requirements, quality assurance provisions, and packaging data for a carrying case which provides a means of stowing and transporting a fire control instrument (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel; Packaging of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army Frankford Arsenal

F8587581	Case, Optical Bore Sight: 8587581

PACKAGING DATA SHEET

MIL-P-14232/P8587581	Packaging of Case, Optical Bore Sight: 8587581

(Copies of specifications, standards, drawings, and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1270

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials.- The materials shall be in accordance with the drawings, material specifications, and general specifications forming a part of this specification.

3.2 Fabrication.- The case shall be manufactured in accordance with Drawing F8587581 and all drawings pertaining thereto.

3.2.1 Initial production sample.- Requirements for the submission of an initial production sample by the contractor shall be as specified in the contract.

3.3 General specification.- The contractor shall be responsible for adherence to the following requirements of MIL-F-13926:

(a) Dimensions and tolerances
(b) Inorganic protective surface finishes
(c) Part identification and marking
(d) Workmanship

3.4 Environmental service conditions.

3.4.1 Storage temperatures.- The case shall show no evidence of physical failure after having been thermally stabilized at ambient temperatures of -80° and +160° Fahrenheit (F).

3.4.2 Standard ambient temperature.- Subsequent to the requirements of 3.4.1, the case shall meet the requirements of 3.4.4 and 3.4.5 and all performance requirements of this specification at a standard ambient temperature between +60° and +90°F.

3.4.3 Extreme operating temperatures.- The case shall meet all performance requirements of this specification while thermally stabilized at ambient temperatures of -65° and +150°F.

3.4.4 Shock.- The locked case, fitted with a dummy load equivalent in weight and distribution to the intended contents (see 6.1), shall withstand two drops onto a concrete floor from a height of 36 inches at the standard ambient temperature of 3.4.2. The shocks shall not unlatch the lid from the body. Subsequent to the two drops, there shall be no evidence of openings along seams or welds, splitting or cracking of the case material, or any other damage that will impair the functionability of the case. The case shall then meet the requirements of 3.4.5 and 3.5.

3.4.5 Water immersion.- This requirement shall be met with the case thermally stabilized at the standard ambient temperature of 3.4.2. Subsequent to immersion of the locked case in water for 3 minutes ± 15 seconds, with the top of the lid being at least 3 inches below the surface of the water, the interior of the case shall show no evidence of leakage or moisture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

3.5 Performance.

3.5.1 Fastening devices.- The spring-loaded catches, when engaged to the strikes on the lid, shall encounter compression resistance when the catch levers are a minimum of 45 degrees from their fully closed position. With the levers fully closed, the catches shall lock the lid securely to the body and shall show no evidence of looseness.

3.5.2 Lid.- The lid shall fit true and even and shall open and close easily without restriction or binding.

3.5.3 Molded inserts.- The molded inserts shall show no visible evidence of damage, such as cracking or deterioration, and shall be securely cemented in place.

3.5.4 Gasket.- The gasket shall be securely cemented in position and shall show no evidence of damage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 Initial production test.- Initial production test samples shall be submitted in accordance with contract requirements. Unless otherwise specified in the contract, samples shall be the first two production units and shall have been manufactured using the same materials, processes, and procedures as will be used in regular production. Initial production testing shall be in accordance with 4.3, 4.4, and 4.6 and shall be witnessed by the Government representative for all examinations and tests. The Government reserves the right to conduct any or all examinations or tests as may be deemed necessary.

4.2.1 Initial production sample failure.- Should one unit fail to meet the initial production testing specified in 4.2, the contractor shall cease those operations which are causing the rejection and make the necessary corrections thereto. When corrections in the process or controls have been made, two additional (new) production models shall be submitted in accordance with 4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.3 Inspection provisions.

4.3.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, lot formation, and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.- Components and subassemblies shall be inspected in accordance with the inspection provisions contained in MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Tables I, II, and III herein. Examinations and tests for packaging, packing, and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot.

TABLE I - CLASSIFICATION OF DEFECTS

CLASS	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
CRITICAL: NONE			
MAJOR: AQL 2.5% Defective			
101.	Fastening devices	3.5.1	4.6.2.1
102.	Lid	3.5.2	4.6.2.2
103.	Molded inserts	3.5.3	4.6.2.3
104.	Gasket	3.5.4	4.6.2.4
MINOR: NONE			

4.3.3 Acceptance and rejection.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling.

4.4.1 General.- One case shall be selected at random as a special sampling from each 100 produced. The sample shall meet the requirements and tests in Table II.

TABLE II

	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
301.	Fabrication	3.2	Applicable drawings - visual
302.	General specification	3.3	MIL-F-13926 - visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.4.2 Environmental.- Three cases shall be selected at random as samples from each 50 produced, or from each month's production, whichever occurs first. Each sample shall have met the requirements and tests in Table I and shall then meet the requirements and tests in Table III.

TABLE III

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
303. Storage temperatures	3.4.1	4.6.1.1
304. Extreme operating temperatures	3.4.3	4.6.1.2
305. Shock	3.4.4	4.6.1.3
306. Water immersion	3.4.5	4.6.1.4

4.4.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the product shall be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.3.3).

4.5 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design.- Unless otherwise specified in the contract, all inspection equipment specified by the contract shall be supplied by the contractor in accordance with 4.5.

4.5.2.2 Contractor design.- The contractor shall design and supply inspection equipment compatible with the "Test methods and procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.6 Test methods and procedures.

4.6.1 Environmental.

4.6.1.1 Storage temperatures.- The case shall be exposed to temperatures specified in 3.4.1 in accordance with Procedure II of MIL-F-13926. After exposure, the case shall show no evidence of damage and shall meet the requirements of 3.4.1.

4.6.1.2 Extreme operating temperatures.- The case shall be exposed to the temperatures specified in 3.4.3 in accordance with Procedure I of MIL-F-13926. While exposed to these temperatures the case shall meet the requirements of 3.5.

4.6.1.3 Shock.- The locked case, fitted with a dummy load as specified in 3.4.4, shall be dropped twice onto a concrete floor from a height of 36 inches. One drop shall be on the edge of the lid; the second drop shall be on the bottom edge of the case. Subsequent to the two drops, the case shall meet the requirements specified in 3.4.4.

4.6.1.4 Water immersion.- This test shall be performed in accordance with Procedure I of the water immersion test specified in MIL-F-13926, except the depth and time of immersion shall be as specified in 3.4.5.

4.6.2 Performance.

4.6.2.1 Fastening devices.- Fastening devices shall function without interference and shall lock the lid to the body as specified in 3.5.1.

4.6.2.2 Lid.- The lid shall open and close without restriction and shall meet the requirements specified in 3.5.2.

4.6.2.3 Molded inserts.- A visual and tactile examination shall be performed to determine that the inserts are free of damage and are securely cemented to the lid and body of the case as specified in 3.5.3.

4.6.2.4 Gasket.- A visual and tactile examination shall be performed to determine that the gasket is undamaged and securely cemented in position as specified in 3.5.4.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking.- Packaging, packing, and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P8587581. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The case covered by this specification is intended to house and transport Optical Bore Sight: 8587577.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of preservation.
(c) Applicable stock number.
(d) Applicable packaging data sheet (see 5.1).
(e) Order of document precedence.
(f) Requirements for submission of initial production sample.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1270-A030Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.