MIL-D-80039B
8 May 1984
SUPERSEDING
MIL-D-80039A
21 April 1971

MILITARY SPECIFICATION

DRILLING MACHINES, UPRIGHT, BENCH TYPE, BOX COLUMN, SLIDING HEAD, ELECTRIC MOTOR DRIVEN, HAND FEED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers electric motor driven, box column, manual feed, sliding head, single and multiple spindle, bench type drilling machines with accessories as described herein.

1.2 Classification. This specification covers drilling machines of the following styles and sizes, as specified (see 6.2.1):

Style A - One spindle
Style B - Two spindles
Style C - Three spindles
Style D - Four spindles
Style E - Five spindles
Style F - Six spindles

Size	Drill Capacity (Inches)	Swing (Inches)
12	5/16 (7.93mm)	12
14	3/8 (9.52mm)	14
16	1/2 (12.70mm)	16
18	3/4 (19.05 mm)	18
20	1 (25.44mm)	20
24	1-1/4 (31.75mm)	24

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-TES, Memphis, Tennessee 38114, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3413

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 79 - (ANSI C113.1) Electrical Standard for Metalworking Machine Tools and Plastics Machinery

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issue of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI/B5.10 - Machine Tapers, Self-holding and Steel Taper Series
ANSI/B5.1 - T-Slots, Their Bolts, Nuts, Tongues, and Cutters
ANSI/IEEE268 - Metric Practice
ANSI/B11.8 - Drilling, Milling, and Boring Machine - Safety Requirements for the Construction, Care and Use

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D-3951 - Commercial Packaging, Standard Practice for.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First Article. When specified, (see 6.2.1) a sample shall be subjected to first article inspection (see 4.3 and 6.2).

3.2 Design. The machine shall be new and one of the manufacturer's current models capable of drilling workpieces within its specified capacity in accordance with the requirements herein. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the machine. When only one system of measurements is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes and capacities are given in U.S. units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in ANSI/IEEE 268.

3.2.1.1 Measuring and indicating device calibrations. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used to graduate measuring and indicating devices such as scales, depth stops, carriage stops, dial indicators, pressure gauges, temperature indicators, and other similar devices. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the machine shall be graduated in the same system.

3.2.1.1.1 Dual calibrations. When specified (see 6.2.1), measuring and indicating devices shall be graduated in both the US and the SI System of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

Measurements. When a dual US and SI system is furnished, both feed dials shall have independent zero adjustments and both dials shall be calibrated in such a manner that the last dial graduation progresses into and is continuous with the first dial graduation as the dial is rotated through the zero position.

3.2.2 Reclaimed materials. The machine may contain reclaimed materials provided such materials will not jeopardize the machine's intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the machine.

3.2.3 Energy efficiency. The drilling machine and all its applicable components that directly consume energy in normal operation shall be designed and constructed for the highest degree of energy efficiency as governed by the latest developments available within the Industry.

3.2.4 Controls. All operating controls shall be located convenient to the operator at his normal work station.

3.2.5 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the machine that present safety hazards. The safety devices shall not interfere with operation of the machine. The safety devices shall prevent unintentional contact with the guarded part and shall be removable to facilitate inspection, maintenance and repair of the parts. All machine parts, components, mechanisms, and assemblies furnished on the machine, whether or not specifically required herein, shall comply with all of the requirements of OSHA 2206 that are applicable to the machine itself. In addition, the machine shall comply with all requirements of the OSHA and ANSI B11.8 that are designated therein as the responsibility of the machine manufacturer. In the event of conflict between the requirements of OSHA and ANSI Standards, the requirements of OSHA shall apply. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.4).

3.2.6 Environmental protection. The machine shall be designed and constructed such that, under the operating, service, transportation and storage conditions described herein, the machine shall not emit materials hazardous to the ecological system as prescribed by federal, state or local statutes in effect at the point of installation.

3.2.7 Lubrication. An automatic lubricating system shall be provided for all parts and mechanisms requiring a continuous flow of lubricating oil. Means for determining oil level in each reservoir shall be by oil level sight gage, a low oil level warning light or a similar device. Mechanisms requiring periodic manual lubrication shall be readily accessible for servicing. Each recirculating system shall include a cleanable or replaceable filter.

3.2.8 Interchangeability. To provide for replacement of worn or damaged parts, all parts shall be manufactured to definite dimensions and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

tolerances that will permit installation of replacement parts without modification of the part or machine.

3.3 Construction. The drilling machine shall be constructed of parts which are new, without defects and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects such as scale and mismatching. Processes such as welding, peening, plugging, or filling with solders or pastes shall not be used on castings or forgings to reclaim any defective components for use on the machine. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these processes shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), painting shall be in accordance with the manufacturer's commercial practice.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Dials. All dials that indicate stock removal or tool movement shall be graduated in increments not larger than 0.001 inch. Dial diameters shall be such that graduations may be read from the normal operating position. Dials shall be permanently and legibly engraved or etched on a nonglare background.

3.3.8 Gears. All gears shall be constructed of a material suitable for their application. Gears shall be applied in a manner to preclude either premature damage, wear or failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

3.4 Components.

3.4.1 Coolant system. The coolant system shall include a sump or reservoir, a power driven pump and all necessary piping. The sump or reservoir shall have sufficient capacity to permit full flow of coolant. The system shall have means for draining and cleaning and shall include a baffle or a strainer which is easily removable for cleaning. Means shall be provided to permit the operator to direct and control the amount of coolant.

3.4.2 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to ANSI/NFPA-79. Each machine shall draw all of its electrical power from a single 115/230 volt, 1 phase, 60 Hz circuit. Each machine shall have a fused safety disconnect switch or circuit breaker. The machine shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when it is installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in ANSI/NFPA-79 for the disconnect fuse rating.

3.4.3 Motors. Motors shall be rated for 30 minutes duty and shall have ball or roller bearings of the sealed and permanently lubricated type. Unless otherwise specified (see 6.2.1), each motor enclosure shall meet the requirements for a dripproof enclosure.

3.4.4 Base. The base shall be a casting of iron or iron alloy which is rib-braced. The base casting shall form a foundation for the entire drilling machine. Each base shall be of the trough-type having an accurately ground working surface. Working surface shall not deviate from a plane surface by more than 0.002 inch. A coolant trough shall be provided which shall extend completely around the periphery of the work surface with provisions for draining. When specified (see 6.2.1), two T-slots shall be provided. Machined T-slots shall be in accordance with ANSI B5.1. A minimum of three mounting pads shall be provided for securing the machine to a worktable.

3.4.5 Column. The column shall be a casting of box construction, arranged to support the drill head assembly. The column shall have machined and scraped guideways for vertical adjustment of the sliding head. The column shall be secured to the base.

3.4.6 Drill head assembly. The drill head assembly shall be mounted on or be integral with the column and shall consist of the drill head, quill and spindle assembly, power transmission, sliding head, and motor.

3.4.7 Drill head. The drill head shall be designed to house the power transmission assembly. When the drill head is not an integral part of the column, it shall be held securely in position on the column by clamps or other positive means.

3.4.8 Quill and spindle assembly. The quill shall be fitted to the head. Manual drill feeds shall be accomplished by means of a spoke type

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

feed lever through a rack and pinion. A spring assembly or counterweight apparatus shall retract the quill and spindle assembly when the handwheel is released. The spring assembly shall be adjustable for tension. Quill guides shall be provided to support and maintain quill alignment through the full travel of the quill. Not less than two sealed-for-life type bearings shall be provided to suspend the spindle in the quill. The driven end of the spindle shall be multi-splined unless otherwise specified (see 6.2.1). Unless otherwise specified (see 6.2.1), the drill end of the spindle shall have an accurately machined ANSI tapered socket for receiving the tapered shank of the drill, drill chuck, or other attachments. All tapers shall conform to ANSI B5.10. The knock-out slot shall be well rounded to prevent damage from the use of drifts.

3.4.9 Power transmission assembly. The drilling machine shall be powered by an electric motor, vertically mounted on the column at the rear of the drill head. Drive shall be through a belt and pulley arrangement, belt and gears, all gear drive, or direct motor spindle drive. The assembly shall be constructed to provide infinitely variable speeds throughout the speed range in use. Spindle and motor drive pulleys shall be dynamically balanced. Means for adjusting belt tension shall be provided.

3.4.10 Power feed. When specified (see 6.2.1), power feed shall be provided. The number of feeds and their corresponding feed ranges shall be as specified.

3.4.11 Sliding head. The sliding head shall be mounted on the column and shall serve as a support for the quill and spindle assembly. The head shall be vertically adjustable. The ways of the head shall accurately fit the ways of the column and shall be provided with means for clamping the head to the column ways. Means shall be provided for adjustment to take up way wear. The head shall be provided with a counterbalance. Counterbalance shall be adjustable.

3.4.12 Depth stop. Each machine shall be provided with a depth stop equipped with a positive locking device. The depth stop shall have an indicating scale marked in increments of not more than 1/16 of an inch.

3.4.13 Illuminating lamp. An illuminating lamp shall be provided. The lamp shall have a protective shield and shall be attached to the machine in such a manner as to allow the light to swing over the tool and workpiece.

3.4.14 Multiple spindle machines. Each multiple spindle machine shall comprise a plurality of single spindle machines, as specified herein, mounted on a common base. Each spindle shall operate as an independent unit and each unit shall be interchangeable with each of the other units. The spindle center distance shall be as designated and the base size required in table I shall be adjusted accordingly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

3.4.15 Adjusting column. Adjusting type columns shall be furnished. The adjusting mechanism shall allow the operator to change the center to center distance of the spindles on the machine base. Means for clamping after adjustment shall be provided.

3.5 Size and capacity. Unless otherwise specified (see 6.2.1), the size and characteristics of the machine shall be not less than those specified in table I for the machine size specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

TABLE I

REQUIREMENTS

MACHINE CHARACTERISTIC	Size 12	Size 14	Size 16	Size 18	Size 20	Size 24
Capacity (in cast iron), inches	5/16	3/8	1/2	3/4	1	1-1/4
Centerline of spindle to column face, inches	6	7	8	9	10	12
Swing, inches	12	14	16	18	20	24
Spindle, travel, inches	3	3	4	5	5	5-3/4
Spindle nose to base, maximum, inches	9-1/2	12	11	11	11	11
Spindle taper hole, ANSI	1	1	2	2	3	3
Spindle speeds, number	2	4	5	5	5	6
Spindle speed range, RPM	1200 to 1600	600 to 3680	390 to 3100	400 to 4000	400 to 4000	390 to 3100
Spindle diameter, inches	1/2	19/32	3/4	3/4	7/8	7/8
Quill diameter, inches	1-3/4	1-3/4	2	2-1/4	2-3/8	2-3/8
Height overall, inches	35	39	45	48	52	53
Motor horsepower	1/2	1/2	3/4	3/4	1	1
Sliding head traverse	4	4	4	5	5	5
Base, working surface, inches, length X width + or - 1 inch						
Style A	20 x 15	14 x 12	14 x 13	14 x 14	24 x 22	24 x 24
B	28 x 15	23 x 12	22 x 13	26 x 14	24 x 22	42 x 24
C	36 x 15	33 x 12	30 x 13	38 x 14	32 x 22	60 x 24
D	44 x 15	43 x 12	38 x 13	50 x 14	40 x 22	78 x 24
E	56 x 15	63 x 12	46 x 13	62 x 14	48 x 22	96 x 24
F	74 x 15	74 x 12	54 x 13	74 x 14	56 x 22	114 x 24

NOTE: Machine size and capacities shall be not less than the stated requirements of the size ordered nor greater than the requirements of the next larger size shown in above table. When the largest size and capacity machine shown in above table is ordered, the size and capacity of the machine offered shall not exceed the stated requirements by more than 10 percent. When a range is shown, the required performance is from the state minimum or less to the stated maximum or greater.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

[redacted]

TIR at 12 inches from face	.0015 inch
Worktable surface runout TIR in 360° rotation of table with indicator at 6 inches radius	.0015 inch
Quill travel square to table spindle incline outward from column in 12 inches	.002 inch

3.6 Performance. The drilling machine shall be capable of performing the test requirements of 4.6.3.

3.7 Alignment tolerances. Each machine shall meet the alignment accuracies of table II.

3.8 Standard equipment. Unless otherwise specified one set of hand tools, normally furnished by the manufacturer, shall be furnished. Additional equipment required shall be furnished as specified and fully described (see 6.2.1).

3.9 Optional equipment. Optional equipment shall be furnished as specified and shall be fully described (see 6.2.1).

3.10 Additional requirements. Performance features required in addition to, or in lieu of, the requirements herein shall be as specified (see 6.2.1).

3.11 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means of mounting. The chart or plate shall contain the following information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

Points of lubricant application
Servicing interval
Type of lubricant
Viscosity

3.12 Nameplate. Unless otherwise specified (see 6.2.1), a nameplate shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.13 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.14 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article inspection is required, it shall be applied to the first article submitted in accordance

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests in 4.6. Failure of the item to pass the first article tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1) quality conformance inspection shall consist of at least the examination in 4.5 and the tests in 4.6.1. Failure of the item to pass the examination or tests shall be cause for rejection.

4.5 Examination. The machine and equipment shall be examined to determine compliance with the requirements of 3.2 through 3.5 and 3.6 through 3.14.

4.6 TESTS

4.6.1 Operational test. The machine shall be operated at no load for not less than 30 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be verified during the trial period.

4.6.2 Alignment accuracy tests. Each machine shall be tested to determine that it complies with the alignment accuracy requirements of table II (see 3.7).

4.6.3 Performance tests. Each machine shall drill fifteen (15) through holes, of the maximum rated size for the machine, in 1 inch thick soft cast iron. Drilling time shall be not more than twenty minutes, total elapsed time (center drilling time not included). There shall be no evidence of overloading, overheating, excessive vibration, or deformation of any part of the machine during or after drilling operation. When Styles B through F machine are required, each spindle shall be tested in the above manner.

4.7 Packaging inspection. Packaging shall be inspected to determine compliance with the requirements of Section 5.

5. PACKAGING

5.1 Packaging, packing and marking. Unless otherwise specified, packaging, packing, and marking shall be in accordance with ASTM-D 3951. When specified (see 6.2.1), level A packaging, level A or level B packing and special marking shall be accomplished in accordance with MIL-M-18058.

6. NOTES

6.1 Intended use. The drilling machines covered by this specification are intended for use in production shops where wide varieties of drilling operations are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Type, class and size required, etc. (see 1.2).

c. When first article is required for inspection and approval (See 3.1).

d. If machine is required to be configured in a specific measurement system (US or SI), state required system (see 3.2.1).

e. If measuring and indicating devices are required to be graduated in a specific measurement system (US or SI), state required system (see 3.2.1.1).

f. Dual calibrations (US and SI), if required (see 3.2.1.1.1).

g. Additional safety and health requirements, if required (see 3.2.5).

h. Painting, if different (see 3.3.5).

i. Electrical system and input power supply if different (see 3.4.2).

j. Motor enclosure, if different (see 3.4.3).

k. Type of spindle, if different (see 3.4.8).

l. Type of feed if, different (see 3.4.10).

m. Size and capacity, if different (see 3.5).

n. Standard equipment, if different (see 3.8).

o. Specify and fully describe optional equipment required; if different (see 3.9).

p. Additional performance features, if required (see 3.10).

q. Lubrication chart or plate, if different (see 3.11).

r. Nameplate, if different (see 3.12).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

s. First article inspection, if different (see 4.3).

t. Quality conformance inspection, if different (see 4.4).

u. Level of packaging, packing and marking, if different (See 5.1).

6.2.2 Contract data requirements. Required technical data such as operators manuals, parts lists, wiring diagrams; examination, alignment, and tolerance test reports, and other instructions for operation and maintenance (as identified on a DD Form 1664, Data Item Description) should be specified on a DD Form 1423, Contract Data Requirements List incorporated into the contract.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test and approval of the first article.

6.4 Safety and health requirements. Paragraph 3.2.5 requires compliance only with those OSHA requirements that concern the machine itself. It does not require compliance with those OSHA requirements that concern "the machine in its operating environment" such as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, heat, etc. Since OSHA limits the total hazard level of these hazards in the environment (and does not limit the hazard level of individual machines in the environment) the procuring activity is advised to analyze the existing hazard levels in the proposed operating environment, and specify additional machine requirements that will integrate the new machine into its future operating environment. The machine shall be equipped with all points-of-operation guarding normally furnished as standard on the manufacturer's commercial machines supplied to the commercial market. If specific point-of-operation guarding is required, the procuring activity should specify the exact configuration of the guard required as, in most cases, the guard configuration is dependent on the size and configuration of the workpieces. The above, and any other additional safety and health requirements, should be specified in detail under 6.2.1(g).

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Preparing Activity:
DLA-IP

Project Number:
3413-0132

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

Review Activity:

DLA- GS

User Activities:
Army - SM
Navy - YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D080039B	Drilling Machines, Upright, Bench Type, Box Column, Sliding Head, Electric Mtr Driven, Hand Feed

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.