MIL-P-63395 (AR)
12 August 1980

MILITARY SPECIFICATION

PROJECTILE, 155MM: INERT PXR 6325 (M549 (SIM) LOADING, ASSEMBLING AND PACKING

This specification is approved for use by US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing of the Projectile, 155MM: Inert PXR 6325 (M549 SIM)

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-I-45607	-	Inspection Equipment, Supply and Maintenance of
MIL-A-48978	-	Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procesures and Tables for Inspection by Attributes

FSC: 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil/ -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

DRAWINGS (see 6.5)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

7549275 - Pallet
9236063 - Projectile, 155MM: Inert PXR 6325 (M549 SIM)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with the applicable drawings and specifications.

3.2 Assembled projectile. The assembled projectile shall comply with all requirements specified on Drawing (Dwg.) 9236063, and with all requirements specified in the applicable specifications.

3.3 Inert fill. Inert fill shall have a specific gravity as specified on Dwg. 9236063.

3.4 Loading of inert fill

3.4.1 Mating surfaces. The mating surfaces of threads shall be free of inert fill and all threads shall be free of foreign material. If a chemical cleaner is required, acetone or methylene chloride shall be used.

3.4.2 Fuze well. The fuze well shall be free from any foreign matter or loose fill prior to assembly of the liner.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. The requirements of workmanship are as shown on the applicable drawing, in the applicable specifications and the following:

3.6.1 Cleaning. If required the cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:46Z
Check the source to verify that this is the current version before use.

3.6.2 Protection of the rotating band. Care shall be exercised at all times so that the rotating band of each projectile will not be nicked or burred.

3.6.3 Painting. Painting shall comply with the requirements of the applicable drawing. All paint shall be dry to the touch before testing and packing for shipment. Drying time prior to testing shall be in accordance with the applicable specification.

3.6.4 Foreign matter. No part or assembly shall contain dirt, grease, chips, rust corrosion or other foreign matter, prior to inspection and shipping.

3.6.5 Obturator. Care shall be taken at all times to protect obturator from being damaged.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspections shall be performed on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Projectile, 155MM: Inert PXR 6325 (M549 Sim)	9236063	8

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63395 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Projectile, 155MM: Inert PXR 6325 (M549 Sim)	1 OF 1	9236063 NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Projectile (Dwg. 9236063) Examination for Defects	8		3.2	4.4.2.1 to 4.4.2.5

NOTES

DRSMI-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4 QUALITY CONFORMANCE INSPECTION

4.4.1 Inspection lot formation. Inspection lots shall conform with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of loaded projectiles shall contain:

a. Projectile metal parts of one lot interfix number from one manufacturer.

b. Loaded projectile of one weight zone.

c. Fuze well liners from one manufacturer produced in accordance with the same drawing, same drawing revision, same specification, and same specification revision.

4.4.2 Examinations. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63395 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Projectile Prior to Loading				0256063
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRSAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63395 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Projectile and Liner (Prior to Assembly of Liner)				9236063
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth of fuze well, maximum		0.40%	3.2	Gage
102	Foreign matter in fuze well		0.40%	3.4.2	Visual
Minor					
201	Diameter of fuze well, maximum		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRSC -QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63395 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Projectile, Prior to Assembly or Lifting Plug		9236063
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Concentricity of inside diameter of liner with pitch diameter of thread including perpendicularity with face of body		0.40%	3.2	Gage
102	Depth to bottom of liner, min.		0.40%	3.2	Gage
103	Liner missing		100%	3.2	Visual
Minor					
201	Liner damaged		0.65%	3.2	Visual
202	Foreign matter in liner cavity		0.65%	3.2	Visual
203	Anti-seize missing from threads		0.65%	3.2	Visual
204	Inert fill in thread		0.65%	3.4.1	Visual
205	Liner removable by hand		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DLDAP-CA Form 160 Jul 77 Replaces SARPA-CA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63395 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Projectile, 155MM: Inert PXR 6325 (M549 Sim)	1 OF 1	9236063 NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of bourrlelt, max. (Applies if bourrelet has been retouched)		100%	3.2	Gage
102	Torque test failure of lifting plug		0.40%	3.2	Test
103	Lifting plug gasket missing or improperly assembled		0.40%	3.2	Visual
104	Any weight zone punch mark inadequate		0.40%	3.2	Visual/Manual
105	Projectile zone weight incorrect		100%	3.2	Balance
106	Zone stenciling or punch marking incorrect		100%	3.2	Visual
107	Obturating ring missing or damaged		100%	3.2	Visual
Minor					
201	Grommet missing, damaged or improperly assembled		0.65%	3.2	Visual
202	Rotating band damaged (Applies if grommet is missing)		0.65%	3.2	Visual
203	Protective coating with total damaged area in excess of 1/4 square inch		0.65%	3.6.3	Visual
204	Marking misleading or unidentifiable (Except for zones), including incorrect color code		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DD FORM 140 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63395 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Pallet		7549275
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pallet damaged or improperly assembled		0.40%	3.2	Visual
102	Projectile of different zones on the same pallet		0.40%	3.2	Visual
103	Strapping or staple missing or loose		0.40%	3.2	Manual
Minor					
201	Number of projectile assemblies incorrect		0.65%	3.2	Visual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual
203	Strapping or staple improperly engaged		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Inert fill. Prior to the start of loading a sample projectile shall be trial loaded and a core sample taken to determine specific gravity. If acceptable specific gravity is achieved loading may proceed using the loading parameters established during trial loading. Subsequent testing for specific gravity shall precede loading with a new batch or lot of inert filler raw materials and prior to the start of each months production.

4.4.4 Inspection equipment. The contractor shall submit for approval of inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and paragraph 6.3 herein.

4.4.5 Supply & maintenance. Supply and maintenance of the equipment shall be in accordance with MIL-I-45607.

5. PACKAGING

5.1 Packing - Level A. The projectile shall be packed in accordance with Dwg. 7549275.

5.2 Marking. Marking shall be in accordance with Dwg. 7549275.

6. NOTES

6.1 Intended use. The components and assemblies covered by this specification are intended for use on the Projectile, 155MM: Inert PXR 6325 (M549 SIM)

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection designs for approval -See 6.2.3 of MIL-A-48078. Submit equipment designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination the characteristic may be measured or gaged to determine acceptability.

6.5 Drawings. Drawings listed in Section 2 of this specification under the headings US Army Armament Research and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

Development Command (ARRADCOM) may also include drawings prepared by and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.6 Submission of Certificate of Conformance and ammunition data cards. In addition to the normal distribution of records for items procured by the Department of the Army, one copy of all certificates of conformance and ammunition data cards shall be forwarded to Commander, ARRADCOM, Dover, New Jersey 07801, DRDAR-QAR-Q.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No. 1320-A514

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.