MIL-W-50928C(AR)
3 October 1980
SUPERSEDING
MIL-W-50928B(PA)
30 July 1976

MILITARY SPECIFICATION

WARHEAD, FOR DEMOLITION KIT, M180 PARTS AND LOADING ASSEMBLY

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the loading and assembly of one type of warhead designated as Warhead, For Demolition Kit, M180.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-T-45	-	Tape, Gummed, Paper, Reinforced And Plain, For Sealing And Securing
PPP-B-636	-	Boxes, Shipping, Fiberboard

FSC:1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-B-2427 - Box, Ammunition Packing: Wood, Nailed

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9244402 - Warhead, Loading Assembly

9329655 - Check Block V-Clamp

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 100 - 199

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 100 - 199 (latest revision)").

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the currentversion before use.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (dwg.) 9244402 and with all requirements specified in applicable specifications.

3.3 Weight of explosive. The warhead shall contain 39.00 pounds (17.78 kilograms) minimum (min) of high explsoive, type H6.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated, finished, and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. (Required packing shall be dry).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated (See Table I).

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. (See MIL-A-48078)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Warhead, For Demolition Kit, M180 Loading Assembly	SHEET 1 OF 1	DRAWING NUMBER: See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Loading Assembly, Warhead (Dwg. 9244402)				
	Examination for defects	10		3.2	4.4.2.1
	Weight of explosive	10		3.3	4.4.2.1
	Cup, Warhead (Dwg. 9326790)				
	Examination for defects	10		3.1	4.4.2.2
	Shim (Dwg. 9244419)				
	Examination for defects	10		3.1	4.4.2.3
	Cover, End, Warhead (Dwg. 9244436)				
	Examination for defects	10		3.1	4.4.2.4
	Coupling, Flush Latch (Dwg. 9329461)				
	Examination for defects	10		3.1	4.4.2.5

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:44Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of warheads shall contain:

a. Explosive H-6 from not more than two lots produced by one manufacturer.

b. Parts from not more that one lot interfix number from one manufacturer.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Loading Assembly, Warhead	1 OF 1	9244402
			NEXT HIGHER ASSEMBLY: 9244400

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of fuze cavity		0.40%	3.2	Gage
102	Depth of fuze cavity		0.40%	3.2	Gage
103	True position of diameter of fuze cavity with outside diameter of flange		0.40%	3.2	Gage
104	Protrusion of high explosive above surface of flange		0.40%	3.2	Gage
105	Component missing, loose or improperly assembled		0.40%	3.2	Visual/Manual
106	Marking missing or incorrect		0.40%	3.2	Visual
107	Flush latch coupling insecure or missing		100%	3.2	Visual/Manual
108	Weight of explosive incorrect		100%	3.3	4.4.3.1/4.5.1
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cup, Warhead				9326790
					NEXT HIGHER ASSEMBLY
					9244402
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter, maximum (max.)		0.40%	3.1	Gage
102	Inside diameter, minimum (min.)		0.40%	3.1	Gage
103	External height, minimum (min.)		0.40%	3.1	Gage
104	Presence of cracks or tears		0.40%	3.1	Visual
Minor					
201	Width of flange, minimum (min.)		0.65%	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Shim				9244419
					NEXT HIGHER ASSEMBLY 9244402
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter, minimum (min.)		0.40%	3.1	Gage
102	Outside diameter, maximum (max.)		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Cover, End, Warhead				9244436
					NEXT HIGHER ASSEMBLY 9244402
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.1	Gage
102	Angle of chamfer		0.40%	3.1	Gage
103	Outside diameter		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Coupling, Flush-Latch	1 OF 1	9329461
			NEXT HIGHER ASSEMBLY: 9244402

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Coupling fails to fit over check block when force of ten to thirty pounds (10-30 lbs) is applied to end of handle		100%	3.1	Check Block V-Clamp (Dwg. 9320655)
102	Spotwelds or seawealds in restricted area (4 places)		0.40%	3.1	Visual
103	Latch and Connectors fail to rotate freely		0.40%	3.1	Manual
104	Width of V-Band trough (a)		0.40%	3.1	Gage
105	Angle of V-Band trough walls (a)		0.40%	3.1	Gage
106	Welds between V-Band (left and right) and Adaptors missing or improper (4 places)		0.40%	3.1	Visual
107	Welds between Flat Head Pins andd Latch missing or improper (2 places)		0.40%	3.1	Visual
108	Spotwelds between Adaptors (2) and V-Bands (left and right) missing or improper (2 places)		0.40%	3.1	Visual
109	Spotwelds between Outer Jacket and V-Bands (left, right & center) missing or improper		0.40%	3.1	Visual
110	Any components missing or improperly assembled		0.40%	3.1	Visual
Minor					
201	Width of slots on outer jacket (4 places)		0.65%	3.1	Gage
202	Lacquer missing or improper		0.65%	3.1	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: (a) This inspection should be done on each V-Band (left, right, and center).

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:44Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Weight of explosive. This test shall be performed one hundred percent as specified in 4.5.1, using test equipment in accordance with 4.4.4. Any warhead which does not meet the specified requirement shall be classified defective and removed from the lot (Non-destructive test).

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (See 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Weight of explosive. Before loading, the shell assemlies shall be labeled and weighed to the nearest .01 pound (4.5 grams). This tared weight shall be subtracted from the loaded, machined warhead weight.

5. PACKAGING

5.1 The following preservation, packaging, packing and marking requirements shall be applicable when the Warhead Loading Assembly is shipped interplant, separate from the rest of the kit.

5.1.1 Preservation and packaging. Place one warhead in a fiberboard box (Style RSC, Type CF, Class Domestic, Variety SW, Grade 125, PPP-B-636, inside dimensions - 29 3/4" by 6 1/2" by 6 1/2"). Add chipboard fillers as required to insure a tight pack. Close fiberboard box and seal with a 2 inch wide sealing strip. (Tape, paper, PPP-T-45).

5.1.2 Packing. Place one fully packed fiberboard box in a wooden box (Grade C, Type I, Class 1, MIL-B-2427, inside dimensions - 30 3/8" by 6 7/8" by 7 1/8"). Add chipboard fillers as required to insure a tight pack, for closing, sealing and strapping instructions see Drawing 8796522.

5.1.3 Marking.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the currentversion before use.

5.1.3.1 Mark the fiberboard box as follows with black ink, "1-warhead for kit cratering demolition M180".
LOT.....(insert applicable Lot No.)
Letters and figures shall not be less than 1/4 inch high, and shall be located on top o the fiberboard box only.

5.1.3.2 Mark wooden box in accordance with Drawing 8796522. The descriptive nomenclature shall be:
"1-WARHEAD FOR KIT, CRATERING, DEMOLITION M180"
The DOT nomenclature shall be:

"EXPLOSIVE PROJECTILE"

The cubical displacement shall be: "1.4 cubic feet".

6. NOTES

6.1 Intended use. The Warhead Loading Assembly covered by this specification is intended for use in the M180 Demolition Kit.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required, to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. The distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMND (ARRADCOM)" may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1375-A156

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-W-50928C Warhead, for demolition Kit, M180 Parts & Loading Assy

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.