[INCH-POUND]
MIL-B-85667/1A
28 January 1991
SUPERSEDING
MIL-B-85667/1(AS)
14 March 1986 and
MIL-B-8831/1
23 August 1982

MILITARY SPECIFICATION SHEET

BOLT, SLEEVE, STRAIGHT SHANK, PROTRUDING AND FLUSH HEAD, RELIABILITY AND MAINTAINABILITY REQUIREMENTS FOR

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-85667.

1. The expandable sleeve bolt may be used in bolted connections that require a precision controlled clearance fit or controlled interference fit.

2. The sleeve bolt may be used in design, repair and modification The sleeve bolt may be used for the replacement of tapered or straight shank interference fit fatigue rated fasteners.

3. The sleeve bolt shall be modified only by the original sleeve bolt manufacturer.

4. The sleeve bolt shall be used with nuts in accordance with MIL-N-85729 or MIL-N-85730, as applicable, and wrenching elements in accordance with MS33787 for the nuts, 12 point (double hex) for the protruding head sleeve bolts

5. For installation of protruding head sleeve bolts, preload shall be induced by "wrenching" the nut. The "wrenching element" of protruding head sleeve bolts is intended to be used to prevent rotation of the sleeve bolt shank during tightening of the nut

6. The sleeve bolt shall not be used in joints that are routinely disassembled.

7. The sleeve bolt shall not be used if the pin and sleeve have been separated.

8. MIL-B-85667/14 and /15 bolts are intended for use in applications requiring high interference levels They shall not be used where high interference residual tensile stresses may cause stress corrosion cracking, especially in the 7000 series aluminum tempers.

AMSC N/A FSC 5306
DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.

9. MIL-B-85667/16 and /17 bolts are intended for use in fatigue critical areas where controlled low interference levels are required due to material susceptibility to stress corrosion cracking.

Custodians:
Army - AV
Navy - AS
Air Force - 99

Review:
Air Force - 82

Preparing activity:
Navy - AS
(Project No. 5306-1361)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.