MIL-C-63227A (AR)
9 September 1981
SUPERSEDING
MIL-P-63227
1 August 1979

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, PA101 FOR PROJECTILE, 155MM, HE, GUIDED, CANNON LAUNCHED, M712 AND TRAINING M823

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification establishes the requirements for the manufacture and acceptance of the Clam Shell type container used for packing the 155MM, HE, Guided Cannon Launched projectile, M712 and training projectile, M823.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-48078 -Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MIL-STD-105 -Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-810 -Environmental Test Methods

FSC: 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9300440 -Container, Ammunition, Metal, PA101, for Projectile, 155MM, HE, Guided Cannon Launched, M712 and Training M823

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The containers (container assemblies) shall comply with all requirements specified on drawing 9300440 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Handles. Each rope and handle shall be capable of supporting the weight of the loaded container without structurally damaging the assembly when lifted using a device with at least a one inch radius.

3.4 Environmental conditions. The container, when loaded with a tactical projectile or an inert or simulated projectile having the same external configuration, weight, and center of gravity as the tactical projectile, shall withstand exposure to the following environments. After exposure, the projectile shall be capable of being removed and reinserted into the container. There shall have been no damage to the container contents as a result of the testing and the container shall meet the leak test requirements of drawing 9301842.

3.4.1 Salt fog. The container shall protect its contents from and withstand exposure to a five percent sodium chloride and water solution while at an ambient temperature of 95°F (35°C).

3.4.2 Transportation vibration. The container shall withstand exposure to the transportation vibration requirements of MIL-STD-810, Method 514.2, Procedure X.

3.4.3 Loose cargo vibration. The container shall withstand 1 inch double amplitude, circular path motion in a vertical plane at 284 ± 2 revolutions per minute.

3.4.4 Transit drop. The container shall withstand exposure to free falls from a height of 24 inches impacting on a two inch thick plywood surface, backed by concrete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

3.4.5 Fragility shock. The container shall withstand exposure in all three axes, to half sine wave mechanical shock pulses having nominal durations of 10 milliseconds (ms), with nominal peak accelerations of 200 g's.

3.5 Lifting Straps. The lifting straps shall be capable of supporting 150 pounds without tearing or damage.

3.6 First Article Inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges, and other defects that might affect the serviceability, durability, safety, and appearance of the container.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of four (4) painted container assemblies, and five (5) each of every subassembly and component (unpainted) listed under the classification and defect tables herein (para 4.4.2.1 through 4.4.2.25).

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Assemblies and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Container Assemblies (Dwg 9300440)				
	a) Examination for defects	4	100%	3.2	4.4.2.26
	b) Salt fog test	4	100%	3.4.1	4.5.1.1
	c) Transportation vibration test	4	100%	3.4.2	4.5.1.2
	d) Loose cargo vibration test	4	100%	3.4.3	4.5.1.3
	e) Transit drop test	4	100%	3.4.4	4.5.1.4
	f) Fragility shock test	4	100%	3.4.5	4.5.1.5
	g) Leakage test	4	100%	3.2	4.5.2
	h) Handle pull test	4	100%	3.3	4.5.3
	Detailed Parts (Dwg - See Para 4.4.2.1 - 4.4.2.25)				
	Examination for defects	5 ea	100%	3.2	4.4.2.1 thru 4.4.2.25

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Body				9301801
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Length, overall, min.		0.40%	3.2	Gage
102	Wall thickness		0.40%	3.2	Gage
103	Height, overall		0.40%	3.2	Gage
104	Width of flange, (two places)		0.40%	3.2	Gage
105	Height of vertical section (two places)		0.40%	3.2	Gage
106	Width of angled portion		0.40%	3.2	Gage
107	Width of angled and flat portion		0.40%	3.2	Gage
Minor					
201	Location of notches (10 places)		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23 02:26Z
Check the source to verify that the document is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Panel, End		9301802
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Height, overall		0.40%	3.2	Gage
102	Width, overall		0.40%	3.2	Gage
103	Height of vertical section		0.40%	3.2	Gage
104	Thickness		0.40%	3.2	Gage
105	Width of flange		0.40%	3.2	Gage
106	Width of angled portion		0.40%	3.2	Gage
107	Width of angled and flat portion		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Downloaded from https://assist.dla.mil/ Source: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Bulkhead, Forward		9301803
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Location of datum on inside diameter		0.40%	3.2	Gage
103	Width overall		0.40%	3.2	Gage
104	Height overall		0.40%	3.2	Gage
105	Width of angled portion and flat		0.40%	3.2	Gage
106	Width of angled portion		0.40%	3.2	Gage
Minor					
201	Taper missing on outside surface		0.65%	3.2	Visual
202	Height of side cutouts on top		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Pad Nose	1 OF 1	9301843
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Saml1 Outside Diameter		0.40%	3.2	Gage
104	Large Outside Diameter				
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Channel		9301805
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Length		0.40%	3.2	Gage
102	Height		0.40%	3.2	Gage
103	Width		0.40%	3.2	Gage
104	Thickness		0.40%	3.2	Gage
105	Height of cutout in flange		0.40%	3.2	Gage
106	Width of cutout in flange		0.40%	3.2	Gage
107	Height of vertical portion of cutout in flange		0.40%	3.2	Gage
108	Width of angled portion of cutout in flange		0.40%	3.2	Gage
109	Width of angled and flat portion of cutout in flange		0.40%	3.2	Gage
Minor					
201	Holes missing or improper (7 places)		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-04-22T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Cradle		9301806
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Width overall		0.40%	3.2	Gage
102	Width of angled portion		0.40%	3.2	Gage
103	Width of angled and flat portion		0.40%	3.2	Gage
104	Height overall		0.40%	3.2	Gage
105	Thickness		0.40%	3.2	Gage
106	Location of hole		0.40%	3.2	Gage
107	Inside radius		0.40%	3.2	Gage
Minor					
201	Notch missing or improper on top outside edge		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: http://assist.dla.mil/ - Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Bulkhead Aft		9301808
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Height overall, min.		0.40%	3.2	Gage
102	Width overall, min.		0.40%	3.2	Gage
103	Thickness, min.		0.40%	3.2	Gage
104	Thread minor diameter, min.		0.40%	3.2	Gage
105	Thread pitch diameter		0.40%	3.2	Gage
106	Width of angled portion		0.40%	3.2	Gage
107	Width of angled portion and flat		0.40%	3.2	Gage
108	Height to notched section on O.D.		0.40%	3.2	Gage
Minor					
201	Taper on O.D. missing or improper		0.65%	3.2	Visual
202	Small hole missing or obviously improper		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2024-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Stop, Tail	1 OF 1	9301809
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Thread major diameter, max.		0.40%	3.2	Gage
102	Thread pitch diameter		0.40%	3.2	Gage
103	Diameter of lip on front edge		0.40%	3.2	Gage
104	Outside diameter of end with holes		0.40%	3.2	Gage
105	Length of end with holes		0.40%	3.2	Gage
106	Overall length		0.40%	3.2	Gage
Minor					
201	Holes missing or obviously improper (8 places)		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Cage, Latch		9301810
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Overall height		0.40%	3.2	Gage
102	Overall length		0.40%	3.2	Gage
103	Width of center slot		0.40%	3.2	Gage
104	Overall width		0.40%	3.2	Gage
105	Diameter of hole		0.40%	3.2	Gage
Minor					
201	C 'Bore missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Downloaded from http://assist.daps.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9301811
4.4.2.11	Base, Latch				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Width		0.40%	3.2	Gage
102	Height		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
104	Width across two bends		0.40%	3.2	Gage
105	Location of notch		0.40%	3.2	Gage
106	Distance from top to top of notch		0.40%	3.2	Gage
Minor					
201	Hole diameter		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: http://stinet.dtic.mil/ - Downloaded: 2026-10-23T02:26Z
Check the source daily to assure this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Pin, Latch				9301812
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Length of small ID		0.40%	3.2	Gage
103	Large diameter		0.40%	3.2	Gage
104	Small diameter		0.40%	3.2	Gage
Minor					
20	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9301813
4.4.2.13	Latch Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Length of draw bolt		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Document Source: https://assist.dla.mil/ Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Retainer, Gasket, Side		9301814
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Overall length		0.40%	3.2	Gage
104	Holes or notches missing or obviously improper		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Downloaded from http://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Retainer, Gasket, End	1 OF 1	9301815
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Length		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
104	Distance between holes		0.40%	3.2	Gage
105	Hole diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Panel, End, Aft		9301817
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Overall width		0.40%	3.2	Gage
102	Height		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
104	Width of top flange		0.40%	3.2	Gage
105	Width of angled portion		0.40%	3.2	Gage
106	Width of flat and angled portion		0.40%	3.2	Gage
107	Length of vertical section		0.40%	3.2	Gage
Minor					
201	Holes missing or obviously improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil/ Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Handle Adjustment				9301826
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
201	Length		0.40%	3.2	Gage
202	Diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9301823
4.4.2.18	Gasket				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Internal length		0.40%	3.2	Gage
102	Internal width		0.40%	3.2	Gage
103	Cross-sectional width		A	3.2	Gage
104	Cross-sectional height		A	3.2	Gage
105	Diameter of inner hole		A	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

A. Two per lot per mold cavity. The first and last piece made per each mold shall be checked. Failure to meet requirements of the dwg. shall be cause to reject the lot.

Source: https://assist.dla.mil Downloaded: 2026-10-23T02:26Z
Check for the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Ring Tail				9301824
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.20	Strap Lifting				9301825
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Sewing improper		0.40%	3.2	Visual
102	Length		0.40%	3.2	Gage
103	Load test		0.40%	3.5	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: DLA/Assist.mil - Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.21	Tab, Pre-Load		9301828
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Length of cutout		0.65%	3.2	Gage
202	Depth of cutout		0.65%	3.2	Gage
203	Cutout profile improper		0.65%	3.2	Visual
204	Overall length		0.65%	3.2	Gage
205	Overall width		0.65%	3.2	Gage
206	Overall height		0.65%	3.2	Gage
207	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Downloaded from: https://assist.dla.mil/ - Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9301832
4.4.2.22	Strike, Latch				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Width		0.40%	3.2	Gage
102	Height		0.40%	3.2	Gage
103	Length		0.40%	3.2	Gage
104	Thickness of cutout		0.40%	3.2	Gage
105	Height of "J" hook		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil | Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9301833
4.4.2.23	Liner Cradle				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Radius, outside, small		0.40%	3.2	Gage
102	Radius, inside		0.40%	3.2	Gage
103	Location of hole in tab		0.40%	3.2	Gage
104	Width overall		0.40%	3.2	Gage
105	Width between flanges		0.40%	3.2	Gage
106	Material properties		0.40%	3.2	Certificate of conformance
Minor					
201	Thickness of flange		0.65%	3.2	Gage
202	Overall height		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.24	Cover, Assembly	1 OF 1	9301829
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Location of cradles (2 places)		0.40%	3.2	Gage
102	Location of forward cover stop		0.40%	3.2	Gage
103	Location of aft cover stops (3 places)		0.40%	3.2	Gage
104	Any weld missing or improper		0.40%	3.2	Visual
105	Flange flatness		0.40%	3.2	Gage
106	Pads, liners, cradles etc. missing or improperly assembled		0.40%	3.2	Visual
Minor					
201	Protective finish damaged, bare spots exposed metal, etc.		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.25	Body Assembly		9301800
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Location of cradles		0.40%	3.2	Gage
102	Location of forward bulkhead to aft bulkhead		0.40%	3.2	Gage
103	Location of forward bulkhead		0.40%	3.2	Gage
104	Any weld missing or improper		0.40%	3.2	Visual
105	Flange flatness		0.40%	3.2	Gage
106	Pads, liners, cradles etc. missing or improperly assembled		0.40%	3.2	Visual
Minor					
201	Protective finish damaged, bare spots exposed metal, etc.		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: http://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.26	Container Assembly	1 OF 1	9300440
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Cover improperly assembled to body		0.40%	3.2	Visual/Manual
102	Leak test		100%	3.2	Test 4.5.2
103	Opening force on each latch		100%	3.2	Gage
104	Handle pull test		1/lot	3.3	Test 4.5.3
105	Torque of Barrel Nut		100%	3.2	Gage
Minor					
201	Protective finish damaged, bare spots exposing metal, etc.		0.65%	3.2	Visual
202	Marking missing, incomplete or illegible		0.65%	3.2	Visual
203	Straps, handle and Band Assemblies missing prior to sealing		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-04-23T02:26Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. All requirements for testing are contained in the Classification and Defect Tables, paragraphs 4.4.2.1 thru 4.4.2.26.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test Methods.

4.5.1 Environmental tests. The container shall meet the requirements of 3.4 immediately after exposure to the following environmental tests.

4.5.1.1 Salt fog test. The loaded container shall be subjected to the salt fog tests of MIL-STD-810, Method 509.1, Procedure I. There shall be no evidence of corrosion on the inside of the container or its contents as the result of this test. The paint shall show no evidence of blistering due to corrosion of container base metal.

4.5.1.2 Transportation vibration test. The loaded container, shall be subjected to the vibration test of MIL-STD-810, Method 514.2, Procedure X, using the criteria of Table 514.2 - VII and Figure 514.2-7, Curve AX, except search and dwell shall be omitted.

4.5.1.3 Loose cargo vibration test. The loaded container shall be subjected to the vibration test of MIL-STD-810, Method 514.2, Procedure XI with the exception that the item shall not be tested while resting on the two end faces and vibrated 7.5 minutes on each face for a total cycle time of 30 minutes..

5.4.1.4 Transit drop test. The loaded container shall be subjected to the transit drop test of MIL-STD-810, Method 516.2, Procedure II, Table 516.2-I, for a test item weighing 100 to 200 pounds.

5.4.1.5 Fragility shock test. The loaded container shall be subjected to fragility shock in accordance with MIL-STD-810, Method 516.2, Procedure I, Figure 516.2-2, with the exception that the peak value (A) shall be 200 g's and the nominal duration (D) shall be 10 milliseconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

4.5.2 Air leak test. Each container shall be assembled with a simulated projectile and tested as follows. Subject the container assembly to the internal pressure as specified on the applicable drawing and observes air leakage for the specified time frame as specified on the applicable drawing.

4.5.3 Handle pull test. The container complete with simulated projectile shall be lifted by each handle (both rope and metal) one at a time. The handle shall be grasped by means of a hook, rope or similar device and container lifted so as the entire weight of the assembly is supported through the handle in test. Examination to the requirements of 3.3 shall be made after lifting.

5. PACKAGING

5.1 Packaging requirements. None required.

5.2 Packing. Packing shall be commerical. The containers shall be prepared in accordance with paragraph 2.3.1 of MIL-STD-1188.

5.3 Alternate Packing. (When specified by the contracting officer) Containers may be unitized, 6 per pallet, in accordance with dwg. 1948415920 PM1003 except that commercial strapping may be used in lieu of strapping specified.

5.4 Marking. Shipping marking shall comply with MIL-STD-1188 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-R, Dover, New Jersey 07801. This description should include but not be limited to the accuracy and precision of the method, test data demonstrating the accuracy and precision and drawings of any special equipment required.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1320-A615

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.