MIL-C-82252D
4 APRIL 1983
SUPERSEDING
MIL-C-82252C
20 September 1977

MILITARY SPECIFICATION

CLOTH, BROADCLOTH, WOOL, AND WOOL-SYNTHETIC (MOTH-PROOFED)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for wool and wool-synthetic broadcloth fabrics.

1.2 Classification. The broadcloth shall be of the following types and classes (see 6.2):

Type I - Wool

Class 1 - 14.5 Ounce - Blue 3346
Class 2 - 15.5 Ounce - Blue 2307
Class 3 - 16.5 Ounce - Blue 3346
Class 5 - 23.0 Ounce - Blue 3346

Type II - Wool - Synthetic Blend

Class 1 - 15.5 Ounce - Blue 2307
Class 3 - 16.5 Ounce - Blue 3346

2. APPLICABLE DOCUMENTS

*2.1 Government documents

*2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified.

Beneficial comments (recommendations, additions, and deletions) and any pertinent data which may be of use in improving this document should be addressed to: Officer in Charge, Navy Clothing and Textile Research Facility, 21 Strathmore Road, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-P-1132 - Packaging and Packing of Woolen, Worsted, and Wool Blend (Synthetic Fiber; Cotton) Fabrics

MILITARY

MIL-C-43665 - Cloth, Wool: Mothproofing Treatment of

STANDARDS

FEDERAL

FED-STD-191 - Textile Test Methods

MILITARY

MIL-STD-655 - Provisions for Evaluating Quality of Cloth, Wool, Worsted and Wool Blends.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

*2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

LAWS AND REGULATIONS

RULES AND REGULATIONS UNDER THE WOOL PRODUCT LABELING ACT OF 1939

(Application for copy should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20402.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and supplement thereto, if applicable.

U. S. DEPARTMENT OF AGRICUTURE
Methods of Test for Grade of Wool

(Application for copies should be addressed to the U.S. Department of Agriculture, Agricultural Marketing Service, Washington, D.C. 20402.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Standard sample. The finished cloth shall match the standard sample for shade, and shall be equal to or better than the standard sample with respect to all characteristics for which the standard sample is referenced (see 6.3.).

3.2 First article. When specified, the contractor shall furnish a sample of cloth for first article inspection and approval (see 4.3 and 6.2).

3.3 Material.

3.3.1 Stock

3.3.1.1 Wool. The wool stock shall be of fleece or pulled wool, or a combination of both, not lower in grade than 64's U.S. Standard for type I, classes 1, 2, 3 and 5 and type II, class 1; and not lower in grade than 60's U.S. Standard for type II, class 3. The use of reprocessed wools, reused wools, or any wool waste, or wool manufacturing by-products, other than those resulting from the supplier's own current production of this cloth, is prohibited. Inspections shall be performed as specified in 4.4.1.1 and 4.4.2.

3.3.2 Wool content.

3.3.2.1 Type I. The finished cloth shall contain not less than 95 percent wool, based on the oven dry weight of the specimen, when tested as specified in 4.5.

3.3.2.2 Type II. The finished cloth shall be wool blended with first quality synthetic fiber (see 6.2) in such proportion that the finished cloth shall contain not less than 83 percent wool and not more than 17 percent of the specified synthetic fiber when tested as specified in 4.5. Content shall be determined based on the oven dry weight of the specimen.

3.3.3 Yarn. The wool and wool-synthetic fibers shall be blended, carded, and evenly spun on the woolen system into singles yarn for both the warp and the filling when tested as specified in 4.4.1 and 4.5.

3.4 Physical requirements. The finished cloth shall conform to the requirements in Table I when tested as specified in 4.5.

* 3.5 Weave. The weave for all types shall be $\frac{2}{1}$ right hand twill when tested as specified in 4.5.

NOTE: Selvage yarns - To prevent edges of the cloth from building up when rolled, the single yarn used in the selvage may be made of a finer count than those used in the body of the cloth. The fiber content of the selvage yarns shall be the same as that of the body of the cloth.

3.6 Color. The color shall be as specified (see 6.2), and shall be produced by stock or top dying with a suitable dyestuff to match the standard sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

Table I - Physical requirements

	Width (Exclusive of Selvage) (min)	Weight 1/ oz/lin yd (g/lin m)		Yarns/inch (per cm) (min)		Breaking Strength (lbs) (Newtons) (min)		Shrinkage (Percent) (max)	
	Inches (cm)	(min)	(max)	Warp	Filling	Warp	Filling	Warp	Filling
Type I									
Class 1	56 (142.2)	14.0 (362.6)	15.0 (388.5)	54 (21.2)	50 (19.7)	45(200)	42(187)	5.0	4.0
Class 2	54 (137.2)	15.0 (388.5)	16.0 (414.4)	56 (22.0)	55 (21.7)	50(223)	45(200)	2.0	1.5
Class 3	56 (142.2)	16.0 (414.4)	17.0 (440.3)	60 (23.6)	58 (22.8)	40(178)	35(156)	3.5	3.5
Class 5	56 (142.2)	22.0 (569.8)	24.0 (621.6)	90 (35.4)	64 (25.1)	65(289)	40(178)	4.0	3.0
Type II									
Class 1	54 (137.2)	15.0 (388.5)	16.0 (414.4)	56 (22.0)	55 (21.7)	50(223)	45(200)	2.0	1.5
Class 3	54 (137.2)	16.0 (414.4)	17.0 (440.3)	51 (20.0)	51 (20.0)	55(245)	45(200)	3.5	2.5

1/ Weight for type I, classes 1, 3 and 5 are based on a linear yard of 56 inches (142.2cm). Weight for type I, class 2 and type II, classes 1 and 3 are based on a linear yard of 54 inches (137.2cm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

* 3.6.1 Matching. The finished cloth shall match the standard sample under artificial daylight, having a color temperature of 7000 ± 500 kelvin and shall be a good approximation to the standard sample under incandescent lamplight at 2850 ± 100 kelvin.

3.6.2 Colorfastness. The finished cloths shall show colorfastness to light, wet-dry cleaning, crocking and perspiration equal to or better than the standard sample when tested as specified in 4.5. When no standard sample is available, the finished cloths shall show "good" fastness to light, wet-dry cleaning, and perspiration and shall show a Munsell Value for crocking not lower than 8.5 when tested as specified in 4.5.

3.7 Finish. The fabric shall have a finish and hand equal to or better than the standard sample. The fabric shall be thoroughly scoured, properly fulled, free from vegetable matter (carbonized if necessary) and face evenly sheared and pressed.

3.7.1 pH. The pH value of the water extract of the finished cloth shall be not less than 4.0 nor more than 8.0 when tested as specified in 4.5.

3.8 Marking. The back of the cloth shall be marked "BACK" at both ends of each roll with letters not less than 1/2 inch (1.3cm) in height. The marking shall be clearly legible in any indelible marking used commercially and shall not show through on the face of the cloth.

3.9 Length and put-up. Unless otherwise specified (see 6.2), the cloth shall be furnished in continuous lengths, each not less than 40 yards (36.56m). Each length of cloth furnished shall be put-up on rolls with the face side inward as specified in PPP-P-1132.

3.10 Wool content label. Cloth manufactured under this specification shall be labeled in accordance with the Wool Products Labeling Act of 1939.

3.11 Mothproofing. The cloth shall be given a mothproofing treatment in accordance with MIL-C-43665 (see 4.5).

3.12. Workmanship. The finished cloth shall conform to the quality established by this specification. The demerit points per 100 square yards ($83.61m^2$) when calculated as specified in Section 4, shall not exceed the established maximum point value. Each defect shall be marked with a 1 to 1-1/2 inch (2.5 to 3.8cm) long string. The string shall be sewn into the selvage near the defect. A red string shall represent a three or four point defect and a white string shall represent a one or two point defect (see 4.4.3).

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

1. First article inspection (See 4.3)
2. Quality conformance inspection (See 4.4)

4.3 First article inspection. When required, the first article of finished cloth shall be visually examined for color, finish and appearance and shall be tested for chemical and physical properties in accordance with the applicable methods specified in 4.5.

4.4 Quality conformance inspection. Inspection shall be performed in accordance with MIL-STD-655, except where otherwise indicated.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be visually examined and tested in accordance with all requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document. In addition, a certificate of compliance shall be submitted for the blending and spinning of the yarns as specified in 3.3.3.

4.4.1.1 Wool. The wool shall be visually examined for grade in scoured form, prior to dyeing, picking or carding, by comparison with the applicable U.S. Standard (see 2.2). The examination for grade shall be performed on a composite sample of 1 pound (0.45Kg) of scoured wool for each 10,000 pounds (4500 Kg) or fraction thereof in the lot. The composite sample shall be selected from not less than 10 percent of the bales or bags in the lot. In the event of dispute resulting from comparison, the grade shall be determined by a width method (wedge). The lot shall be unacceptable if the sample does not conform to the requirements of 3.3.1.1. Each lot shall consist of one grade of wool only.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to assure that only approved wools are used (see 3.3.1.1). The Government reserves the right to exclude from consideration for acceptance any material for which in-process inspection has indicated nonconformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

* 4.4.3 Examination of the end item. Examination of the end item for yard-by-yard, length, back marking, compliance with the Wool Product Labeling Act, and for defect marking (Stringing of defects) shall be as specified in MIL-STD-655. The fabric quality for the finished cloth shall be quality level 10.

* 4.4.3.1 Limits of slubs and knots. Only slubs and knots which exceed "C" for slubs and "D" for knots on the Sears Fabric Defect Scale (see 6.4) shall be scored.

* 4.4.3.2 Examination for shade and finish, individual rolls. Each roll in the lot shall be examined visually for shade match (see 3.6), and finish (see 3.7). A roll shall be unacceptable if it fails to meet the requirements for shade match or finish as applicable. The sample unit shall be a 4-inch by 20-inch (10.1 by 50.8cm) swatch of the cloth. A sample unit shall be drawn from each roll in the lot.

* 4.4.4 Examination of packaging requirements. An examination shall be made in accordance with the provisions of PPP-P-1132 to determine that packaging, packing and marking comply with the Section 5 requirements of this specification.

4.5 Testing of the end item. The methods of testing specified in FED-STD-191, wherever applicable and as listed in Table II, shall be followed. The physical and chemical values specified in Section 3, except where otherwise indicated, apply to the results of the determinations made on a sample unit for test purposes as specified in the applicable test methods. All test reports shall contain the individual values utilized in expressing the final result. The sample unit shall be 3 1/2 yds (3.2m), full width of the finished cloth. The lot size shall be expressed in units of one yard (0.9m). The lot shall be unacceptable if one or more sample units fail to meet any of the test requirements specified. The sample size shall be in accordance with the following:

Lot size (yards)	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

Table II - Test methods

Characteristics	Requirement paragraph	Test method
Fiber percentage		
Type I	3.3.2.1	2101
Type II	3.3.2.2	2102
Yarn ply	3.3.3	Visual 1/
Weave	3.5	Visual 1/
Weight	3.4	5041
Yarns per inch	3.4	5050
Breaking strength		
Warp and filling	3.4	5100

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

Table II - Test methods (cont'd)

Characteristics	Requirement paragraph	Test method
Shrinkage		
Warp and filling	3.4	5590 2/
Colorfastness to:		
Light	3.6.2	5660
Wet-dry cleaning	3.6.2	5622
Crocking	3.6.2	5651
Perspiration	3.6.2	5680
Finish	3.7	3/
Mothproofing	3.11	4/
pH	3.7.1	2811

1/ One determination per sample unit and the result reported as "pass" or "fail."
2/ Pressing shall be performed on a flat bed press.
3/ A certificate of compliance will be acceptable for the requirements stated.
4/ To be tested in accordance with the requirements of MIL-C-43665.

5. PACKAGING

5.1 Preservation-Packaging. Packaging shall be level A or C as specified.

5.1.1 Levels A and C. The cloth, put up as specified, shall be packaged in accordance with the applicable requirements of PPP-P-1132.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Levels A, B, and C. The cloth shall be packed in accordance with the applicable requirements of PPP-P-1132.

5.3 Marking. In addition to any special marking required in the contract or order, shipments shall be marked in accordance with the requirements of PPP-P-1132.

6. NOTES

6.1 Intended use. The cloths covered by this specification are intended for use in service, semi-dress, and dress uniforms, functional clothing and insignia by the Department of Defense.

* 6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Type and class of cloth required (see 1.2).
c. Type of synthetic fiber required for type II cloth (see 3.3.2.2).
d. Length required when other than specified (see 3.9).
e. Levels of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

f. When a first article inspection is required, the item will be tested and should be a first article sample. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, quantity, and testing and approval of the first article.

6.3 Standard sample. For access to the standard samples, address the procuring activity issuing the invitation for bids (see 3.1).

* 6.4 Fabric defect scales. Sears Fabric Replica Kits are available from Sears, Roebuck and Co, Department 817, (ATTN: BSC 23-29), Sears Tower, Chicago, IL 60684.

* 6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - GL
Navy - NU
Air Force - 11,

Preparing Activity:
Navy - NU

Project No. 8305-0827

Review activities:
Army - MD, IH
Navy - MC
Air Force - 82, 99
DLA - TTCT

User activity:
Navy - CG

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

ficer In Charge
vy Clothing & Textile Research Facility
Strathmore Road
tick, MA 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Officer In Charge
Navy Clothing & Textile Research Facility
21 Strathmore Road
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-C-82252D	Cloth, Broad Cloth, Wool and Wool-Synthetic

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*. _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 R2 MAR — PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil/ - Downloaded: 2025-10-23T06:57Z
Check the source to verify that this is the current version before use.