INCH-POUND

MIL-B-85667/3A
AMENDMENT 1
9 JULY 1998

MILITARY SPECIFICATION SHEET

BOLT, SLEEVE, PROTRUDING HEAD, STRAIGHT SHANK,
CRES 304 SLEEVE, CRES PH 13-8Mo PIN, 220 KSI Ftu

This amendment forms a part of Military Specification MIL-B-85667/3A, dated 28 January 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

5.2 Sleeve. Delete entire paragraph and substitute: "Sleeve material shall be corrosion resistant steel, AISI 304 (UNS S30400), in accordance with MIL-T-8504 (chemistry only) or ASTM A269 (chemistry only)."

Page 2

FIGURE 1. Flanged tension head bolt. On pin only, under head fillet radius dimension R, delete: "R+.010/-.000 " and substitute: " R+.000/-.010 "

Page 3

9. Lubricants. End of last sentence, add "or equivalent." after "...with MIL-L-87132."

Page 5

TABLE I Under heading "F.T. +.015(b)/-.000" delete entire column and substitute the following:

For:			Insert:
Size Nos.	Group		F.T. +.015(b) -.000
-9	1		.025
-9	2		.025
-9	3		.030
-10	1		.025
-10	2		.025
-10	3		.030
-12	1		.030
-12	2		.030
-12	3		.035

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.

Page 6

TABLE II. Mechanical Properties.

Delete: Values under column headings for Ultimate Tensile Strength, Thread Area, and Fatigue Test Loading, and substitute the following:

Dia Dash Number	Ultimate Tensile Strength Lbs-Min (b)	Thread Area In^2 (b)		Fatigue Test Loading Lbs +/- 2% (c)	
				Max	Min
-3	4,970	.0226		2,290	229
-4	8,870	.0404		4,090	409
-5	14,100	.0640		6,500	650
-6	20,900	.0951		9,620	962
-7	28,300	.1288		13,000	1300
-8	37,800	.1717		17,400	1740
-9	47,900	.2176		22,000	2200
-10	59,900	.2724		27,600	2760
-12	86,900	.3953		40,000	4000
-14	119,000	.5392		54,700	5470
-16	155,000	.7027		71,300	7130

Page 9

TABLE III. Bolt grips and lengths (continued). In table, for Grip Number 49, -9 Diameter, change unthreaded pin length from "3.118" to "3.123" and Bolt Length from "3.899" to "3.904".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.

TABLE III. Bolt grips and lengths (continued).

Delete: Values under column headings for -9, -10, and -12 Diameters and substitute the following:

		-9 Diameter		-10 Diameter		-12 Diameter	
Grip Number	Bolt Design Grip	Unthreaded Pin Length (See Figure 1)	Bolt Length	Unthreaded Pin Length (See Figure 1)	Bolt Length	Unthreaded Pin Length (See Figure 1)	Bolt Length
50	3.125	3.185	3.966	3.180	4.023	3.185	4.185
51	3.188	3.248	4.029	3.243	4.068	3.248	4.248
52	3.250	3.310	4.091	3.305	4.148	3.310	4.310
53	3.312	3.373	4.154	3.373	4.216	3.373	4.373
54	3.375	3.435	4.216	3.435	4.278	3.435	4.435
55	3.438	3.498	4.279	3.498	4.341	3.498	4.498
56	3.500	3.560	4.341	3.560	4.403	3.560	4.560
57	3.562	3.623	4.404	3.623	4.466	3.623	4.623
58	3.625	3.685	4.466	3.685	4.528	3.685	4.685
59	3.688	3.748	4.529	3.748	4.591	3.748	4.748
60	3.750	3.810	4.591	3.810	4.653	3.810	4.810
61	3.812	3.873	4.654	3.873	4.716	3.878	4.878
62	3.875	3.935	4.716	3.935	4.778	3.940	4.940
63	3.938	3.998	4.779	3.998	4.841	4.003	5.003
64	4.000	4.060	4.841	4.060	4.903	4.065	5.065
65	4.062	4.123	4.904	4.123	4.966	4.128	5.128
66	4.125	4.185	4.966	4.185	5.028	4.190	5.190
67	4.188	4.248	5.029	4.248	5.091	4.253	5.253
68	4.250	4.310	5.091	4.310	5.153	4.315	5.315
69	4.312	4.373	5.154	4.373	5.216	4.378	5.373
70	4.375	4.435	5.216	4.435	5.278	4.440	5.440
71	4.438	4.498	5.279	4.498	5.341	4.503	5.503
72	4.500	4.560	5.341	4.560	5.403	4.565	5.565
73	4.562			4.623	5.466	4.628	5.628
74	4.625			4.685	5.528	4.690	5.690
75	4.688			4.748	5.591	4.753	5.753
76	4.750			4.810	5.653	4.815	5.815
77	4.812			4.873	5.716	4.878	5.878
78	4.875			4.935	5.778	4.940	5.940
79	4.938					5.003	6.003
80	5.000					5.065	6.065
81	5.062					5.128	6.128
82	5.125					5.190	6.190
83	5.188					5.253	6.253
84	5.250					5.315	6.315
85	5.312					5.378	6.378
86	5.375					5.440	6.440
87	5.438					5.503	6.503
88	5.500					5.565	6.565
89	5.562					5.628	6.628
90	5.625					5.690	6.690

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AV
Navy - AS
Air Force - 99

Preparing Activity:
DLA-IS

(Project 5306-2051)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.