INCH-POUND

MIL-B-85667/5A
AMENDMENT 1
31 AUGUST 1998

MILITARY SPECIFICATION SHEET

BOLT, SLEEVE, PROTRUDING HEAD, STRAIGHT SHANK, TITANIUM ALLOY PIN, 160 KSI Ftu

This amendment forms a part of Military Specification MIL-B-85667/5A, dated 28 January 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

5.2 Sleeve. Delete entire paragraph and substitute: "Sleeve material shall be corrosion resistant steel, AISI 304 (UNS S30400), in accordance with MIL-T-8504 (chemistry only) or ASTM A269 (chemistry only)."

Page 2

9. Lubricants. End of last sentence, add "or equivalent." after "...with MIL-L-87132."

Page 3

FIGURE 1. Flanged tension head bolt. On pin only, under head fillet radius dimension R, delete: "R+.010/-.000 " and substitute: " R+.000/-.010 "

Page 5

TABLE I Under heading "F.T. +.015(b)/-.000" delete entire column and substitute the following:

For: Insert:

Size Nos.	Group		F.T. +.015(b) -.000
-9	1		.025
-9	2		.025
-9	3		.030
-10	1		.025
-10	2		.025
-10	3		.030
-12	1		.030
-12	2		.030
-12	3		.035

AMSC N/A FSC 5306

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.

TABLE II. Mechanical Properties.

Delete: Values under column headings for Ultimate Tensile Strength, Thread Area, and Fatigue Test Loading, and substitute the following:

Dia Dash Number	Ultimate Tensile Strength Lbs-Min (b)	Thread Area In^2 (b)		Fatigue Test Loading Lbs +/- 2% (c)	
				Max	Min
-3	3,620	.0226		1,450	145
-4	6,470	.0404		2,590	259
-5	10,200	.0640		4,080	408
-6	15,200	.0951		6,080	608
-7	20,600	.1288		8,240	824
-8	27,500	.1717		11,000	1100
-9	34,800	.2176		13,920	1392
-10	43,600	.2724		17,440	1744
-12	63,200	.3953		25,280	2528
-14	86,300	.5392		34,520	3452
-16	112,000	.7027		44,800	4480

Table II, Note c. Delete entire note. Substitute: “Maximum fatigue load is based on 40% of the ultimate tensile strength. Minimum fatigue load is 10% of maximum fatigue load.”

TABLE III. Bolt grips and lengths (continued). In table, for Grip Number 49, -9 Diameter, change unthreaded pin length from “3.118” to “3.123” and Bolt Length from “3.899” to “3.904”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.

TABLE III. Bolt grips and lengths (continued).
Delete: Values under column headings for -9, -10, and -12 Diameters and substitute the following:

		-9 Diameter		-10 Diameter		-12 Diameter	
	Bolt	Unthreaded		Unthreaded		Unthreaded	
Grip	Design	Pin Length	Bolt	Pin Length	Bolt	Pin Length	Bolt
Number	Grip	(See Figure 1)	Length	(See Figure 1)	Length	(See Figure 1)	Length
50	3.125	3.185	3.966	3.180	4.023	3.185	4.185
51	3.188	3.248	4.029	3.243	4.068	3.248	4.248
52	3.250	3.310	4.091	3.305	4.148	3.310	4.310
53	3.312	3.373	4.154	3.373	4.216	3.373	4.373
54	3.375	3.435	4.216	3.435	4.278	3.435	4.435
55	3.438	3.498	4.279	3.498	4.341	3.498	4.498
56	3.500	3.560	4.341	3.560	4.403	3.560	4.560
57	3.562	3.623	4.404	3.623	4.466	3.623	4.623
58	3.625	3.685	4.466	3.685	4.528	3.685	4.685
59	3.688	3.748	4.529	3.748	4.591	3.748	4.748
60	3.750	3.810	4.591	3.810	4.653	3.810	4.810
61	3.812	3.873	4.654	3.873	4.716	3.878	4.878
62	3.875	3.935	4.716	3.935	4.778	3.940	4.940
63	3.938	3.998	4.779	3.998	4.841	4.003	5.003
64	4.000	4.060	4.841	4.060	4.903	4.065	5.065
65	4.062	4.123	4.904	4.123	4.966	4.128	5.128
66	4.125	4.185	4.966	4.185	5.028	4.190	5.190
67	4.188	4.248	5.029	4.248	5.091	4.253	5.253
68	4.250	4.310	5.091	4.310	5.153	4.315	5.315
69	4.312	4.373	5.154	4.373	5.216	4.378	5.373
70	4.375	4.435	5.216	4.435	5.278	4.440	5.440
71	4.438	4.498	5.279	4.498	5.341	4.503	5.503
72	4.500	4.560	5.341	4.560	5.403	4.565	5.565
73	4.562			4.623	5.466	4.628	5.628
74	4.625			4.685	5.528	4.690	5.690
75	4.688			4.748	5.591	4.753	5.753
76	4.750			4.810	5.653	4.815	5.815
77	4.812			4.873	5.716	4.878	5.878
78	4.875			4.935	5.778	4.940	5.940
79	4.938					5.003	6.003
80	5.000					5.065	6.065
81	5.062					5.128	6.128
82	5.125					5.190	6.190
83	5.188					5.253	6.253
84	5.250					5.315	6.315
85	5.312					5.378	6.378
86	5.375					5.440	6.440
87	5.438					5.503	6.503
88	5.500					5.565	6.565
89	5.562					5.628	6.628
90	5.625					5.690	6.690

Custodians:
Army - AV
Navy - AS
Air Force - 99

Preparing Activity:
DLA-IS

(Project 5306-2053)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:19Z
Check the source to verify that this is the current version before use.