MILITARY SPECIFICATION

DESTRUCTOR, WARHEAD, SINGLE POINT, M13, M13E1 AND M14: SUBASSEMBLIES OR METAL PARTS

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for the subassemblies or metal parts for one type of destructor entitled Destructor, Warhead, Single Point, M13, M13E1 and M14: Subassemblies or Metal Parts which is used in the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

DRAWINGS

ORDNANCE CORPS

8795879	- Body.
8795880	- Fuze, Detonating.
8795885	- Cup.
8795887	- Ring Retaining Assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

8795888 - Holder.
8795889 - Destructor Loading Assembly M13.
8795902 - Destructor, Warhead, Single Point, M14.
8795914 - Nut.
8796069 - Cup Relay.
8797371 - Sleeve.
8799093 - Plate Mounting Safety Locking Device.
8799094 - Plate Mounting Safety Locking Device.
8799096 - Spacer Assembly, Arming Well, M14.
8799100 - Cable, Receptacle, Split Shell.
8799101 - Cable, Receptacle, Split Shell.
8799122 - Spacer, Arming Well, M14.
8810179 - Wrench Assembly.
8810181 - Connector.
EL-8815582 - Equipment Lists.
EL-8815675 - Equipment Lists.
8825224 - Cup Relay M13E7 and M13.
8826698 - Nut M13E7 and M13.
8826704 - Connector M13E7 and M13.
EL-8829542 - Equipment Lists.
8830310 - Destructor, Warhead, Single Point, M13.
8830811 - Destructor Lead Assembly, M13 and M13E1.
8864725 - Destructor Loading Assembly.
8864763 - Destructor, Warhead, Single Point, M13E1.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The destructor parts and assemblies shall comply with all requirements specified on the drawings listed below, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

8795889 - Destructor Loading Assembly M13.
8795902 - Destructor, Warhead, Single Point, M14.
8799093 - Plate Mounting Safety Locking Device.
8799096 - Spacer Assembly, Arming Well, M14.
8810179 - Wrench Assembly.
8830310 - Destructor, Warhead, Single Point, M13.
8830811 - Destructor Lead Assembly, M13 and M13E1.
8864725 - Destructor Loading Assembly.
8864763 - Destructor, Warhead, Single Point, M13E1.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.4 Mounting plate (M14 only).

3.4.1 Continuity and resistance. The circuit shall be electrically continuous and shall have a resistance value of 0.015 maximum (max.) ohm when the circuits in Table I are tested as specified in 4.4.1.

Table I

Between pins on receptacle 8799100 and 8799101

	R-ohms (max)
Pin H to H	0.015
Pin A to A	0.015
Pin A to C on 8799100	0.015
Pin A to C on 8799101	0.015
Pin C to C	0.015
Pin B to B	0.015
Pin B to D on 8799100	0.015
Pin B to D on 8799101	0.015
Pin D to D	0.015
Pin E to E	0.015
Pin F to F	0.015
Pin G to K	0.015

3.4.2 Dielectric strength. There shall be no evidence of dielectric failures as indicated by arcing between electrically isolated pins, or inability to attain and maintain an alternating current (ac) potential of 500 plus or minus (±) 5 cycles per second (cps), when tested as specified in 4.4.2.

3.4.3 Insulation resistance. The insulation resistance shall not be less than 20 megohms when tested as specified in 4.4.3.

3.5 Soldering. All soldering shall comply with the requirements specified in MIL-STD-1460.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.6.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwgs listed in 3.2) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table II. Tests shall be conducted in order specified in Table II.

Table II

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Continuity and resistance (see 3.4.1)		X
3. Dielectric strength (see 3.4.2)		X
4. Insulation resistance (see 3.4.3)		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table III and Table IV), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table III
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table IV
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Mounting plate assembly (M-14 only) (see dwg 8799094 covering a detail of 8799093).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Mounting hole incorrectly located	Gage
	102. Length of mounting plate	Gage
	103. Width of mounting plate	Gage
	104. Pitch diameter of receptacle thread, max	Gage
	105. Connector thread damaged	Visual
	106. Connector incorrectly located	Visual
	107. Cracks or fractures	Visual
	108. Marking missing, incorrect or unidentifiable	Visual
	109. Receptacle thread damaged	Visual
	110. Any contact damaged	Visual
	111. Any component loose or missing	Visual
	112. Connector protrudes below mounting plate surface	Visual
	113. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Protective finish damaged to the extent of exposing base metal	Visual
	202. Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Wiring assembly (M14 only) (see dwg 8799093).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Leads damaged or of incorrect color	Visual
102.	Incorrect wiring	Visual
103.	Cold solder connections	Visual
104.	Incorrect stripping of wire	Visual
105.	Excessive solder	Visual
106.	Sleeving incorrect	Visual
107.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.3 Connector (see dwg 8810181).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pitch diameter of thread min	Gage
102.	Major diameter of thread, min	Gage
103.	Length to end of thread, min	Gage
104.	Inside diameter, min	Gage
105.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Length of thread pilot, max	Gage
202.	Total length	Gage
203.	Length to shoulder, min	Gage
204.	Protective coating damaged to the extent of exposing base metal	Visual
205.	Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Sleeve (for M13 and M14 only) (see dwg 8797371).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Length, min	Gage
102.	Inside diameter, min	Gage
103.	Diameter of flange, min	Gage
104.	Wall thickness	Gage
105.	Crack or fracture	Visual
106.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.5 Nut (for M14 only) (see dwg 8795914).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pitch diameter of thread, min	Gage
102.	Major diameter of thread, min	Gage
103.	Length to end of thread, min	Gage
104.	Inside diameter, min	Gage
105.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Length of thread pilot, max	Gage
202.	Total length	Gage
203.	Length to shoulder, min	Gage
204.	Protective coating damaged to extent of exposing base metal	Visual
205.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.6 Cup, relay (for M13, M13E1 and M14) (see dwg 8796069).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Major:

101.	Inside diameter, min	Gage
102.	Outside diameter, max	Gage
103.	Thickness of bottom, max	Gage
104.	Total length, min	Gage
105.	Any operation missing	Visual
106.	Crack or fracture	Visual
107.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.7 Cup (for M13, M13E1 and M14) (see dwg 8795885).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Major:

101.	Inside diameter, min	Gage
102.	Outside diameter of flange	Gage
103.	Length	Gage
104.	Outside diameter, max	Gage
105.	Thickness of bottom	Gage
106.	Crack or fracture	Visual
107.	Any operation missing	Visual
108.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Protective finish damaged to the extent of exposing base metal	Visual
202.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.8 Holder (for M13, M13E1 and M14) (see dwg 8795888).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Major:

101.	Diameter of flange	Gage
102.	Outside diameter	Gage
103.	Pitch diameter of threads	Gage
104.	Minor diameter of threads, max	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

105.	Length of flange face to shoulder below threads	Gage
106.	Thickness of flange	Gage
107.	Inside diameter	Gage
108.	Total length	Gage
109.	Width of thread undercut, max	Gage
110.	Any operation missing	Visual
111.	Stamping mislocated, incorrect or unidentifiable	Visual
112.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective finish damaged to the extent of exposing base metal	Visual
202.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.9 Ring, retaining assembly (for M13, M13E1 and M14) (see dwg 8795887).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Major diameter of thread, min	Gage
102.	Pitch diameter of thread, max	Gage
103.	Inside diameter	Gage
104.	Total length	Gage
105.	Width of wrench slots, min	Gage
106.	Location of wrench slots, (functional)	Gage
107.	Concentricity of inside diameter with threads	Gage
108.	Depth of wrench slots, min	Gage
109.	Length of thread pilot, max	Gage
110.	Diameter of thread pilot, max	Gage
111.	Any operation missing	Visual
112.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective coating damaged to the extent of exposing base metal	Visual
202.	Evidence of poor workmanship (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.10 Body (for M13, M13E1 and M14) (see dwg 8795879).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pitch diameter of external thread, min.	Gage
102.	Major diameter of external thread, min.	Gage
103.	Pitch diameter of internal thread, max.	Gage
104.	Minor diameter of internal thread, max.	Gage
105.	Length of internal thread, min	Gage
106.	Depth of internal thread cavity	Gage
107.	Diameter of center cavity	Gage
108.	Depth of center cavity	Gage
109.	Thickness	Gage
110.	Diameter of hole below internal threads	Gage
111.	Length of external thread	Gage
112.	Depth and width of slot, min (functional)	Gage
113.	Depth of slot, max	Gage
114.	Length of angled surface	Gage
115.	Diameter of internal thread counterbore	Gage
116.	Location of holes below internal threads	Gage
117.	Depth of internal thread counterbore, max	Gage
118.	Concentricity of hole below internal threads with center cavity including location with angled surface	Gage
119.	Drill spot in bottom of center cavity	Visual
120.	Stamping mislocated, incorrect or unidentifiable	Visual
121.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective finish damaged to the extent of exposing base metal	Visual
202.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.11 Wrench assembly (for M14, M13 and M13E1) (see dwg 8810179).

Categories	Characteristics	Method of Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Critical: None defined.

Major:

101.	Outside diameter below flange	Gage
102.	Inside diameter	Gage
103.	Location and width of lug, min (functional)	Gage
104.	Total length, min	Gage
105.	Thickness of flange, max	Gage
106.	Length of lugs, min	Gage
107.	Length across handles, max	Gage
108.	Handle protrudes beyond interior wall	Visual
109.	Handle visibly bent or tilted	Visual
110.	Stamping mislocated, incorrect or unidentifiable	Visual
111.	Weld inadequate (separation looseness, porosity, etc)	Manual/Visual
112.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Diameter of flange, min	Gage
202.	Protective finish damaged to the extent of exposing base metal	Visual
203.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.12 Spacer, arming well (for M14 only) (see dwg 8799122).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101.	Length	Gage
102.	Width	Gage
103.	Thickness of web-interior	Gage
104.	Location of web-interior	Gage
105.	Length of opening through interior	Gage
106.	Width of opening through interior	Gage
107.	Length of top and bottom relief areas	Gage
108.	Width of top and bottom relief areas	Gage
109.	Location and profile of interior areas	Gage
110.	Location of ten holes near outer surface	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

111. Location of four spring fastener holes.....Gage
112. Location and min. diameter of single hole near outer surface.....Gage
113. Objective evidence relative to material missing or improper (see 3.1).....Visual

Minor:
201. Profile of exterior corners obviously malformed.....Visual
202. Protective coating damaged to extent of exposing base metal.....Visual
203. Evidence of poor workmanship (see 3.6).....Visual

4.3.2.1.13 Spacer assembly, arming well (for M14 only) (see dwg 8799096).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Spring fastener or rivet missing, damaged or insecure	Visual
102.	Either decal missing or misleading (improperly located)	Visual
103.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.14 Cup, relay (M13E1 and M13 only) (see dwg 8825224).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Inside diameter, min	Gage
102.	Outside diameter, max	Gage
103.	Thickness of bottom, min	Gage
104.	Total length, min	Gage
105.	Any operation missing or incomplete	Visual/Manual
106.	Crack or fracture	Visual/Manual
107.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual
202. Protective finish damaged to the extent of exposing base metal.....Visual

4.3.2.1.15 Nut (M13E1 and M13 only) (see dwg 8826698).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pitch diameter of thread, max.	Gage
102.	Major diameter of thread, min.	Gage
103.	Length to end of thread, min.	Gage
104.	Length of thread pilot, max.	Gage
105.	Total length.	Gage
106.	Length to shoulder.	Gage
107.	Inside diameter, min.	Gage
108.	Outside diameter at front end.	Gage
109.	Knurl missing.	Visual
110.	Objective evidence relative to material missing or improper (see 3.1).	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6).	Visual
202.	Protective finish damaged to the extent of exposing base metal.	Visual

4.3.2.1.16 Connector (M13E1 and M13 only) (see dwg 8826704).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Length to end of thread, min.	Gage
102.	Length to thread pilot, max.	Gage
103.	Inside diameter, min.	Gage
104.	Total length.	Gage
105.	Length to shoulder, min.	Gage
106.	Outside diameter at front end.	Gage
107.	Pitch diameter of thread, min.	Gage
108.	Major diameter of thread, min.	Gage
109.	Knurl missing.	Visual
110.	Objective evidence relative to material missing or improper (see 3.1).	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual
202. Protective finish damaged to the extent of exposing base metal.....Visual

4.3.2.1.17 Fuse, detonating (M13E1 and M13 only) (see dwg 8795880).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Length, min	Gage
102.	Any operation missing, improper or incomplete	Visual
103.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.18 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packaging and packing not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Continuity and resistance (M14)	Major
b. Dielectric strength (M14)	Major
c. Insulation resistance (M14)	Major

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Continuity and resistance, dielectric strength and insulation resistance. Each mounting plate and cover assembly shall be tested in accordance with 4.4.1, 4.4.2 and 4.4.3. If any item fails to comply with 3.4.1, 3.4.2 and 3.4.3, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8815582, 8815675 and 8828542). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or IIdentifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Continuity and resistance. Circuit continuity and resistance of the mounting plate assembly (see dwg 879.9093) shall be determined by applying a dc potential of 1.5 volts to the contacts and measuring resistance with a zero calibrated ohmmeter or other suitable means.

4.4.2 Dielectric strength. Each contact in the mounting plate assembly shall be subjected to the required ac potential between electrically isolated contacts and between each contact and the case for a minimum time duration of 15 seconds. The current shall be limited to a maximum of 5 milliamperes to protect human life.

4.4.3 Insulation resistance. Each contact in the mounting plate assembly shall be subjected to a dc potential of 500 ± 25 volts until a steady reading is obtained, using an insulation resistance tester from which a direct reading of resistance in megohms can be obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The destructor parts and assemblies shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The destructor parts and assemblies shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing.

5.2.1 Levels A and C. The destructor parts and assemblies shall be packed in accorance with the applicable instructions contained in MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1348 (Rev. 3) dated 19 March 1965.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A187

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.