MIL-R-87034A(SH)
22 October 1986
SUPERSEDING
MIL-R-87034(SA)
8 July 1977
(See 6.9)

MILITARY SPECIFICATION

REPAIR KIT, DIVERS (MK-12)

This specification is approved for use within the Naval Sea Systems Command Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a kit containin the items and materials necessary for repairing the MK-12 diver's clothing and harness.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

L-P-378 - Plastic Sheet and Strip, Thin Gauge, Polyolefin.
V-T-295 - Thread, Nylon.
GG-R-60 - Razors, Safety; and Blades, Razor.
QQ-N-290 - Nickel Plating (Electrodeposited).
GGG-S-278 - Shears and Scissors.
MMM-A-188 - Adhesive; Urea-Resin-Type (Liquid and Powder).
PPP-B-26 - Bag, Plastic, (General Purpose).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4220
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-W-4088 - Webbing, Textile, Woven Nylon.
MIL-C-4150 - Cases, Transit and Storage, Waterproof and Water-Vaporproof.
MIL-H-9890 - Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous.
MIL-C-14538 - Chromium Plating, Black (Electrodeposited).
MIL-F-21840 - Fastener Tapes, Hook and Pile, Synthetic.
MIL-H-87028 - Harness, Divers (MK-12).
MIL-D-87030 - Divers Dress Suit (MK-12).
MIL-B-87031 - Boots, Divers, MK-12.
MIL-C-87032 - Coverall, Diver's (MK-12).

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MS22007 - Adjuster Assembly, Safety Shoulder Harness Belt.
MS22043 - Snap Hook - Coiled Spring, Parachute, Quick Fit.
MS22045 - Ring - Parachute Harness "V".

2.1.2 Other Government drawings. The following other Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

NAVY

4758692 - MK-12, SSDS, Container, Storage.

AIR FORCE

44B26454 - Link - Safety Belt, Latch Fastener.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

3.2 Materials.

3.2.1 Container and component parts. Repair kits shall consist of a water resistant transit case complete with the following component parts contained therein:

(a) Three tailor's crayons.
(b) One seam roller.
(c) One package razor blades (five to package).
(d) Three zipper panels.
(e) Four square feet laminated foam, both sides, 1/4 inch thick patching material.
(f) Two square feet laminated foam, one side, 1/4 inch thick patching material.
(g) One pair small dry suit boots.
(h) Two pair medium dry suit boots.
(i) Three pair large dry suit boots.
(j) One pair X-large dry suit boots.
(k) One pair of XX-large dry suit boots.
(l) Six neck piece and gasket assembly.
(m) One-half pint chloroprene cement compound.
(n) One electric heat sealing iron.
(o) One can plastic resin adhesive.
(p) One 12 inch heavy duty shears.
(q) Twelve knee patches (coveralls).
(r) Twelve elbow patches (coveralls).
(s) One pair small thigh weight pockets (coveralls).
(t) One pair medium thigh weight pockets (coveralls).
(u) One pair large thigh weight pockets (coveralls).
(v) One pair X-large thigh weight pockets (coveralls).
(w) One pair small calf weight pockets (coveralls).
(x) One pair medium calf weight pockets (coveralls).
(y) One pair large calf weight pockets (coveralls).
(z) One pair X-large calf weight pockets (coveralls).
(aa) Six hip weight pockets (coveralls).
(bb) Six shoulder loops (coveralls).
(cc) Twelve feet of 2 inch wide fastener tape hook.
(dd) Twelve feet of 2 inch wide fastener tape loop.
(ee) Thirty feet of 1-3/4 inch wide nylon webbing.
(ff) Four waist belt adjusters (harness).
(gg) Four shoulder belt adjusters (harness).
(hh) Three waist belt latch and locking pin assemblies (harness).
(ii) Three waist belt links (harness).
(jj) Three V-rings (harness).
(kk) Two buckles, strap bar (harness).
(ll) Four rear jocking strap assemblies (harness).
(mm) Three rear jocking strap snap hooks (harness).
(nn) One ring "V" assembly (harness).
(oo) One ring "V" quick-fit (harness).
(pp) One spool nylon thread.
(qq) Six buckles, non-slip (boot).
(rr) One hundred and two inches strapping (boot).
(ss) Six rectangular wire loops (boot).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

3.2.1.1 Bag, plastic. Bags used to package the loose items of the repair kit shall conform to type II, grade A, style 3 of PPP-B-26. The bags shall be made of polyethylene film conforming to type I, class I, grade A, finish 1 of L-P-378. The size of the bags shall be suitable for the items and quantity intended.

3.2.1.1.1 Labeling. Each bagged package shall have a white paper label inserted within. The part identification specified in 3.2.1 shall be printed in letters not less than 1/8 inch in height upon the label.

3.2.1.2 Container, transit case. The transit case shall conform to type I, style 2, class A of MIL-C-4150 and Drawing 4758692 with the exception that the removable panel between the lower and upper portions of the case is not required.

3.2.1.2.1 Nameplate. The nameplate shall be as specified in MIL-C-4150, except that the following information shall be substituted:

"REPAIR KIT, DIVERS, (MK-12)"

3.2.1.2.2 Listing. A sheet of paper with a listing of all component parts contained within shall be firmly affixed to the inside top of each transit case. The listing shall be identical to that specified in 3.2.1. The listing shall be laminated with plastic on both sides.

3.2.1.3 Tailor's crayon. The tailor's crayon shall be of the standard flat type approximately 1-3/4 inches long by 1-1/2 inches wide. The color of the crayon shall be white.

3.2.1.3.1 Crayon packaging. Three crayons shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.4 Seam roller. The seam roller shall be 1-1/2 to 2 inches wide and 1 to 1-1/4 inches in diameter, equipped with a handle.

3.2.1.5 Razor blades. The razor blades shall be of the single edge style with carbon steel blades as specified in GG-R-60.

3.2.1.5.1 Razor blade packaging. Five razor blades in their commercially supplied boxes shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.6 Zipper panel. The zipper panel shall conform to MIL-D-87030. Each repair kit shall contain three zipper panels.

3.2.1.7 Patching material. Patching material shall consist of 4 square feet of chloroprene foam material 1/4 inch thick with laminated stretch cloth on both sides and 2 square feet of chloroprene foam material 1/4 inch thick with laminated stretch cloth on one side and skin on the other side. The chloroprene material shall conform to MIL-D-87030.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

3.2.1.7.1 Patching material packaging. The 4 square feet of two side nylon shall be supplied full width of the sheet stock (approximately 40 inches) and a height sufficient to give a total area of 4 square feet. The 2 square feet of one side nylon shall be supplied in a rectangular shape 2 feet long by 1 foot wide. The two materials shall be separately rolled upon itself and secured with tape or elastic bands.

3.2.1.8 Dry suit boots. The dry suit boots shall conform to MIL-D-87030. Each repair kit shall contain 8 pair of dry suit boots in the following sizes:

One pair	size 1 (small)
Two pairs	size 2 (medium)
Three pairs	size 3 (large)
One pair	size 4 (X-large)
One pair	size 5 (XX-large)

3.2.1.9 Neck piece and gasket assembly. The neck piece and gasket assembly shall conform to MIL-D-87030. Each repair kit shall contain six neck pieces and gasket assemblies.

3.2.1.10 Adhesive cement. The adhesive cement shall conform to MIL-D-87030 and the requirements specified herein. Each repair kit shall contain a 1-pint can of adhesive cement.

3.2.1.11 Electric heat sealing iron. The electric heat sealing iron shall have a sole plate of approximately 1-3/8 by 4 inches and shall have an adjustable heat setting that can produce a sole plate temperature range of approximately 150 to 550.5 degrees Fahrenheit (°F) (see 6.6).

3.2.1.11.1 Heat sealing iron packaging. One heat sealing iron in its commercially supplied box shall be packed in each repair kit.

3.2.1.12 Plastic resin adhesive. One 8-ounce can of plastic resin adhesive, conforming to type II of MMM-A-188, shall be packed in each repair kit.

3.2.1.13 Shears, heavy duty. The heavy duty 12 inch shears shall conform to type I, class 1, style A, design 2, of GGG-S-278.

3.2.1.14 Knee patches. Knee patches shall conform to MIL-C-87032. The back side of each patch shall have the word "BACK" stamped or printed thereon with an indelible marking medium. The size and color of the stamping or printing shall be sufficient to permit easy identification.

3.2.1.14.1 Knee patch packaging. Twelve knee patches shall be stacked together and packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.15 Elbow patches. Elbow patches shall conform to MIL-C-87032. The back side of each patch shall have the word "BACK" stamped or printed thereon with an indelible marking medium. The size and color of the stamping or printing shall be sufficient to permit easy identification.

3.2.1.15.1 Elbow patch packaging. Twelve elbow patches shall be stacked together and packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

3.2.1.16 Thigh weight pockets. Thigh weight pockets shall conform to MIL-C-87032. The back side of each pocket shall have the word "LEFT" or "RIGHT" as applicable (see MIL-C-87032) stamped or printed thereon with an indelible marking medium. The size and color of the stamping or printing shall be sufficient to permit easy identification.

3.2.1.16.1 Thigh weight pocket packaging. Thigh weight pockets shall be prepared for packaging as follows. Turn down pocket flap and press closed securing fastener tapes. Wrap leg band around back of pocket and over front so that fastener tapes match. Press tapes together thus forming a rectangular pocket approximately 9-1/2 by 13 inches. Six thigh weight pockets, three left leg pockets and three right leg pockets, shall be stacked together and packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.17 Calf weight pockets. Calf weight pockets shall conform to MIL-C-87032. The back side of each pocket shall have the word "LEFT" or "RIGHT" as applicable (see MIL-C-87032), stamped or printed thereon with an indelible marking medium. The size and color of the stamping or printing shall be sufficient to permit easy identification.

3.2.1.17.1 Calf weight pocket packaging. Calf weight pockets shall be prepared for packaging as follows; turn down pocket flap and press closed securing fastener tapes. Wrap leg band around back of pocket and over front so that fastener tapes match. Press tapes together thus forming a rectangular pocket approximately 7-1/2 by 10 inches. Six calf weight pockets, three left leg pockets and three right leg pockets shall be stacked together and packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.18 Hip weight pockets. The hip weight pockets shall conform to MIL-C-87032.

3.2.1.18.1 Hip weight pocket packaging. Six hip weight pockets shall be stacked together and packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.19 Shoulder loops. The shoulder loops shall conform to MIL-C-87032.

3.2.1.19.1 Shoulder loop packaging. Six shoulder loops shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.20 Fastener tape. The 2 inch width hook and pile fastener tape shall conform to type II, class 4, color black 3230 as specified in MIL-F-21840.

3.2.1.20.1 Fastener tape packaging. Twelve feet of fastener tape, hook and pile, shall be rolled upon itself and shall be secured on the end by a piece of its opposite component. Each roll, one of hook and one of pile, shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.21 Nylon webbing. The webbing shall be 1-3/4 inch wide conforming to type XIII specified in MIL-W-4088. The color of the webbing shall be black.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

3.2.1.21.1 Nylon webbing packaging. Thirty feet of webbing shall be tightly rolled upon itself with the end taped down with tape. The roll of tape shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.22 Adjuster, waist belt. The adjusters for the waist belts shall conform to MS22007. The adjuster shall be furnished without finish or plating except as required in 3.3.

3.2.1.22.1 Adjuster, waist belt, packaging. Four waist belt adjusters shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.23 Adjuster, shoulder strap. The adjuster for the shoulder straps shall conform to United States Forgecraft part number 60D562 or equal. The adjuster shall be furnished without finish or plating except as required in 3.3

3.2.1.23.1 Adjuster, shoulder belt packaging. Four shoulder belt adjusters shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.24 Latch and locking pin assembly. The latch and locking pin assembly shall be as specified in MIL-H-87028.

3.2.1.24.1 Latch and locking pin assembly packaging. Three latch and locking pin assemblies shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.25 Link, waist belt. The link shall conform to Drawing 44B26454. The link shall be furnished without finish or plating except as required in 3.3.

3.2.1.25.1 Link, waist belt packaging. Three links shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.26 V-ring. The V-ring shall conform to MS22045. The V-ring shall be furnished without finish or plating except as required in 3.3.

3.2.1.26.1 V-ring packaging. Three V-rings shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.27 Buckle. The buckle shall conform to United States Forgecraft Corporation part number 2060A or equal. The buckle shall be furnished with one tongue and roller and without finish or plating except as required in 3.3.

3.2.1.27.1 Buckle packaging. Two buckles shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.28 Rear jocking strap assembly. The rear jocking strap assembly shall be as specified in MIL-H-87028. Each repair kit shall contain four complete rear jocking strap assemblies.

3.2.1.29 Snap hook, adjustable. The adjustable snap hook shall conform to MS22043. The adjustable snap hook shall be furnished without finish or plating except as required in 3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

3.2.1.29.1 Snap hook, adjustable packaging. Three adjustable snap hooks shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.30 Front jocking strap link. The front jocking strap link shall be as specified in MIL-H-87028.

3.2.1.30.1 Front jocking strap link packaging. One front jocking strap link shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.31 Crotch strap link. The crotch strap link shall conform to MIL-H-87028.

3.2.1.31.1 Crotch strap link packaging. One crotch strap link shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.32 Buckles, boot. The quick release buckle shall conform to type XIV of MIL-H-9890 (see 6.4).

3.2.1.32.1 Buckles, boot packaging. Six boot buckles shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.33 Boot straps. The strapping material shall conform to MIL-B-87031.

3.2.1.33.1 Boot strap packaging. One hundred and two inches of strapping shall be rolled upon itself with the end taped down. The roll of strapping shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.34 Rectangular loops. The loops shall be brass wire, with a chrome or rustproof finish, 0.135 inch diameter. Inside dimensions of the loop opening shall be approximately 1 by 1/2 inch (see 6.5).

3.2.1.34.1 Rectangular loop packaging. Six rectangular loops shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.2.1.35 Thread, nylon. The nylon thread shall conform to type I, class A, size 3 of V-T-295. The color of the thread shall be black AA, CA 66043.

3.2.1.35.1 Thread, nylon packaging. One spool of nylon thread containing a minimum of 500 yards shall be packaged and sealed in a polyethylene bag as specified in 3.2.1.1.

3.3 Finish, metal. Metal hardware items specified in 3.2.1.22 through 3.2.1.31 with the exception of 3.2.1.24, 3.2.1.24.1 and 3.2.1.28, shall be nickel and black chrome plated, after all basic metal heat treatments and mechanical operations such as machining, brazing, welding, forming and perforating of the article have been completed, as follows:

(a) The unfinished metal hardware items shall have a nickel plated finish applied over a copper underplating of 0.0002 to 0.0004 inch thick. The nickel plating shall conform to class 1, grade C of QQ-N-290. After the nickel has been applied, a

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

coating of black chrome shall be applied. The black chrome plating shall be of a sufficient thickness to meet the finish requirements specified in MIL-C-14538.

(b) The stainless steel grommets and washers shall only have the above black chrome plating applied. The stainless steel locking pin, locking pin catch spring and nut, bolt and washer that retain the locking pin catch spring, shall remain unplated.

3.4 Packaging of transit case. The transit case shall be packed as follows. Metal hardware items shall be neatly placed in the bottom of the case and spread out so as to take up the least amount of height. Neatly place all other specified items with the exception of the neoprene foam items. The three zipper panels shall then be placed in the upper portion of the container and spread out flat against the four side walls so as to prevent any sharp bends in the zipper. The remaining neoprene foam items shall be placed in the remaining void in the case. Slight compression of the neoprene foam items is allowed so as to accomplish easy closure of the case.

3.5 Workmanship. The completed repair kit shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL) (see 4.5.1).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. First article inspection shall consist of the examinations specified in 4.5.2, and 4.5.3.

4.4 Quality conformance.

4.4.1 Sampling for quality conformance inspection. Sampling for quality conformance inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated herein.

4.5 Examinations.

4.5.1 Inspection levels and acceptable quality levels. The inspection levels and AQL's expressed in defects per 100 units for visual examinations shall be as follows:

	AQL's	Inspection level
Major	10	II
Total (major and minor combined)	25	II

4.5.2 Visual examination. The completed repair kits shall be examined for defects as specified in table I.

TABLE I. Visual defects.

Defect	Major	Minor
GENERAL		
Any specified component omitted, incomplete or other than type, size or color specified.	X	
Any component defective or otherwise impaired unless otherwise classified herein.	X	
Number of components less than specified.		X
Number of components more than specified.	X	
METALLIC COMPONENTS SPECIFIED IN 3.2.1.23 THROUGH 3.2.1.32		
Any surface rough, misaligned, distorted or contains corrosion, scale, pit, nick, sliver, burr, sharp edge, dent or crack.	X	
Any loose, detached, or otherwise not securely retained or incomplete assembly.	X	
Any component malformed, fractured, broken, chipped or bent.	X	
Webbing adjusters that do not hold webbing or cause webbing to bind or fray.	X	
Protective finish omitted or not as specified.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

TABLE I. Visual defects. - Continued

Defect	Major	Mino
POCKETS		
Calf or thigh weight pockets not folded or folded incorrectly.	X	
Calf or thigh weight pockets not marked on back as specified.	X	
LABELING		
Outside of transit case not labeled as specified.		X
Listing of components missing, incomplete or illegible.	X	
Individually bagged packages not labeled as specified.	X	
PACKAGING		
Any components not packaged and sealed as specified.	X	
Transit case not packed as specified.	X	
Zipper panels packed so as to produce sharp bends.		X

4.5.3 Examination of the end item. Examination of the end item shall be as specified in 4.5.2. The applicable inspection levels and AQL's shall be as specified in 4.5.1. The sample unit shall be one completed repair kit. The lot size shall be expressed in terms of the sample unit.

5. PACKAGING

Not applicable.

6. NOTES

6.1 Intended use. The repair kits are intended to contain the items and equipment necessary for making emergency repairs to the divers dress suit, coverall and harness while at the site of a dive.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) When first article is required (see 3.1).

6.3 First article. When a first article inspection is required, the item should be a first article sample. The first article should consist of one unit. The contracting officer should include specific approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders and that bidders

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 The quick-release buckle specified in 3.2.1.32 may be obtained from Prentice Corp., Kensington, CN 06037, part no. 3832.

6.5 The rectangular loops specified in 3.2.1.34 may be obtained from Wilcox-Crittenden (North & Judd), PO Box 111, Middletown, CN 06457, part no. 595 - 1 inch wide by 1/2 inch high - 0.135 inch diameter steel wire.

6.6 The heat sealing iron specified in 3.2.1.11 may be obtained from Wells Manufacturing Corporation, 202 Littlefield Ave., South San Francisco, CA 94080, type TF-B Thermosealer.

6.7 Metal hardware items specified in 3.2.1.22 through 3.2.1.31 with the exception of the grommets and washers specified in 3.2.1.28, may be obtained from, United States Forgecraft Corporation, PO Box 387, Fort Smith, AR 72902.

6.8 Subject term (key word) listing.

Divers (MK-12) repair kit
Repair kit, divers (MK-12)

6.9 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 4220-N307)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-87034A(SH)	REPAIR KIT, DIVERS (MK-12)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:37Z
Check the source to verify that this is the current version before use.