MIL-STD-1485A
28 April 1978
SUPERSEDING
MIL-STD-1485
25 September 1969

MILITARY STANDARD

CHEMICALS AND CHEMICAL PRODUCTS

USED FOR DOD LAUNDERING

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE

Washington, DC 20301

CHEMICALS AND CHEMICAL PRODUCTS USED FOR DOD LAUNDERING

MIL-STD-1485A

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.

2. Recommended corrections, additions, or deletions should be addressed to the Commander, US Army Natick Research and Development Command, ATTN: DRDNA-TDC, Natick, MA 01760.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

FOREWORD

This book format standard is approved for use by all DOD agencies. This document lists all the items presently necessary to perform laundering operations in military launderies. Many unnecessary or obsolete items have been eliminated. While it is the intent of this document to prevent unnecessary items from cluttering up the supply system, it in no way restricts the Military Services from selecting new improved items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

PARAGRAPH	CONTENTS	PAGE
1.	SCOPE	1
1.1	Coverage	1
2.	REFERENCED DOCUMENTS	2
3.	DEFINITIONS	3
3.1	Laundering	3
4.	GENERAL REQUIREMENTS	4
4.1	Item names	4
4.2	Use	4
4.3	Safety	4
4.4	Storage	4
5.	DETAILED REQUIREMENTS	4
5.1	Soaps	4
5.1.1	Soap, Laundry (High-Titer)	4
5.1.2	Soap, Laundry Powdered (Low-Titer)	5
5.2	Detergents	5
5.2.1	Detergent Laundry (Low Sudsing and Low Phosphate)	5
5.2.2	Detergent Laundry (Low Sudsing and Non-Phosphate)	5
5.2.3	Detergent Laundry (High Sudsing and Low Phosphate)	6
5.3	Alkali soap builders	6
5.3.1	Alkali, Laundry	6
5.3.2	Sodium Orthosilicate	7

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

PARAGRAPH	CONTENTS (cont'd)	PAGE
5.4	Laundry bleach	7
5.4.1	Sodium Hypochlorite	7
5.4.2	Calcium Hypochlorite, Technical	8
5.4.3	Bleach, Laundry, Organic Chlorine	8
5.5	Laundry sour	9
5.5.1	Sour, Laundry; Dry, Sodium Silico Fluoride and Sodium Acid Fluoride (Type I) and, Ammonium Bifluoride (Type II)	9
5.5.2	Sour, Laundry: Dry Form	9
5.6	Laundry blue	10
5.6.1	Bluing, Laundry, Liquid Form	10
5.7	Laundry starch	10
5.7.1	Starch, Laundry, Thin Boiling, Lubricated	10
5.7.2	Starch, Laundry, Thick Boiling, Lubricated	11
5.7.3	Starch, Laundry: Non-Boiling, Instant, Lubricated	11
5.8	Laundry Rinse Additive	12
5.8.1	Rinse Additive, Laundry	12
5.9	Water conditioners	12
5.9.1	Sodium Hexametaphosphate	12
5.10	Special treatment of clothing and materials	13
5.10.1	Insect Repellent, Formula M1960	13
5.10.2	Dye Mix, Seal Brown	13
5.10.3	Dye Mix, Blue Green 320 (Replaces Direct Green 14)	13

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

PARAGRAPH	CONTENTS (cont'd)	PAGE
5.10.4	Dye Mix, Dark Green Shade OG-109	14
5.10.5	Water Repellent Compound, Textile Finish, Aqueous	14
5.11	Miscellaneous chemicals and chemical products used in laundering	15
5.11.1	Bentonite	15
5.11.2	Wax, Paraffin, Technical	15
5.11.3	Petrolatum, Technical	15
5.11.4	Kerosene	16
5.11.5	Sodium Thiosulfate	16
5.11.6	Sodium Chloride, Technical	16
5.11.7	Amyl Acetate, Technical	17
5.11.8	Oxalic Acid, Dehydrated, Technical	17
5.11.9	Impregnite XXCC3	18
5.11.10	Sodium Carbonate, Anhydrous, Technical	18
5.11.11	Antisetting Compound, Decontaminating Slurry	19
5.11.12	Organic Chelating Agent	19
5.11.13	Decontaminating Agent	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Coverage. This standard covers the nomenclature, description, use, cautions and storage data for items of supply used for DOD laundering. This standard presents data relative to laundering only, although many of these items may have other uses as well. The following list of items are covered by this standard.

Name	Size of Container
Alkali, Laundry	100-lb. (45 kg) drum
Amyl Acetate	16 fluid oz (473 ml) bottle
Antisetting Compound, Decontaminating Slurry	12-1/2-lb. (5.7 kg) bag
Bleach, Laundry, Organic Chlorine (15%)	25, 50, 125-lb. drums
Bluing, Laundry; Liquid Form: For Sour or Nonsour	1-qt. (0.94 liter) bottle
Bluing, Sour, Laundry; Dry Form	50-lb. (22.7 kg) drum
Calcium Hypochlorite (65%)	3-3/4-lb. (1.7 kg) bottle
Calcium Hypochlorite (65%)	100-lb. (45 kg) drum
Decontaminating Agent "STB"	50-lb. (22.7 kg) drum
Detergent, Laundry (Low Sudsing and Low Phosphate)	25-lb. (11.3 kg) drum (type I)
Detergent, Laundry (Low Sudsing and Low Phosphate)	50-lb. (22.7 kg) drum (type I)
Detergent, Laundry (Low Sudsing Nonphosphate)	25-lb. (11.3 kg) drum (type II)
Detergent, Laundry (Low Sudsing Nonphosphate)	50-lb. (22.7 kg) bag (type II)
Detergent, Laundry (High Sudsing and Low Phosphate)	25-lb. (11.3 kg) drum (type III)
Detergent, Laundry (High Sudsing and Low Phosphate)	200-lb. (90.7 kg) drum (type III)
Dye Mix, Dark Green Shade OG-109	4-lb. (1.8 kg) box
Dye Mix, Blue Green 320	25-lb. (11.3 kg) pail
Dye Mix, Seal Brown	25-lb. (11.3 kg) pail
Impregnite XXCC3	75-lb. (34 kg) drum
Insect Repellent	1-gal. (3.8 L) can
Kerosine	5-gal. (19 liter) can
Organic Chelating Agent	55-gal. (208 liters) drum
Oxalic Acid	100-lb. (45 kg) drum
Petrolatum, Technical	35-lb. (15.8 kg) pail (type I)
Rinse Additive, Laundry	175-lb. (79 kg) drum (type II)
Rinse Additive, Laundry	55-gallon (208 liters) drum (type III)
Soap, Laundry, Powdered (High Titer)	100-lb. (45 kg) drum Type I Class 2
Soap, Laundry, Chip (High Titer)	100-lb. (45 kg) drum Type I Class 1
Soap, Laundry (Low-Titer)	50-lb. (22.7 kg) sack Type II Class 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

Name	Size of Container
Sodium Carbonate (Soda Ash)	100-lb. (45 kg) bag
Sodium Chloride	100-lb. (45 kg) bag
Sodium Hexametaphosphate (Flake)	100-lb. (45 kg) bag
Sodium Hypochlorite	5-gal. (19 liter) bottle
Sodium Hypochlorite	55-gal. (208 liter) drum
Sodium Orthosilicate	100-lb. (45 kg) drum
Sodium Thiosulfate	100-lb. (45 kg) drum
Sour, Laundry	50-lb. (22.7 kg) drum
Sour, Laundry	100-lb. (45 kg) drum
Starch, Laundry, Thick boiling, lubricated	50-lb. (22.7 kg) sack
Starch, Laundry, Thick boiling, lubricated	265-lb. (120 kg) drum
Starch, Laundry, Thin boiling, lubricated	1-lb. (0.45 kg) box
Starch, Laundry, Thin boiling, lubricated	265-lb. (120 kg) drum
Starch, Laundry; Non-Boiling; Instant, Lubricated	50-lb. (22.7 kg) sack
Water Repellent Compound, Textile Finish, Aqueous	5-gal. (19 liter) pail
Wax, Paraffin, Technical (Cake Form)	1-lb. (0.45 kg) package

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on the date of invitations for bid or request for proposal, form a part of this standard to the extent specified herein.

SPECIFICATIONS

FEDERAL

O-B-420 - Bleach, Laundry, Organic Chlorine
O-B-491 - Bluing, Laundry
O-C-114 - Calcium Hypochlorite, Technical
O-O-690 - Oxalic Acid, Dihydrate, Technical
O-S-571 - Sodium Carbonate, Anhydrous, Technical
O-S-602 - Sodium Hypochlorite Solution
O-S-635 - Sodium Polyphosphate, Technical
O-S-1926 - Sodium Chloride, Technical
P-A-450 - Alkali, Laundry, Containing Carboxymethylcellulose
P-D-245 - Detergent (Powder, Flake, Bead or Granular) For Laundering and Dishwashing

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

P-L-130	-	Laundry Sour and Blue
P-R-001420	-	Rinse Additive, Laundry
P-S-651	-	Sodium Orthosilicate, Technical
P-S-683	-	Sour, Laundry (Fluoridated)
P-S-1792	-	Soap, Laundry (Neutral and Built)
TT-A-511	-	Amyl Acetate
TT-W-156	-	Water Repellent Compound, Textile Finish
VV-K-211	-	Kerosene
VV-P-236	-	Petrolatum, Technical
VV-W-95	-	Wax, Paraffin, Technical
JJJ-S-701	-	Starch, Laundry

MILITARY

MIL-I-285	-	Impregnite, Unstabilized (CC2) and Stabilized (XXCC3)
MIL-D-2273	-	Dye Mix (Recoloring and Field-Dyeing)
MIL-I-12123	-	Insect Repellent Clothing Application, Formula M1960
MIL-D-12468	-	Decontaminating Agent, STB
MIL-A-51027	-	Antisetting Compound, Decontaminating Slurry M2

STANDARD

MILITARY

MIL-STD-129	-	Marking for Shipment and Storage

MILITARY PUBLICATIONS

NEDTRA 10293	-	Ship's Serviceman Laundry Handbook (RTA/NRCC) (1510)
TM 10-280	-	Field Laundry, Bath and Clothing Exchange Operations
FM 10-17	-	Army Fixed Laundry Organization and Operation

NOTE: The above referenced Military publications are not referenced in sections 3, 4 or 5 of this Standard but should be used in conjunction with this document when conducting laundering operations.

3. DEFINITIONS

3.1 Laundering. Laundering is the process by which soiled clothing and other fabric items are received, marked, classified and cleaned with the aid of mechanical action in water solutions of detergents and other additives. The laundering process also includes drying and folding of the washed items and, if specified, starching, water repellent treating, ironing, or pressing as maybe required.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:30Z
Check the source to verify that this is the current version before use.

4. GENERAL REQUIREMENTS

4.1 Item names. Official Department of Defense nomenclature, taken from DD Form 146 (FIINs), is used for all items available through the central supply system.

4.2 Use. The use data found in Section 5 of this standard has been taken from applicable specifications and military publications. The use data is limited to laundering operations only.

4.3 Safety. All toxic or hazardous chemicals are noted as such under the "caution" paragraphs of Section 5, and must be labeled in accordance with MIL-STD-129 and the Manufacturing Chemists' Association's "Guide to Precautionary Labeling of Hazardous Chemicals".

4.4 Storage. The storage data found in Section 5 of this standard is for ideal storage conditions. The storage life of most chemicals will be shortened if they are exposed to moisture, direct sunlight or temperature extremes.

5. DETAILED REQUIREMENTS

5.1 Soaps.

5.1.1 Name. Soap, Laundry (High-Titer).

NSN 7930-00-224-7901 100-pound (45 kg) drum (Type I Class 2)
NSN 7930-00-579-8532 100-pound (45 kg) drum (Type I Class 1)

5.1.1.1 Specification. P-S-1792 - Soap, Laundry, (Neutral and Built).

5.1.1.2 Description. The Type I Class 1 soap has a light color and is in chip or flake form. The Type I Class 2 soap has a light color and is in powdered form.

5.1.1.3 Use. High-titer soap is used in washing white (undyed) and fast colored items at high temperatures for good soil removal. It is also used in field launderies for deimpregnation of protective clothing. This soap must be used in soft water and may be used with added alkali in the laundering process.

5.1.1.4 Precautions. Avoid breathing soap dust as it can be irritating. Also avoid prolonged contact with skin because it may cause dermatitis.

5.1.1.5 Storage. Store away from moisture.

Source: https://assist.dla.mil -- Downloaded: 202640-24T00:30Z
Check the source to verify that this is the current version before use.

5.1.2 Name. Soap, Laundry Powdered (Low-Titer).

NSN 7930-00-664-0337 50-pound (22.7 kg) bag Type II Class 2

5.1.2.1 Specification. P-S-1792 - Soap, Laundry (Neutral and Built).

5.1.2.2 Description. The Type II, Class 2 soap has a uniform light color and is in a powdered or granular form.

5.1.2.3 Use. Low-titer soap is intended primarily for use with soft water in cleaning wool, synthetic fabrics, and permanent press items requiring low temperature 90° - 100°F (32° - 38°C) washing.

5.1.2.4 Precautions. Avoid breathing soap dust as it can be irritating. Also avoid prolonged contact with the skin because it may cause dermatitis.

5.1.2.5 Storage. Store in a cool, dry place.

5.2 Detergents.

5.2.1 Name. Detergent Laundry (Low Sudsing and Low Phosphate).

NSN 7930-00-990-7391 25-lb. (11.3 kg) drum (type I)
NSN 7930-00-929-1220 50-lb. (22.7 kg) drum (type I)

5.2.1.1 Specification. P-D-245 - Detergent for Laundry and Dishwashing.

5.2.1.2 Description. A combination of a low foaming, synthetic, organic, nonionic surfactant; polyphosphates, silicates, sodium carboxymethylcellulose, and optical brighteners.

5.2.1.3 Use. For laundering cottons, white cotton/polyester fabrics and white durable press items in soft and hard water.

5.2.1.4 Precautions. Avoid unecessary breathing of detergent dust as it can be irritating. Also, avoid prolonged skin contact because it can cause dermatitis.

5.2.1.5 Storage. Store in a cool, dry place.

5.2.2 Name. Detergent Laundry (Low Sudsing and Nonphosphate).

NSN 7930-00-929-1221 25-lbs. (11.3 kg) drum (type II)
NSN 7930-00-252-6797 50-lbs. (22.7 kg) bag (type II)

Source: https://assist.dla.mil -- Downloaded: 202640-24T00:30Z
Check the source to verify that this is the currentversion before use.

5.2.2.1 Specification. P-D-245 - Detergent for Laundering and Dishwashing.

5.2.2.2 Description. A combination of a low foaming, synthetic organic, nonionic sufactant; sodium carboxymethylcellulose, borax and optical brighteners.

5.2.2.3 Use. For laundering woolens and colored durable press fabrics in soft, hard and sea water and cotton in sea water.

5.2.2.4 Precautions. Avoid unecessary breathing of detergent dust as it can be irritating. Also, avoid prolonged skin contact because it can cause dermatitis.

5.2.2.5 Storage. Store in a cool, dry place.

5.2.3 Name. Detergent Laundry (High Sudsing and Low Phosphate)

NSN 7930-00-634-0342 25-lbs. (11.3 kg) drum (type III)
NSN 7930-00-634-0341 200-lbs. (90.7 kg) drum (type III)

5.2.3.1 Specification. P-D-245 - Detergent for Laundry and Dishwashing.

5.2.3.2 Description. A combination of high foaming, synthetic organic, anionic surfactant; polyphosphates, silicates, sodium carboxymethylcellulose and optical brighteners.

5.2.3.3 Use. For manual washing of dishes and clothing and for use in some top loading fabric washing machines, and for general cleaning purposes.

5.2.3.4 Precautions. Avoid unecessary breathing of detergent dust as it can be irritating. Also, avoid prolonged skin contact because it can cause dermatitis.

5.2.3.5 Storage. Store in a cool dry place.

5.3 Alkali soap builders.

5.3.1 Name. Alkali, Laundry.

NSN 7930-00-281-1839 100-pound (45 kg) drum

5.3.1.1 Specification. P-A-450 - Alkali, Laundry, Containing Carboxymethylcellulose.

5.3.1.2 Description. The laundry alkali is in powdered or granular form and contains sodium hydroxide, sodium carbonate and sodium carboxymethylcellulose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.3.1.3 Use. This laundry alkali is intended for use with synthetic detergents or soaps in the heavy duty laundering of cotton fabrics in soft or hard water. It is not intended for use in laundering woolen, silk or synthetic fabrics.

5.3.1.4 Precautions. Use gloves when handling. Laundry alkali can cause severe burns to skin and eyes. Avoid contact with skin, eyes and clothing. Do not take internally. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.3.1.5 Storage. Keep container closed and store in a cool, dry place.

5.3.2 Name. Sodium Orthosilicate.

NSN 6810-00-264-6523 100-pound (45 kg) drum

5.3.2.1 Specification. P-S-651 - Sodium Orthosilicate, Technical.

5.3.2.2 Description. Sodium orthosilicate is a free-flowing intimate mixture of caustic soda and sodium metasilicate in granular or flake form.

5.3.2.3 Use. Sodium orthosilicate is intended for laundry and general cleaning purposes as a builder to increase the cleansing action of the soaps and detergents, and to neutralize the acidity induced by garments and soils in wash solutions.

5.3.2.4 Precautions. Use gloves and goggles when handling. Sodium orthosilicate can cause severe burns to skin and eyes. Avoid contact with skin, eyes and clothing. Do not take internally. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.3.2.5 Storage. Keep container closed and store in a cool, dry place.

5.4 Laundry bleach.

5.4.1 Name. Sodium Hypochlorite.

NSN 6810-00-900-6276 5-gallon (19 liter) bottle (5%) Available Chlorine
NSN 6810-01-029-5565 55-gal. (208 liters) drum (15%) Available Chlorine

5.4.1.1 Specification. O-S-602 (Grade 1) Sodium Hypochlorite Solution. There is no specification covering the 15% Sodium Hypochlorite.

5.4.1.2 Description. Sodium hypochlorite is a clear liquid having a chlorine odor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.4.1.3 Use. Sodium hypochlorite is a bleach intended to remove yellowness from white fabrics and to remove stains. It also helps to sanitize washed materials.

5.4.1.4 Precautions. Do not take internally. Keep away from heat, acids, reducing agents and oxidizing agents.

5.4.1.5 Storage. Sodium hypochlorite should be kept in tightly closed containers and stored in a cool, dry place.

5.4.2 Name. Calcium Hypochlorite, Technical.

NSN 6810-00-242-4770 3-3/4-pound (1.7 kg) bottle
NSN 6810-00-255-0472 100-pounds (45 kg) drum

5.4.2.1 Specification. O-C-114 - Calcium Hypochlorite, Technical.

5.4.2.2 Description. Calcium hypochlorite is a white powder containing a minimum of 65% available chlorine.

5.4.2.3 Use. Calcium hypochlorite is used in launderies having equipment and facilities for preparing bleach solutions (1 percent available chlorine) of sodium hypochlorite from this compound. It is also used in decontamination procedures.

5.4.2.4 Precautions. Do not allow dry calcium hypochlorite to come in contact with skin or eyes, because it can be extremely irritating and is poisonous. Keep away from heat and acids, oils and paints. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.4.2.5 Storage. Keep container tightly closed and store in a cool, dry place away from acids.

5.4.3 Name. Bleach, Laundry, Organic Chlorine.

NSN 6850-00-063-2842 25-pound (11.3 kg) drum
NSN 6850-00-063-2843 50-pound (22.7 kg) drum
NSN 6850-00-063-2841 125-pound (56.7 kg) drum

5.4.3.1 Specification. O-B-420 - Bleach, Laundry, Organic Chlorine.

5.4.3.2 Description. This bleach is a white powder or bead containing an organic chlorine-liberating compound. The laundry bleach does not contain caustic soda.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.4.3.3 Use. This bleach is intended to remove yellowness from white fabrics and to remove stains. It may be added directly to the wash wheel in powdered form.

5.4.3.4 Precautions. Do not take internally. Keep away from heat, acids, reducing agents and oxidizing agents.

5.4.3.5 Storage. This bleach should be kept in tightly closed containers and stored in a cool, dry place.

5.5 Laundry sour.

5.5.1 Name. Sour, Laundry; Dry, Sodium Silico Fluoride and Sodium Acid Fluoride (Type I) and, Ammonium Bifluoride (Type II).

NSN 7930-00-291-8321 (Type I) 50-lb. (22.7 kg) drum
NSN 7930-00-924-5365 (Type II) 50-lbs. (22.7 kg) drum
NSN 7930-00-252-0509 (Type I) 100-lbs. (45 kg) drum
NSN 7930-00-924-5366 (Type II) 100-lbs. (45 kg) drum

5.5.1.1 Specification. P-S-683 - Sour, Laundry (Fluoridated).

5.5.1.2 Description. Type I laundry sour is comprised of dry flakes, crystals or powder of sodium silico fluoride and sodium acid fluoride.

Type II laundry sour is comprised of dry flakes of ammonium bifluoride.

5.5.1.3 Use. Laundry sour is intended for use in washing formulas to neutralize residual alkali present either in the fabrics after rinsing or in the water supply, and to remove rust stains and prevent discoloration of the fabrics. Type II laundry sour is more readily soluble than Type I, and should be used when required.

5.5.1.4 Precautions. Fatal if swallowed, causes severe burns which may not be immediately visible or painful. Wear protective clothing and avoid contact with skin and eyes. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.5.1.5 Storage. Keep container tightly closed and store in a cool, dry place.

5.5.2 Name. Sour, Laundry: Dry Form (Type I, Class 2).

NSN 7930-00-205-2882 50-pound (22.7 kg) drum (Type I, Class 2)

5.5.2.1 Specification. P-L-130 - Laundry Sour (Bluing and Brighteners).

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.5.2.2 Description. Laundry blue and sour consists of a blue dye mixed with acid salts to produce a product that neutralizes and blues fabrics at the same time.

5.5.2.3 Use. Laundry blue and sour is used in launderies to neutralize any residual alkali that may be present in fabrics after completion of the rinsing cycle, to neutralize any alkali that may be present in the water supply, and to uniformly tint cotton fabrics.

5.5.2.4 Precautions. In hospital laundry work do not use on babies' diapers.

5.5.2.5 Storage. No special storage requirements.

5.6 Laundry blue.

5.6.1 Name. Bluing, Laundry, Liquid Form.

NSN 7930-00-250-2619 1-quart (0.946 liter) bottle

5.6.1.1 Specification. O-B-491 - Bluing, Laundry.

5.6.1.2 Description. This laundry bluing is a water solution of a blue dye.

5.6.1.3 Use. Laundry bluing is intended for general laundry use to mask the yellowness of fabrics. The bluing performs satisfactorily in acid, alkaline or neutral solutions and may be used whether or not souring is done.

5.6.1.4 Precautions. In hospital laundry work, do not use on babies' diapers.

5.6.1.5 Storage. No special storage necessary.

5.7 Laundry starch.

5.7.1 Name. Starch, Laundry, Thin Boiling, Lubricated (Type I, Classes 1 and 2).

NSN 7930-00-819-6081 1-pound (0.45 kg) box (Type I, class 1) (corn or wheat)
NSN 7930-00-997-6002 265-pound (120 kg) drum (Type I, class 2) (equal parts corn and wheat)

5.7.1.1 Specification. JJJ-S-701 - Starch, Laundry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.7.1.2 Description. Laundry starch is a free-flowing white to cream colored powder or granular material.

5.7.1.3 Use. Type I laundry starch is intended to produce a full bodied finish without imparting stiffness.

5.7.1.4 Precautions. None.

5.7.1.5 Storage. Store in a dry place.

5.7.2 Name. Starch, Laundry, Thick Boiling, Lubricated (Type III, Class 1)

NSN 7930-00-597-6108 50-pound (22.7 kg) drum (Type III, Class 1)
NSN 7930-00-851-6719 265-pound (120 kg) drum (Type III, Class 1)

5.7.2.1 Specification. JJJ-S-701 - Starch, Laundry.

5.7.2.2 Description. Laundry starch is free-flowing white to cream colored powder or granular material.

5.7.2.3 Use. Type III laundry starch is intended for use where a stiff or firm finish is required.

5.7.2.4 Precautions. None.

5.7.2.5 Storage. Store in a dry place.

5.7.3 Name. Starch, Laundry: Non-Boiling: Instant, Lubricated (Type V).

NSN 7930-00-841-6362 50-pound (22.7 kg) sack (Type V)

5.7.3.1 Specification. JJJ-S-701 - Starch, Laundry.

5.7.3.2 Description. Laundry starch is a free-flowing white to cream colored powder or granular material.

5.7.3.3 Use. This starch is used in cool or lukewarm water, without cooking, to produce a full bodied finish on clothing items. It is used when space is at a premium or starch cooking equipment is not available.

5.7.3.4 Precautions. None.

5.7.3.5 Storage. Store in a dry place.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:30Z
Check the source to verify that this is the current version before use.

5.8 Laundry Rinse Additive.

5.8.1 Name. Rinse Additive, Laundry.

NSN 7930-00-965-9830 175-pound (79 kg) drum (type II) powder form
NSN 7930-00-764-6606 55-gallon (208 liter) drum (type III) liquid form

5.8.1.1 Specification. P-R-1420 - Rinse Additive, Laundry.

5.8.1.2 Description. Type II rinse additive is a uniform powder consisting of a mixture of a quaternary ammonium compound and a water soluble carrier, so formulated that it will not cake.

Type II rinse additive is a single phase, homogeneous solution.

5.8.1.3 Use. Type II rinse additive is used in the final rinse water of a laundering operation to impart softness to fabrics, reduce drying time, eliminate static, minimize wrinkling and linting and improve flatwork ironer and press operations. Type III rinse additive is used for the treatment of nurses polyester/cotton white uniforms or other items that require good antistatic properties.

5.8.1.4 Precautions. None.

5.8.1.5 Storage. Store in a dry place.

5.9 Water conditioners.

5.9.1 Name. Sodium Hexametaphosphate (Type II granular form).

NSN 6810-00-949-8331 100-pound (45 kg) bag (Type II granular form)

5.9.1.1 Specification. O-S-635 - Sodium Polyphosphates, Technical.

5.9.1.2 Description. Sodium hexametaphosphate is a water-soluble, white flake.

5.9.1.3 Use. Sodium hexametaphosphate is used to soften water in launderies and as a substitute for organic chelating agents.

5.9.1.4 Precautions. Sodium hexametaphosphate can be irritating to skin and eyes. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.9.1.5 Storage. Sodium hexametaphosphate should be stored in a cool, dry place.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:30Z
Check the source to verify that this is the current version before use.

5.10 Special treatment of clothing and materials.

5.10.1 Name. Insect Repellent, Formula M1960.

NSN 6840-00-270-6200 1-gallon (3.8 L)

5.10.1.1 Specification. MIL-I-12123 - Insect Repellent, Clothing Application, Formula M-1960.

5.10.1.2 Description. Formula M-1960 consists of 30% 2-Butyl-2-ethyl-1, 3-propanediol, 30% Benzyl benzoate, 30% N-Butyl acetanilide and 10% Polyoxy-eythlene (20) sorbitan monooleate.

5.10.1.3 Use. Formula M-1960 is to be used for the impregnation of clothing to protect against mites, fleas, ticks, mosquitoes and land leaches.

5.10.1.4 Precautions. Keep away from heat or flame. Harmful if swallowed. Concentrate causes skin irritaion, may cause eye irritation. Wash after handling. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.10.1.5 Storage. Store away from heat, flame and oxidizing agents.

5.10.2 Name. Dye Mix, Seal Brown.

NSN 6820-00-255-8199 25-pound (11.3 kg) pail (Type III)

5.10.2.1 Specification. MIL-D-2273 - Dye Mix: (Recoloring and Field Dyeing).

5.10.2.2 Description. Seal Brown Dye Mix is a homogeneous mixture of Direct Brown 31, Direct Red 1 and Direct Black 38.

5.10.2.3 Use. Seal Brown Dye Mix is used for dyeing previously colored cotton or woolen clothing items and cotton hospital linens.

5.10.2.4 Precautions. Avoid prolonged contact with skin.

5.10.2.5 Storage. Store in a dry place.

5.10.3 Name. Dye Mix, Blue Green 320 (Replaces Direct Green 14).

NSN 6820-00-822-2500 25-pound (11.3 kg) pail (Type V)

5.10.3.1 Specification. MIL-D-2273 - Dye Mix: (Recoloring and Field Dyeing).

5.10.3.2 Description. Dye mix, Blue Green 320 is a homogeneous powder consisting of Direct Green 6, Direct Blue 6 and Direct Black 38.

Source: https://assist.dla.mil -- Downloaded: 202640-24T00:30Z
Check the source to verify that this is the currentversion before use.

5.10.3.3 Use. Dye Mix, Blue Green 320 is used for dyeing operating room cotton linens.

5.10.3.4 Precautions. Avoid prolonged contact with skin.

5.10.3.5 Storage. Store in a dry place.

5.10.4 Name. Dye Mix, Dark Green Shade OG-109.

NSN 6820-00-732-2682 4-pound (1.8 kg) box containing 12 packages. Each package contains dye mix, common salt and after fixing material. (Type IV)

5.10.4.1 Specification. MIL-D-2273 - Dye Mix: (Recoloring and Field-Dyeing).

5.10.4.2 Description. Dye Mix, Dark Green Shade OG-109 is a homogeneous mixture of Direct Blue 71, Direct Orange 37, Direct Orange 34 or Direct Orange 61.

5.10.4.3 Use. Dye Mix, Dark Green Shade OG-109 is a camouflage color and is used to achieve field camouflage of white cotton handkerchiefs, towels, summer drawers and undershirts.

5.10.4.4 Precautions. Avoid prolonged contact with skin.

5.10.4.5 Storage. Store in a dry place.

5.10.5 Name. Water Repellent Compound, Textile Finish, Aqueous.

NSN 8030-00-264-3875 5-gallon (19 liter) pail (Type I)

5.10.5.1 Specification. TT-W-156 - Water Repellent Compound, Textile Finish.

5.10.5.2 Description. Type I water repellent compound is a light colored, stable, homogeneous wax or resin emulsion of the oil-in-water type.

5.10.5.3 Use. Type I water repellent compound (aqueous) is applied to cotton fabrics to obtain water repellency on untreated items and to replenish water repellent finishes which have deteriorated or which have been removed during laundering.

5.10.5.4 Precautions. Keep from freezing.

5.10.5.5 Storage. Store at above freezing temperatures and do not store for longer than 6 months.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.11 Miscellaneous chemicals and chemical products used in laundering.

5.11.1 Name. Bentonite.

No Stock Number - Buy commercial

5.11.1.1 Specification. None.

5.11.1.2 Description. Bentonite is a fine powdered clay.

5.11.1.3 Use. Bentonite is used with wash formulas for washing greasy wiping rags. Bentonite aids in the suspension of soils removed, and prevents their redeposition on fabrics during the wash and rinse cycles.

5.11.1.4 Precautions. None.

5.11.1.5 Storage. Store on the floor in a dry place.

5.11.2 Name. Wax, Paraffin, Technical.

NSN 9160-00-285-2044 1-pound (0.45 kg) package (Type I, Grade A)

5.11.2.1 Specification. VV-W-95 - Wax, Paraffin, Technical.

5.11.2.2 Description. Type I paraffin wax is fully refined cake wax free from odor and taste.

5.11.2.3 Use. Paraffin wax is used in cleaning press heads.

5.11.2.4 Precautions. Keep away from open flame.

5.11.2.5 Storage. Store in a cool place away from heat or flame.

5.11.3 Name. Petrolatum, Technical.

NSN 9150-00-250-0928 35-pound (15.8 kg) pail

5.11.3.1 Specification. VV-P-236 - Petrolatum, Technical.

5.11.3.2 Description. Petrolatum is a homogeneous and refined grease.

5.11.3.3 Use. Petrolatum is used to lubricate washers, tumblers and flatwork irons.

5.11.3.4 Precautions. Keep away from open flame.

5.11.3.5 Storage. Store in a cool place away from open flame.

Source: https://assist.dla.mil -- Downloaded: 202640-24T00:30Z
Check the source to verify that this is the current version before use.

5.11.4 Name. Kerosene.

NSN 9140-00-242-6749 5-gallon (19 liter) can

5.11.4.1 Specification. VV-K-211 - Kerosene.

5.11.4.2 Description. Kerosene is a pale yellow to water-white, oily, liquid hydrocarbon.

5.11.4.3 Use. Kerosene is used in the procedure for deimpregnation of protective clothing (clothing treated with Impregnite XXCC3).

5.11.4.4 Precautions. Avoid unnecessary breathing of the vapors and contact with the skin. Keep away from heat or open flame.

5.11.4.5 Storage. Store in a cool place away from open flame and oxidizing agents.

5.11.5 Name. Sodium Thiosulfate.

NSN 6810-01-035-0442 100-lb. (45 kg) drum

5.11.5.1 Specification. None.

5.11.5.2 Description. Sodium thiosulfate is an odorless chemical in the form of colorless crystals or white granules.

5.11.5.3 Use. Sodium thiosulfate is used as an antichlor and for the deimpregnation of protective clothing by washing.

5.11.5.4 Precautions. Sodium thiosulfate emits dangerous fumes if heated to decomposition.

5.11.5.5 Storage. Sodium thiosulfate should be stored away from heat.

5.11.6 Name. Sodium Chloride, Technical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

NSN Class	Pkg. Data	Condition	Spec. Type
NSN 6810-00-227-0437	100-lb. (45 kg) bag	Crude	I
NSN 6810-00-174-5157	100-lb. (45 kg) bag	Processed	II
NSN 6810-00-914-1568	100-lb. (45 kg) bag	Processed	III

5.11.6.1 Specification. O-S-1926 - Sodium Chloride, Technical.

5.11.6.2 Description. Sodium chloride is free-flowing, clean, white, grayish-white or brownish-white in color.

5.11.6.3 Use. Sodium chloride is used to deposit dyestuffs on fabrics to prevent bleeding and for regenerating water softening units in fixed DOD laundries.

5.11.6.4 Precautions. None.

5.11.6.5 Storage. Store in a dry area.

5.11.7 Name. Amyl Acetate, Technical.

NSN 6810-00-174-6604 16 fluid oz. (473 ml) bottle

5.11.7.1 Specification. TT-A-511 - Amyl Acetate, Technical.

5.11.7.2 Description. Amyl acetate is a flammable, colorless liquid with a pungent disagreeable odor.

5.11.7.3 Use. Amyl acetate is used in spotting procedures for removing paint, lacquer, nail polish and mimeograph correction fluid.

5.11.7.4 Precautions. Use only in a well ventilated area, avoid breathing vapors and keep away from heat or flame.

5.11.7.5 Storage. Amyl acetate should be stored in its original container in a cool, well ventilated place out of the direct rays of the sun. It should be kept away from open flame and oxidizing agents.

5.11.8 Name. Oxalic Acid, Dehydrated, Technical.

NSN 6810-00-264-6625 100-pound (45 kg) drum (Class 2)

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:30Z
Check the source to verify that this is the current version before use.

5.11.8.1 Specification. O-O-690 - Oxalic Acid, Dehydrate, Technical.

5.11.8.2 Description. Oxalic acid is a white, poisonous transparent crystal that effloresces in dry air.

5.11.8.3 Use. Oxalic acid is used for removing rust from fabrics, for neutralizing alkalis and for cleaning laundry machines.

5.11.8.4 Precautions. Avoid contact with skin and eyes. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention. Use only in a well ventilated area and avoid breathing the dust.

5.11.8.5 Storage. Do not store near food products. Store in a cool, dry place away from oxidizing materials. Keep containers tightly closed.

5.11.9 Name. Impregnite XXCC3.

NSN 6850-00-281-4244 75-pound (34 kg) drum (Type II)

5.11.9.1 Specification. MIL-I-285 - Impregnite, Ustablized (CC2) and Stablized (XXCC3).

5.11.9.2 Description. Impregnite XXCC3 is a mixture of N,N'-dichloro-bis-2, 4, 6-trichlorophenyl urea, and zinc oxide.

5.11.9.3 Use. Impregnite XXCC3 is used to impregnate clothing used to protect personnel against the action of vesicant-type chemical agents.

5.11.9.4 Precautions. Keep away from open flame and heated surfaces; use only in a well ventilated area and avoid inhalation of vapors.

5.11.9.5 Storage. Prolonged storage without proper ventilation is conducive to spontaneous combustion. Do not store XXCC3 at temperatures above 120°F (49°C). Filled drums of impregnite XXCC3 should be placed on a pallet and positioned no less than 6 inches (152 mm) apart and no less than 6 inches (152 mm) from a wall.

5.11.10 Name. Sodium Carbonate, Anhydrous, Technical.

NSN 6810-00-233-1715 100-pound (45 kg) bag (Type I or II)

5.11.10.1 Specification. O-S-571 - Sodium Carbonate, Anhydrous, Technical.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:30Z
Check the source to verify that this is the current version before use.

5.11.10.2 Description. Sodium carbonate is a white solid in granular or powder form containing 58 percent ash (Na_2O).

5.11.10.3 Use. Sodium carbonate is used to build soap and in the preparation of bleach solutions. It is also used in formulations for removal of Impregnite XXCC3 from cotton and woolen blends.

5.11.10.4 Precautions. Avoid contact with skin and eyes. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention. Use only in a well ventilated area and avoid breathing the dust.

5.11.10.5 Storage. Sodium carbonate should be stored in a cool, dry place in tightly closed containers.

5.11.11 Name. Antisetting Compound, Decontaminating Slurry.

NSN 6850-00-656-0926 12-1/2-pound (5.7 kg) bag in fiber can

5.11.11.1 Specification. MIL-S-51027 - Antisetting Compound, Decontaminating Slurry, M2.

5.11.11.2 Description. The antisetting compound is a thoroughly blended mixture of 46.5% citric acid, 50.5% sodium tripolyphosphate and 3% calcium oxide.

5.11.11.3 Use. Antisetting compound, decontaminating slurry, M2 is intended for use in retarding the settling and the setting of a slurry mixture of the decontaminating agent STB. It is necessary only if the slurry is held or stored for a period of time before use, and is not required if the slurry is made up and used immediately.

5.11.11.4 Precautions. Avoid contact with skin and eyes. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.11.11.5 Storage. Store in a dry place.

5.11.12 Name. Organic Chelating Agent.

No Stock Number - Buy Commercial

5.11.12.1 Specification. None.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.11.12.2 Description. The organic chelating agent, a white powder, is the tetrasodium salt of ethylenediamine tetra-acetic acid.

5.11.12.3 Use. The organic chelating agent is used in a laundry procedure to decontaminate by combining with the metallic ions in radioactive materials. It is also used for solubilizing insoluble soap left in fabrics after laundering.

5.11.12.4 Precautions. Do not take internally. Avoid contact with eyes. In case of eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention.

5.11.12.5 Storage. Store in a dry place.

5.11.13 Name. Decontaminating Agent.

NSN 6850-00-297-6653 50-pound (22.7 kg) drum

5.11.13.1 Specification. MIL-D-12468 - Decontaminating Agent, STB.

5.11.13.2 Description. This decontaminating agent is an intimate mixture of calcium oxide and bleaching powder ($CaOCl_2$).

5.11.13.3 Use. This decontaminating agent is used in destroying or converting certain chemical warfare agents into harmless or less toxic compounds.

5.11.13.4 Precautions. Keep away from heat. Avoid contact with skin and eyes. In case of skin or eye contact, flush with copious amounts of water for 15 to 20 minutes and get medical attention. Use only in a well ventilated area and avoid breathing the dust.

5.11.13.5 Storage. Keep container tightly closed and store in a dry area away from heat.

Custodians:

Army - GL
Navy - YD

Review activities:

Army - MD, EA
Navy - MS
DLA - GS

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 7930-0336

☆U.S. GOVERNMENT PRINTING OFFICE: 1978 — 703-122/2479

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-STD-1485A Chemicals & Chemical Products Used for DOD Laundering

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-24T00:30Z
Check the source to verify that this is the current version before use.