MIL-S-52362D(ME)
29 August 1977
SUPERSEDING
MIL-S-52362C
22 November 1971

MILITARY SPECIFICATION

SURVEYING SET, GENERAL-PURPOSE: FOR PLANIMETRIC CONSTRUCTION AND TOPOGRAPHIC SURVEYS, PACKAGING OF

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for methods, materials, and procedures for the preservation, packing, and marking of Surveying Set, General Purpose, SC 6675-97-CL-E21 (NSN 6675-00-641-3639).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-T-60	- Tape: Packaging, Waterproof.

FSC 6675

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 20260-22T21:16Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classificiatio Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:16Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects (see 6.4).

3.2 Preproduction pack. The contractor shall furnish a preproduction pack for examination within the time frame specified (see 6.2), to prove, prior to starting production packaging that the applied preservation, packing, and marking comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The preproduction pack may be accomplished utilizing either the preproduction model or a production model. If the proproduction model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction model and the production model.

3.3 Preservation. Preservation shall be Level A or Commercial as specified (see 6.2),

3.3.1 Level A.

3.3.1.1 Cleaning and drying. Cleaning and drying shall be in accordance with MIL-P-116, cleaning process C-1 and drying procedure D-4. Prior to preservation of the instruments and accessories, all metal surfaces shall be cleaned and dried. Lenses and mirrors shall be cleaned with optical type lens tissue.

3.3.1.2 Preservative. Preservative specified herein shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116. Preservative shall not be applied to the instruments specified herein that are to be preserved Method II. Preservative shall not contact lenses, mirrors, instrument finish, or nonmetallic surfaces. Surfaces coated with preservative shall be wrapped or covered with barrier material conforming to MIL-B-121, Type II, Grade A, Class 1 or 2. The barrier material shall be secured with tape conforming to PPP-T-60, Type IV, applied on the barrier material and not in contact with the instrument finish, or secured by heat sealing.

3.3.1.3 Methods of preservation. Methods of preservation specified herein by symbols shall conform to the applicable symbols listed in MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:16Z
Check the source to verify that this is the current version before use.

3.3.1.4 Exposed threads and metal surfaces. Immediately after cleaning and drying, exposed threads and exposed metal surfaces of instruments, parts and accessories requiring a contact preservative in accordance with MIL-P-116, shall be coated with Type P-7 preservative.

3.3.1.5 Alidade, calculator, dumpy levels, and planimeter. Each instrument, and its accessories, shall be placed in the carrying case and preserved Method IIb. The carrying case shall be the inner container. The outer container shall be a close-fitting box conforming to PPP-B-636, W5c or W6c as applicable. The box shall be closed and sealed as specified for Method V in the appendix to the box specification.

3.3.1.6 Theodolites. Each complete theodolite shall be preserved Method IId or IIf as applicable. The sealed case for the theodolite shall serve as the rigid container. Each preserved theodolite shall be placed and secured in the transport case.

3.3.1.7 Range poles, stadia rods, unbrella, and tripods. Each rod, polec umbrella, and tripod shall be unjointed, folded, retracted, or collapsed to the minimum dimensions and placed in the carrying case, when a case is provided. Each complete rod, pole, unbrella, and tripod shall then be preserved Method III in a close-fitting box conforming to PPP-B-636, W5c. The box shall be closed and sealed as specified for Method V in the appendix to the box specification.

3.3.1.8 Arrow sets, measuring tapes, tension handles, and toolbox. Each measuring tape shall be preserved Method I using Type P-7 preservative. Each arrow set, preserved measuring tape, tension handle, and toolbox shall be placed in a close-fitting box conforming to PPP-B-636, W6c. The box shall be closed and sealed as specified for Method V in the appendix to the box specification.

3.3.1.9 Plumb bobs. Each plumb bob complete with extra points and line shall be preserved Method III in a close-fitting box conforming to PPP-B-636, W6c. The box shall be closed and sealed as specified for Method V in the appendix to the box specification.

3.3.1.10 Drafting scales, surveying levels, crayons, erasers, lead, and pencils. These items furnished in a case, box, or tube shall be preserved Method IC-2.

3.3.1.11 Compasses, pocket transit, protractors, triangles cloth, cord and clamps. Each item shall be preserved Method IC-1.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:16Z
Check the source to verify that this is the current version before use.

3.3.1.12 Drawing paper. The drawing paper shall be arranged in a neat stack with a fiberboard sheet of the same length and width as the paper placed on the top and bottom of the stack and then preserved Method IC-1.

3.3.1.13 Plastic sheets. The plastic sheets shall be preserved as specified in 3.3.1.12.

3.3.1.14 Plane table. The board shall be placed in the case provided and preserved Method IC-1.

3.3.1.15 Consolidation. Set components shall be consolidated in the chest as space permits. Components that will not fit into the chest shall be consolidated together in close-fitting boxes conforming to PPP-B-636, W5c. Cushioning and blocking shall be provided to control movement of components within the chest or boxes. Boxes shall be closed and sealed as specified for Method V in the appendix to the box specification. Large components placed in fiberboard boxes or transport cases shall not require consolidation.

3.3.2 Commercial. Components of each complete set shall be preserved in a manner to afford protection against deterioration and damage from the contractor to the initial destination. Set components furnished with cases shall be placed within the applicable case and all components placed within the chest as space permits.

3.4 Packing. Packing shall be Level A, Level B, or Commercial as specified (see 6.2).

3.4.1 Level A. The chest and any other components that would not fit in the chest, comprising a complete surveying set, shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, style optional. Components shall be arranged to provide a box of minimum cube. Blocking, bracing, and anchoring of the boxed contents shall be in accordance with MIL-STD-1186. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

3.4.2 Level B. Packing shall be as specified in 3.4.1 for Level A except that the box shall be Domestic Type. Box closure and strapping shall be in accordance with the appendix to the box specification.

3.4.3 Commercial. The chest and any other components th8t would not fit in the chest, comprising a complete surveying set, shall be packed in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings in a container complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:16Z
Check the source to verify that this is the currentversion before use.

3.5 Marking.

3.5.1 Military. Marking for military levels of protection shall be in accordance with MIL-STD-129.

3.5.2 Commercial. Marking for commercial packaging shall reflect as a minimum, the item name, National Stock Number, quantity, contract or purchase order number, and appropriate address markings on the shipping container. The marking shall be applied with a waterproof material, shall be legible, and shall provide a definite contrast.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classificiation of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in two stages as follows:

(a) The first stage shall include inspection of materials, methods, containers, and markings inside the shipping container.
(b) The second stage shall include inspection of materials and markings after closing the container.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:16Z
Check the source to verify that this is the currentversion before use.

4.4.2 Unit of product. For the purpose of inspection, a completed pack of any one level prepared for shipment shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in Table I. Acceptable Quality Level (AQL) shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. Packs shall be examined for the following defects specified in Table I:

TABLE I. Classification of Defects

Defect	Level		
	A	B	Commercial
101. Materials, methods, or containers not as specified. Each incorrect material, method, or container shall constitute one defect (3.1, 3.3, 3.4).	X	X	X
102. Exposed threads and metal surfaces not processed as specified (3.3.1.4).	X	-	-
103. Boxes not closed and sealed by method specified (3.3.1.5, 3.3.1.7, 3.3.1.8, 3.3.1.9, 3.3.1.15).	X	-	-
104. Consolidation not as specified.	X	-	-
105. Strapping not as specified.	X	-	-
106. Components not arranged to provide a shipping box of minimum cube.	X	X	-
107. Marking illegible, incomplete, incorrect, or missing.	X	X	X

5. PACKAGING

(Not applicable to this specification.)

6. NOTES

6.1 Intended use. This specification is intended to be used for direct reference in contracts or orders for the preservation, packing, and marking of Surveying Set, SC 6675-97-CL-E21, (NSN 6675-00-641-3639).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:16Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.1).
(c) Degree of preservation and packing required (see 3.3 and 3.4).
(d) When other than Finish B strapping is required (see 3.4.1).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the surveying sets in accordance with this specification.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.1).

Custodian:
Army - ME

Review activities:
Army - SM
DLA - GS

Preparing activity:
Army - ME

Project 6675-0649

Source: https://assist.dla.mil -- Downloaded: 20260-22T21:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-S-52362D(ME) Surveying Set, General-Purpose: f/Planimetric Construction & Topographic Surveys, Pkg Of

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:16Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:16Z
Check the source to verify that this is the current version before use.