INCH-POUND

MIL-M-48261 (AR)
AMENDMENT 6
26 July 1991

SUPERSEDING
AMENDMENT 5
1 May 1990

MILITARY SPECIFICATION

MINES, M718/M741 SYSTEM, METAL PARTS

This Amendment forms a part of Military Specification MIL-P-48261 (AR), dated 4 May 1977, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1: Delete the following dwgs.:

9277743 - Simulant
9277820 - Simulant, Modified
9277763 - Booster, Simulant

PAGE 3

4.3.1: Delete the following parts:

Simulant	- Dwg. 9277743
Simulant, Modified	- Dwg. 9277820
Booster, Simulant	- Dwg. 9277763

PAGE 5

TABLE I: Delete the following parts and the corresponding examinations and tests:

Simulant	- Dwg. 9277743
Simulant, Modified	- Dwg. 9277820
Booster, Simulant	- Dwg. 9277763

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

PAGE 8

Add the following major defect to paragraph 4.4.2.1:

Category	Examination or Test	AQL	Requirement Paragraph	Inspection Method
Major 114	Radius from ID to flange, above max.	0.40%	3.2	4.5.2

PAGE 9

4.4.2.2:

Add the following major defect "111: Flats along the outside and bottom edges not present, 0.40% 3.2 Visual."

* Major 109: Delete "Comparator/Gage" and substitute "Standard Measuring Equipment/Tool Control".

PAGE 12

4.4.2.5: Simulant. Delete paragraph in its entirety.

PAGE 13

4.4.2.6: Simulant, Modified. Delete paragraph in its entirety.

PAGE 14

4.4.2.7:

Add the following major defect: "105 Chamfer above max. 0.40% 3.2 Gage"

* Minor 202: Under examination or test column, change to read "Thickness of ring below notch (2), improper".

PAGE 15

4.4.2.8: Booster, Simulant. Delete paragraph in its entirety.

PAGE 19

4.4.2.12: Pad spherical. Add Major 101 "Material improper/ Hardness improper, - - , 3.1, Certification".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

PAGE 26

4.4.3.2: Density of the simulant. Delete paragraph in its entirety.

PAGE 27

4.5.2: Density of simulant. Delete paragraph in its entirety.

Add paragraph 4.5.2:

"4.5.2 Inspection of radius. The internal radius between the body inner diameter and the flange shall be measured on an optical comparator, after having obtained a mold of the interfacing surface using a quick setting plaster of similar material."

* 5.1.1: Delete "Level C" and substitute "Level B".

Add the following to end of paragraph: "For Body & Pad Assy (9277994), packaging shall be moistureproof in accordance with MIL-STD-1169, para 4.3.1.2.2."

* 5.2.1: Delete "Level C" and substitute "Level B".

Add the following to end of paragraph: "For Body & Pad Assy (9277994), fillers shall be provided as required, between bagged packaging and packing, to prevent abrasion or tearing of the bog. For wood boxes, a mandatory filler shall cover nails; and for wire bound boxes, a mandatory filler shall be provided for all surfaces."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relation to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A603)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.