NOT MEASUREMENT SENSITIVE

MIL-PRF-71226(AR)
12 July 96

PERFORMANCE SPECIFICATION

FOR

ARMAMENTS AND MUNITIONS, STANDARD PROVISIONS, GENERAL SPECIFICATION FOR

This specification is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers general requirements, examinations and tests for all types of armaments and munitions including related fire control, weapons, support materiel, propellants, explosives and pyrotechnics, together with associated training items or devices.

1.2 Application: This general specification is to be used in conjunction with an item drawing, specification, quality assurance provisions and the other provisions of the applicable contract. In the event of a conflict between the text of this specification and the references cited herein, except references to higher level program unique specifications for this program, the text of this specification takes precedence. However, nothing in this document supersedes applicable laws and regulations unless a specific exemption has been obtained.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are needed to meet the requirements specified in sections 3, 4, and 5 of this specification. This section does not include documents which are listed in other sections of this specification or

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander, U.S. Army ARDEC, ATTN: AMSTA-AR-EDE-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 10GP
DISTRIBUTION STATEMENT A. **Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

recommended for additional information or cited as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all requirements documents cited in sections 3, 4, and 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. None are applicable.

2.2.2 Other Government documents, drawings, and publications. None are applicable.

2.3 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI/J-STD-001 - Requirements for Soldered Electrical and Electronic Assemblies
ANSI Z540-1 - General Requirements for Calibration and Measuring and Test Equipment

(Copies are available from the American National Standards Institute, 1430 Broadway, New York, NY 10018-3308.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B117 - Standard Practice for Operating Salt Spray (fog) Testing
ASTM D3951 - Commercial Packaging, Practice for

(Copies are available from the American Society For Testing And Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS

ASME Y14.5 - Dimensioning and Tolerancing

(Copies are available from the American Society of Mechanical Engineers, 345 East 47th Street, New York,NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

INSTITUTE FOR INTERCONNECTING & PACKAGING ELECTRONIC CIRCUITS

IPC-TM-650 - Test Methods Manual

(Copies are available from The Institute For Interconnecting & Packaging Electronic Circuits, 7380 N. Lincoln Avenue, Lincolnwood, IL 60646)

INSTITUTE FOR ELECTRICAL & ELECTRONIC ENGINEERS

IEEE-1498/EIA640 - Software Measurement

(Copies are available from the Institute For Electrical & Electronic Engineers, 445 Hoes Lane, PO Box 1331, Piscataway NJ 08855-1331)

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO 10012-1 - Quality Assurance Requirements for Measuring Equipment
ISO 12207 - Information Technology, Software Life Cycle Processes

(Copies are available from the International Organization For Standardization, Case Postale 56, CH-1211 Geneve 20, Switzerland.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained (See contract provisions for additional precedence criteria).

3. REQUIREMENTS

3.1 System safety. Armament and munitions systems shall have an inherent safety failure rate that assures a probability of no more than one in a million opportunities of a safety incident (see 6.6.8). In order to assure safety during manufacturing, material handling systems for characteristics defined as critical (see 6.6.1) shall ensure that procedures are in place for positive identification and control of material with features identified as critical characteristics. These procedures shall be documented.

3.2 Reliability. Unless otherwise specified, the materiel shall meet all of the reliability requirements stated in the item specification or contract. When explicit reliability requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

are not stated, performance shall conform to industry best practice.

3.3 Shelf life. Unless otherwise specified, the materiel shall meet all of the performance requirements stated in the item specification or contract after storage under expected environmental conditions for the stated shelf life. When there is a shelf life requirement, but the requirement is not specifically stated, the materiel shall be expected to survive 20 years in controlled storage at 70 degrees F and 50% relative humidity.

3.4 Corrosion prevention and control. Unless otherwise specified, all materiel shall be safe, operable and corrosion resistant. Compliance will be based on the results of a 96 hour salt spray test as detailed in 4.6.4.4.

3.5 Interchangeability. When required, all component parts, assemblies, and spares shall be interchangeable without modification, except those parts which may be fitted at assembly as part of normal maintenance.

3.6 Computer software. Computer software embedded in materiel shall meet all of the requirements of the contract and item specification. Unless otherwise specified, computer software shall also meet requirements contained in ISO 12207 and IEEE-1498/EIA640.

3.7 Special processes. Unless otherwise specified, all special processes (see 6.6.9) shall be performed in accordance with documented procedures. As a minimum, the procedure(s) shall include the process, tools, equipment, materials, process controls, test/inspection processes and acceptance criteria. Special processes shall be controlled to uniformly produce the properties necessary to meet the performance requirements stated in the item specification, contract or on the applicable drawings.

3.7.1 Bonding of materials. Bonding methods (e.g.; welding, brazing, adhesives) shall provide all the strength and structural integrity required to meet the requirements of the item specification or contract. Bonding materials shall be free from contamination, discontinuities and workmanship defects which may cause the materiel not to meet its performance requirements.

3.7.2 Soldering of electronics. Soldering procedures shall include all soldering and soldering related operations (e.g.; hand soldering, tinning, solderability testing or verification, automated soldering, inspection and process controls). In lieu of developing a soldering procedure, ANSI/J-STD-001, Class 3, may be utilized with the cleanliness designator as indicated below:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

FLUX TYPE IN USE	CLEANLINESS DESIGNATOR
Low Residue/No clean Flux	C02
Rosin Based Flux	C22
Water Soluble Flux	C22

3.8 Inspection equipment. Unless otherwise specified, inspection equipment shall comply with ISO 10012-1 and ANSI Z540-1. Inspection data shall be absolute; measurement error shall be compensated for so that an out of tolerance product is never accepted. Nondestructive inspection systems (including procedures and accept/reject standards) shall make accept/reject decisions automatically and be robustly designed to reject 100% of the critical defects (see 6.3a and 6.3b).

3.9 Tolerances. Unless otherwise specified, geometric and tolerancing controls used to define features such as location, form, runout, and size, surface finish, etc., shall be defined and interpreted in accordance with ASME Y14.5. All drawings shall be toleranced (see 6.3c). Limits of dimensions shall be absolute.

3.10 Design changes. All design changes, including changes of materials, material properties and additions (e.g.; lubricants and sealants) shall be documented and evaluated to assure that such changes do not adversely impact safety, performance, reliability, maintainability, corrosion resistance or shelf life.

3.11 First article. When specified in the contract, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.12 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner and all manufacturing, processing and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, dirt, grease, oil (except where specifically required), rust, foreign matter or any evidence of poor workmanship that could render the system unsuitable for its intended purpose.

4. VERIFICATION

4.1 General provisions. Unless otherwise specified, the contractor is responsible for the performance of all applicable inspection requirements as specified herein. The Government reserves the right to perform any of the inspections in this specification where such inspections are deemed necessary to assure supplies or services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

4.2.1 First article inspection (see 4.3). A first article inspection is performed to demonstrate the manufacturer's ability to interpret the requirements of the technical data package and to produce a satisfactory unit of product utilizing the intended production processes. The identification and number of samples shall be specified in the item specification, quality assurance provisions or contract.

4.2.2 Conformance inspection (see 4.4). Conformance inspection is performed to determine the acceptance or rejection of an inspection lot. The procedures to be followed for lot formation and sample size shall be specified in the item specification, the contract or per 4.4.1.

4.2.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the conditions specified in the item specification, applicable test method document or applicable paragraph(s) in this specification.

4.3 First article inspection.

4.3.1 Submission. First article samples shall be submitted as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample(s) shall consist of the assemblies, components and test specimens listed in the item specification, contract and applicable drawings. If a quantity is not specified, the sample size shall be three.

4.3.2 Inspections to be performed. Unless otherwise specified, the first article assemblies, components and test specimens are to comply with all of the examinations and tests specified in this specification, the item specification, drawings and contract.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

4.4 Conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

Unless otherwise specified, units of product selected for inspection will represent only the inspection lot from which they are drawn and will not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity will be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions (see 6.3d and e).

4.4.2 Examinations and tests.

4.4.2.1 Classification of characteristics. Conformance examinations and tests are specified as critical, special, major, or workmanship (see 6.6.1-6.6.4) as defined by the item specification, quality assurance provisions or drawings. The quality system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing, as a minimum, the conformance criteria specified.

4.4.2.2 Sample sizes for inspection of characteristics.

4.4.2.2.1 Critical and special characteristics. Unless otherwise specified, inspection for critical and special characteristics shall be 100% and shall be done with automatic decision making equipment.

4.4.2.2.2 Major and workmanship characteristics. Unless otherwise specified, attributes sampling inspection shall be conducted in accordance with TABLE I below, using the inspection levels stated in the Classification of Characteristics paragraphs of the item specification. If inspection levels are not specified, major characteristics shall use a Level III inspection level and workmanship characteristics shall utilize a Level V inspection level (see Table I).

4.4.2.3 Alternative conformance procedures. Unless otherwise specified in the item specification or provided for in the contract, alternative conformance procedures, methods or equipment, such as statistical process control, tool control, variables sampling or other types of sampling plans, etc., may be used when they provide, as a minimum, the level of assurance required by the provisions herein (see 6.3f). Prior to applying such alternative procedures, methods or equipment, the alternative procedures shall be submitted in a written proposal to the Government for evaluation/approval (see 6.5). Statistical evidence (e.g.; control charts, capability study results) shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified conformance provisions(s) herein. In case of dispute as to whether the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

proposed alternative(s) provides equivalent assurance, the provisions of the item specification shall apply.

TABLE I. Attributes sample inspection.

	Inspection Levels					
Lot Size	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150001 to 500000	1250	500	200	125	50	13
500001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

4.5 Certification provisions. When an item/component specification or contract provision requires test data or certification for a specific characteristic, results of objective tests performed on the material shall be provided in the form of a certified test report (CTR). The CTR shall be properly authenticated by a responsible company official to attest to compliance with the requirements of the applicable specification. CTRs shall support the First Article sample and production materiel. CTRs shall, as a minimum, include the following:

a. Name of company and date.

b. Contract number or purchase order number, national stock number (if applicable) and drawing number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

c. Complete nomenclature of supplies together with lot number or other identification. The quantity in each lot or shipment shall be given.

d. All inspections and tests required by contract (e.g., material, processes, performance, functional, etc.) shall be recorded in test reports. These reports shall identify each lot submitted for acceptance by lot number, the specification or drawing, revision and date, grade or type as applicable, number of specimens tested, specified characteristics and requirements, and actual results obtained.

e. Reports of the raw material producer's chemical, mechanical, and physical analyses.

f. A statement, as follows, certifying that material meets all requirements of the contract:

"The undersigned, individually, and as the authorized representative of the company identified above, warrants and represents that: All the information supplied above is true and accurate; the material covered by this certificate conforms to all contract requirements except as noted (including but not limited to the drawings and specifications); the inspection and test results, and the analyses appearing herein are true and accurate; and this certificate is made for the purpose of inducing payment and with knowledge that the information and certification may be used as a basis for such payment."

g. Signature and title of certifying official.

4.6 Inspection requirements.

4.6.1 Compliance with requirements. Materials, parts, and items shall be inspected as necessary to insure compliance with the requirements of the item specification, applicable requirements of Section 3 of this specification and other applicable documents as listed in the contract. When inspection methods and procedures are not specified in item specifications or other applicable documents, they shall be in accordance with 4.6.4 of this specification.

4.6.2 Responsibility for testing. Unless otherwise specified, all testing of materials, parts and items, and the handling, sampling, preparation of test specimens, chemical analysis, and other operations necessary for such testing, shall be done by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

4.6.3 Destructive test samples. Unless otherwise specified, all samples, specimens, parts and items destroyed in tests required as a part of the contract shall be in addition to the quantity specified in the procurement documents, and shall be furnished as part of the order or contractual agreement.

4.6.4 Inspection and testing methods. The following inspection and testing methods apply unless otherwise specified.

4.6.4.1 System safety. Verify through demonstration that documented procedures ensure positive identification and control of material with features identified as critical characteristics and that the item has an inherent safety failure rate that assures a probability of no more than one in a million opportunities of a safety incident.

4.6.4.2 Reliability. Verify through demonstration attainment of the reliability requirements as detailed in the item specification or to the provisions of the contract. When explicit reliability performance test criteria, functioning test criteria or similar demonstration evaluations are not specified, performance shall conform to industry best practice.

4.6.4.3 Shelf life testing. Provide evidence that the materiel shall meet all of the performance requirements stated in the item specification or contract after storage under expected environmental conditions for the stated shelf life. If historical data on the materiel is not available, an accelerated aging test shall be designed and conducted (see 6.4).

4.6.4.4 Corrosion prevention and control. Unless otherwise specified, the materiel shall be subjected to the salt spray test cited in ASTM-B117 for 96 hours. The materiel shall show no evidence of corrosion or corrosion products after testing and the item shall perform as intended.

4.6.4.5 Interchangeability. Unless otherwise specified, participation in interchangeability assessments shall be necessary to verify interface compatibility.

4.6.4.6 Computer software verification and validation. Materiel containing embedded computer software shall undergo the verification and validation activities contained in IEEE-1498/EIA640.

4.6.4.7 Inspection of product from special processes. Functional tests or nondestructive tests shall be utilized to inspect product produced using special processes to assure compliance with the requirements of the item drawings, specification, contract provisions and special process procedures. Personnel shall have proper qualifications to

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

perform nondestructive testing (see 6.3g). Nondestructive test procedures for critical, special and major characteristics shall be submitted for Government approval as specified in the contract (see 6.3h,i,j,k,l and 6.4). When statistical process controls are to be utilized, statistical evidence (e.g.; control charts, capability study results) that demonstrates the effectiveness of the control of the special process shall be provided (see 4.4.2.3 and 6.4).

4.6.4.7.1 Inspection of bonded materials. Functional tests or nondestructive tests shall be utilized to inspect bonded materials to assure compliance with the requirements of the item drawings, specification and contract provisions.

4.6.4.7.2 Inspection of soldered electronics. utilizing the soldering procedure offered in 3.7.2 in lieu of developing a soldering procedure, the following acceptance criteria apply.

4.6.4.7.2.1 Hardware processed using rosin-based flux. One sample unit of each printed wiring assembly being produced shall be tested utilizing IPC-TM-650 Method 2.3.25, 2.3.26, or 2.3.26.1 from the end of each daily production run. The test sample shall contain less than 1.56 micrograms/square centimeter sodium chloride (NaCl) equivalent ionic or ionizable flux residue to be acceptable.

4.6.4.7.2.2 Hardware processed using non-rosin flux. A baseline test shall be performed utilizing IPC-TM-650 Method 2.6.3.3 using the IPC-B-36 test specimen. The acceptance criteria shall be a minimum value of 100 megohms at each test point. This test shall be repeated whenever the manufacturing methodology (e.g.; flux, solvent/cleaning agent, procedure or equipment) is altered. In addition, the testing cited in 4.6.4.7.2.1 also applies.

4.6.4.7.2.3 Hardware processed using no-clean/low residue flux. The tests cited in 4.6.4.7.2.2 apply with the following modifications. The value of 1.56 micrograms/square centimeter is for reference only. Once a nominal microgram/square centimeter value has been established, any gross deviation from the established value shall require retesting in accordance with IPC-TM-650 Method 2.6.3.3 as described in 4.6.4.7.2.2.

4.6.4.8 Inspection equipment. Contractor inspection equipment designs for critical, special and major characteristics shall be submitted for Government approval to verify compliance to the requirements of paragraph 3.8 (see 6.4). Designs which provide variables data are preferred in order to maximize the potential for utilizing statistical process control.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging For acquisition purposes, the packaging requirements shall be specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. This specification is to be used in contracts for the procurement, manufacture and inspection of all types of armaments and munitions including related fire control, weapons, support materiel, propellants, explosives and pyrotechnics. This specification should be tailored for the particular application.

6.2 Acquisition requirements. Acquisition documents should specify the following unless tailored or supplemented by the contract or item specification:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.1).

c. Requirements for submission of first article sample.

d. Requirements for lot numbering of ammunition (see 6.3d)

e. Requirements for submission and maintenance of data cards for ammunition items (see 6.3e).

f. Requirements for submission of inspection equipment designs, test procedures and special process procedures (see 6.4).

g. Packaging requirements (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

h. Certified test report for each lot or shipment of product.

i. Notification/approval of design changes.

j. Tailoring of this specification as appropriate.

6.3 Reference documents. The following documents are listed for guidance only.

a.	MIL-A-70625	- Automated Acceptance Inspection Equipment Design, Testing and Approval	(para. 3.8)
b.	MIL-HDBK-204	- Design of Inspection Equipment for Dimensional Characteristics	(para. 3.8)
c.	Machinery's Handbook		(para. 3.9)
d.	MIL-STD-1168	- Ammunition Lot Numbering	(para. 4.4.1)
e.	MIL-STD-1167	- Ammunition Data Cards	(para. 4.4.1)
f.	MIL-STD-1916	- DOD Preferred Methods for Acceptance of Product	(para.4.4.2.3)
g.	MIL-STD-410	- Nondestructive Testing Personnel Qualification and Certification	(para. 4.6.4.7)
h.	ASTM E709	- Magnetic Particle Examination	(para. 4.6.4.7)
i.	ASTM E165	- Liquid Penetrant Inspection Method	(para. 4.6.4.7)
j.	ASTM E164	- Ultrasonic Contact Examination of Weldments	(para. 4.6.4.7)
k.	MIL-STD-453	- Inspection, Radiographic	(para. 4.6.4.7)
l.	MIL-STD-1264	- Radiographic Inspection for Soundness of Welds in Steel by Comparison to Graded ASTM E390 Reference Radiographs	(para. 4.6.4.7)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

m. CFR TITLE 49 - Transportation of Hazardous Materials (para. 5.1.1)

n. MIL-STD-129 - Marking for Shipment and Storage (para. 5.2)

6.4 Submission of contractor inspection equipment designs, test procedures and special process procedures for approval. Submit copies of all contractor inspection equipment designs and test procedures as required to the responsible Government activity on the DD Form 1423.

6.5 Submission of alternative conformance provisions. All contractor proposed alternative conformance provisions shall be submitted to the Government technical agency for evaluation/ approval as directed by the contracting activity.

6.6 Definitions.

6.6.1 Critical characteristic - A critical characteristic is a characteristic that in the event of a defect would result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the product, or that a defect is likely to prevent performance of the tactical function of a major end item such as a tank, land vehicle, missile, aircraft, artillery, or other major weapon system.

6.6.2 Special Characteristic (For ammunition only) - A special characteristic is a characteristic, other than critical, that in the event of a defect is likely to, depending upon the degree of variance from the design requirement:

a. Result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the product; or

b. Prevent performance of the tactical function of a major end item.

6.6.3 Major Characteristic - A major characteristic is a characteristic, other than critical or special, that in the event of a defect is likely to result in failure, or to reduce materially the usability of the unit of product for its intended purpose.

6.6.4 Workmanship Characteristic - A workmanship characteristic is a characteristic that in the event of a defect is not likely to reduce materially the usability of the unit of product for its intended purpose, or is a departure from established standards that is not likely to reduce the effective use or operation of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

6.6.5 Critical characteristic material handling system - All operations subsequent to the creation of the feature classified as a critical characteristic including manufacturing, inspection, material transport, storage, marking, rework, repair and disposal.

6.6.6 Workmanship Defects - defined as an imperfection or fault which may affect performance. Defects include but are not limited to, pits, voids, cracks, cavities, distortion, gouges, inclusions, laps, seams, porosity and tool marks.

6.6.7 Foreign matter - defined as, but not limited to, dirt, corrosion, grease, chips or other matter that is not consistent with the intended use of the item, or otherwise degrades the quality of the item.

6.6.8 Safety Incident - an occurrence involving unintended personnel injury or the potential for unintended injury of personnel.

6.6.9 Special Process - Any production process which has the potential to adversely impact the materiel’s ability to meet the performance requirements stated in the item specification, contract or on the applicable drawings. Special processes include, but are not limited to welding, brazing, soldering, heat treatment, case hardening, adhesive bonding, anodizing and painting.

6.7 This specification replaces MIL-A-02550, MIL-A-48078, MIL-F-13926, MIL-W-13855, MIL-W-63150, and MIL-C-13931 which have been made inactive for new designs. This specification supports performance-based acquisition and is intended to be tailored when appropriate.

6.8 Subject term (key word) listing.

corrosion prevention and control
explosives
first article
fire control
inspection equipment
interchangeability
propellants
pyrotechnics
reliability
shelf life
software
soldering
special process
surface finish

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

system safety
tolerances
weapons

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 10GP-0013)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced documents(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-PRF-71226	960712

3. DOCUMENT TITLE

ARMAMENTS AND MUNITIONS, STANDARD PROVISIONS, GENERAL SPEC FOR

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*)	d. TELEPHONE (*Include Area Code*) (1) Commercial (2) AUTOVON (*if applicable*)	7. DATE SUBMITTED (*YYMMDD*)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (*Include Area Code*) (1) Commercial	(2) AUTOVON
U. S. Army ARDEC	(201) 724-2163	880-2163
c. ADDRESS (*Include Zip Code*) ATTN: AMSTA-AR-EDE-S, B-12 Picatinny Arsenal, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.