MILITARY SPECIFICATION

REFILL KIT, CHEMICAL AGENT DETECTOR, V-G COMPONENTS, ABC-M30A1

This amendment forms a part of MIL-R-51237A(EA), dated 24 August 1984, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1:

Under "SPECIFICATIONS" "FEDERAL" delete the following:

"L-P-378 - Plastic Sheet and Strip, Thin Gauge, Polyolefin
NN-P-71 - Pallets, Material Handling, Wood, Stringer Construction, 2-Way and 4-Way (Partial)
PPP-B-585 - Boxes, Wood, Wirebound
PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-B-676 - Boxes, Setup
PPP-F-320 - Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes"

Under "SPECIFICATIONS" "MILITARY" delete the following:

"MIL-P-116 - Preservation, Methods of
MIL-B-117 - Bags, Sleeves and Tubing - Interior Packaging"

After "STANDARDS" insert the following:

"FEDERAL

FED. TEST METHOD STD. NO. 101 - Test Procedures for Packaging Materials"

Under "STANDARDS" "MILITARY" delete the following:

"MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads"

AMSC N/A FSC 6665

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

2.1.2:

Line 6: Delete "CHEMICAL RESEARCH AND DEVELOPMENT CENTER" and substitute "CHEMICAL RESEARCH, DEVELOPMENT AND ENGINEERING CENTER".

Lines 10 and 11: Delete "5-77-2347 - Marking for Refill Kit, Chemical Agent Detector, V-G Components, ABC-M30A1".

Add after the list of drawings the following:

"SPECIAL PACKAGING INSTRUCTIONS (SPI)

PMIL-R-51237 - Refill Kit, Chemical Agent Detector, V-G Components, ABC-M30A1"

PAGE 3

2.2: Delete in its entirety.

PAGE 4

4.2.2.1: Delete in its entirety and substitute the following:

"4.2.2.1 For examination and tests. Sampling for examination of item and the examination and testing for the packaging shall be conducted in accordance with MIL-STD-105."

4.2.3.1: Delete in its entirety and substitute the following:

"4.2.3.1 For examination and nondestructive tests. Sample refill kits and the packaging thereof shall be examined and tested in accordance with the following classification of defects and MIL-STD-105."

Insert the following in sequence after 4.2.3.1:

"4.2.3.1(a) For destructive tests. The test specimens shall be tested in accordance with 4.2.4.2. The AQL for sample sizes greater than eight shall be 4 percent defective. For sample sizes eight or less the sample size specified in MIL-STD-105 shall be used without regard to the AQL and the acceptance number shall be zero."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

4.2.3.2.2: Delete in its entirety and substitute the following:

"4.2.3.2.2 Packaging (section 5).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.5 percent defective	
101	Item not completely cleaned and dried	
102	Kit component missing from unit pack	
103	Closure of unit, intermediate or shipping container not as specified	
104	Unit, intermediate or shipping container damaged	
105	Unit container corners not blunted	
106	Unit pack not cushioned properly	
107	Marking of unit, intermediate or shipping container missing, incorrect or illegible	
108	Unit, intermediate or shipping container not as specified	
109	Unit container leakage	4.2.4.1"

Insert the following in sequence after 4.2.3.2.2:

"4.2.4 Tests.

4.2.4.1 Unit pack container leakage (SPI PMIL-R-51237). The leakage characteristics of the unit pack container (barrier bag) containing the item shall be determined by subjecting the samples to the vacuum chamber technique of test method 5009.2 of FED. TEST METHOD STD. NO. 101 (as an alternate, the hot water technique may be used).

4.2.4.2 Heat seal seam test (SPI PMIL-R-51237). The heat seal seams of the unit pack container (barrier bag) shall be tested in accordance with test method 2024 of FED. TEST METHOD STD. NO. 101, except that the static load shall be 50 ounces ± 2 ounces, and a 5 percent reduction in this static load shall be permitted when room temperature in test area exceeds 90°F."

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.

PAGE 5 AND 6

Section 5 "Packaging": Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Packaging. Packaging shall be as specified in SPI PMIL-R-51237."

PAGE 7

6.2, line 3: Delete in its entirety and substitute "(b) Level of packing required (see 5.1)".

6.2: Add in sequence "(c) Shelf life code".

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 6665-A549

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.