INCH-POUND

MIL-W-70467 (AR)
AMENDMENT 4
16 June 1994
SUPERSEDING
AMENDMENT 3
14 October 1992

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, PRACTICE: XM274

This amendment forms a part of MIL-W-70467 (AR), dated 15 May 1986, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete "XM274" and substitute "M274".

1.1: Delete "XM274" and substitute "M274".

PAGE 2

2.1.2: Delete "XM274" and substitute "M274".

Delete "MIS-50263 Rocket, 2.75 Inch, Complete Round with MK40 and MK 4 Motor: Assembling, Packing, and Testing".

Delete "INSPECTION EQUIPMENT DRAWINGS 9201212
Envelope Drawing, Safety, and Arming Inspection Equipment".

PAGE 6

4.3.1: Delete "XM274" and substitute "M274".

Delete "Plug 9370245 15"

Add the following:

"Washer, Felt	12599973	15
Cap, Smoke Tube	12599974	15
Tube, Smoke	12599976	15
Smoke, Tube Assembly	12599977	25"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

PAGE 7

TABLE I: Delete "XM274" and substitute "M274".

PAGE 8

TABLE I: Delete "XM274" and substitute "M274".

Delete:

"Plug (Dwg. 9370245) Examination for defects	15	3.2	4.4.2.8".

PAGE 9

TABLE I: Delete "XM274" and substitute "M274".

PAGE 10

TABLE I: Delete "XM274" and substitute "M274".

PAGE 11

TABLE I: Delete "XM274" and substitute "M274".

PAGE 12

TABLE I: Delete "XM274" and substitute "M274".

Add the following:

"Tube, Smoke (Dwg. 12599976) Examination for defects	16	3.2	4.4.2.25
Cap, Smoke Tube (Dwg. 12599974) Examination for defects	15	3.2	4.4.2.26
Washer, Felt (Dwg. 12599973) Examination of defects	15	3.2	4.4.2.27
Smoke Tube Assembly (Dwg. 12599977) Examination for defects	25	3.2	4.4.2.28"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.1: Delete "XM274" and substitute "M274".

PAGE 18

4.4.2.5, under Major 101: Delete "Diameter" and substitute "Outside Diameter".

Add Major 103 as follows:

"103	Location of Hole	0.40%	3.2	Gage".

Add Minor 201 as follows:

"201	Inside Diameter	0.65%	3.2	Gage".

PAGE 21

4.4.2.8: Delete in its entirety.

PAGE 22

4.4.2.9: Delete Major 104 in its entirety.

Add Minor 204 as follows:

"204	Diameter of partition hole	0.65%	3.2	Gage".

PAGE 23

4.4.2.10: Delete Major 107 in its entirety.

Add Majors 111 and 112 as follows:

"111	Retainer groove diameter	0.40%	3.2	Gage
112	Retainer groove location	0.40%	3.2	Gage".

PAGE 27

4.4.2.13: Delete "8883686" and substitute "9215619-1".

PAGE 29

4.4.2.15: Add "-1" next to 9215619.

PAGE 34

4.4.2.20: Add "-1" next to 9215619.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

PAGE 36

4.4.2.22: Add "-1" next to 9215619.

PAGE 37

4.4.2.23: Delete Minor 201 in its entirety.

PAGE 38

4.4.2.24: Delete "XM274" and substitute "M274".

PAGE 39

Add 4.4.2.25 enclosed as Page 5 (38a).

Add 4.4.2.26 enclosed as Page 6 (38b).

Add 4.4.2.27 enclosed as Page 7 (38c).

Add 4.4.2.28 enclosed as Page 8 (38d).

PAGE 41

4.5.5: Delete "4.5.5" and substitute "4.5.4".

PAGE 44

4.5.5.17: Delete "4.4.4.3 and 4.4.4.4" and substitute "4.4.5.1 and 4.4.5.2".

PAGE 46

4.5.7: Delete "or MIS-50263, or whichever is applicable".

PAGE 47

4.5.7: Delete "or MIS-50263, or whichever is applicable".

* 4.5.8: Delete second paragraph and substitute:

"The sample warheads shall be packed and packaged in accordance with MIS-30862 except that dummy 2.75 inch rocket motors shall be substituted. The warheads shall be equally divided and temperature conditioned to -50° ± 5°F, 70° ± 15°F and 160° ± 5°F. The conditioning time shall be 8 hours minimum and 24 hours maximum."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Tube, Smoke	1 OF 1	12599976
			NEXT HIGHER ASSEMBLY: 12599977

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Wall thickness of radius end	0.40%	3.2	Gage
Minor				
201	Total length	0.65%	3.2	Gage
202	Outside diameter	0.65%	3.2	Gage
203	Wall thickness	0.65%	3.2	Gage
204	Thread pitch	0.65%	3.2	Gage
205	Evidence of poor workmanship	0.65%	3.18	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-70467 (AR)
AMENDMENT 4

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.26	Cap, Smoke Tube	1 OF 1	12599974
			NEXT HIGHER ASSEMBLY: 12599977

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major	None defined.			
Minor				
201	Height	0.65%	3.2	Gage
202	Inside diameter	0.65%	3.2	Gage
203	Thread pitch	0.65%	3.2	Gage
204	Evidence of poor workmanship	0.65%	3.18	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.27	Washer, Felt	1 OF 1	12599973

NEXT HIGHER ASSEMBLY: 9370252

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major	None defined.			
Minor				
201	Thickness	0.65%	3.2	Gage
202	Hole diameter	0.65%	3.2	Gage
203	Evidence of poor workmanship	0.65%	3.18	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-70467 (AR)
AMENDMENT 4

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.28	Smoke Tube Assembly	1 OF 1	12599977

NEXT HIGHER ASSEMBLY: 9370252

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Joint of smoke tube cap and smoke tube taped incorrectly (note 4)	0.40%	3.2	Visual
102	Smoke tube cap installed incorrectly	0.40%	3.2	Visual
Minor				
201	Weight of smoke composition	0.65%	3.2	Gage
202	Evidence of poor wormanship	0.65%	3.18	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

8 (38d)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

PAGE 51

* 4.5.12: Delete and substitute:

"4.5.12 Ballistic test. The requirements for the warhead is to provide a visible signature, at impact, with a functional reliability of greater than 93.7% when fired with MK66 motors. Performance shall be evaluated by ground launching a sample of 36 M274 warheads. Twelve rockets shall be conditioned at -50°F + 5°F, 12 rockets at 70°F ± 15°F, 12 rockets at 150°F - 5°F for a minimum period of 6 hours. All 36 rockets shall be fired from an M260 or M261 launcher to impact at 6000 meters. If three or more warheads fail to function, the lot shall be rejected."

5.1: Add "When shipping the loaded S&A's to the warhead assembly site, CFR49, Parts 100-199 apply."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A935)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.