MILITARY SPECIFICATION

YEAST AUTOLYSATE, DRIED, TECHNICAL

This amendment forms a part of Military Specification MIL-Y-51021, 29 June 1960, and has been approved by the Department of Defense and is mandatory for use of the Departments of the Army, the Navy, and the Air Force.

Page 2, paragraph 3.5, insert the following as the last line of table 1: Under "Property" add "Water insoluble matter", under "Requirements" add "0.0% (max.)" and "Clear solution", and under "Test paragraph" add "4.5.8".

Page 5, add:

"**4.5.8** *Water insoluble matter.*

"**4.5.8.1** *Preparation of gooch crucible.* Digest a good grade of long fiber amphibole asbestos, prepared for gooch crucibles, in hydrochloric acid (1 to 3) for about 1 hour. Wash the asbestos with water to remove the acid, allow the major portion of the asbestos to settle, decant the mixture to remove fine particles, and add sufficient water to form a thin slurry. Using a vacuum, prepare a well-packed asbestos mat approximately 1 millimeter thick in a gooch crucible and wash the mat thoroughly with hot water. Dry the mat at 135° ±2° C., ignite the crucible, rewash the mat under vacuum, and dry the mat at 135° ±2° C. Place the crucible in a desiccator to cool and weigh the crucible. Repeat the washing, heating, and drying cycle until the crucible reaches constant weight at 1 mg accuracy.

"**4.5.8.2** *Procedure.* Weigh approximately 1.0 g of the sample and place it in a 500-ml Erlenmeyer flask containing about 200 ml of water at room temperature. Stopper the flask and shake it on a shaking machine for about 15 minutes. Transfer the solution into a clear glass 250-ml cylinder and visually examine the solution. Report the yeast as passing the clear solution requirement (table 1) if no visible cloud or sediment is observed. Using vacuum, filter the solution through the prepared mat in a tared gooch crucible and wash the mat with three approximately 25-ml portions of water. Dry the crucible in an oven at 135° ±2° C., cool it in a desiccator, and reweigh the crucible.

"**4.5.8.3** *Calculation.*

$$\text{Percent water insoluble matter} = \frac{100\ b}{a}$$

where:

a = weight of sample used.

b = weight of residue in gooch."

Custodians:
Army—CmlC
Navy—BuMed

Preparing activity:
Army—CmlC

611041—61—(184)

FSC 6810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:47Z
Check the source to verify that this is the current version before use.