MIL-E-1/804A(SigC)
10 May 1956
Superseding
MIL-E-1/804(SigC)
3 October 1955

INDIVIDUAL MILITARY SPECIFICATION SHEET

Electron Tube, Receiving, Pentode, Miniature

TYPE 6AK5WB

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.

This specification sheet forms a part of the latest issue of Military Specification MIL-E-1.

Description: Pentode, RF, Sharp Cut-off.

Ratings:	Ef	Eb	Ecl	Ec2	Ehk	Rgl	Ic	Ik	Pp	Pg2	T Env.	Alt.
Absolute	V	Vdc	Vdc	Vdc	V	Meg	mAdc	mAdc	W	W	°C	ft.
Maximum:	6.9	200	0	155	135	0.1	1.0	20	1.65	0.55	+165	60,000
Minimum:	5.7	--	-50	--	--	--	--	0.5	--	--	--	--
Test Cond:	6.3	120	-2	120	0 Note 1	--	--	--	--	--	--	--

Cathode: Coated Unipotential
Base: Miniature Button, 7-pin

Height: 1-3/4 in. max.
Diameter: 3/4 in. max.

Pin No:	1	2	3	4	5	6	7
Element:	gl	k g^3	h	h	p	g2	k g^3

Envelope: T-5 1/2

The following tests shall be performed:

For the purposes of inspection, use applicable reliable paragraphs of MIL-E-1 and Inspection Instructions for Electron Tubes.

For miscellaneous requirements, see Paragraph 3.3 Inspection Instructions for Electron Tubes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.

Ref.	Test	Conditions	AQL%	Insp. Level or Code	Sym.	LIMITS Min.	LAL	Bogie	UAL	Max.	ALD	Units
	Qualification Approval Tests											
3.1	Qualification Approval:	Required: Note 9		--								
--	Marking:	Note 24										
--	Cathode:	Coated Unipotential	--	--								
3.4.3	Base Connections:											
4.9.20.3	Vibration (1):	Rp= 10,000; Note 7	--	--	Ep:	--	--	--	--	150	--	mVac
	Measurements Acceptance Tests, Part 1, Note 3											
4.10.8	Heater Current:	Note 4	--	--	If:	--	168	175	182	--	14	mA
4.10.8	Heater Current:		0.65	II	If:	160	--	--	--	190	--	mA
4.10.15	Heater-Cathode Leakage:	Ehk= +100Vdc	0.65	II	Ihk	--	--	--	--	10	--	uAdc
		Ehk= -100Vdc			Ihk	--	--	--	--	10	--	uAdc
4.10.6.1	+Grid Current (1):	Rgl = 0.1 Neg	0.65	II	Ic1:	0	--	--	--	-0.1	--	uAdc
4.10.4.1	Plate Current (1):	Note 4	--	--	Ib:	--	6.5	7.5	8.5	--	2.5	mAdc
4.10.4.1	+Plate Current (1):		0.65	II	Ib:	5.0	--	--	--	11.0	--	mAdc
4.10.4.3	Screen Grid Current:		0.65	II	Ic2:	0.8	--	--	--	4.0	--	mAdc
4.10.9	Transconductance (1):	Note 4	--	--	Sm:	--	4500	5000	5500	--	1025	umhos
4.10.9	Transconductance (1):		0.65	II	Sm:	4000	--	--	--	6200	--	umhos
4.7.5	Continuity & Shorts: (Inoperatives)		0.4	II		--	--	--	--	--	--	
4.9.1	Mechanical Inspection	Envel. (6-1) No. 6-4	--	--		--	--	--	--	--	--	

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.

Ref.	Test	Conditions	AQL%	Insp. Level or Code	Sym.	LIMITS Min.	LAL	Bogie	UAL	Max.	ALD	Units
	Measurements Acceptance Tests, Part 2											
4.8.2	Insulation of Electrodes:											
		g1-all	2.5	IA	R:	100	--	--	--	--	--	Meg
		p-all			R:	100	--	--	--	--	--	Meg
4.10.4.1	Plate Current (2):	Ec1= -10Vdc	2.5	I	Ib:	--	--	--	--	200	--	uAdc
4.10.4.1	Plate Current (3):	Ec1= -5.5Vdc	2.5	I	Ib:	5.0	--	--	--	--	--	uAdc
4.10.9	Transconductance (2):	Ef=5.7V; Note 21	2.5	I	△Sm Ef:	--	--	--	--	15	--	%
4.10.6.2	Grid Emission	Ef=7.5V; Ec1= -45V Rg1=0.1 Meg: Note 19	2.5	I	Ic1	0	--	--	--	-0.5	--	uAdc
4.10.3.1	RF Noise:	Eca1=15.0mVac; Note 22 Ec1=0; Rk=200;Ck=0.2uf	2.5	I		--	--	--	--	--	--	
4.10.3.5	Noise & Microphonics:	Ef=6.3Vac; Ehk=0; Ebb=200Vdc; Ecc2=200Vdc; Ec1=0; Eca1=100 mVac; Rk=1000; Rp=0.1 Meg; Rg2=0.5 Meg Cg2=2uf; Note 20	2.5	I		--	--	--	--	--	--	
4.10.14	Capacitance:	Shield No. 316		Code E	Cg1p:	--	--	--	--	.020	--	uuf
		Shield No. 316	6.5		Cin:	3.60	--	--	--	4.40	--	uuf
		Shield No. 316			Cout:	2.45	--	--	--	3.25	--	uuf
4.10.14	Capacitance:	Shield No. 316			Cin:	--	3.80	4.00	4.20	--	.20	uuf
		Shield No. 316 Note 4			Cout:	--	2.70	2.85	3.00	--	.20	uuf

Source: https://assist.dla.mil -- Downloaded: 2026/0-15T13:40Z
Check the source to verify that this is the current version before use.

Ref.	Test	Conditions	AQL%	Insp. Level or Code	Sym.	LIMITS Min.	LAL	Bogie	UAL	Max.	ALD	Units
	Measurements Acceptance Tests, Part 2 cont.											
--	Low Pressure Voltage	Pressure=55±5 mm Hg; Voltage=500 Vac;Note 6	6.5	Note 5		--	--	--	--	--	--	
4.9.19.1	Vibration (2):	Rp=10,000; Note 7	6.5	Code I	Ep:	--	--	--	--	150	--	mVac
	Degradation Rate Acceptance Tests, Note 8											
4.9.20.5	Shock:	Hammer angle=30°; Ehk= +100Vdc;Rg=0.1Meg	20	--		--	--	--	--	--	--	--
4.9.20.6	Fatigue:	G=2.5;F=25 min. 60 max Fixed Frequency	6.5	Note 5		--	--	--	--	--	--	
--	Post Shock & Fatigue	Vibration(2)		--	Ep:	--	--	--	--	450	--	mVac
	Test End Points:	Heater-Cathode Leakage										
		Ehk= +100 Vdc	--	--	Ihk:	--	--	--	--	30	--	uAdc
		Ehk= -100 Vdc	--	--	Ihk:	--	--	--	--	30	--	uAdc
		Change in Transconductance	--	--	Δ Sm	--	--	--	--	15	--	%
		(1) of Individual Tubes Grid Current	--	--	Icl:	0	--	--	--	-0.2	--	uAdc
4.9.6.1	Min. Tube Base Strain		--	--		--	--	--	--	--	--	
--	Glass Strain:	Note 10	2.5	I		--	--	--	--	--	--	

Source: https://assist.dla.mil -- Downloaded: 2026/10-15T13:40Z
Check the source to verify that this is the current version before use.

Ref.	Test	Conditions	AQL%	Insp. Level or Code	Allowable Defectives per 1st Sample	Allowable Defectives per Combined Sample	Sym.	LIMITS Min.	LIMITS Max.	Units
	Acceptance Life Tests, Note 8									
4.11.7	Heater Cycling Life Test:	Ef=7.5V;Ehk= +135 Vdc; Ec1=Ec2=Eb=0; Note 11	--	--	--	--		--	--	
4.11.4	Heater Cycling Life Test End Points:	Heater-Cathode Leakage								
		Ehk= +100 Vdc	--	--	--	--	Ihk:	--	20	uAdc
		Ehk= -100 Vdc	--	--	--	--	Ihk:	--	20	uAdc
--	Stability Life Test	Eb=150 Vdc; Ec1=0; Ec2=125 Vdc; Ehk= +135 Vdc: Rk=130; Rgl=0.1 Meg; TA=Room; Note 12	1.0	Code I	--	--		--	--	
--	Stability Life Test End Points:	Change in Transconductance (1) of individual Tubes	--	--	--	--	Δ Smt	--	10	%
--	Survival Rate Life Test:	Stability Life Test Conditions or equivalent; Notes 13, 14	--	II	--	--		--	--	
4.11.4	Survival Rate Life Test End Points:	Continuity and Shorts	0.65	--	--	--		--	--	
		Transconductance (1)	1.0	--	--	--	Sm:	3550	--	umhos
4.11.5	Intermittent Life Test:	Stability Life Test Conditions; T Envelope = +165°C min; Notes 15, 16	--	--	--	--		--	--	

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.

Ref.	Test	Conditions	AQL%	Insp. Level or Code	Allowable Defective per 1st Sample	Allowable Defective per Combined Samples	Sym.	LIMITS Min.	LIMITS Max.	Units
	Acceptance Life Tests, Note 8, Cont.									
4.11.4	Intermittent Life Test	Note 17								
	End Points:	Inoperatives; Note 18	--	--	1	3		--	--	
	(500 Hours)	Grid Current	--	--	1	3	Icl:	0	-0.1	uAdc
		Heater Current	--	--	1	3	If:	160	193	mA
		Change in Transconductance (1) of individual tubes	--	--	1	3	Δ Sm t:	--	20	%
		Transconductance (2)	--	--	2	5	Ep Ef:	--	15	%
		Heater-Cathode Leakage								
		Ehk= +100 Vdc	--	--	1	3	Ihk:	--	10	uAdc
		Ehk= -100 Vdc					Ihk:	--	10	uAdc
		Insulation of Electrodes								
		g1 - all	--	--	2	5	R:	50	--	Meg
		p - all					R:	50	--	Meg
		Transconductance (1)	--	--	--	--	Avg Δ Sm t:	--	15	%
		Average Change								
		Total Defectives	--	--	4	8		--	--	
4.11.4	Intermittent Life Test	Note 17								
	End Points:	Inoperatives; Note 18	--	--	2	5		--	--	
	(1000 Hours)	Grid Current	--	--	2	5	Icl:	0	-0.1	uAdc
		Heater Current	--	--	2	5	IC:	160	196	mA
		Change in Transconductance (1) of individual tubes	--	--	2	5	Δ Sm t:	--	25	%
		Heater-Cathode Leakage								
		Ehk= +100 Vdc			2	5	Ihk:	--	10	uAdc
		Ehk= -100 Vdc					Ihk:	--	10	uAdc
		Total Defective	--	--	5	10		--	--	

Source: https://assist.dla.mil -- Downloaded: 2026-01-15T13:40Z
Check the source to verify that this is the current version before use.

Note 1: The reference point for heater-cathode potential shall be the positive terminal of the cathode resistor.

Note 2: If altitude rating is exceeded, reduction of instantaneous voltage (Ef, excluded) may be required.

Note 3: The AQL for the combined defectives for attributes in Measurements Acceptance Tests, Part 1, excluding Inoperatives and Mechanical shall be one (1) percent. A tube having one (1) or more defects shall be counted as one (1) defective. MIL-STD-105, Inspection Level II shall apply.

Note 4: Variables Sampling Procedure:

Test for Lot-Average Acceptance:

Select a 35 tube sample at random from the lot. Number these tubes consecutively.

Determine the numerical average value of the characteristic as specified on the specification sheet of the 35 tube sample. If this value is on or above the LAL and on or below the UAL, accept for lot Average.

TEST FOR LOT Dispersion Acceptance:

Divide the 35 tube sample into seven (7) consecutive sub-groups of five (5) tubes each. Determine the range, R, of each sub-group for the measured characteristic specified on the Specification Sheet.

Compute the numerical average of the R values which is equal to $\bar{R}$. If $\bar{R}$ is equal to or less than the ALD, accept for Lot Dispersion.

Source: https://assist.dla.mil -- Downloaded: 2026-01-15T13:40Z
Check the source to verify that this is the current version before use.

Note 4: (Cont'd) Alternate Variables Sampling Procedure:

Test for Lot-Average Acceptance, Using Median

Select a 35 tube sample at random from the lot.

Test for all electrical characteristics for which variables acceptance limits are shown on the Tube Specification Sheet.

Arrange the 35 measurements in order of magnitude.

Find the value of the 18th measurement of the sample so arranged. This is the median ($\bar{x}$) of the sample of 35.

If the $\bar{x}$ is on or above the LAL and on or below the UAL, accept for lot average.

Test for Lot Dispersion Acceptance, Using Quasi-range.

Arrange the 35 measurements in order of magnitude.

Find the difference between the 3rd and 33rd measurements of the samples so arranged. This is the quasi-range (QR3) of the sample of 35.

Multiply this quasi-range by 0.83

If QR3 multiplied by 0.83 is equal to or less than the ALD, accept the characteristic for lot dispersion.

Note 5: This test shall be conducted on the initial lot and thereafter on a lot approximately every 30 days. Once a lot has passed, the 30-day rule shall apply. In the event of lot failure, the lot shall be rejected and the succeeding lot shall be subjected to this test. MIL-STD-105, sample size code letter F shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.

Note 6: Tubes shall be tested in a chamber under the conditions of pressure specified on the specification sheet. The specified voltage shall be applied between the base pins (or leads) of elements carrying B+ voltage and their adjacent pins (or leads). Voltage shall be of sinusoidal wave form with F=60 cycles. Tubes showing evidence of corona or arcing shall be considered defective.

Note 7: The impedance of the plate voltage supply shall not exceed that of a 40 uf capacitor at 10 cps.

Note 8: Destructive tests:

Tubes subjected to the following destructive tests are not to be accepted under this specification.

4.9.20.5 Shock.
4.9.20.6 Fatigue.
4.11.7 Heater-Cycling Life Test.
4.11.5 Intermittent Life Test.

Note 9: Application for qualification approval shall be made in accordance with Inspection Instructions for Electron Tubes, with the exception that the request for qualification approval shall be addressed to Director, Evans Signal Laboratory, Attention: Director, Electron Devices Division, and shall reference the number and date of the applicable contract, if any.

Note 10: Glass strain procedures - All tubes submitted to this test shall have been sealed a minimum of 48 hours prior to conducting this test. All tubes shall be at room temperature. The entire tube shall be immersed in water not less than 97°C for 15 seconds and immediately thereafter immersed in water not more than 5°C, for 5 seconds. The volume of water shall be large enough so that the temperature will not be appreciably affected by the test. The method of submersion shall be in accordance with Drawing #245-JAN, and such that a minimum of heat is conducted away by the holder used. The tubes shall be placed in the water so that no contact is made with the containing vessel, nor shall the tubes contact each other. After the 5-seconds submersion period, the tubes shall be removed and allowed to cool at room temperature on a wooden surface. After drying at room temperature for a period of 48 hours, the tubes shall be inspected and rejected for evidence of air leaks. (Paragraph 5.3.6.1, Inspection Instructions for Electron Tubes). Electrical rejects, other than inoperatives, may be used in the performance of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-01-15T13:40Z
Check the source to verify that this is the current version before use.

Note 11: The no-load to steady stage full load regulation of the heater voltage supply shall be not more than 3.0 percent. This test shall be made on a lot by lot basis. A failure or defect shall consist of an open heater, open cathode circuit, heater cathode short, or heater cathode leakage current in excess of the specified heater cycling life test end point limit.

Note 12: Stability Life Test:

a. Life test samples shall be selected from a lot at random in such a manner as to be representative of the lot. If such selection results in a sample containing tubes which are outside the initial specification sheet limits for the relevant life test end point characteristics, such tubes shall be replaced by randomly selected acceptable tubes.

b. Serially mark all tubes from the sample.

c. Record referenced characteristic measurements after a maximum operation of 15 minutes under specified voltage and current conditions on the entire sample.

d. Operate at life test conditions for one (1) hour (plus 30 minutes, minus 0 minutes). Life test shall be conducted as per Paragraphs 4.11 and 4.11.5, MIL-E-1, except that the following shall be substituted for the third sentence of 4.11 "The mean electrode potentials, except heater or filament, may be established at values differing by not more than 5% from the specified values provided the same average electrode dissipations are obtained that occur with the specified voltages. Fluctuations of all voltages including heater or filament voltage shall be as small as practical.

e. Record referenced characteristic measurements at the end of this test period. Referenced characteristic measurements shall be taken immediately following the test or tubes shall be preheated 15 minutes under specified test voltages and current conditions, and immediately measured. The 15 minutes preheat shall be considered as part of the test time.

f. A defective shall be defined as a tube having a change in referenced characteristic greater than that specified on the specification sheet.

g. A resubmitted lot must be subjected to all Measurements Acceptance Tests except Mechanical Inspection, Vibration, and Low Pressure Voltage Breakdown tests.

Source: https://assist.dla.mil -- Downloaded: 2026-01-15T13:40Z
Check the source to verify that this is the current version before use.

Note 13: Means of Assuring Survival Rate

The procedure for assuring the maintenance of a desirable quality level in terms of early life survival consists of a series of normal, reduced, and tightened inspection plans for use at 100 hours. The sample size is dependent upon lot size, and the transfer between normal, reduced, and tightened inspection is dependent upon quality history.

The selection of inspection scheme and sampling plan shall be in accordance with Inspection Instructions for Electron Tubes Paragraph 5.3.4.2 through 5.3.4.3.1.3 inclusive except that Paragraph 5.3.4.2.2 shall be modifed by deleting the last part of the first sentence which states "-----or if no lot in the last 20 lots inspected shall have been declared nonconforming for life test qualities." At the manufacturer's option, reduced inspection may be used if no lot in the last ten (10) lots inspected have been declared non-conforming.

Inspection Procedures

a. Select sample in accordance with Note 12, Paragraph (a).

b. Tubes to be tested at 100 hours as provided in MIL-E-1 (4.7.5). When any tap-short indication is obtained, the test shall be repeated. When any short indication is again obtained the tube will be rejected as an inoperative.

c. Determine the number of defective tubes at the 100 hour period.

d. If more than the allowable number of defectives occur, declare the lot non-conforming.

e. A resubmitted lot must be subjected to all Measurements Acceptance Tests except Mechanical Inspection, Vibration, and Low Pressure Voltage Breakdown tests.

Note 14: For survival Rate Life Test, the equivalent Stability Life Test conditions shall be interpreted as having the same heater voltage (Ef) and heater-cathode voltage (Ehk) as the Stability Life Test; and the same interruptions of MIL-E-1 Paragraph 4.11.5 as the Intermittent Life Test. The electrode voltages shall be such that the element dissipations are not less than 80 percent, nor more than 100 percent of Stability Life Test Plate Dissipation. These voltages are to be maintained within the limits of plus 200, minus 50 percent of the Stability Life Test voltages.

Source: https://assist.dla.mil -- Downloaded: 2026-01-15T13:40Z
Check the source to verify that this is the current version before use.

Note 15: Intermittent Life Tests:

a. The first 20 tubes of the Stability Life Test sample which meet the Measurements Acceptance Test Limits for those characteristics specified as Intermittent Life Test End Points may be used for the Intermittent Life Test sample. In the event that a second Stability Life Test sample is used, the first 20 tubes from that sample which meet the above conditions shall be used.

b. In the event of failure of the first sample on Intermittent Life Test, take a completely fresh sample (MIL-STD-105 sample size code letter I) and stabilize it in accordance with the conditions of the Stability Life Test. Then select from it the first 40 tubes which meet the measurements acceptance test limits for those characteristics specified as Intermittent Life Test End Points.

Subject these 40 tubes to the Intermittent Life Test. Acceptance shall then be based on combined results from the first and second samples.

As an alternate method, the manufacturer may select his life test sample as described in Note 13, Paragraph (a).

d. Regular Life Test:

1. Regular Life Test shall be conducted for 1000 hours.

2. Regular Life Test acceptance shall be on the basis of the 500 and 1000 hours requirements as indicated on the Specification Sheet.

3. Regular Life Test shall be in effect initially and shall continue in effect until the eligibility criteria for the Reduced Hours Life Test have been met.

e. Reduced Hours Life Test:

1. Reduced Hours Life Test shall be conducted for 500 hours and acceptance shall be based on the 500 hour end point limits.

2. Eligibility for Reduced Hours Life Tests: No lot failure due to the 1000 hour life test has occurred in the preceding three (3) consecutive lots.

3. Loss of eligibility for Reduced Hours Life Tests: Two (2) or more 500 hour life test lot failures occurring in the last three (3) consecutive lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.

Note 15: (Cont'd)

f. The life test sample be read at the following times:

0 hours
500 hours (plus 48 hours; minus 24 hours)
1000 hours (plus 48 hours; minus 24 hours; when in force)

Additional reading periods may be used at the discretion of the electron tube manufacturer.

g. Acceptance: The lot shall be considered satisfactory for acceptance provided that:

The specified allowable defects are not exceeded and the change of the average of any characteristic in the life test sample specified for life test control of averages is not exceeded. The average percentage change shall be ascertained from the determination of the individual changes for each tube in the life test sample from the zero (0) hour value for the referenced characteristic or characteristics. For purposes of computation of this average percentage change, the absolute values of the individual changes for each tube in the life test sample shall be used. Any tube found inoperative during life testing shall not be considered in the calculation of this average.

h. A resubmitted lot must be subjected to all Measurement Acceptance Tests except Mechanical Inspection, Vibration, and Low Pressure Voltage breakdown.

i. Not more than one (1) accidental breakage shall be allowed in the life test sample. If one (1) test tube is accidentally broken, acceptability of the life test sample shall be based upon the remaining tubes in the sample provided that the broken tube was not known to be a defective.

Note 16: Envelope Temperature is defined as the highest temperature indicated when using a thermocouple of #40 BS or smaller diameter elements welded to a ring of .025 inch diameter phosphor bronze in contact with the envelope. Bulb temperature requirements will be satisfied if tube, having bogie Ib (± 5%) under normal test conditions, is determined to operate at minimum specified temperature at any position of the life test rack.

Note 17: Order for Evaluation of Life Test Defects: - If a tube is defective for more than one attribute characteristic, the characteristic appearing first in the life Test End Points shall constitute the failure.

Source: https://assist.dla.mil -- Downloaded: 2026/10-15T13:40Z
Check the source to verify that this is the current version before use.

Note 18: An inoperative as referenced in Life Test is defined as a tube having one (1) or more of the following defects: discontinuity (Ref. MIL-E-1, para. 4.7.1), shorts (Ref. MIL-E-1, para 4.7.2), air leaks (Ref. Inspection Instructions for Electron Tubes, para. 5.3.6.1).

Note 19: Prior to this test the tube shall be preheated a minimum of five minutes at the conditions indicated below. (A three minute test period is not permitted). Test within 3 seconds after preheating. Grid emission shall be the last test performed on the sample selected for the grid emission test.

Ef	Ec1	Ec2	Eb	R_k	Rg1
V	Vdc	Vdc	Vdc	ohms	Meg
7.5	O	125	150	130	0.1

Note 20: The cathode resistor shall be shunted with a capacitive reactance not exceeding 3 ohms at 60 cycles. The rejection level shall be set at the VU meter reading obtained during calibration.

Note 21: Transconductance (2) is the percent change in Transconductance (1) of an individual tube resulting from the change in Ef.

Note 22: In addition to the rejection criteria of Para. 4.10.3.1, MIL-E-1, the output shall be read on a VU meter using a rejection limit of five (5) VU. Five (5) VU is the meter deflection obtained with a steady state output of 3 mW from the amplifier.

Note 23: Reference specification shall be of the issue in effect on the date of invitation for bid.

Note 24: Electron Tube 6AK5WB procured directly or indirectly on Army contracts shall have "U. S. ARMY" marked preceding, or above, the type designation. The letter "JAN" or any abbreviation thereof, shall not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:40Z
Check the source to verify that this is the current version before use.