INCH-POUND

MIL-DTL-3943/208B
5 January 2015
SUPERSEDING
MIL-DTL-3943/208A
7 August 2012

DETAIL SPECIFICATION SHEET


MEDAL, NAVAL RESERVE MERITORIOUS SERVICE, U.S. NAVY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER: 1-3/8 inches (REF)
THICKNESS (At thickest point): 0.140 inch $\pm$ 0.010 inch

REVERSE LUG: Reverse (exclusive of the lug) shall be flat and suitable for engraving.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:29Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/99

3. The use of any type of plastic packaging material is prohibited.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-2015-051)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:29Z
Check the source to verify that this is the current version before use.