NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/209D
10 August 2022
SUPERSEDING
MIL-DTL-3943/209C
29 September 2017

DETAIL SPECIFICATION SHEET

MEDAL, GOOD CONDUCT, U.S. MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE




REVERSE



SUSPENSION
RIFLE



ASSEMBLED
OBVERSE



ASSEMBLED
REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH (-1 and -2): Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:29Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
PENDANT:
DIAMETER:
-1: 1-3/8 inches (REF)
-2: 5/8 inch (REF)
THICKNESS (At rim):
-1: 0.105 inch ± 0.010 inch
-2: 0.080 inch ± 0.010 inch
SUSPENSION RIFLE:
HEIGHT: (At lug):
-1: 1/4 inch (REF)
-2: 1/8 inch (REF)
WIDTH (Overall):
-1: 1-19/32 inches (REF)
-2: 51/64 inch (REF)
THICKNESS (At thickest point):
-1: 0.075 inch ± 0.010 inch
-2: 0.060 inch ± 0.010 inch

SUSPENSION RIFLE & RING:

1. A hole 1/16 inch + 1/64 inch - 0 in diameter shall be drilled through the medal and suspension rifle in the location shown.

2. The pendant ribbon ring for -1 shall be formed from 0.050 inch ± 0.002 inch diameter wire and shall have an outside diameter of 9/32 inch ± 1/64 inch.

3. The suspension rifle and the pendant for -2 shall be one piece height shall be 1/8 inch and the width shall be 51/64 inch.

4. The width of the opening above the pendant rifle shall be 1-3/8 inches + 1/64 inch -0 for -1 and 11/16 inch + 1/64 inch - 0 for -2.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/69.

3. For commercial sale only may be manufactured using 24K Gold Plate Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:29Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Navy - MC

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-142)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:29Z
Check the source to verify that this is the current version before use.