INCH-POUND

MIL-DTL-3943/210A
24 July 2012
SUPERSEDING
MIL-DTL-3943/210
30 June 1997

DETAIL SPECIFICATION SHEET

MEDAL, U. S. MARINE CORPS EXPEDITIONARY

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH (-1 and -2): Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:29Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

DIAMETER:

-1: 1-1/4 inches (REF)

-2: 5/8 inch (REF)

THICKNESS (At rim):

-1: 0.105 inch ± 0.010 inch

-2: 0.080 inch ± 0.010 inch

PENDANT RING:

1. The pendant ring shall be fabricated from 0.050 inch ± 0.002 inch nominal diameter wire with the same material and finish as the pendant.

2. The ring shall have an outside diameter of 0.200 inch ± 0.010 inch.

3. The ring shall be hard soldered to the top center of the pendant as shown.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/81.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Review activities:
Navy – MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-2012-060)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:29Z
Check the source to verify that this is the current version before use.