NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/211
30 June 1997
SUPERSEDING
MIL-M-3946/34D
6 October 1994

DETAIL SPECIFICATION SHEET

MEDAL, SELECTED MARINE CORPS RESERVE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH metal finish chip Number 4.

DIMENSIONS:
DIAMETER:
-1: 1-1/4 inches (3.18 cm) (REF)
-2: 5/8 inch (1.59 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:30Z
Check the source to verify that this is the current version before use.

THICKNESS (At Rim):
-1: 0.105 inch ± 0.010 inch (0.256 cm ± 0.025 cm)
-2: 0.080 inch ± 0.010 inch (0.203 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The pendant ring shall be fabricated from 0.050 inch ± 0.002 inch (0.127 cm ± 0.005 cm) nominal diameter wire with the same material and finish as the pendant. The ring shall have an outside diameter of 0.200 inch ± 0.010 inch (0.508 cm ± 0.025 cm). The ring shall be hard soldered to the top center of the pendant as shown.

3. The ribbon for the pendant drape shall conform to MIL-DTL-11589/113.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0897)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:30Z
Check the source to verify that this is the current version before use.