MIL-B-55521C
24 May 1983
SUPERSEDING
MIL-B-55521B
5 January 1977

MILITARY SPECIFICATION

BATTERIES, NONRECHARGEABLE,
PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for packaging of non-rechargeable batteries during shipment and storage.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
NN-P-71	-	Pallets, Material Handling, Wood, Double Faced, Stringer Construction, 2-Way and 4-Way (Partial)
QQ-S-781	-	Strapping, Steel and Seals
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-585	-	Boxes, Wood, Wirebound
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall
PPP-B-676	-	Boxes, Setup
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to US Army Communications-Electronics Command, ATTN: DRSEL-MMD-P, Fort Monmouth, New Jersey 07703, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

PPP-S-760 - Strapping, Nonmetallic (And Connectors)
PPP-T-97 - Tape; Packaging/Industrial, Filament Reinforced

MILITARY

MIL-P-116 - Preservation, Packaging Methods of

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads for 40" x 48" Pallets

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preservation. Preservation shall be level A or B, as specified (see 6.2).

3.1.1 Level A.

3.1.1.1 Cleaning. Each battery shall be cleaned in accordance with process C-1 of MIL-P-116.

3.1.1.2 Drying. Each battery shall be dried in accordance with the applicable procedures of MIL-P-116.

3.1.1.3 Preservative application. No preservative required.

3.1.1.4 Terminal protection. Battery terminals shall be protected by non-corrosive, insulating materials to prevent damage and short-circuiting.

3.1.1.5 Unit packs. Batteries, in the quantities specified in table II or III, and of the same type and date of manufacture, shall be unit packed in accordance with submethod IC-2 (modified) of MIL-P-116 (except as specified in footnotes 1 and 2) as follows: Place within a close-fitting box conforming to PPP-B-566, variety 1, or PPP-B-636, type CF, class domestic, style optional. Closure shall be as specified in the appendix of the applicable box specification. The boxed batteries shall be placed in a polyethylene bag conforming to L-P-378, type I, class 1, grade B, finish 1, having a minimum thickness of 4.0 $\pm$ 0.5 mils. Closure of the bag shall be by heat seal. The bagged batteries shall be placed in a close-fitting box conforming to PPP-B-636, type CF,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

class weather-resistant, style optional or PPP-B-566, variety 2, style II or PPP-B-676, type I, variety 2. Closure shall be in accordance with the appendix of the applicable box specification.

3.1.1.6 Intermediate packs. When specified in table II or III, the unit packed batteries shall be placed in a close-fitting box conforming to PPP-B-636, type CF, class weather-resistant, style optional. When intermediate packing is specified, the outer box for the bagged batteries specified in 3.1.1.5 shall be deleted. Closure shall be in accordance with the appendix of the applicable box specification.

3.1.2 Level B. Batteries shall be preserved as specified in 3.1.1.

3.2 Packing. Packing shall be level A or B, as specified (see 6.2). Shipping containers for all levels shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents when tested in accordance with Methods 5016 and 5017 of FED-STD-101.

3.2.1 Level A. A multiple quantity of batteries, unit or intermediate packed as specified in 3.1 and bearing the same stock number, shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, class 2, style 4; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A. When the quantity of a stock numbered item being shipped to a single destination comprises a shipping container volume of less than one cubic foot, packing shall be as specified for level B.

3.2.1.1 Unitization. Palletization shall be required when: containers specified in 3.2.1 do not require skids; quantities per destination exceed either a total of 250 pounds (excluding the pallet) or a volume of 20 cubic feet; and the container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers, packed as specified in 3.2.1 except that container strapping may be omitted, shall be placed on a pallet, load type I conforming to MIL-STD-147. The pallet shall conform to NN-P-71, type IV, group I or II woods. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film conforming to L-P-378, type IV. Stretch wrap in accordance with MIL-STD-147 is authorized for shipments within the Continental United States and for containerized shipments.

3.2.2 Level B. A multiple quantity of batteries, unit or intermediate packed as specified in 3.1 and bearing the same stock number, shall be packed within a close-fitting box conforming to PPP-B-601, domestic type; PPP-B-621, class 1, style 4; PPP-B-585, style 2 or 3, class 3; PPP-B-640, class 2, style E; or PPP-B-636, type CF, class weather-resistant, style optional. The gross weight of boxes conforming to PPP-B-640 shall not exceed 250 pounds. Closure shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97 and PPP-S-760, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71, group I or II woods. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A or shrink film conforming to L-P-378, type IV. When a single unit is shipped to a single destination, no packing is required; the unit container (other than a bagged item) may serve as the shipping container. Reinforcing shall be as specified above. When the unit container is a bag, the unit pack shall be inclosed in a box as specified in 3.1.1.5.

3.2.2.1 Unitization. When the palletization requirements specified in 3.2.1.1 are met, a quantity of items, unit or intermediate packed as specified in 3.1 and bearing the same stock number, shall be palletized as specified in 3.2.1.1.

3.2.3 General. Shipping containers for a battery type shall be uniform in shape, size, style and kind. Shipping containers of minimum cube and weight consistent with the protection prescribed are required to the greatest extent practicable.

3.3 Marking. In addition to special marking required by the contract or order, and marking required by MIL-STD-129, the following special marking shall be applied:

a. Each unit pack of the battery types requiring special marking, as specified in the individual military specification sheets for the batteries, shall have test data applied in the format specified in the individual specification sheets.

b. The date of manufacture shall be shown on all containers. On unit packs only, the date shall be shown in code.

c. Each shipping container or palletized load shall have the following special marking applied in accordance with MIL-STD-129, except as specified in 3.3.1:

PERISHABLE
STORE UNDER REFRIGERATION
TO PREVENT DETERIORATION

3.3.1 Exceptions. Exceptions to special marking requirements cited in 3.3c are as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

a. Preproduction and production (Group C) samples when it is not economically feasible to ship under refrigeration.

b. BA-605/U, BA-617/U, BA-627/U, BA-628/U, and NSN 6135-00-655-2279.

3.4 Workmanship. The quality of workmanship shall be such as to permit acceptance of the completed packaging requirements in accordance with the inspection specified in section 4.

3.5 Deviations. Requests for deviation in packaging design shall be supported by test data proving the ability of the batteries, packaged in accordance with the proposed design change, to withstand the applicable tests for the selected method, including the rough handling tests in accordance with MIL-P-116. Deviation approval shall be contingent on availability of packaging materials selected and economies realized.

3.6 Dimensional data. When the dimensions of the batteries vary from those cited, the dimensions of the packaging materials shall be adjusted accordingly.

3.7 Unlisted batteries. For batteries not listed in this document, packaging shall be developed using a battery possessing the same or similar mechanical, physical, or electrical characteristics. Unit and intermediate pack quantities shall be based on the requirements listed in the tables.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First Article Inspection of packaging.

b. Quality Conformance Inspection of packaging.

4.2.1 First article inspection of packaging. When specified (see 6.2), first article inspection shall be performed by the contractor, after award of contract and prior to production, at a time and location acceptable to the Government. First article inspection shall not be required:

a. When there have been no changes in materials, processes, or packaging design that will adversely affect item protection since the last recorded inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

b. When a prior successful inspection was conducted on a like item and pack (subject to the approval of the administrative contracting officer).

4.2.2 Quality conformance inspection of packaging.

4.2.2.1 Materials inspection. All materials to be used in packaging shall be inspected in accordance with the applicable material specification.

4.2.2.2 Preservation inspection. Inspection of preservation and interior markings shall be in accordance with group A and B quality conformance inspection requirements of MIL-P-116. Lot formation and sampling procedures shall be as specified therein.

4.2.2.3 Packing inspection. Inspection of packing and the marking for shipment and storage shall consist of the examinations specified in table I, "Packing inspection provisions." Lot formation shall consist of all packs made of the same materials during an identifiable period and submitted at one time for acceptance. Sampling procedures shall be in accordance with MIL-STD-105, using a single sampling plan and acceptable quality level of 4.0 percent defective.

TABLE I. Packing inspection provisions.

NO.	CHARACTERISTIC	METHOD OF INSPECTION
101	Intermediate container not as specified	Visual
102	Improper closure of intermediate container	Visual
103	Shipping containers not in accordance with specification	Visual
104	Excessive cube	Visual
105	Improper blocking and bracing	Visual
106	Closure not in accordance with specification	Visual
107	Weight and size exceed container limitations	Weight and Measure
108	Strapping not in accordance with specification, incorrectly applied, omitted	Visual
109	Marking omitted, incorrect, or illegible	Visual

5. PACKAGING

5.1 Packaging. Not applicable to this specification.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:17Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Intended use. The preservation, packing, and marking specified herein are primarily intended for direct shipments to the Government. However, this specification may also be used for the preparation of batteries for shipment from the parts contractor to the original equipment manufacturer.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Level A or B preservation and packing (see section 3).

c. When first article inspection is required (see section 4).

d. When first article packaging inspection test reports require Acquisition Activity approval prior to production unit packing.

6.3 Level B preservation. When level B preservation is specified, this level of protection will only be used under known favorable conditions during transportation, storage and handling.

6.4 Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or preparing activity for recommended disposability methods.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - SH
Air Force - 99

Preparing activity:
Army - CR

(Project PACK-0706)

Review activities:
Army - SM
Navy - AS
Air Force - 80

User activities:
Army - MI, PA
Navy - YD, MC, OS, MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Unit pack quantity, arrangement, dimensions; intermediate pack quantity and arrangement.

BATTERY TYPE BA-	UNIT PACK			INTER. PACK	
	QUP	ARR (L-W-D)	APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	IPQ	ARR (L-W-D)
2	6	2-3-1	7 x 6-3/8 x 3-1/8	4	2-1-2
8	4	2-2-1	13-1/4 x 8-1/8 x 3-1/2	4	1-2-2
9	10	2-5-1	5-1/8 x 4-3/8 x 3-1/8	8	2-2-2
15A	8	2-4-1	5-3/8 x 5-3/8 x 4-5/8	4	2-1-2
23	6	3-2-1	7-3/4 x 5-1/8 x 6-3/4	--	--
26	1	--	8-1/4 x 4-1/2 x 8	--	--
27	8	2-4-1	8-1/8 x 6 x 3-3/4	4	1-2-2
28	15	3-5-1	6 x 3-3/8 x 2-3/4	8	2-2-2
30	24	6-4-1	7-7/8 x 5-1/4 x 2-3/8	4	1-2-2
		6-2-2	7-7/8 x 2-5/8 x 4-3/4	4	1-2-2
31	10	2-5-1	5 x 4-1/4 x 3-1/4	8	2-2-2
33	2	1-2-1	6-1/4 x 7-1/4 x 5-7/8	--	--
34	12	2-6-1	8-1/4 x 5-1/4 x 3-1/2	4	1-2-2
35	6	3-2-1	8 x 5-3/8 x 4-5/8	4	1-2-2
36	3	1-3-1	4-1/4 x 7-1/2 x 6-1/2	--	--
37	12	3-4-1	4-1/8 x 5-3/8 x 6-1/4	4	2-2-1
38	12	3-4-1	4-1/8 x 5-1/2 x 11-3/4	--	--
39	2	1-2-1	6-1/2 x 7-5/8 x 7-5/8	--	--
40	2	2-1-1	10-5/8 x 4-1/4 x 7-1/2	--	--
41	4	2-2-1	4-3/4 x 4-1/4 x 3-1/2	8	2-2-2
42	24	6-4-1	6-1/8 x 4-1/8 x 2	12	2-2-3
		6-2-2	6-1/8 x 2-1/8 x 4	12	2-3-2
44	1	--	10-1/2 x 2-7/8 x 7-1/2	--	--
48	4	1-4-1	10-1/8 x 8-7/8 x 5	--	--
51	10	2-5-1	5-1/2 x 6-5/8 x 3-7/8	4	2-1-2
53	4	1-4-1	3-1/8 x 7-5/8 x 5-1/4	4	2-2-1
56	10	2-5-1	5-1/4 x 4-7/8 x 3-3/4	4	2-2-1
58	24	12-1-2	6-3/4 x 9/16 x 3-7/8	24	1-12-2
		6-2-2	3-3/8 x 1-1/8 x 3-7/8	24	2-6-2
59	6	2-3-1	7-1/8 x 5-1/4 x 5-5/8	--	--
63	4	2-2-1	6 x 4-5/8 x 4-1/4	4	2-2-1
65	6	3-2-1	8 x 5-3/8 x 4-1/8	--	--
67	4	1-4-1	4-1/8 x 7-3/4 x 4-5/8	4	2-1-2
70	1	--	10-3/8 x 4-5/8 x 7-3/4	--	--
90	24	6-4-1	6-1/4 x 2-3/4 x 2-1/8	12	2-2-3
200/U	12	4-3-1	10-5/8 x 8 x 4-1/2	2	1-2-1
202/UF	24	6-2-2	8 x 2-3/4 x 2-1/2	6	1-3-2
203/U	2	1-2-1	4 x 5-5/8 x 5-5/8	4	2-2-1
205/U	8	2-4-1	5-3/8 x 5-3/8 x 4-3/4	4	2-2-1
206/U	1	--	7-7/8 x 5-3/8 x 7-1/2	--	--
207/U	1	--	8-5/8 x 4-1/8 x 6-5/8	--	--
208/U	18	3-6-1	4-1/4 x 4-1/4 x 3	8	2-2-2
210/U	6	3-2-1	8 x 5-3/8 x 4-1/8	4	1-2-2
211/U	6	1-3-2	4-1/8 x 7-5/8 x 6	4	2-2-1
216/U	2	2-1-1	7-7/8 x 4 x 6	4	2-2-1

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:17Z
Check the source to verify that this is the currentversion before use.

TABLE II. Unit pack quantity, arrangement, dimensions; intermediate pack quantity and arrangement. - Continued

BATTERY TYPE BA-	UNIT PACK QUP	UNIT PACK ARR (L-W-D)	UNIT PACK APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	INTER. PACK IPQ	INTER. PACK ARR (L-W-D)
221/U	4	1-4-1	3-3/4 x 7-3/8 x 6-5/8	4	2-2-1
222/U	1	--	8-1/4 x 2-3/4 x 6-1/2	4	1-4-1
223/U	6	3-2-1	12-1/4 x 5-1/4 x 5-3/8	--	--
225/U	2	1-2-1	4 x 5-3/8 x 6-1/4	4	2-2-1
226/U	10	2-5-1	8 x 6-5/8 x 4-3/4	--	--
228/U	6	2-3-1	6 x 3-3/8 x 4-5/8	4	2-2-1
230/U	6	2-3-1	8-3/8 x 7-5/8 x 3-3/8	--	--
231/U	1	--	1-3/8 x 1-3/8 x 4-1/8	50	5-5-2
232/U	1	--	1-3/4 x 1-1/2 x 3	50	5-5-2
233/U	1	--	2-1/8 x 1-1/2 x 3	50	5-5-2
234/U	1	--	2-1/8 x 1-1/2 x 4	50	5-5-2
235/U	1	--	8 x 8 x 7-3/8	--	--
239/U	1	--	10-1/2 x 2-3/4 x 7	--	--
243/U	1	--	3-1/4 x 3-1/4 x 6-7/8	12	4-3-1
245/U	1	--	1 x 1 x 2-3/4	50	5-5-2
249/U	1	--	10-1/2 x 2-3/4 x 7-1/2	--	--
251/U	10	2-5-1	3-3/8 x 4-3/8 x 3-3/8	12	3-2-2
261/U	24	4-6-1	4-1/8 x 3-3/4 x 2	16	2-2-4
266/U	8	2-4-1	4-1/4 x 5-5/8 x 4-1/2	6	3-2-1
270/U	12	4-3-1	11-1/8 x 7-7/8 x 7-1/2	--	--
271/U	1	--	3-5/8 x 3-5/8 x 6-1/4	10	5-2-1
272/U	24	4-6-1	4-5/8 x 3-5/8 x 2-1/8	16	2-2-4
279/U	2	1-2-1	8-1/2 x 4-3/4 x 8-1/2	--	--
291/U	1	--	2-3/4 x 2-1/4 x 4	25	5-5-1
305/U	24	3-4-2	3-1/8 x 2-1/2 x 5-1/8	16	4-4-1
309/U	4	2-2-1	8 x 5-3/8 x 4-5/8	--	--
310/U	4	2-2-1	5-3/8 x 5-3/8 x 4-3/4	6	3-2-1
314/U	12	3-4-1	8-1/2 x 5-1/2 x 2-5/8	4	1-2-2
326/U	4	2-2-1	10-5/8 x 5-1/2 x 4-5/8	--	--
331/U	1	--	1-1/8 x 3/4 x 1-1/2	100	5-10-2
332/U	1	--	3/4 x 3/4 x 1-1/2	100	10-5-2
333/U	1	--	3/4 x 3/4 x 2	100	10-5-2
334/U	1	--	1-1/4 x 5/8 x 1-1/2	100	5-10-2
335/U	1	--	5/8 x 3/8 x 2-5/8	100	10-10-1
358/U	2	1-1-2	8-3/4 x 4-1/2 x 5-5/8	--	--
377/U	1	--	14-1/4 x 12-1/4 x 1-1/2	8	1-1-8
386/PRC-25	1 1/	--	9-1/2 x 3-5/8 x 2-1/8	8	1-4-2
398/PRC-25	1	--	12-1/4 x 11-1/4 x 1-1/2	8	1-2-4
399/U	1 2/	--	2 x 1-3/8 x 3-1/4	50	5-5-2
401/U	20	5-4-1	6-3/4 x 5-3/8 x 3-5/8	4	1-2-2
402/U	8	2-4-1	5-3/8 x 5-3/8 x 4-5/8	4	2-1-2
403/U	6	2-3-1	8 x 4-3/8 x 4-5/8	4	1-2-2
404/U	6	3-2-1	8 x 5-3/8 x 4-5/8	--	--
405/U	4	2-2-1	8 x 5-3/8 x 4-5/8	--	--
406/U	10	2-5-1	5-3/8 x 7 x 3-1/4	6	2-1-3
[illegible]	2	2-4-1	5-3/8 x 5-5/8 x 4-5/8	4	2-1-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Unit pack quantity, arrangement, dimensions, intermediate pack quantity and arrangement. - Continued

BATTERY TYPE BA-	UNIT PACK			INTER. PACK	
	QUP	ARR (L-W-D)	APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	IPQ	ARR (L-W-D)
408/U	8	2-2-2	8 x 4-3/8 x 4-5/8	4	1-2-2
409/U	6	3-2-1	8 x 5-3/8 x 4-5/8	--	--
410/U	4	1-2-1	8 x 5-3/8 x 4-5/8	--	--
411/U	1	--	5-1/2 x 4 x 6-1/8	4	2-2-1
412/U	1	--	7-7/8 x 4 x 6-1/8	--	--
413/U	12	3-4-1	4-7/8 x 5-7/8 x 3-3/8	8	2-2-2
414/U	12	3-4-1	9 x 5-7/8 x 3-3/8	4	1-2-2
415/U	6	6-1-1	8-3/4 x 5-1/2 x 3-3/8	4	1-2-2
416/U	4	2-2-1	8-3/8 x 5-7/8 x 3-3/8	4	1-2-2
417/U	6	3-2-1	7-1/4 x 4-5/8 x 4-1/4	4	1-2-2
418/U	6	2-3-1	8-1/4 x 7-1/8 x 4-1/4	--	--
419/U	3	1-3-1	7-3/4 x 7-1/8 x 4-1/4	--	--
420/U	2	1-2-1	6-3/4 x 8-7/8 x 4-1/4	--	--
421/U	6	2-3-1	5-3/8 x 7-5/8 x 4-7/8	--	--
422/U	3	1-3-1	4-1/4 x 7-3/4 x 5-3/4	--	--
424/U	2	1-2-1	7-3/4 x 8-1/2 x 5-3/4	--	--
471/U	6	3-2-1	8 x 5-3/8 x 4-5/8	--	--
505/U	4	4-1-1	2-3/8 x 5/8 x 5-3/8	50	5-10-1
605/U	1	--	1-7/8 x 1-7/8 x 2-3/8	50	5-5-2
617/U	1	--	2 x 2 x 4-3/4	50	5-5-2
627/U	1	--	2-1/4 x 2-1/4 x 2-1/8	40	5-4-2
628/U	1	--	1-5/8 x 1-5/8 x 2-3/8	50	5-5-2
802/U	1	--	2-3/4 x 1-5/8 x 4-1/2	25	5-5-1
803/U	2	2-1-1	5-1/4 x 2-5/8 x 4-1/2	12	2-3-2
804/U	1	--	7-1/4 x 4-1/8 x 6-1/2	4	2-2-1
805/U	1	--	3-3/4 x 1-3/8 x 3-3/4	20	2-5-2
806/U	1	--	3-5/8 x 2-3/8 x 4-5/8	20	2-5-2
807/U	1	--	7-7/8 x 3 x 7-1/8	8	2-4-1
808/U	1	--	8 x 5-1/8 x 7-3/8	--	--
809/U	1	--	5-3/4 x 1-5/8 x 3-3/8	20	2-5-2
810/U	1	--	3-7/8 x 2-3/8 x 6-3/8	12	3-4-1
811/U	1	--	2-3/4 x 2-3/4 x 4-7/8	20	5-4-1
813/U	6	2-3-1	5-7/8 x 2 x 1-1/2	40	2-4-5
815/U	1	--	4-1/4 x 2-3/4 x 5-5/8	12	3-4-1
816/U	2	1-2-1	3-1/2 x 6-1/4 x 4-1/2	12	3-2-2
818/U	1	--	2-1/8 x 2-1/8 x 2-3/4	40	5-4-2
820/U	1	--	2-7/8 x 2-7/8 x 9-5/8	12	4-3-1
821/U	4	2-2-1	3-1/4 x 1-3/4 x 3-1/8	20	2-5-2
823/U	1	--	1-7/16 x 1-1/8 x 2-7/8	50	5-5-2
828/U	6	2-3-1	8-1/8 x 4-1/8 x 4-1/4	4	1-2-2
829/U	6	2-3-1	16-1/4 x 12-1/4 x 7-3/8	--	--
832/U	1	--	2-3/4 x 3-5/16 x 5-9/16	12	4-3-1
833/U	1	--	3-1/8 x 1-3/8 x 2-11/16	24	3-4-2
834/U	3	1-3-1	1-1/8 x 2 x 3-3/4	40	5-4-2
1003/U	4	4-1-1	5-3/4 x 4 x 5-1/8	--	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Unit pack quantity, arrangement, dimensions, intermediate pack quantity and arrangement. - Continued

BATTERY TYPE BA-	UNIT PACK			INTER. PACK	
	QUP	ARR (L-W-D)	APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	IPQ	ARR (L-W-D)
1006/U	40 4/	OPTIONAL	OPTIONAL	--	--
1010/U	10 4/	2-1-5	3 x 1-1/2 x 2-1/8	20	2-10-1
1015/A/U	8 4/	2-4-1	5-3/8 x 5-3/8 x 4-5/8	4	2-1-2
1030/U	24 4/	6-4-1	7-7/8 x 5-1/4 x 2-3/8	4	1-2-2
		6-2-2	7-7/8 x 2-5/8 x 4-3/4	4	1-2-2
1051/U	10	2-5-1	5-1/2 x 6-5/8 x 3-7/8	4	2-1-2
1082/U	2 3/	1-2-1	2-1/8 x 3-1/4 x 2-5/8	24	4-3-2
1083/U	1	--	2-3/4 x 2-3/4 x 5-3/4	10	5-2-1
1085/U	10	5-2-1	3-5/8 x 1-1/2 x 4-5/8	12	2-6-1
1086/U	10 3/	5-2-1	3-3/8 x 1-3/8 x 6	12	3-4-1
1087/U	10	5-2-1	3-3/8 x 1-3/8 x 6	10	2-5-1
1089/U	20	5-4-1	2-5/8 x 2-1/8 x 1-1/8	50	2-5-5
1090/U	24	6-4-1	6-1/4 x 2-3/4 x 2-1/8	12	2-2-3
1092/U	10	5-2-1	3-1/2 x 1-3/8 x 2	12	3-4-1
1093/U	10 3/	5-2-1	3-3/8 x 1-3/8 x 4	16	2-8-1
1094/U	10	5-2-1	3-3/8 x 1-3/8 x 1-3/4	24	2-4-3
1096/U	1	--	3/4 x 3/8 x 3/4	100	5-10-2
1098/U	10	5-2-1	3-3/8 x 1-3/8 x 2	100	5-5-4
1100/U	12 3/	6-2-1	9-1/8 x 3-1/8 x 2-1/2	4	1-2-2
1101/U	1	--	1-1/8 x 1-1/8 x 3	100	10-5-2
1102/U	20 4/	5-2-2	6-1/8 x 2-1/2 x 1-3/8	20	1-5-4
1104/U	5 3/	1-1-5	3/4 x 3/4 x 1-1/8	100	2-10-5
1105/U	1	--	5/8 x 5/8 x 2	100	10-10-1
1106/U	10 3/	1-5-2	5 x 2 x 2	50	2-5-5
1110/U	20 4/	2-2-5	2-1/8 x 2-1/8 x 2-5/8	24	4-3-2
1111/U	1	--	1-1/8 x 1-1/8 x 6	100	10-10-1
1112/U	1	--	3-3/4 x 7/8 x 4-1/2	24	3-8-1
1210/U	6	3-2-1	8 x 5-3/8 x 4-1/8	4	1-2-2
1232/U	1	--	1-5/8 x 1-3/8 x 3	50	5-5-2
1234/U	1	--	2-1/8 x 1-3/8 x 4	25	5-5-1
1264/U	1	--	3-5/8 x 1-3/4 x 6-3/4	12	3-4-1
1277/U	6 4/	2-3-1	5-1/8 x 4-1/8 x 4-1/4	4	2-2-1
1278/U	4	1-4-1	3-3/8 x 5-3/8 x 4-1/4	4	2-2-1
1288/U	20 4/	5-4-1	6-3/4 x 5-1/2 x 3/4	16	2-2-4
1293/U	10	5-1-2	4 x 7/8 x 2-1/2	40	2-10-2
1312/U	40 4/	8-5-1	5-1/8 x 3-1/4 x 3/4	24	2-3-4
1313/U	1	--	2-3/4 x 2-1/8 x 7-5/8	8	2-4-1
1315/U	1	--	3-1/2 x 1-5/8 x 6-3/4	12	2-6-1
1318/U	25 3/	5-5-1	3-3/8 x 3-3/8 x 1-1/8	24	3-2-4
1322/U	3	3-1-1	8 x 2-3/4 x 3-1/4	8	1-4-2
1328/U	25 4/	5-5-1	3-1/4 x 3-1/4 x 2	12	3-2-2
1330/U	20 4/	5-4-1	5-3/8 x 4-3/8 x 3/4	24	2-2-6
1363/U	25 3/	5-5-1	3-1/4 x 3-1/4 x 2-3/8	12	3-2-2
1371/U	10	5-2-1	3-3/8 x 1-3/8 x 2-3/4	40	4-5-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Unit pack quantity, arrangement, dimensions, intermediate pack quantity and arrangement. - Continued

BATTERY TYPE BA-	UNIT PACK QUP	UNIT PACK ARR (L-W-D)	UNIT PACK APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	INTER. PACK IPQ	INTER. PACK ARR (L-W-D)
1372/U	2 3/	2-1-1	1-1/2 x 3/4 x 1-3/8	40	4-5-2
1373/U	10 3/	5-2-1	3-3/8 x 1-3/8 x 1-3/8	50	2-5-5
1387/U	1	--	3-1/2 x 1-9/16 x 5-3/4	16	2-8-1
1389/U	25 3/	5-5-1	3-3/8 x 3-3/8 x 5-3/8	4	2-2-1
1391/U	20 4/	2-2-5	3 x 3 x 2-3/4	12	3-2-2
1393A/U	1	--	1-1/2 x 1-1/4 x 5-1/2	40	8-5-1
1396/U	25 3/	5-5-1	3-3/8 x 3-3/8 x 1-7/8	16	2-2-4
1400/U	10	5-2-1	3-3/8 x 1-3/8 x 2-1/4	40	4-5-2
1425/U	20 4/	10-2-1	4-3/4 x 1 x 1-1/8	50	2-5-5
1499/U	4	2-2-1	5 x 3-5/8 x 2-5/16	40	2-5-4
1509/PRC-64	1	--	4-7/8 x 1-3/4 x 4-3/4	12	2-6-1
1516/U	2	1-2-1	4-3/4 x 3-3/4 x 1-1/2	24	2-3-4
1531/U	1	--	2-7/8 x 7/8 x 1-3/4	40	2-10-2
1532/U	1	--	1-1/16 x 1-1/16 x 5/16	100	5-5-4
1533/U	2	2-1-1	2 x 1 x 3/8	24	3-4-2
1542/U	1	--	3-3/8 x 3-3/8 x 8	8	4-2-1
1544/U	1	--	3-3/8 x 3-3/8 x 17-1/2	--	--
1545/U	1	--	4 x 3-7/8 x 3	16	2-4-2
1546/U	1	--	2-3/4 x 2-3/4 x 4-1/2	12	4-3-1
1548/U	1	--	3 x 3 x 10-1/4	4	2-2-1
1549/U	1	--	5-1/2 x 5-3/4 x 2-1/8	12	3-2-2
1567/U	1	--	1-1/16 x 1-1/16 x 7/8	100	5-5-4
1568/U	1	--	1-1/8 x 1-1/8 x 3-1/8	50	5-5-2
1570/U	1	--	4-5/8 x 4-5/8 x 7	12	4-3-1
1574/U	10	5-2-1	5 x 2 x 2-5/8	24	2-6-2
1579/U	20 3/	5-4-1	2-5/8 x 2-1/8 x 1-1/8	50	5-5-2
1588/U	1	--	3-1/2 x 1-1/4 x 2-1/8	40	4-5-2
1844/U	1	--	6-1/8 x 1 x 2-5/8	40	2-10-2
2245/U	1 5/	--	1 x 1 x 2-3/4	50	5-5-2
3030/U	24	6-4-1	7-7/8 x 5-1/4 x 2-3/8	4	1-2-2
		6-2-2	7-7/8 x 2-5/8 x 4-3/4	4	1-2-2
3036/U	3	1-3-1	4-1/4 x 7-1/2 x 6-1/2	--	--
3042/U	24	6-4-1	6-1/8 x 4-1/4 x 2	12	2-2-3
		6-2-2	6-1/8 x 2-1/8 x 4	12	2-3-2
3044/U	1	--	10-1/2 x 2-7/8 x 7-1/2	--	--
3051/U	10	2-5-1	5-1/2 x 6-5/8 x 3-7/8	4	2-1-2
3058/U	24	12-1-2	6-3/4 x 9/16 x 3-7/8	24	1-12-2
		6-2-2	3-3/8 x 1-1/8 x 3-7/8	24	2-6-2
3090/U	24	6-4-1	6-1/4 x 2-3/4 x 2-1/8	12	2-2-3
3200/U	12	4-3-1	10-5/8 x 8 x 4-1/2	2	1-2-1
3202/UF	24	6-2-2	8 x 2-3/4 x 2-1/2	6	1-3-2
3515/U	1	--	8-5/8 x 4-1/4 x 1-3/4	8	1-2-4
3517/U	1	--	7 x 5-3/4 x 5-3/4	8	2-2-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Unit pack quantity, arrangement, dimensions, intermediate pack quantity and arrangement. - Continued

BATTERY TYPE BA-	UNIT PACK			INTER. PACK	
	QUP	ARR (L-W-D)	APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	IPQ	ARR (L-W-D)
3553/U	1	--	5-3/4 x 2 x 4-1/2	8	2-4-1
3590/U	1	--	4-1/2 x 2-1/2 x 5	12	3-4-1
4200/U	12	4-3-1	10-5/8 x 8 x 4-1/2	2	1-2-1
4386/PRC-25	1 1/	--	9-5/8 x 3-3/4 x 2-1/4	8	1-4-2
4505/U	1	--	11/16 x 11/16 x 5-3/8	100	10-10-1
4534/U	1	--	5/8 x 5/8 x 3-3/4	100	10-10-1
4840/U	1	--	11-5/8 x 3-1/2 x 6	--	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

TABLE III. Unit pack quantity, arrangement, dimensions; intermediate pack quantity and arrangement.

NSN 6135	UNIT PACK QUP	UNIT PACK ARR (L-W-D)	UNIT PACK APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	INTER. PACK IPQ	INTER. PACK ARR (L-W-D)
00-023-5309	1	--	2-3/4 x 2-1/8 x 4-5/8	25	5-5-1
00-034-5014	1	--	1-3/4 x 1-3/4 x 3-1/8	25	5-5-1
00-042-5414	1	--	5-9/16 x 5-9/16 x 5-3/8	--	--
00-044-1822	1	--	5/8 x 5/8 x 2-1/8	100	10-10-1
00-087-3933	1	--	1 x 1 x 5-7/8	100	10-10-1
00-100-0398	1	--	2-3/4 x 2-3/4 x 4-7/8	24	4-3-2
00-110-4135	1	--	7-1/8 x 2-7/8 x 2-7/8	8	1-4-2
00-110-7463	1	--	3-1/4 x 3-1/4 x 2-1/4	24	4-3-2
00-156-4280	1	--	7 x 7 x 14	--	--
00-168-8419	1	--	15-1/8 x 2-3/4 x 2-3/4	12	1-4-3
00-195-0219	1	--	5-1/4 x 5 x 6-5/8	--	--
00-209-6918	40	OPTIONAL	OPTIONAL	--	--
00-220-2061	1	--	1-1/16 x 1-1/16 x 2	100	10-5-2
00-256-4344	1	--	3/4 x 3/4 x 3/4	96	8-6-2
00-266-9787	1	--	3-5/8 x 1-3/8 x 3-5/8	20	2-5-2
00-284-1406	1	--	1-3/8 x 1-3/8 x 2-1/2	40	5-4-2
00-299-6374	1	--	3-1/2 x 2-1/8 x 3-1/16	40	4-5-2
00-311-9384	1	--	5/8 x 5/8 x 5-7/8	100	10-10-1
00-474-9529	1 2/	--	1 x 1 x 1/4	100	5-5-4
00-498-2456	1	--	3/4 x 3/4 x 2-3/8	100	10-10-1
00-553-7995	1	--	1-1/4 x 1-1/4 x 2-3/8	40	5-4-2
00-557-8874	1	--	2-3/4 x 2-3/4 x 4-1/4	24	4-3-2
00-643-1307	1	--	10-3/8 x 2-3/4 x 7-1/4	4	1-4-1
00-643-1310	1	--	2-5/8 x 2-5/8 x 4-3/8	24	4-3-2
00-643-3485	1	--	1-1/8 x 5/8 x 2	100	5-10-2
00-655-2279	6	3-2-1	5-5/8 x 3-3/4 x 3-3/4	12	3-2-2
00-681-2702	1	--	4-1/16 x 2-5/8 x 5-5/8	24	3-4-2
00-683-0537	1	--	2-5/8 x 2 x 2-3/4	50	5-5-2
00-728-9860	1	--	3/4 x 3/4 x 4	100	10-10-1
00-735-8530	1	--	1-3/8 x 1-3/8 x 2-3/8	100	10-5-2
00-754-8191	1	--	4-3/8 x 2-3/4 x 4-3/8	16	2-4-2
00-763-5793	1	--	1-1/8 x 5/8 x 1-3/4	100	5-10-2
00-782-6988	1	--	1-1/8 x 1-1/8 x 5	50	10-5-1
00-801-0586	1	--	1-3/8 x 1 x 1-5/8	100	5-10-2
00-801-0587	1	--	3/4 x 3/4 x 3-1/4	100	10-10-1
00-816-9053	1	--	5/8 x 5/8 x 2	100	10-10-1
00-825-6692	1	--	5-3/8 x 2-7/8 x 5	12	2-3-2
00-835-7211	1	--	1-3/8 x 1-3/8 x 2-1/2	100	10-5-2
00-853-8670	60	OPTIONAL	OPTIONAL	--	--
00-891-4944	1	--	1 x 3/4 x 2	100	10-10-1
00-898-6996	10	OPTIONAL	OPTIONAL	--	--
00-900-2139	1	--	1 x 5/8 x 2	100	5-10-2
00-912-9787	1 2/	--	1 x 1 x 1/4	100	5-5-4
00-918-6993	1	--	3/4 x 3/4 x 1-7/8	100	10-10-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

TABLE III. Unit pack quantity, arrangement, dimensions; intermediate pack quantity and arrangement. - Continued

NSN 6135-	UNIT PACK QUP	UNIT PACK ARR (L-W-D)	UNIT PACK APPROXIMATE BOX SIZE INSIDE (INCHES) 6/	INTER. PACK IPQ	INTER. PACK ARR (L-W-D)
00-921-6487	1	--	3-1/8 x 1-5/8 x 5-5/8	24	4-6-1
00-945-0016	6	OPTIONAL	OPTIONAL	100	OPTIONAL
00-950-9380	1	--	1-1/8 x 1-1/8 x 2-5/8	100	10-5-2
00-968-8594	1	--	2-1/4 x 1-1/4 x 6-1/4	50	5-5-2
00-973-5632	1	--	1-1/8 x 1-1/8 x 1-3/4	100	10-5-2
00-976-4590	1	--	5/8 x 5/8 x 1/4	100	5-5-4
00-985-7845	1	--	5/8 x 5/8 x 2	100	10-10-1
00-985-8292	1	--	1 x 1 x 3-3/8	100	10-5-2
00-988-3922	1	--	1-3/8 x 1-3/8 x 3-5/8	40	5-4-2
00-990-1822	1	--	3/4 x 3/4 x 2	100	10-10-1
00-997-5891	1	--	5/8 x 5/8 x 1/4	100	5-5-4
01-018-8623	1	--	6-3/8 x 1-1/2 x 2-3/4	16	2-4-2
01-031-0862	1	--	1/2 x 1/2 x 1-1/8	100	10-10-1
01-072-0415	24	6-4-1	6-1/4 x 2-3/4 x 2-1/8	12	2-2-3
01-091-3289	1	--	1-3/8 x 1-3/8 x 2-3/8	100	10-5-2
01-094-6536	1	--	3-9/16 x 1-1/4 x 2-7/16	24	2-6-2
01-096-0330	6	OPTIONAL	OPTIONAL	100	OPTIONAL
01-101-9006	12	4-3-1	10-5/8 x 8 x 4-1/2	2	1-2-1
01-103-6514	1	--	1-1/4 x 1-1/4 x 2-3/8	100	10-5-2
01-104-4485	1	--	9 x 3 x 2-1/4	10	1-5-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

1/ Each battery shall be individually unit packed submethod IC-1 of MIL-P-116. Place the battery in a barrier bag fabricated of material conforming to L-P-378, type I, class 1, grade B, finish 1, having a minimum thickness of 4.0 ± 0.5 mils. Closure of the bag shall be by heat seal. The bagged battery shall be placed in a close-fitting box conforming to PPP-B-636, type CF, class weather-resistant, style optional or PPP-B-566, variety 2, style II or PPP-B-676, type I, variety 2. Closure shall be as specified in the appendix of the applicable box specification.

2/ Each battery shall be individually unit packed submethod IC-1 of MIL-P-116. Place the battery in a barrier bag fabricated of material conforming to L-P-378, type I, class 1, grade B, finish 1, having a minimum thickness of 4.0 ± 0.5 mils. Closure of the bag shall be by heat seal.

3/ Prepack each cell or battery within a polyethylene bag conforming to L-P-378, type I, class 1, grade B, finish 1, having a minimum thickness of 2.0 mils. Closure of the bag shall be by heat seal.

4/ Prepack each cell within a close-fitting box conforming to PPP-B-566, variety 1. Unit pack, in the quantities specified in table II or III, in accordance with submethod IC-2 (modified) of MIL-P-116 as follows: Place within a close-fitting box conforming to PPP-B-566, variety 1. Closure shall be as specified in the appendix of the applicable box specification. The boxed batteries shall be placed in a bag conforming to L-P-378, type I, class 1, grade B, finish 1, having a minimum thickness of 4.0 ± 0.5 mils. Closure of the bag shall be by heat seal.

5/ Battery Type BA-2245/U only: Each battery shall have a printed wrap-around label, on olive drab paper, in black bold face lettering, outside of the polyethylene bag and held in place with an elastic band, with the following information: This battery is designed for use at low temperature (below 20°F/-6.7°C) but is also satisfactory for use at normal temperatures. Store at lowest temperature practical; temperature in excess of 70°F/21.1°C will cause rapid deterioration. For maximum service at low temperature, whenever feasible, warm battery to approximately 70°F/21.1°C before using. When used cold, battery will be only partially discharged but if warmed, will give additional service.

6/ Refer to table IV for metric conversion.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:17Z
Check the source to verify that this is the currentversion before use.

TABLE IV. Metric conversion.*

INCHES / FRACTIONS	0	1	2	3	4	5	6	7	8
		25.400	50.800	76.200	101.600	127.000	152.400	177.800	203.200
1/16		26.987	52.387		103.187				
1/8	3.175	28.575	53.975	79.375	104.775	130.175	155.575	180.975	206.375
3/16		30.162	55.562		106.362				
1/4	6.350	31.750	57.150	82.550	107.950	133.350	158.750	184.150	209.550
5/16		33.337	58.737	84.137	109.537				
3/8	9.525	34.925	60.325	85.725	111.125	136.525	161.925	187.325	212.725
7/16		36.512	61.912						
1/2	12.700	38.100	63.500	88.900	114.300	139.700	165.100	190.500	215.900
9/16	14.287	39.687		90.487		141.287	166.687		
5/8	15.875	41.275	66.675	92.075	117.475	142.875	168.275	193.675	219.075
11/16	17.462		68.262				169.862	195.262	
3/4	19.050	44.450	69.850	95.250	120.650	146.050	171.450	196.850	222.250
13/16	20.637		71.437			147.637			
7/8	22.225	47.625	73.025	98.425	123.825	149.225	174.625	200.025	
15/16		49.212	74.612	100.012					

INCHES / FRACTIONS	9	10	11	12	13	14	15	16	17
	228.600				330.200	355.600			
1/16									
1/8	231.775								
3/16									
1/4	234.950	260.350	285.750	311.150		361.950		412.750	
5/16									
3/8		263.525							
7/16									
1/2	241.300	266.700	292.100		342.900				444.500
9/16									
5/8	244.475	269.875							
11/16									
3/4	247.650		298.450						
13/16		274.637							
7/8									
15/16									

*METRIC EQUIVALENTS SPECIFIED IN TABLE ARE FOR GENERAL INFORMATION AND ARE BASED UPON 1 INCH = 25.4 MM

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Communications-Electronics Command
ATTN: DRSEL-ED-TO
Ft Monmouth, NJ 07703

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-55521C (CR)	Batteries, Nonrechargeable, Packaging of

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:17Z
Check the source to verify that this is the current version before use.