MIL-T-55335(EL)
30 August 1971

MILITARY SPECIFICATION
TEST FACILITIES KIT, MK-1191( )/AR
(UNITS OF)

1. SCOPE

1.1 This specification covers one type of maintenance kit which provides facilities for troubleshooting and bench testing of communication systems and direction finding equipment. The maintenance kit is designated, Test Facilities Kit, MK-1191( )/AR( ). (See 6.1 and 6.3).

2. APPLICABLE DOCUMENTS

2.1 The documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Box, Wood, Cleated plywood
PPP-B-621	Box, Wood, Nailed and Lock-corner
PPP-B-636	Box, Fiberboard
PPP-B-640	Boxes, Fiberboard, Corrugated, Triple-wall
PPP-F-320	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-S-760	Strapping; Non-Metallic
PPP-T-76	Tape, pressure-sensitive Adhesive Paper, (for Carton Sealing)
PPP-T-97	Tape, pressure-sensitive, Filament Reinforced
QQ-S-781	Strapping, Flat Steel

MILITARY

MIL-P-116	Preservation, Methods of Barrier
MIL-P-3938	Pallet, Material Handling Hardwood Stringer Construction, 4 way (partial)
MIL-T-5422	Testing, Environmental, Aircraft Electronic Equipment

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the currentversion before use.

MIL-P-15011	Pallet, Material Handling, Wood, Post Construction, 4 Way Entry
MIL-M-13231	Marking of Electronic Items
MIL-F-14072	Finishes for Ground Signal Equipment

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-108	Definitions of and Basic Requirement for Enclosure for Electric and Electronic Equipment
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-252	Wired Equipment, Classification of Visual and Mechanical Defects
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-810	Environmental Test Methods

DRAWING

ELECTRONIC COMMAND

SC-DL-694400	Test Facilities Kit, MK-1191( )/AR

(Copies of specification, standard and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity, or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Description. - The Test Facilities Kit, MK-1191( )/AR is a portable maintenance kit contained in a lightweight aluminum transit case. The Maintenance Kit provides accessories and special tools for troubleshooting and alignment of Radio Sets, AN/ARC-114( ), AN/ARC-115( ), AN/ARC-116( ) and Direction Finder Set, AN/ARN-89( ). The Kit is a completely passive device that makes connections and affords points for otherwise inaccessible circuits in the radio sets. All power supplied

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:16Z
Check the source to verify that this is the currentversion before use.

to the Maintenance Kit is external source. A bench area is necessary when using the kit. The accessories consist of: breakout boxes, extender cards, extender cables, adapters and connectors. The accessories are not exposed when the case cover is in place.

3.2 Preproduction samples. - The contractor shall furnish three (3) preproduction samples for approval, if required by the invitation for bids and contract. (See 4.3 and 6.2)

3.3 Construction. - The equipment shall be constructed in accordance with the following data lists and drawings thereon:

SC-DL-694400 Test Facilities Kit MK-1191( )/AR

3.4 Cleaning. -

3.4.1 Parts. - After fabrication, parts shall be cleaned in accordance with good commercial practice, or as specified in an applicable document. Cleaning processes shall have no deleterious effect. Corrosive material shall be removed completely before the parts are mounted on chassis, panels, etc.

3.4.2 Units. - After assembly, units shall be cleaned thoroughly and shall be free from particles of solder, flux, and other material. In addition, when necessary, such cleaning shall also be performed before final assembly of the units.

3.5 Controls - All movable controls shall operate properly without binding or other undue restriction. Controls shall not be assembled in a misaligned condition.

3.6 Finish, protective. - The equipment shall be given protective finish in accordance with Specification MIL-F-14072 and the equipment drawings. This includes finish of hardware, such as handles, hinges, screws, etc., and necessary touch-up after mounting. The final paint film on Type 1 surfaces shall be semi-gloss, light gray (Film E) conforming to Specification MIL-F-14072. (See 4.4)

3.7 Securing of parts. -

3.7.1 General. - Brackets, lugs, inserts, bolts, and other mounting arrangements shall retain items securely when subjected to specified service conditions.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the current version before use.

3.7.2 Securing of parts by threaded fasteners. - Nylok or other screws with plastic devices and Loctite or similar sealants shall not be subjected to temperature in excess of 250°F (as during baking of paint). Loctite or similar sealants shall be applied in accordance with the manufacturer's instructions.

3.8 Marking. -

3.8.1 General. - Marking shall conform to Specification MIL-M-13231. Front panel marking shall be Group I as described in that specification. (See 4.4)

3.8.2 Visibility. - Wherever practicable, parts shall be so mounted that their identification markings will be readily visible with minimum disassembly of the equipment.

3.8.3 Serial numbers . - The following items shall be serial numbered:

Test Facilities Kit MK-1191( )/AR

3.9 Soldering. -

3.9.1 Solder. - Solder shall conform to the equipment drawings.

3.9.2 Acid or acid salts. - No acid or acid salts shall be used in preparation for or during soldering; however, exception is permitted for preliminary tinning of electrical connections and for tinning or soldering of mechanical joints not used to complete electrical circuits, but in no case shall acid or acid salts be used where they can come in contact with insulation material. Where acid or acid salts are used, as permitted above, they shall be completely neutralized and removed immediately after use.

3.9.3 Proeess. - There shall be no sharp points or rough surfaces resulting from insufficient heating. The solder shall feather out to a thin edge, indicating proper flowing and wetting actions, and shall not be crystalized, overheated, or underheated. The miminum necessary amount of flux and solder shall be used for electrical connections. Any means employed to remove an unavoidable excess of flux shall not incur the risk of loose particles of flux, brush bristles, or other foreign material remaining in the equipment; flux being spread over a larger area; or damage to the unit. Insulation material that has been subjected to heating during the soldering operation shall be undamaged and parts fastened thereto shall not have become loosened.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the currentversion before use.

3.10 Wiring and cabling. - Wiring and cabling shall be neat and sturdy.

3.10.1 Cabling. - Insulated wires shall be formed into cables except where operation of the equipment would be adversely affected thereby or where it is physically impracticable as in the case where the resulting cables would be excessively large and would interfere with operation or maintenance.

3.10.2 Slack. - Wires and cables shall be as short as practical except that sufficient slack shall be provided for the following purposes:

a. To prevent undue stress on cable forms, wires and connections, including connections to resiliently supported parts.

b. To enable parts to be removed and replaced during servicing without disconnecting other parts.

c. To provide for at least two replacements of the part to which the wire or cable is connected, except where uninsulated wires are used.

3.10.3 Protection. - Wires and cables shall be so placed and protected as to avoid contact, under specified service conditions, with rough or irregular surfaces or sharp edges.

3.10.4 Support. - Wire and cable shall be properly supported and secured to prevent undue stress on the conductors and terminals and undue change in position of the wire or cable (1) during and after subjection of the equipment to specified service conditions or (II) after service or repair of the equipment in a normal manner.

3.10.5 Clearance. - Clearance between solder connections or bare conductors, on terminal boards, relays, or other parts, shall be such that no accidental contact can occur between adjacent connections when subjected to specified service conditions.

3.10.6 Splicing. - Wires in a continuous run between two terminals shall not be spliced during the wiring operation.

3.10.7 Connections. -

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:16Z
Check the source to verify that this is the current version before use.

3.10.7.1 General. - Before being soldered to terminal lugs or fixed terminals, wires shall be mechanically secured so that the connections are not dependent for strength on solder alone. Where practicable, wires soldered to fixed terminals shall be looped at least one-half turn but not more than three-quarters turn around the terminal before soldering. Bared ends of wire leads to be terminated in solder-type terminal lugs shall be tinned, silver plated, or lead-alloy coated. No varnish, lacquer, inspection paint, or other coating shall be applied to completed electrical connections.

3.11 Tropicalization of materials. - Materials shall be treated as follows:

3.11.1 Treating materials. - Treating materials containing a mercury-bearing fungicide shall not be used. The contractor shall determine that the treating material is compatible with the material or surface to be treated. Selection of treating materials shall be such that any increase in flammability of treated material will be held to the practical minimum.

3.11.2 Toxicity. - Treating materials shall cause no skin irritation or other injury to personnel handling the treated material during fabrication, transportation, operation, or maintenance of the equipment, or during use of the finished items when used for the purpose intended.

3.11.3 Flexibility. - Treatment shall not affect the flexibility of treated materials, to the extent that the equipment may fail to meet specified requirements when subjected to the specified service conditions.

3.11.4 Statement of treatment. - The contractor shall submit for approval, to the contracting officer, a statement describing in detail the materials to be treated and the treating materials processes that he proposes to use. (See 6.2)

3.12 Service Conditions (See 4.8). - The MK-1191( )/AR shall meet the following service conditions where a test is referenced, meeting the test shall be considered as compliance with the requirement:

3.12.1 Temperature (See 4.8.1). -

3.12.1.1 Operating. - Ambient temperature in the range of +100°F to 0°F exposure at the high temperature extreme not to exceed 4 hours, and at the low temperature extreme not to exceed 72 hours, at any one time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

3.12.1.2 Non-operating. - Exposure in the range of +160°F to -65°F; exposure at the high temperature extreme is not to exceed 4 hours, and at the low temperature extreme not to exceed 24 hours, at any one time.

3.12.2 Humidity (See 4.8.2). - The equipment shall meet the requirements in accordance with the procedure prescribed in MIL-T-5422 as specified herein.

3.12.3 Altitude (See 4.8.3). -

3.12.3.1 Operating. - Up to 10,000 feet above sea level.

3.12.3.2 Non-operating. - Up to 50,000 feet above sea level.

3.12.4 Spray-tight protection (See 4.8.4). - The equipment shall meet the Table I conditions of MIL-STD-108 for "spray-tight" enclosure. There shall be no evidence of moisture inside the equipment.

3.12.5 Fungus (See 4.8.5). - The unit(s) including accessories shall show no evidence of viable fungus or corrosion after being subjected to 28 days of fungus test.

3.12.6 Vibration (See 4.8.6). - The equipment shall meet the requirements of Test Method 514-1 and Figure 514-6 (Curve AB) in MIL-STD-810.

3.12.7 Shock (See 4.8.7). - The equipment shall not suffer damage or fail to operate after subjection to the requirements of Table 1, as follows:

TABLE I

Paragraph Heading	Paragraph No	Performance after Test
Shock: Bench-handling	4.8.7.1	Specified performance (Note A)
Shockdrop	4.8.7.2	No physical damage. Operable (Note A). Any physical damage shall be minor only.

Note A: The equipment shall meet requirements listed in 4.8.

3.13 Electrical requirements (See 4.9). -

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the currenversion before use.

3.13.1 Adapter, Breakout Box MX-( ) (See 4.9.1). - The continuity of each wire shall be in accordance with SM-B-625701. The resistance between each terminal and test point shall not exceed 0.5 ohms.

3.13.2 Adapter, Breakout Box MX-( ) (See 4.9.2). - The continuity of each wire shall be in accordance with SM-B-625706. The resistance between each terminal and test point shall not exceed 0.5 ohms.

3.13.3 Adapter, Breakout Box MX-( ) (See 4.9.3). - The continuity of each wire shall be in accordance with SM-B-625711. The resistance between each terminal and test point shall not exceed 0.5 ohms.

3.13.4 Adapter, Breakout Box MX-( ) (See 4.9.4). - The continuity of each wire shall be in accordance with SM-B-625716. The resistance between each terminal and test point shall not exceed 0.5 ohms.

3.13.5 Cable, CX-10894( )/AR (See 4.9.5). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.6 Cable, CX-12182( )/U (See 4.9.6). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.7 Cable, CX-12183( )/U (See 4.9.7). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.8 Cable, CX-12184( )/U (See 4.9.8). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.9 Cable, CX-12185( )/U (See 4.9.9). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.10 Cable, CX-12186( )/U (See 4.9.10). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.11 Cable, CX-12187( )/U (See 4.9.11). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.12 Cable, CX-12188( )/U (See 4.9.12). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.13 Cable, CX-12189( )/U (See 4.9.13). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the current version before use.

3.13.14 Cable, CX-12190( )/U (See 4.9.14). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.15 Cable, CX-12191( )/U (See 4.9.15). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.16 Cable, CX-12192( )/U (See 4.9.16). - The continuity requirement of each wire between each connector pin shall not exceed 0.5 ohms.

3.13.17 Cable, Assembly, Headset CX-( ) (See 4.9.17). - The continuity of each wire shall be in accordance with SM-B-625791. The resistance between each connector pin shall not exceed 0.5 ohms.

3.13.18 Cable, CG-3475( )/U (See 4.9.18). - Continuity requirement of the inner conductor shall not exceed 1.0 ohm. The continuity requirement of the outer conductor shall not exceed 0.5 ohms.

3.13.19 Power Supply Termination MX-( ) (See 4.9.19). - The continuity of each wire shall be in accordance with SM-B-625877. The resistance between each terminal shall not exceed 0.5 ohms.

3.13.20 Power Supply Termination MX-( ) (See 4.9.20). - The continuity of each wire shall be in accordance with SM-B-625879. The resistance between each terminal shall not exceed 0.5 ohms.

3.13.21 Power Supply Termination MX-( ) (See 4.9.21). - The continuity of each wire shall be in accordance with SM-B-625792. The resistance between each terminal shall not exceed 0.5 ohms.

3.13.22 Headset Termination MX-( ) (See 4.9.22) - The continuity of each wire shall be in accordance with SM-B-625790. The resistance between each terminal shall not exceed 0.5 ohms.

3.13.23 Microphone Termination MX-( ) (See 4.9.23). - The continuity of each wire shall be in accordance with SM-B-625789. The resistance between each terminal shall not exceed 0.5 ohms.

3.13.24 Adapter, MX-8503( )/AR (See 4.9.24). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.25 Adapter, MX-8504( )/AR (See 4.9.25). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the currentversion before use.

3.13.26 Adapter, MX-8505( )/AR (See 4.9.26). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.27 Adapter, MX-8506( )/AR (See 4.9.27). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.28 Adapter, MX-8507( )/AR (See 4.9.28). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.29 Adapter, MX-8508( )/AR (See 4.9.29). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.30 Adapter, MX-8509( )/AR (See 4.9.30). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.31 Adapter, MX-8510( )/AR (See 4.9.31). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.32 Adapter, MX-8511( )/AR (See 4.9.32). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.33 Adapter, MX-8527( )/AR (See 4.9.33). - The continuity requirement of each trace between each terminal shall not exceed 0.5 ohms.

3.13.34 Adapter, Breakout Box MX-( ) (See 4.9.34). - The insulation shall be in accordance with SM-B-625701. With the applicable voltage applied, the resistance shall meet the requirements specified in Table V.

3.13.35 Adapter, Breakout Box MX-( ) (See 4.9.35). - The insulation shall be in accordance with SM-B-625706. With the applicable voltage applied, the resistance shall meet the requirements specified in Table V.

3.13.36 Adapter, Breakout Box MX-( ) (See 4.9.36) - The insulation shall be in accordance with SM-B-625711. With the applicable voltage applied, the resistance shall meet the requirements specified in Table V.

3.13.37 Adapter, Breakout Box MX-( ) (See 4.9.37). - The insulation shall be in accordance with SM-B-625716. With the applicable voltage applied, the resistance shall meet the requirements specified in Table V.

3.13.38 Cable, CX-10894( )/AR (See 4.9.38). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the current version before use.

3.13.39 Cable, CX-12182( )/U (See 4.9.39). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.40 Cable, CX-12183( )/U (See 4.9.40). - With the applicable voltage applied, the insultation resistance shall meet the requirement specified in Table VI.

3.13.41 Cable, CX-12184( )/U (See 4.9.41). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.42 Cable, CX-12185( )/U (See 4.9.42). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.43 Cable, CX-12186( )/U (See 4.9.43). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.44 Cable, CX-12187( )/U (See 4.9.44). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.45 Cable, CX-12188( )/U (See 4.9.45). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.46 Cable, CX-12189( )/U (See 4.9.46). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.47 Cable, CX-12190( )/U (See 4.9.47). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.48 Cable, CX-12191( )/U (See 4.9.48). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.49 Cable, CX-12192( )/U (See 4.9.49). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the currentversion before use.

3.13.50 Cable, Assembly, Headset CX-( ) (See 4.9.50). - The insulation shall be in accordance with SM-B-625791. With the applicable voltage applied, the resistance shall meet the requirement specified in Table VI.

3.13.51 Cable, CG-3475( )/U (See 4.9.51). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table VI.

3.13.52 Power Supply Termination MX-( ) (See 4.9.52). - The resistance shall be in accordance with SM-B-625877. The measurements shall be within limits specified in Table VII.

3.13.53 Power Supply Termination MX-( ) (See 4.9.53). - The resistance shall be in accordance with SM-B-625879. The measurements shall be within limits specified in Table VII.

3.13.54 Power Supply Termination MX-( ) (See 4.9.54). - The resistance shall be in accordance with SM-B-625792. The measurements shall be within limits specified in Table VII.

3.13.55 Headset Termination MX-( ) (See 4.9.55). - The resistance shall be in accordance with SM-B-625790. The measurements shall be within limits specified in Table VIII.

3.13.56 Microphone Termination MX-( ) (See 4.9.56). - The resistance shall be in accordance with SM-B-625789. The measurements shall be within limits specified in Table IX.

3.13.57 Adapter, MX-8503( )/AR (See 4.9.57). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.58 Adapter, MX-8504( )/AR (See 4.9.58). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.59 Adapter, MX-8505( )/AR (See 4.9.59). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X,

3.13.60 Adapter, MX-8506( )/AR (See 4.9.60). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the currentversion before use.

3.13.61 Adapter, MX-8507( )/AR (See 4.9.61). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.62 Adapter, MX-8508( )/AR (See 4.9.62). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.63 Adapter, MX-8509( )/AR (See 4.9.63). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.64 Adapter, MX-8510( )/AR (See 4.9.64). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.65 Adapter, MX-8511( )/AR (See 4.9.65) - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.66 Adapter, MX-8527( )/AR (See 4.9.66). - With the applicable voltage applied, the insulation resistance shall meet the requirement specified in Table X.

3.13.67 30dB Attenuator CN-( ) (See 4.9.67). - The attenuation shall be in accordance with SM-A-625793. With the applicable frequency applied, the requirements shall be within limits specified in Table XI.

3.13.68 30dB Attenuator CN-( )(See 4.9.68). - The voltage standing wave ratio (VSWR) shall be in accordance with SM-A-625793. With the applicable frequency applied, the VSWR shall not exceed the limits specified in Table XII.

3.14 Bounce preconditioning (See 4.6). - The equipment shall be capable of meeting the requirements specified herein, without subsequent processing, after subjection to the bounce preconditioning.

3.15 Operational inspection (See 4.12). - The test set shall be capable of meeting the specified test after applicable processes, inspection and test have been completed to determine that each test set on order is operable prior to packaging.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the currentversion before use.

3.16 Interchangeability (See 4.11). - Like units, assemblies, sub-assemblies, modules and replaceable parts shall conform to requirement 7 of MIL-STD-454, and shall be physically and functionally interchangeable, without modification of such items or of the units.

3.17 Technical literature and spare parts. - Technical literature and running spares and spare parts shall be furnished if specified in the contract. Spare parts shall be identical to corresponding parts in the equipment furnished on the order. (See 6.2)

3.18 Workmanship. - The equipment shall be manufactured and assembled in accordance with the equipment drawings and requirement nine (9) of MIL-STD-454 and the following paragraphs herein:

Cleaning	3.4
Controls	3.5
Securing of parts	3.7
Soldering	3.9
Wiring and Cabling	3.10
Tropicalization of Materials	3.11

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. - Inspection shall be classified as follows:

a. Preproduction inspection (does not include preparation for delivery.) (See 4.3)

b. Inspection covered by subsidiary documents. (See 4.4)

c. Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

(1) Quality conformance inspection of equipment before preparation for delivery. (See 4.5)

(2) Quality conformance inspection of preparation for delivery. (See 4.13 and 4.14)

4.3 Preproduction inspection. - This inspection will be performed by the Government unless otherwise specified in the contract. It shall consist of the inspection specified in the subsidiary documents covering the items listed in 4.4 and the inspection specified for Group A, Group B, and Group C, (See Tables II and III and IV respectively). The preproduction inspection will normally be performed in this order: (1) altitude, (2) temperature, (3) vibration, (4) humidity, (5) shock and bench-handling, and (6) shock drop. Other preproduction inspection may precede, follow, or be interspersed between the foregoing.

4.4 Inspection covered by subsidiary documents. - The following shall be inspected under the applicable subsidiary documents as part of the inspection of the units before preparation for delivery:

Item	Where Required
Finish	3.6
Marking	3.8

4.5 Quality conformance inspection of equipment before preparation for delivery. - The contractor shall perform the inspection specified in 4.4 and 4.5.1 through 4.5.6. This does not relieve the contractor of his responsibility for performance of any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. The Government will review and evaluate the contractor's inspection procedures and examine the contractor's inspection records. In addition the Government at its discretion, may perform all or any part of the specified inspection, to verify the contractor's compliance with specified requirements. (See 6.7) Test equipment for Government verification inspection shall be made available by the contractor. Each unit shall be bounce preconditioned after final assembly and shall not be considered as a portion of acceptance inspection. (See 3.14)

4.5.1 Group A inspection. - Each unit of each lot of equipment shall be inspected for conformance to all the inspection and test requirements of Table II. Each lot will be subject to verification utilizing the procedures of MIL-STD-105 using the general inspection levels and the AQL's indicated in Table II. Group A inspection shall be performed in any order which is satisfactory to the Government, except that the operations inspection 4.12 shall be last (See 6.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE II - GROUP A INSPECTION

INSPECTION	REQT PARA	INSP PARA	AQL MAJOR	AQL MINOR	
Visual and Mechanical:	3.18	4.10			
MK-1191( )/AR (Assembled) w/accessories			1.0%	4.0%	
Breakout Boxes			4.0%	6.5%	
Cables Assemblies (Assembled)			1.0%	4.0%	
Adapter, extender cards			1.0%	4.0%	
Transit Case (Assembled)			4.0%	6.5%	
Cases, Accessories					
Adapter Connectors					
Termination Boxes			1.0%	6.5%	
Tools					
Electrical:					
Accessories:					
Breakout Box MX-( )	3.13.1	4.9.1			*1.0% for the combined group (cables excluded)
Breakout Box MX-( )	3.13.2	4.9.2			
Breakout Box MX-( )	3.13.3	4.9.3			
Breakout Box MX-( )	3.13.4	4.9.4			
Cable, CX-10894( )/AR	3.13.5	4.9.5			
Cable, CX-12182( )/U	3.13.6	4.9.6			
Cable, CX-12183( )/U	3.13.7	4.9.7			
Cable, CX-12184( )/U	3.13.8	4.9.8			
Cable, CX-12185( )/U	3.13.9	4.9.9			
Cable, CX-12186( )/U	3.13.10	4.9.10			*1.0% for the cables
Cable, CX-12187( )/U	3.13.11	4.9.11			
Cable, CX-12188( )/U	3.13.12	4.9.12			
Cable, CX-12189( )/U	3.13.13	4.9.13			
Cable, CX-12190( )/U	3.13.14	4.9.14			
Cable, CX-12191( )/U	3.13.15	4.9.15			
Cable, CX-12192( )/U	3.13.16	4.9.16			
Cable, Assy Headset CX-( )	3.13.17	4.9.17			
Cable, CG-3475( )/U	3.13.18	4.9.18			
Power Supply Term MX-( )	3.13.19	4.9.19			
Power Supply Term MX-( )	3.13.20	4.9.20			
Power Supply Term MX-( )	3.13.21	4.9.21			
Headset Term MX-( )	3.13.22	4.9.22			
Microphone Term MX-( )	3.13.23	4.9.23			

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE II - CONTINUED

INSPECTION	REQT PARA	INSP PARA	AQL MAJOR	AQL MINOR
Accessories:				
Adapter, MX-8503( )/AR	3.13.24	4.9.24		
Adapter, MX-8504( )/AR	3.13.25	4.9.25		
Adapter, MX-8505( )/AR	3.13.26	4.9.26		
Adapter, MX-8506( )/AR	3.13.27	4.9.27		
Adapter, MX-8507( )/AR	3.13.28	4.9.28		
Adapter, MX-8508( )/AR	3.13.29	4.9.29		
Adapter, MX-8509( )/AR	3.13.30	4.9.30		
Adapter, MX-8510( )/AR	3.13.31	4.9.31		
Adapter, MX-8511( )/AR	3.13.32	4.9.32		
Adapter, MX-8527( )/AR	3.13.33	4.9.33		
30dB Attenuator CN-( )	3.13.67	4.9.67		
30dB Attenuator CN-( )	3.13.68	4.9.68		
Operational Inspection	3.15	4.12	0.1%	

*All electrical defects shall be considered major defects.

4.5.2 Group B inspection. - This inspection, including sampling shall conform to Table III and to the procedures for small-sample inspection of standard MIL-STD-105 using the special inspection levels. The AQL shall be 6.5 percent defective and the inspection level shall be S-4 for normal, tightened, and reduced inspection. Group B inspection shall normally be performed on inspection lots that have passed Group A inspection and on samples selected from units that have not met the Group A inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE III - GROUP B INSPECTION

INSPECTION	REQT PARA	INSP PARA	AQL MAJOR	AQL MINOR
Insulation resistance:				
Breakout Box MX-( )	3.13.34	4.9.34	6.5% for the Breakout Boxes and Adapters (combined)	
Breakout Box MX-( )	3.13.35	4.9.35		
Breakout Box MX-( )	3.13.36	4.9.36		
Breakout Box MX-( )	3.13.37	4.9.37		
Cable, CX-10894( )/AR	3.13.38	4.9.38		
Cable, CX-12182( )/U	3.13.39	4.9.39		
Cable, CX-12183( )/U	3.13.40	4.9.40		
Cable, CX-12184( )/U	3.13.41	4.9.41		
Cable, CX-12185( )/U	3.13.42	4.9.42		
Cable, CX-12186( )/U	3.13.43	4.9.43	6.5% for the cables	
Cable, CX-12187( )/U	3.13.44	4.9.44		
Cable, CX-12188( )/U	3.13.45	4.9.45		
Cable, CX-12189( )/U	3.13.46	4.9.46		
Cable, CX-12190( )/U	3.13.47	4.9.47		
Cable, CX-12191( )/U	3.13.48	4.9.48		
Cable, CX-12192( )/U	3.13.49	4.9.49		
Cable Assy, Headset CX-( )	3.13.50	4.9.50		
Cable, CG-3475( )/U	3.13.51	4.9.51		
Adapter, MX-8503( )/AR	3.13.57	4.9.57		
Adapter, MX-8504( )/AR	3.13.58	4.9.58		
Adapter, MX-8505( )/AR	3.13.59	4.9.59		
Adapter, MX-8506( )/AR	3.13.60	4.9.60		
Adapter, MX-8507( )/AR	3.13.61	4.9.61		
Adapter, MX-8508( )/AR	3.13.62	4.9.62		
Adapter, MX-8509( )/AR	3.13.63	4.9.63		
Adapter, MX-8510( )/AR	3.13.64	4.9.64		
Adapter, MX-8511( )/AR	3.13.65	4.9.65		
Adapter, MX-8527( )/AR	3.13.66	4.9.66		
Resistance:				
Power Supply Term MX-( )	3.13.52	4.9.52	6.5% for the Power Supply Terminations, Headset and Microphone (Combined)	
Power Supply Term MX-( )	3.13.53	4.9.53		
Power Supply Term MX-( )	3.13.54	4.9.54		
Headset Term MX-( )	3.13.55	4.9.55		
Microphone Term MX-( )	3.13.56	4.9.56		
Interchangeability	3.16	4.11	6.5% for the Interchangeability	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.5.3 Group C inspection. - This inspection shall be as listed in Table IV, and shall normally be performed on sample units that have been subject to and met Group A and B inspection. No defects shall be allowed. Sample unit(s) shall be selected in accordance with 4.5.4.

TABLE IV - GROUP C INSPECTION

INSPECTION	REQT PARA	INSP PARA
SUBGROUP I:		
Altitude	3.12.3	4.8.3
Temperature	3.12.1	4.8.1
Vibration	3.12.6	4.8.6
Humidity	3.12.2	4.8.2
SUBGROUP II:		
Spray tight protection	3.12.4	4.8.4
Shock, bench-handling	3.12.7	4.8.7.1
Shock, drop	3.12.7	4.8.7.2
SUBGROUP III:		
Fungus	3.12.5	4.8.5

4.5.4 Sampling for inspection of equipment. - Units selected for each Group C inspection shall be selected without regard to their quality in accordance with the following:

4.5.4.1 Subgroup I. - For this subgroup, two units from the first 10 production units shall be selected for the first Group C inspection. For subsequent Group C inspections, one unit from each successive 25 or fractions thereof shall be selected.

4.5.4.2 Subgroup II. - For this subgroup, two units from the first 10 production units shall be selected for the first Group C inspection. For subsequent Group C inspections, one unit from each successive 50 or fractions thereof shall be selected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.5.4.3 Subgroup III. - For this subgroup, only one (1) unit(s) from the first 10 production units shall be selected for the first Group C inspection. For subsequent inspections, one (1) unit(s) shall be selected when one half of the units on order have been accepted by the Government's QA Representative.

4.5.5 Noncompliance. - The contractor shall immediately report in writing each Group C failure occurrence, including details of the failure and characteristics affected. The contractor shall immediately investigate the cause of failure and further report the results of investigation and details of the proposed corrective action on (i) the process and materials, as applicable, and (ii) all units of product which were manufactured under the same conditions and which the Government considers subject to the same failure. Reports shall be forwarded to the responsible technical activity designated in the contract through the Quality Assurance Representative. After corrective action has been taken, additional sample units shall be subjected to Group C inspection (all inspections, or the inspections which the sample failed, at the option of the Government) and Group A and B inspection may be reinstituted; however, final acceptance and shipment will be withheld until the Group C re-inspection results have shown that the corrective action was effective. (See 6.4)

4.5.6 Reinspection of conforming Group C sample units. - Unless otherwise specified, sample units which have been subjected to and passed Group C inspection may be delivered on the contract or order, provided all damage is repaired, cleaned of all foreign matter, and the sample units are resubjected to and pass Group A inspection.

4.6 Bounce preconditioning. - The Facilities Kit shall be placed in its normal operating position on a L.A.B. ARC-30-200 vibration table or suitable equivalent. The unit shall be secured to the vibration table and subjected to a two (2) minutes vibration. The vibration force shall be approximately 1g at 25 Hz. After bounce preconditioning, the unit shall not be repaired, aligned, cleaned, or otherwise changed prior to subjection to acceptance inspection.

4.7 Standard test conditions. - Unless otherwise specified, all inspection shall be performed at normal room temperature, pressure, and humidity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.8 Service conditions. - The service condition tests shall be conducted as specified. When electrical tests are required, the equipment shall meet the requirements of 3.13.1 thru 3.13.68. Upon completion of each service condition test, the equipment shall be subjected to and pass a visual and mechanical inspection. No defects will be allowed.

4.8.1 Temperature (See 3.12.1). -

4.8.1.1 Operating. - The equipment shall be subjected to the temperature limits in accordance with Methods 501 and 502 of MIL-STD-810. Tests shall be conducted at ambient before and after the temperature tests, and at extreme temperatures when the temperature limits have been reached. The requirements of 3.12.1.1 shall be met.

4.8.1.2 Non-operating. - The equipment shall be subjected to the temperature limits in accordance with Methods 501 and 502 of MIL-STD-810. Electrical tests shall be conducted at ambient before and after the temperature tests. The requirements of 3.12.1.2 shall be met.

4.8.2 Humidity. - The equipment shall be subjected to and meet the humidity test of Specification MIL-T-5422 with the transit case open. The upper and lower hold down plate assemblies shall be removed from transit case and placed in the chamber. Mechanical-Visual inspection and electrical tests shall be performed before and after the humidity test. The requirements of 3.12.2 shall be met.

4.8.3 Altitude. - The equipment shall be subjected to the altitude tests in accordance with Procedure 1, Method 500, of MIL-STD-810. Electrical tests shall be conducted before and after the altitude test at ambient pressure and at 10,000 feet. The requirements of 3.12.3 shall be met.

4.8.4 Spray-tight protection. - The equipment shall have Transit Case in place and be subjected to the tests specified in Table 1 of Specification MIL-STD-108, except the equipment shall be sprayed as normal rainfall, for compliance with paragraph 3.12.4.

4.8.5 Fungus. - The unit(s) shall be subjected to 28 days of the fungus test specified in Procedure 1, Method 508 of MIL-STD-810. For gasket or other non-hermetically sealed equipment, the parts and materials of the chassis shall be sprayed with the spore suspension. The interior of the case shall also be sprayed. The unit(s) shall be subjected to the test in this open condition and as specified for compliance with 3.12.5; the unit(s) shall not be required to operate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.8.6 Vibration. - The equipment shall be subjected to the vibration test in accordance with Method 514-1 of MIL-STD-180, except the equipment shall not be operated during vibration. Electrical tests shall be conducted before and after the vibration test. With the equipment mounted in the test fixture on the vibration table, determine resonant modes of the maintenance kit by varying the frequency of applied vibration slowly through the specified range at an amplitude not exceeding that for which the equipment is to be tested. Individual resonance surveys shall be conducted with vibration applied along each of the three orthogonal axes of the equipment. Electrical tests shall be conducted after the completion of the vibration tests. The requirements of 3.12.6 shall be met.

4.8.7 Shock. -

4.8.7.1 Shock, bench-handling (See 3.12.7). - The chassis-with-front-panel assembly shall be removed from its combination case, as for servicing, and placed in a suitable position for servicing on a solid, 2-inch fir bench top. The test shall be performed as follows, in a manner simulating shocks liable to occur during servicing:

a. Tilt up the assembly through an angle of 30 degrees, using one edge of the assembly as an axis, and permit the assembly to drop back freely to the horizontal. Repeat, using other practicable edges of the same horizontal face as axes, for a total of four drops.

b. Repeat "a", with the assembly resting on other faces, until it has been dropped for a total of four times on each face on which the assembly might practically be placed during servicing. Electrical tests shall be conducted after completion of the bench-handling test.

4.8.7.2 Shock, drop. - The equipment in its transit case shall be subjected to 18 impact shocks of 15g. consisting of 3 shocks in opposite directions along each of 3 mutually perpendicular axes, each shock impulse having a time duration of 11 $\pm$ 1 milliseconds. Except for abrasion, paint chipping, and small local deformations, no damage shall occur. Upon completion of the test, without adjustment or repair, the equipment shall be tested for compliance with 3.12.7.

4.9 Electrical requirements. -

4.9.1 Adapter, Breakout Box MX-( ). - Check the continuity of each wire between the applicable terminals and test points in accordance with SM-B-625701, to determine compliance with 3.13.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.9.2 Adapter, Breakout Box MX-( ). - Check the continuity of each wire between the applicable terminals and test points in accordance with SM-B-625706, to determine compliance with 3.13.2.

4.9.3 Adapter, Breakout Box MX-( ). - Check the continuity of each wire between the applicable terminals and test points in accordance with SM-B-625711, to determine compliance with 3.13.3.

4.9.4 Adapter, Breakout Box MX-( ). - Check the continuity of each wire between the applicable terminals and test points in accordance with SM-B-625716, to determine compliance with 3.13.4.

4.9.5 Cable, CX-10894( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.5.

4.9.6 Cable, CX-12182( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.6.

4.9.7 Cable, CX-12183( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.7.

4.9.8 Cable, CX-12184( )/U . - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.8.

4.9.9 Cable, CX-12185( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.9.

4.9.10 Cable, CX-12186( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.10.

4.9.11 Cable, CX-12187( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.11.

4.9.12 Cable, CX-12188( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.12.

4.9.13 Cable, CX-12189( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.13.

4.9.14 Cable, CX-12190( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.14.

4.9.15 Cable, CX-12191( )/U . - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.15.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.9.16 Cable, CX-12192( )/U. - Check the continuity of each wire between the applicable pins to determine compliance with 3.13.16.

4.9.17 Cable Assembly, Headset CX-( ). - Check the continuity of each wire between the applicable terminals in accordance with SM-B-625791, to determine compliance with 3.13.17.

4.9.18 Cable, CX-3475( )/U. - Check the continuity of each wire between the applicable terminals to determine compliance with 3.13.18.

4.9.19 Power Supply Termination MX-( ). - Check the continuity of each wire between the applicable terminals in accordance with SM-B-625877, to determine compliance with 3.13.19

4.9.20 Power Supply Termination MX-( ). - Check the continuity of each wire between the applicable terminals in accordance with SM-B-625879, to determine compliance with 3.13.20.

4.9.21 Power Supply Termination MX-( ). - Check the continuity of each wire between the applicable terminals in accordance with SM-B-625792, to determine compliance with 3.13.21.

4.9.22 Headset Termination MX-( ). - Check the continuity of each wire between the applicable terminals in accordance with SM-B-625790, to determine compliance with 3.13.22.

4.9.23 Microphone Termination MX-( ). - Check the continuity of each wire between the applicable terminals in accordance with SM-B-625789, to determine compliance with 3.13.23.

4.9.24 Adapter, MX-8503( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.24.

4.9.25 Adapter, MX-8504( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.25.

4.9.26 Adapter, MX-8505( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.26.

4.9.27 Adapter, MX-8506( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.27.

4.9.28 Adapter, MX-8507( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.28.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.9.29 Adapter, MX-8508( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.29.

4.9.30 Adapter, MX-8509( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.30.

4.9.31 Adapter, MX-8510( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.31.

4.9.32 Adapter, MX-8511( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.32.

4.9.33 Adapter, MX-8527( )/AR. - Check the continuity of each trace between the applicable terminals to determine compliance with 3.13.33.

4.9.34 Adapter, Breakout Box MX-( ). - Apply the voltage specified in Table V, measure the insulation resistance in accordance with SM-B-625701 to determine compliance with 3.13.34.

4.9.35 Adapter, Breakout Box MX-( ). - Apply the voltage specified in Table V, measure the insulation resistance in accordance with SM-B-625706 to determine compliance with 3.13.35.

4.9.36 Adapter, Breakout Box MX-( ). - Apply the voltage specified in Table V, measure the insulation resistance in accordance with SM-B-625711 to determine compliance with 3.13.36.

4.9.37 Adapter, Breakout Box MX-( ). - Apply the voltage specified in Table V, measure the insulation resistance in accordance with SM-B-625716 to determine compliance with 3.13.37.

4.9.38 Cable, CX-10894( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.38.

4.9.39 Cable, CX-12182( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.39.

4.9.40 Cable, CX-12183( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.40.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.9.41 Cable, CX-12184( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.41.

4.9.42 Cable, CX-12185( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.42.

4.9.43 Cable, CX-12186( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.43.

4.9.44 Cable, CX-12187( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.44.

4.9.45 Cable, CX-12188( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.45.

4.9.46 Cable, CX-12189( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.46.

4.9.47 Cable, CX-12190( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.47.

4.9.48 Cable, CX-12191( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.48.

4.9.49 Cable, CX-12192( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.49.

4.9.50 Cable Assembly, Headset CX-( ). - With 100 VDC applied, the insulation resistance shall be measured in accordance with SM-B-625791 as indicated in Table VI, to determine compliance with 3.13.50.

4.9.51 Cable, CG-3475( )/U. - Apply 100 VDC, measure the insulation resistance between points indicated in Table VI, to determine compliance with 3.13.51.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.9.52 Power Supply Termination MX-( ). - These resistance measurements shall be made in accordance with SM-B-625877 as indicated in Table VII, to determine compliance with 3.13.52.

4.9.53 Power Supply Termination MX-( ). These resistance measurements shall be made in accordance with SM-B-625879 as indicated in Table VII, to determine compliance with 3.13.53.

4.9.54 Power Supply Termination MX-( ). - These resistance measurements shall be made in accordance with SM-B-625792 as indicated in Table VII, to determine compliance with 3.13.54.

4.9.55 Headset Termination MX-( ). - These resistance measurements shall be made in accordance with SM-B-625790 as indicated in Table VIII, to determine compliance with 3.13.55.

4.9.56 Microphone Termination MX-( ). - These resistance measurements shall be made in accordance with SM-B-625789 as indicated in Table IX, to determine compliance with 3.13.56.

4.9.57 Adapter, MX-8503( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.57.

4.9.58 Adapter, MX-8504( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.58.

4.9.59 Adapter, MX-8505( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.59.

4.9.60 Adapter, MX-8506( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.60

4.9.61 Adapter, MX-8507( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.61.

4.9.62 Adapter, MX-8508( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.62.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.9.63 Adapter, MX-8509( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.63.

4.9.64 Adapter, MX-8510( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.64.

4.9.65 Adapter, MX-8511( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.65.

4.9.66 Adapter, MX-8527( )/AR. - Apply 100 VDC, measure the insulation resistance between points indicated in Table X, to determine compliance with 3.13.66.

4.9.67 30dB Attenuator CN-( ). - The attenuation shall be measured in accordance with SM-A-625793 as indicated in Table XI, to determine compliance with 3.13.67.

4.9.68 30dB Attenuator CN-( ). - The voltage standing wave shall be measured in accordance with SM-A-625793 as indicated in Table XII, to determine compliance with 3.13.68.

TABLE V - INSULATION RESISTANCE

ITEM	FROM	TO	OHMS	VOLTS
Adapter, Breakout Box Assembly SM-B-625701	Each test point in Test point field	All other test points on Breakout Box	> 1 Meg	100 VDC
Adapter, Breakout Box Assembly SM-B-625706	Each test point in Test point field	All other test points Breakout Box	> 1 Meg	100 VDC
Adapter, Breakout Box Assembly SM-B-625711	Each test point in Test point field	All other test points on Breakout Box	> 1 Meg	100 VDC
Adapter, Breakout Box Assembly SM-B-625716	Each test point in Test point field	All other test points on Breakout Box	> 1 Meg	100 VDC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE VI - INSULATION RESISTANCE

ITEM	FROM	TO	OHMS	VOLTS
Cable Assembly, Special Purpose, Electrical CX-12183/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose, Electrical CX-12184/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose Electrical CX-12185/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose, Electrical CX-12186/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose, Electrical CX-12187/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose Electrical CX-12188/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose, Electrical CX-12189/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose Electrical CX-12190/U	P1-14	P1-42	> 1 Meg	100 VDC
	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE VI - INSULATION RESISTANCE (CONT)

ITEM	FROM	TO	OHMS	VOLTS
Cable Assembly, Special Purpose, Electrical CX-12191/U	P1-1	P1-3	> 1 Meg	100 VDC
	P1-2	P1-3	> 1 Meg	100 VDC
	P1-10	P1-11	> 1 Meg	100 VDC
	P1-10	P1-12	> 1 Meg	100 VDC
	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose, Electrical CX-12192/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Headset Adapter SM-B-625791	P1-1	P1-2	> 1 Meg	100 VDC
	P1-1	P2-1	> 1 Meg	100 VDC
	P1-1	P2-2	> 1 Meg	100 VDC
	P1-2	P2-1	> 1 Meg	100 VDC
	P1-2	P2-2	> 1 Meg	100 VDC
	P2-1	P2-2	> 1 Meg	100 VDC
Cable Assembly, Special Purpose CG-3475/U	P1-Inner	P1-Outer	> 1 Meg	100 VDC
Cable Assembly, Special Purpose Electrical CX-10894/AR	P1-1	P1-2	> 1 Meg	100 VDC
	P1-2	P1-5	> 1 Meg	100 VDC
	P1-2	P1-8	> 1 Meg	100 VDC
	P1-2	P1-9	> 1 Meg	100 VDC
	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC
Cable Assembly, Special Purpose, Electrical CX-12182/U	Each pin on one connector	All other pins on same connector	> 1 Meg	100 VDC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE VII - RESISTANCE

ITEM	FROM	TO	LIMITS OHMS (MIN)	LIMITS OHMS (MAX)
Power Supply Termination SM-B-625877	J1-42	J1-1	53	59
	J1-42	J1-13	78	86
	J1-42	J1-18	2850	3150
	J1-42	J1-32	209	231
Power Supply Termination SM-B-625879	J1-16	J1-13	4845	5355
	J1-16	J1-14	95	105
	J1-16	J1-15	25.7K	29.3K
	J1-16	J1-28	31.3	34.7
	J1-16	J1-50	104.5	115.5
Power Supply Termination SM-B-625792	J1-14	J1-7	114	126
	J1-14	J1-26	3135	3465
	J1-14	J1-44	64.5	71.5
	J1-14	J1-47	31.3	34.7

TABLE VIII - RESISTANCE

ITEM	FROM	TO	LIMITS OHMS (MIN)	LIMITS OHMS (MAX)
Headset Termination SM-B-625790	J1	J2	7.8	8.6

TABLE IX - RESISTANCE

ITEM	FROM	TO	LIMITS OHMS (MIN)	LIMITS OHMS (MAX)
Microphone Termination SM-B-625789	J1	J3	4845	5355
	J1	J2	4.8	5.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE X - INSULATION RESISTANCE

ITEM	FROM	TO	OHMS	VOLTS
Adapter, Test MX-8503/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8504/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8505/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8506/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8507/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8508/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8509/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8510/AR	Each connector trace	Each adjacent connector trace	1 Meg	100 VDC
Adapter, Test MX-8511/AR	Each test point	Each adjacent test point	1 Meg	100 VDC
Adapter, Test MX-8527/AR	Each test point	Each adjacent test point	1 Meg	100 VDC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

TABLE XI - ATTENUATION

ITEM	FREQUENCY	ATTENUATION		
		NOMINAL	MINIMUM	MAXIMUM
30 dB Attenuator SM-A-625793	30 MHz	30 dB	29 dB	31 dB
	76 MHz	30 dB	29 dB	31 dB
	150 MHz	30 dB	29 dB	31 dB
	225 MHz	30 dB	29 dB	31 dB
	400 MHz	30 dB	29 dB	31 dB

TABLE XII - VSWR

ITEM	FREQUENCY	VSWR (MAXIMUM)
30 dB Attenuator SM-A-625793	30 MHz	1.15:1
	76 MHz	1.15:1
	150 MHz	1.15:1
	225 MHz	1.15:1
	400 MHz	1.15:1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

4.10 Visual and Mechanical Inspection. - Prior to and after assembly, the equipment shall be examined for the defects in accordance with MIL-STD-252.

4.11 Interchangeability. - The dimensions listed below shall be gaged or measured to determine compliance with the physical interchangeability requirements of 3.16. When a listed dimension is not within specified or design limits, it shall be considered a major defect.

a. External and internal dimensions of cases, covers, and insertable assemblies when such dimensions affect mating of parts.

b. Dimensions of cavities, of the console and other units, when such dimensions affect insertion of items.

c. Location of hinges and fasteners on separable parts or assemblies which must mate, such as cases, covers and mountings.

d. Location of connectors, locking pins, fasteners, slides and mountings which receive mating parts of plug-in assemblies and major units, and location of the mating parts on the plug-in assemblies or major units.

e. Size and form of special threads.

4.12 Operational inspection test. - The MK-1191( )/AR shall be inspected and tested for assurance that all accessories are in place and that the test set controls perform their required functions.

4.13 Quality conformance inspection of preparation for delivery. - Preparation for delivery shall be inspected in accordance with Specification MIL-P-116 to determine conformance to the packaging requirements of Section 5.

4.14 Rough handling test (preparation for delivery). - When rough handling test in accordance with Specification MIL-P-116 is required by the contract, the operational inspection test 4.12 shall be conducted to determine freedom from operational malfunction caused by rough handling.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. - Preservation and packaging shall be level A or C as specified (See 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:16Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. -

5.1.1.1 Cleaning. - Test Facilities Kit MK-1191( )/AR shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. - Test Facilities Kit MK-1191( )/AR shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. - None required.

5.1.1.4 Unit packaging. - Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. - Each technical literature shall be packaged method IC-1.

5.1.1.4.2 Test Facilities Kit MK-1191( )/AR. - Units of the Test Facilities Kit MK-1191( )/AR shall be packaged method III as follows: Stow the units within the compartments provided in the carrying case. Close the lid of the carrying case and secure fastenings. Cushion the case on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF. class weather-resistant, variety SW, grade W5c, designed to protect all projections and absorb the shock of impact in handling and transit. Place the cushioned item within a close fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, packages as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.1.2 Level C. - Test Facilities Kit MK-1191( )/AR shall be preserved and packaged in a manner that will afford adequate protection against physical and environmental damage during shipment, handling and limited intransit storage.

5.2 Packing. - Packing shall be level A, B or C as specified. Shipping containers for all levels shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents. (See 6.2).

5.2.1 Level A. - Test Facilities Kit MK-1191( )/AR, packaged as specified in 5.1, shall be individually packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2, or PPP-B-585, style 2 or 3, class 3. Fiberboard boxes being placed directly in the shipping container shall be waterproofed with tape

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:16Z
Check the source to verify that this is the current version before use.

conforming to PPP-T-76, in accordance with the taping requirements of the appendix of the box specification. When the gross weight exceeds 200 pounds, or the container length and width is 48 X 24 inches or more and the weight exceeds 100 pounds, 3 X 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, class B.

5.2.2 Level B. - Test Facilities Kit MK-1191( )/AR, packaged as specified in 5.1, shall be individually packed within a close-fitting box conforming to PPP-B-601, domestic type; PPP-B-621, style 4, class 1; PPP-B-585, style 2 or 3, class 3; PPP-B-640, class 2, style E; or PPP-B-636, type CF, class weather-resistant. The gross weight of boxes conforming to PPP-B-640 shall not exceed 250 pounds. When the gross weight of wood boxes exceeds 200 pounds, or the container length and width is 48 X 24 inches or more and the weight exceeds 100 pounds, 3 X 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specfied in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. When the gross weight of fiberboard boxes exceeds 200 pounds, or the container length and width is 48 X 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to MIL-P-15011 or MIL-P-3938. Closure and strapping or reinforcing shall be in accordance with the applicable container specification or appendix thereto; except that fiberboard shipping containers shall be reinforced by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97. Type IV and PPP-S-760, type II, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification.

5.2.3 Level C. - Test Facilities Kit MK-1191( )/AR, packaged as specified in 5.1, shall be individually packed within a close fitting box conforming to PPP-B-640, Class 1, Style E, or PPP-B-636, Type CF, Class domestic. The gross weight of boxes conforming to PPP-B-640 shall not exceed 250 pounds. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to MIL-P-15011 or MIL-P-3938. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing of boxes conforming to PPP-B-640 shall be by nonmetallic strapping or pressure-sensitive filament tape handling or nonmetallic strapping conforming to PPP-S-760, Type II and PPP-T-97, Type IV respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:16Z
Check the source to verify that this is the currentversion before use.

5.3 Marking. - In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. - The Test Facilities Kit, MK-1191( )/AR is to be used in conjunction with the MK-994/AR and standard test equipment to facilitate testing and fault isolation of various components. MK-1191( )/AR provides breakout boxes, extender cards, extender cables, adapters and special tools for bench testing, alignment and repair of Radio Sets, AN/ARC-114( ), AN/ARC-115( ), AN/ARC-116( ) and Direction Finder Set, AN/ARN-89( ), at the general support level of maintenance.

6.2 Ordering data. - Procurement documents should specify the following:

a. Title, number, and date of this specification and any amendment thereto.

b. Level of preservations, packaging and level of packing required for shipment.

c. The specific paragraphs of Section 5 which are applicable to the particular procurement.

d. Preproduction inspection. -

(1) Three (3) sample units of each item cited in Section 1 are generally required so that lengthly environmental tests can be completed on sample unit while complete performance measurements can be made on the second sample unit. (See 3.2)

(2) Preproduction pack(s) as follows:

(a) Makeup of pack(s)

(b) Number of each kind of pack to be submitted.

(c) Inspection to be performed thereon. (Including rough handling and functional tests)

e. Marking and shipping of samples.

f. Place of final inspection.

g. Technical literature required. (See 3.17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:16Z
Check the source to verify that this is the current version before use.

h. Quantity of tools and running spare parts required.

i. Submission of the statement of treatment referenced in 3.11 should be submitted as specified in the solicitation /contract. This statement should be submitted to the contracting officer.

6.3 Nomenclature. - The parentheses in the nomenclature will be deleted or replaced by a letter identifying the particular design; for example: MK-1191W/AR. The contractor should apply for nomenclature in accordance with the applicable clause in the contract.

6.4 Group C Inspection. - Approval to ship may be withheld, at the discretion of the Government, pending results of the corrective action specified in the contract.

6.5 Definition of Level B. - Level B packaging requirements detailed herein are designed to furnish protection against corrosion, deterioration, and physical damage during domestic shipments; covered storage for a period of three years or less; and distribution within the continental limits of the United States.

6.6 Location of Operational Inspection. - It is desirable that the operational inspection 4.12 be performed at a location that will minimize handling (which might cause damage to the units) after this inspection. It is recommended that the entire lot (including the sample units) be inspected immediately prior to packaging.

6.7 Verification Inspection. - Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive Quality Assurance provisions established in this specification and the contract. The amount of verification inspection by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

Custodian:
Army EL

Preparing Activity
Army EL
FSC 6625-A477

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-FM 1068-68

To detach this cut along this line

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:16Z
Check the source to verify that this is the current version before use.