MILITARY SPECIFICATION SHEET

CABLE, RADIO FREQUENCY, FLEXIBLE, COAXIAL, 50 OHMS, UNARMORED M17/79-RG218, AND ARMORED M17/79-RG219

This amendment forms a part of Military Specification Sheet MIL-C-17/79D, dated 4 June 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following acquisition note, add:

" NOTE: THE AIR FORCE HAS RESTRICTED THE USE OF PVC IN AEROSPACE AND GROUND SUPPORT APPLICATIONS. CABLES WITH PVC JACKETING SHALL BE USED FOR RETROFIT PURPOSES ONLY UNTIL AN ALTERNATE JACKET IS APPROVED. "

PAGE 2

ENGINEERING INFORMATION, Inner conductor properties, delete and substitute the following:

"DC resistance (maximum at 20°C): 0.0278 ohm per 100 feet.

Elongation: 30 percent, minimum.

Tensile strength: Not applicable."

REQUIREMENTS, Environmental and mechanical, following entry for Aging stability, add:

"Cold bend: -40°C ±2°C."

REQUIREMENTS, Environmental and mechanical, entry for Weight: Delete "0.575" and substitute "0.510". Delete "0.635" and substitute "0.550".

REQUIREMENTS, Electrical, entry for Test frequency: Delete in its entirety.

REQUIREMENTS, Electrical, entry for Spark test: Delete "8,000 V rms, minimum" and substitute "8,000 V rms +10%, -0%."

REQUIREMENTS, Electrical, entry for Voltage withstanding: Delete the word "minimum" and substitute "+10%, -0%."

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AR, AT, ME
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 6145-0911-16)

FSC 6145

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:06Z
Check the source to verify that this is the current version before use.