MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL,
50 OHMS, M17/84-RG223

This amendment forms a part of MIL-C-17/84B, dated 18 July 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I, delete and substitute:

" TABLE I. Description.

Components	Construction details
Inner conductor	Solid silver-coated copper wire Diameter: 0.035 inch ±0.001.
Dielectric core	Type A-1: Solid polyethylene Diameter: 0.116 inch ±0.004
Outer conductor:	Double braid of AWG size 36, silver-coated copper wire. Diameter: 0.176 inch maximum.
Inner braid	Coverage: 95.0% nominal Carriers: 16 Ends: 7 Picks/inch: 11.5 ±10%
Outer braid	Coverage: 94.2% nominal Carriers: 16 Ends: 7 Picks/inch: 15.0 ±10%
Jacket	Type IIa: PVC. Diameter: 0.212 inch ±0.004

"

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH, TD
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AR, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 6145-1076)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:07Z
Check the source to verify that this is the current version before use.