MIL-C-63267 (AR)
13 July 1984
SUPERSEDING
FA-PD-MI-2673 Rev O
30 June 1965

# MILITARY SPECIFICATION

## CASE, CARTRIDGE, BLANK 105MM, M15B2

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts for Case, Cartridge, Blank, 105MM, M15B2.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

| | | |
|---|---|---|
| MIL-A-48078 | - | Ammunition, Standard Quality Assurance Provisions, General Specifications for |

STANDARDS

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes |

FEDERAL

| | | |
|---|---|---|
| FED-STD-151 | - | Metals; Test Methods |

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

2.1.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.6)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

| | | |
|---|---|---|
| 7548320 | - | Ammunition for Interplant Shipment of Brass, Aluminum and Spirally Wrapped Steel Cartridge Cases, Empty, 75MM to 120MM Inclusive |
| 10534917 | - | Case, Cartridge, Blank, 105MM, M15B2 |

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg.) 10534917, associated drawings and with all requirements specified in applicable specifications, and standards.

3.3 Protective finish. Protective finish shall be in accordance with the applicable drawing and the specification listed.

3.4 Corrosion resistance. Following exposure to five percent salt spray for 168 hours. Test pieces shall comply with the requirements of the applicable drawing and the specification listed.

3.5 Maximum profile. The maximum profile of the cartridge case shall comply with the requirements of the applicable drawing.

3.6 Workmanship. Each cartridge case shall be free from cracks, splits, seams, deep scratches, burrs (those which may interfere with assembly or prove injurious to personnel handling the item) or foreign matter which may impair proper functioning.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of 30 Cases, Cartridge, Blank, 105MM, M15B2. Four cases of the 30 shall be used for protective finish tests after completion of Mechanical/Visual inspections.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for Major and Minor defects shall be in accordance with MIL-STD-105, Inspection Level II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

**CLASSIFICATION OF DEFECTS & TESTS** MIL-C-63267 (AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 10534917 |
|---|---|---|---|---|---|
| | Case, Cartridge Blank, 105MM, M15B2 | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Case, Cartridge, Blank 105MM, M15B2 (Dwg. 10534917) | | | | |
| | Examination for defects | 30 | | 3.2 | 4.4.2.1 |
| | Protective finish | 4 | | 3.4 | 4.5.1 |

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET 1 OF 2 | | DRAWING NUMBER 10534917 |
|---|---|---|---|---|---|
| 4.4.2.1 | Case, Cartridge, Blank 105MM, M15B2 | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined. | | | | |
| Major | | | | | |
| 101 | True position of primer hole with body | | 0.40% | 3.2 | Gage |
| 102 | True position of primer hole counterbore with primer hole | | 0.40% | 3.2 | Gage |
| 103 | Diameter of primer hole | | 0.40% | 3.2 | Gage |
| 104 | Diameter of primer hole counterbore, min. | | 0.40% | 3.2 | Gage |
| 105 | Depth of primer hole counterbore, min. | | 0.40% | 3.2 | Gage |
| 106 | Depth from front face of flange to bottom of primer hole counterbore, min. | | 0.40% | 3.2 | Gage |
| 107 | Thickness of head, min. | | 0.40% | 3.2 | Gage |
| 108 | Taper in primer hole, incorrect | | 0.40% | 3.2 | Gage |
| 109 | Diameter of flange | | 0.40% | 3.2 | Gage |
| 110 | Thickness of flange | | 0.40% | 3.2 | Gage |
| 111 | Wall thickness at mouth for minimum length | | 0.40% | 3.2 | Gage |
| 112 | Taper on body outside diameter | | 0.40% | 3.2 | Gage |
| Minor | | | | | |
| 201 | Diameter of mouth inside, min. | | 0.65% | 3.2 | Gage |
| 202 | Diameter of body under flange, min. | | 0.65% | 3.2 | Gage |
| 203 | Length to basic diameter, min. | | 0.65% | 3.2 | Gage |
| 204 | Length total | | 0.65% | 3.2 | Gage |
| 205 | Wall thickness near head, min. | | 0.65% | 3.2 | Gage |

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 2 OF 2 | | DRAWING NUMBER 10534917 |
|---|---|---|---|---|---|
| 4.4.2.1 | Case, Cartridge, Blank 105MM, M15B2 | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined. | | | | |
| 206 | Surface finish, improper | | 0.65% | 3.2 | Visual |
| 207 | Protective finish, inadequate or damaged | | 0.65% | 3.3 | Visual |
| 208 | Stamping, missing, incorrect or illegible | | 0.65% | 3.2 | Visual |
| 209 | Workmanship | | 0.65% | 3.6 | visual |

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63267 (AR)

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.2 | Carton, Ammo for Interplant Shipment of Brass, Aluminum & Spirally Wrapped Steel Ctg. Cases, Empty, 75MM to 120MM Inclusive | 1 OF 1 | 7548320 |
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined. | | | | |
| Major | None defined. | | | | |
| Minor | (Prior to Sealing) | | | | |
| 201 | Improper assembly | | 0.65% | 3.2 | Visual |
| | (After Sealing) | | | | |
| 201 | Carton damaged (cut or gouged through all layers) | | 0.65% | 3.2 | Visual |
| 202 | Sealing improper | | 0.65% | 3.2 | Visual |
| 203 | Marking, missing, incorrect or illegible | | 0.65% | 3.2 | Visual |

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection table.

4.4.3.1 Maximum profile. Each cartridge case shall be gaged in a contractor certified maximum profile gage. Failure of any cartridge case to freely enter the gage in such manner as to permit the slide to close without interference shall be cause for rejection of the cartridge case.

4.4.3.2 Protective finish.

4.4.3.2.1 Salt spray. Four cartridge cases from the initial production sample and four cartridge cases from each production lot shall be subjected to this test to determine compliance with 3.4. Failure of one or more cartridge cases to comply shall be cause for rejection of the initial production sample or production lot.

4.4.4 Inspection equipment. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and Paragraph 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Salt spray. Procedures and equipment used in performing this test shall be as prescribed in Federal Test Method Standard No. 151.

5. PACKAGING

5.1 Packaging requirements Packaging shall be as specified on dwg. 7548320.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on 75MM Howitzers.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection procedures and equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required to Commander, US Army Armament Research and Development Center, ATTN: DRSMC-QAR-I(D), Dover, NJ 07801.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal or ARRADCOM drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A171)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.