MIL-D-60254A(MU)
12 August 1966
SUPERSEDING
MIL-D-60254(MU)
7 December 1965

MILITARY SPECIFICATION

DUMMY CARTRIDGE, 5.56MM, M232, INERT LOADED

1. SCOPE

1.1 This specification covers an inert-loaded dummy cartridge used for testing metallic link belts and the mechanism of 5.56mm small arms.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-636	- Visual Inspection Standards for Small Arms Ammunition through Caliber .50
MIL-STD-644	- Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition

DRAWINGS

Munitions Command

*	D10534146	- Dummy Cartridge, 5.56mm, M232, Inert Loaded
	C7643674	- Classification of Cartridge Case Defects
	F10523635	- Packing & Marking Ctgs, 5.56mm, Cartons; Box, Ammunition, M2A1; Box, Wirebound
*	IEL-10534146	- Inspection Equipment List for Dummy Cartridge, 5.56mm, M232, Inert Loaded

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

Munitions Command
AMSMU-P715-501FA1 - Ammunition Ballistic Acceptance Test Methods, Test Procedures for 5.56mm Cartridges

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The cartridge shall comply with Drawing D10534146, referenced specifications and the following:

* 3.2 First article sample.- Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.3 Bullet extraction.- The force required to extract the bullet from the cartridge case shall be not less than 175 lbs.

3.4 Residual stress.- The cartridge case shall not split when subjected to a 1% mercurous nitrate solution for 15 minutes.

3.5 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specification and the following:

3.5.1 Metal defects.- The cartridge shall be free of splits.

3.5.2 Foreign matter.- The cartridge shall be free of corrosion, dirt and oil.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commericial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

* 4.2 First article sample.

* 4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 100 cartridges. The samples shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

* 4.2.1.1 Examination and Test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

* 4.2.1.2 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Lot identification.- Each lot of ammunition shall be identified as to type, caliber and model, as well as with a lot number and the manufacturer's identification as assigned by the procuring activity. Each lot shall be further identified by a Federal Stock Number assigned by the procuring activity.

4.3.2 Examination.- Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, using applicable sampling plans and acceptance criteria of MIL-STD-105. The acceptable quality level (AQL) for the major class shall be 1.00 percent and the AQL for the minor class shall be 2.50 percent. All non-conforming cartridges shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of defects.- The classification of defects shall be as specified in Table I.

TABLE I

No.	Defect and Method of Inspection	Major	Minor
	Visual 1/		
	Cartridge		
1	Discolored, dirty, oily		X
2	Corroded or stained, if etched	X	
2A	Identification missing or incorrect	X	
	Case		
4	Round head	X	
5	Dent		X
6	Split case	X	
7	Perforated case	X	
10	Beveled underside of head	X	
11	Case mouth not crimped in cannelure	X	
12	Scaly metal		X
13	No chamfer on head (rim)	X	
14	Fold		X
15	Wrinkle		X
16	Buckle		X
17	Bulge		X
19	Defective head		X
20	Defective mouth		X
	Bullet		
24	Split bullet jacket		X
25	Loose bullet	X	
26	Missing cannelure	X	
27	Scaly metal (bullet)		X
	Gaging		
32	Total length	X	
33	Cartridge profile failure (requiring more than 10 pounds dead weight to insert in profile and alignment gage)	X	
34	Diameter of extractor groove, max.	X	
35.	Diameter of extractor groove, min.		X
36.	Diameter of head	X	
37	Thickness of head	X	
38	Length to shoulder datum	X	
	Weighing		
39	Weight, min.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

1/ Refer to MIL-STD-636 (NATO Caliber 7.62 section) for visual standards for defects 1 through 27. In the event of conflict between Table I of this specification and MIL-STD-636 as to defect classification, the classification specified in Table I shall apply.

4.3.2.2 Inert charge.- The contents of each cartridge case obtained from the bullet extraction test shall be emptied and examined. The presence of propellant, in lieu of inert mixture, in any cartridge case shall be cause for rejection of the lot.

4.3.3 Tests.- The following tests shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Bullet extraction.- A sample of fifty cartridges shall be tested for bullet extraction. Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample may be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

4.3.3.2 Residual stress (Mercurous nitrate).- A sample of twenty cartridges shall be subjected to the mercurous nitrate test. Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample may be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

4.3.4 Packaging, packing and marking inspection.- During or immediately prior to the packaging operation, 100% examination of the cartridges shall be performed to ascertain that no primer is present in the primer pocket. The presence of a primer shall be classed as a critical defect and all cartridges containing a primer shall be rejected. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644 as applicable to the drawing.

* 4.3.5 Inspection equipment.- The examination and tests shall be made using the equipment listed on IEL 10534146.

4.4 Test methods and procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.4.1 Bullet extraction.- The test shall be conducted in accordance with AMSMU-P715-501 FA1. The rate of travel of the test head shall be not less than three nor more than six inches per minute.

4.4.2 Residual stress (Mercurous nitrate).- The test shall be conducted in accordance with AMSMU-P715-501 FA1.

5. PREPARATION FOR DELIVERY

5.1 Packing - Level A.- **(Worldwide shipment)** - The cartridges shall be packed in accordance with Drawing F10523635.

5.2 Marking and labeling.- Packing boxes shall be marked and labeled in accordance with the applicable drawing cited in 5.1.

6. NOTES

6.1 Ordering data.- Invitations for bids or request for proposal and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Type and level of packing.

6.1.3 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for accptance inspection purposes.

6.1.4 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government.

* 6.1.5 Requirement for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

* The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1305-A459

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.