MILITARY SPECIFICATION

HANDLING DEVICE: H-4164A

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of handling tool entitled Handling Device: H-4164A.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-C-490 - Cleaning and Preparation of Ferrous and Zinc Coated Surfaces for Organic Protective Coating.
MIL-T-5021 - Tests; Aircraft Welding Operator's Certification.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8808362 - Container, Packing, Ammunition for Domestic (CONUS) Shipments of Special Weapons Items, Packing and Marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

8839248 - Handling Device; H-416A.
8858718 - Carton, Packing, Ammunition, for Handling Tool, H-4164A.
8858719 - Box, Packing, Ammunition for Handling Device, H-4164A.
EL-8856516 - Equipment Lists.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. Requirements

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The handling tool shall comply with all requirements specified on the drawing (dwg) 8839248, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Static load. The handling tool shall be capable of supporting a 100 pound load without evidence of permanent distortion, cracked welds, or other physical damage as could be experienced by the rubber pads and adhesive when tested as specified in 4.3.1.

3.4 Paint adhesion. The painted surface shall adhere to the base material without evidence of peeling, flaking, or chipping when tested as specified in 4.3.2.

3.5 Welding. Welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of fusion, penetration and soundness of weld deposit representative of good welding practice. They shall be free of irregularities which indicate lack of good practice on the part of the operator. All welding fluxes, scale, weld spatter, guide, and basic solutions shall be removed prior to application of any finish coat.

3.5.1 Welding operators All fusion welding shall be performed by operators who are currently certified as Class "B" welders in accordance with MIL-T-5021.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All componants shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Lot formation.

4.2.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.2.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.2.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	25	70-76	34	245-335	42
21	19	37-40	27	77-86	35	335-519	42
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.2.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Handling device, H-4164A (see dwg 8839248).

Categories	Characteristics	Method of Inspection
Critical:		
	1. Crack in weld	Visual
	2. Improper weld (see 3.5.1)	Visual
	3. Component cracked or loose	Visual
Major:		
	101. Thread on knob assembly damaged	Visual
	102. Knob does not turn freely	Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

103. Objective evidence relative to material missing or improper (see 3.1).....Visual

Minor:

201. Finish inadequate.....Visual
202. Evidence of poor workmanship (see 3.6).....Visual
203. Cushion torn, damaged or loose.....Visual/Manual

4.2.2.1.2 Carton, packing, ammunition for handling device H-4164A (see dwg 8858718).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Metal strips of item not strapped	Visual
	102. Insufficient cushioning material	Visual/Manual
	103. Packing material wet	Visual/Manual
	104. Contents loose	Manual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual
	202. Marking missing or incorrect	Visual

4.2.2.1.3 Box, packing, ammunition, for handling device, H-4164A prior to closing (see dwg 9959819).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

Major:

101. Carton sealed improperly.....Visual
102. Insufficient filler material.....Visual/Manual
103. Packing material not dry.....Visual/Manual

Minor:

201. Evidence of poor workmanship (see 3.6).....Visual

4.2.2.1.4 Box, packing, ammunition for handling device: H-4164A (see dwg 8858719).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Box strapped and sealed improperly.....Visual
102. Car seal missing.....Visual
103. Board broken, cracked or split.....Visual

Minor:

201. Marking missing, mislocated or incorrect.....Visual
202. Evidence of poor workmanship (see 3.6).....Visual

4.2.2.1.5 Container, packing ammunition for domestic (CONUS) shipments of special weapons items, packing and marking (see dwg 8808362).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Marking missing, incorrect or mislocated.....Visual
102. Packing material visibly wet.....Visual
103. Contents loose.....Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

Minor:

201. Evidence of poor workmanship (see 3.6).....Visual

4.2.3 Testing. All tests shall be performed. Tests need not performed in the order specified below:

Test	Test classification
a. Static weight	Major
b. Paint adhesion	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.2.3.1 Static weight, and paint adhesion. Each handling tool shall be tested in accordance with 4.3.1 and 4.3.2. If any item fails to comply with 3.3 and 3.4 the item shall be rejected and removed from the lot.

4.2.4 Acceptance inspection equipment

4.2.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipmemt, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8856516). When either of the conditions listed below exist, the contractor shall design required equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.2.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.3 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.3.1 Static weight. A 100 pound static weight in the shape of a truncated cone 20.10 inches long, tapering from 15.30 to 5.00 inches in diameter, with a center of gravity located 6.3 inches from the large end shall be secured to the handling tool. This assembly shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

lifted by its handles and suspended for 1 minute. It shall then be lowered and supported by its legs and stand assembly on a level platform or floor for 1 minute.

4.3.2 Paint adhesion. Paint adhesion shall be determined in accordance with the tape test specified in MIL-C-490.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The handling tool shall be packaged in accordance with dwg 8858718 using the specified moisture barrier.

5.1.2 Level C. The handling tool shall be packaged in accordance with dwg 8858718 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The handling tool shall be packed in accordance with dwg 8858719 for overseas shipment.

5.2.2 Level A and C. The handling tool shall be packed in accordance with dwg 8858718 for domestic shipment, (CONUS).

5.3 Marking. Marking shall be as specified in accordance with dwg 8858719 or 8808362 as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.2.4.1). Data specified in 4.2.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.2.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-N-I.

6.4 Supersession data. This specification supersedes the requiements of Purchase Description PA-PD-1994 dated 31 July 1961.

Custodian:
Army - PA

Preparing activity:
Army -PA

Project No. 1190-A078

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.