MILITARY SPECIFICATION

MINE, APERS, M18A1E1 (WITH ACCESSORIES) LOADING, ASSEMBLING AND PACKING

This Specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of mine designated as Mine, APERS, M18A1E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	-	Preservation, Packaging, Method of.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-1168	-	Lot Numbering of Ammunition.

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

9271910	-	Extension Line and Spool Assembly
9285519	-	Mine, APERS, M18A1E1
9287716	-	Packing and Marking for Mine, APERS, M18A1E1
9287717	-	Box, Packing Ammunition, Wirebound.

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly. - The mine assembly, with accessories, shall comply with all requirements specified on drawing (dwg.) 9285519 and with all requirements specified in applicable specifications.

3.3 Functioning. - The loaded mine assembly with accessories, following temperature-conditioning, shall function satisfactorily as evidenced by completely destroying itself. The test shall be performed at an approved Government facility.

3.4 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), holes, tears, voids, porosity, warpage, excess flash, cracks, chipped edges, blisters, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following type of inspection shall be conducted on this item.

a. Quality Conformance Inspection

4.3 Quality conformance inspection

4.3.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Lot numbering as required shall be in accordance with MIL-STD-1168. In addition, each lot of mines shall contain:

a. Parts of one lot interfix number from one manufacturer.
b. Composition C-4 from not more than two lots.
c. Firing devices of one lot interfix number from one manufacturer.
d. Electrical test sets of one lot interfix number from one manufacturer.
e. Electrical blasting cap assemblies of one lot interfix number from one manufacturer.

4.3.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837104
4.3.2.1	Assembly, Mine, APERS, M18A1E1, prior to sealing Cover to Case				NEXT HIGHER ASSEMBLY 9285519
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Gap between explosive and inside surface of sidewall, maximum		0.40%	3.2	Gage
Minor:					
201.	Bead of cement applied less than 360°		0.65%	3.2	Visual
202.	Edges chipped or broken		0.65%	3.2	Visual
203.	Locking lug missing or damaged		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-48379 (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.2	Assembly, Mine, APERS, M18A1E1, after sealing Cover to Case.	1 OF 1	8837104
			NEXT HIGHER ASSEMBLY 9285519

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Detonator well depth, minimum		0.40%	3.2	Gage
102.	Detonator well diameter, minimum		0.40%	3.2	Gage
103.	Shipping plug-priming adapter missing, damaged or improperly assembled		0.40%	3.2	Visual/Manual
Major B:					
131.	Leg assembly twisted, bent or otherwise damaged		0.40%	3.2	Visual
132.	Crimp missing or within inside wall surface		0.40%	3.2	Visual
Minor:					
201.	Crack or split		0.65%	3.2	Visual
202.	Marking misleading or unidentifiable		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

5

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9285519
4.3.2.3	Mine, APERS, M18A1E1				NEXT HIGHER ASSEMBLY N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Mine or accessory missing		0.40%	3.2	Visual
102.	Mine or accessory damaged		0.40%	3.2	Visual
Major B:					
131.	Mine or accessory incorrectly packed		0.40%	3.2	Visual
132.	Tag damaged or missing from bandoleer containing test set		0.40%	3.2	Visual
Minor:					
201.	Marking misleading or unidentifiable		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-48379 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.4	Box Fiberboard, prior to Sealing				9287719
					NEXT HIGHER ASSEMBLY 9287716
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Any spool of wire missing		0.40%	3.2	Visual
132.	Spool block missing		0.40%	3.2	Visual
133.	Any mine pack missing or incorrectly positioned in box		0.40%	3.2	Visual
134.	Packing component missing		0.40%	3.2	Visual
Minor:					
201.	Cushioning improperly positioned		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

-7

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-48379 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.5	Box Fiberboard, Sealed				9287719
					NEXT HIGHER ASSEMBLY 9287716
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Contents move when box is shaken (insufficient filler material)		0.40%	3.2	Visual/Manual
132.	Sealing tape missing		0.40%	3.2	Visual
133.	Box damaged so that contents are exposed or liable to be exposed		0.40%	3.2	Visual/Manual
Minor:					
201.	Marking misleading or unidentifiable		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.6	Bag, barrier sealed				9287720
					NEXT HIGHER ASSEMBLY 9287716
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Waterproofness destroyed by poor seal or damaged (separation of heat seal, rip, or puncture)		0.40%	3.2	Visual/Manual
Minor:					
201.	Heat seal incorrectly located		0.65%	3.2	Visual
202.	Excess air not removed from barrier bag		0.65%	3.2	Visual/Manual
203.	Marking misleading or unidentifiable		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

6

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-M-48379 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.7	Box, packing, ammunition, wirebound, sealed				9287717
					NEXT HIGHER ASSEMBLY 9287716
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Wire loose or improperly assembled		0.40%	3.2	Visual/Manual
132.	Board broken		0.40%	3.2	Visual
Minor:					
201.	Wire loop incorrectly closed		0.65%	3.2	Visual
202.	Metallic seal missing or improperly positioned		0.65%	3.2	Visual
203.	Marking misleading or unidentifiable		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

4.3.3 Testing.

4.3.3.1 Functioning (see 3.3). - Major A defect - The sampling plan for this test shall be in accordance with MIL-STD-105, Code letter G, double sampling plan and an AQL of 1.5 percent. The test shall be performed as specified in 4.4.1 using equipment in accordance with 4.3.4. Any assembly which fails to comply with the specified requirement shall be classed defective. (Destructive Test)

4.3.3.2 Heat seal test of sealed barrier bag. - (See dwg. 9287716) Major A defect. - Sampling, acceptance criteria and test procedures for this test shall be as specified in MIL-P-116. (Destructive test)

4.3.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.3.2.1, and the test method paragraphs (see 4.4). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.3 herein.

4.4 Test Methods and Procedures

4.4.1 Functioning. - This test shall be performed at an approved Government facility. The loaded mine and the accessories contained in its bandoleer including the extension lines shall be conditioned at minus 40, plus or minus 2 degrees, Fahrenheit for 25 plus or minus 5 hours. It shall then be functioned with the conditioned accessories within 3 minutes after removal from the temperature-conditioning chamber. Functioning shall be in accordance with the instruction sheet sewn on the bandoleer. Observation shall be made to determine compliance with the requirement specified in 3.3.

5. PREPARATION FOR DELIVERY.

5.1 Preservation and Packaging.

5.1.1 Level A. - Packaging for Mine, APERS, M18A1E1 with accessories dwg. 9285519, including extension lines dwg. 9271910 shall be in accordance with dwg. 9287716.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A. - Packing for Mine, APERS, M18A1E1 shall be in accordance with dwgs. 9287716 and 9287717.

5.3 Marking. - Marking shall be as specified on dwgs. 9287716, 9287719 and 9287720.

6. NOTES.

6.1 Intended Use. - The following items are used with the Mine, APERS, M18A1E1 system:

a. Firing Device, Electrical, M57E1.
b. Test Set, Electrical, M40E1.
c. Cap, Blasting, Electric, M4.
d. Bandoleer, M7.
e. Extension Line and Spool Assembly.

6.2 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions of MIL-A-48078.

6.3 Submission of Inspection Equipment Designs for Approval (See MIL-A-48078). Submit equipment designs as required to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1345-A-073

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

Nil

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 JAN 72 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.