
INCH-POUND
MIL-PRF-83287/4C
15 February 2007
SUPERSEDING
MIL-PRF-83287/4B
30 August 1999

PERFORMANCE SPECIFICATION SHEET


INDICATORS, FAULT LOCATING, DUAL DRUM INDICATING, MECHANICAL RESET

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-83287.




SOLDER LEADS





WIRE LEADS

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:46Z
Check the source to verify that this is the current version before use.







Inches	mm
.003	0.08
.006	0.15
.040	1.02
.044	1.12
.045	1.14
.060	1.52
.120	3.05
.155	3.94
.200	5.08
.220	5.59
.240	6.10
.313	7.95
.327	8.31
.335	8.51
.370	9.40
.395	10.03
.445	11.30
.4687	11.904
.470	11.94
.563	14.30
.593	15.06

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).
4. The mounting nut shall be black.
5. The shape and location of the solder terminal shown is not intended to limit specific manufacturing processes. When the shape of terminal in the schematic is used, the hole diameter shall be as shown.
6. No fault indication color may be lusterless gray as specified in FED-STD-595/36081.
7. Mounting torque of 5 to 7 in lbs may be used.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:46Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and characteristics: See figure 1 and table I.

Weight (including hardware): 6.5 grams, maximum.

Pulse power: 50 milliwatts, minimum.

Transfer pulse length: A pulse length of 25 milliseconds or greater shall cause a fault indication. A pulse length of 2 millisecond or less shall not cause a fault indication.

Terminal strength:

Rigid type solder terminals:	Test condition A (3 pounds, minimum). Test condition E (8 ounce-inches, minimum.)
Wire type solder terminals:	Test condition A (3 pounds, minimum). Test condition C (1 pound, minimum).

Marking of terminals: The positive terminal shall be identified by a red dot.

Vibration: Test condition B of MIL-STD-202 (method 204).

Extent of qualification: Qualification testing and approval of M83287/04-01 and M83287/04-24 shall be sufficient to grant qualification approval for all indicators covered by this specification sheet.

Part or Identifying Number (PIN): M83287/04- (dash number from table I).

Random vibration: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:46Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Military PIN M83287/04-	Voltage (volts, dc)			DC Coil resistance at						Termination type	Anti-reflection coating
		Operating		-65°C		+125°C		Ambient (+25°C)			
	Rated	Min 1/	Max	Min	Max	Min	Max	Min	Max		
01	1.5	1.2	1.8	26	33	55	70	40	50	Wire leads	No coating
02											With coating
03										Solder terminals	No coating
04											With coating
05	3.0	2.4	3.6	106	129	224	274	162	198	Wire leads	No coating
06											With coating
07										Solder terminals	No coating
08											With coating
09	6.0	4.8	7.2	423	518	897	1097	648	792	Wire leads	No coating
10											With coating
11										Solder terminals	No coating
12											With coating
13	12.0	9.6	14.4	1694	2070	3590	4388	2592	3168	Wire leads	No coating
14											With coating
15										Solder terminals	No coating
16											With coating
17	24.0	19.2	28.8	6763	8267	14335	17520	10350	12650	Wire leads	No coating
18											With coating
19										Solder terminals	No coating
20											With coating
21	28.0	22.4	30.0	9233	11286	19570	23919	14130	17270	Wire leads	No coating
22											With coating
23										Solder terminals	No coating
24											With coating

1/ Refers to the minimum operating voltage which the indicator will operate.

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-83287, this document references the following:

MIL-STD-202
FED-STD-595/36081

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:46Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Navy - AS
Air Force - 11
DLA – CC

Preparing activity:
DLA - CC

(Project 6625-0950-000)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:46Z
Check the source to verify that this is the current version before use.