MILITARY SPECIFICATION
SHELTER, ELECTRICAL EQUIPMENT
S-583 ( )/TRC-151(V)

This Amendment forms a part of Military Specification MIL-S-49181(CR), dated 18 Apr 79, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 10

Paragraph 4.2c. - Delete- Part c in its entirety and substitute "c. Quality conformance inspection of equipment before packaging (see 4.5)".

Paragraph 4.2d. - Add the following paragraph , "d. Packaging inspection (see 4.19)."

PAGE 20

Paragraph.4.6.3.1c: Delete "Radio-To-Cable O.W" from line 1 and substitute "Radio Repeater to O. W.".

Paragraph 4.6.3.1, part d. - Delete- "Cable assemblies marked "AN/GRC-103' C to C, and D to D" from the first sentence and substitute " cable assemblies marked AN/GRC-103 COMB O. W. Sys-1" and "TD-202 O. W. Sys-1": A to A, B to B, C to C and D to D".

Paragraph 4.6.3.1, part e.- Delete - " 12 ch radio (GRC-103) Repeater Patch thru", from line 1 and substitute "Radio repeater to Radio repeater".

Paragraph 4.6.3.1, part f. - Delete - "D to E' from the first sentence and substitute "D to D".

Paragraph 4.6.3.1, part g. - Delete - "Cable repeater Patch thru" from line one and substitute "Cable Repeater to Cable Repeater".

Paragraph 4, 6.3.1, part h, - Delete - "TD-754 Patch thru Sys-2" from sentence one and substitute " TD-204/754 Patch thru Sys-2".

PAGE 27

Paragraph 4.6.4.1, part g, - Delete- "Pin H of switchbox mux Ch 5-8 Sys-1 Connector " from line 2 and substitute " Pin G of switchbox Buffer Ch 5-8 Sys-1 connector".



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:54Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.4.1 part h, - Delete- "Pin G of switchbox mux Ch 5-8 Sys-1 connector" from line 2 and substitute "Pin H of switchbox buffer CH-5-8 Sys-1 connector".

Paragraph 4.6.4.1. part i - Delete - "Pin F of switchbox mux Ch 5-8 Sys-1 connector " from line 2 and substitute " Pin E of switchbox buffer Ch 5-8 Sys-1 connector".

Paragraph 4.6.4.1 part j - Delete - "Pin E of switchbox mux Ch 5-8 Sys-1 connector " from line 2 and substitute "Pin F of switchbox buffer Ch 5-8 Sys-1 connector".

PAGE 28

Paragraph 4.6.4.1, part n, - Delete - the table of part n and substitute the following table:

| From Patch Panel Marked | To Cable Assembly Marked |
|---|---|
| TD-660, K6-27 12 CHAN PCM OUT Sys-1 | TD-660/352 PCM OUT Sys-1 |
| TD-660, KG-27 12 CHAN PCM IN Sys-1 | TD-660/352 PCM In Sys-1 |
| TD-660, KG-27 TIM IN Sys-1 | TD-660/352 TIM IN Sys-1 |
| TD-660, KG-27 TIM OUT Sys-1 | TD-660/352 TIM OUT Sys-1 |
| TD-660, KG-27 ALT PCM OUT Sys-1 | TD-660/352 ALT PCM OUT Sys-1 |
| TD-660, KG-27 SYNC OUT XMTR Sys-1 | TD-660/352 SYNC OUT XMTR Sys-1 |
| TD-660, KG-27 SYNC IN Sys-1 | TD-660/352 SYNC IN SYS-1 |
| TD-660, KG-27 SYNC OUT RCVR Sys-1 | TD-660/352 SYNC OUT RCVR Sys-1 |
| TD-202 12 CHAN PCM OUT Sys-1 | TD-202 PCM OUT-1 Sys-1 |
| TD-202 12 CHAN PCM IN Sys-1 | TD-202 PCM IN-1 Sys-1 |
| TD-202 TIM IN Sys-1 | TD-202 TIM IN Sys-1 |
| TD-202 TIM OUT Sys-1 | TD-202 TIM OUT-1 Sys-1 |
| TD-202 12 CHAN PCM IN-2 Sys-1 | TD-202 PCM IN-2 Sys-1 |



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:54Z
Check the source to verify that this is the currentversion before use.

| | |
|---|---|
| TD-202 12 CHAN PCM OUT-2 Sys-1 | TD-202 PCM OUT-2 Sys-1 |
| TD-202 TIM OUT-2 Sys-1 | TD-202 TIM OUT-2 Sys-1 |
| TD-754 12 Chan PCM OUT Sys-1 | TD-204/754 PCM OUT-1 Sys-1 |
| TD-754 12 CHAN PCM IN Sys-1 | TD-204/754 PCM IN-1 Sys-1 |
| TD-754 TIM IN Sys-1 | TD=204/754 TIM IN Sys-1 |
| TD-754 TIM OUT Sys-1 | TD-204/754 TIM OUT-1 Sys-1 |
| TD-754 12 CHAN PCM IN-2 Sys-1 | TD-204/754 PCM IN-2 Sys-1 |
| TD-754 12 CHAN PCM OUT-2 Sys-1 | TD-204/754 PCM OUT-2 Sys-1 |
| TD-754 TIM OUT-2 Sys-1 | TD-204/754 TIM OUT-2 Sys-1 |
| TD-754 from Cable Sys-1 | TD-204/754 from Cable Sys-1 |
| TD-754 to Cable Sys-1 | TD-204/754 to Cable Sys-1 |
| VID ENT Box from Cable Sys-1 | VID ENT Box Male (M) Sys-1 |
| VID ENT Box to Cable Sys-1 | VID ENT Box Female (F) Sys-1 |
| GRC-102 12 CHAN PCM OUT Sys-1 | GRC-103 PCM Sys-1 |
| GRC-103 TIM OUT Sys-1 | GRC-103 TMG Sys-1 |
| GRC-103 12/24 CHAN PCM in Sys-1 | GRC-103 Video TR Sys-1 |
| GRC-103 24 CHAN PCM OUT Sys-1 | GRC-103 VID Sys-1 |
| TD-202 12/24 CHAN PCM IN Sys-1 | TD-202 from Radio RCVR Sys-1 |
| TD-202 24 CHAN PCM OUT Sys-1 | TD-202 to Radio XMTR Sys-1 |

PAGE 35

Paragraph 4.7.1j.(3). Add the following paragraph, " Operate the power ON/OFF switch to ON. The power indicator lamp shall light. Ignore the frame alarm lamp and the audible alarm. To silence the alarm depress the Audible alarm disable switch.

Paragraph 4.7.1.k. Add the following paragraph " k. perform the following procedures on Data Buffer TD-1065( )/G:

(1) Operate power ON/OFF switches on both Data Buffers TD-1065( )/G to on. Power indicator lamp shall light. Ignore the frame alarm lamp and the audibel alarm. to silence the alarm depress the BUZZER OFF switch".

Paragraph 4.7.1.L(1), (2). Add the following paragraphs "L Perform the following procedures on each Muliplexer Td-754/G

(1) Operate the Cable Power switch to OFf
(2) Check to see that the correct plug-in panels are sealed firmly in their proper slots.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:54Z
Check the source to verify that this is the current version before use.

Paragraph 4.19 - Delete - paragraph 4.19 in its entirety and substitute the following paragraph and table:

4.19 Packaging inspection. - Packaging inspection requirements specified herein are classified as follows:

a. First Article Inspection of Packaging.

b. Quality Conformance Inspection of Packaging.

4.19.1 First Article Inspection Packaging. Unless otherwise specified in the contract, First Article Inspection of Packaging shall be in accordance with the Unit Pack Design Validation Requirements of MIL-P-116.

4.19.2 Quality Conformance Inspection of Packaging.

4.19.2.1 Materials inspection. - All materials to be used in packaging shall be inspected in accordance with the applicable material specification.

4.19.2.2 Preservation inspection. - Inspection of preservation and interior markings shall be in accordance with group A and B Quality Conformance Inspection Requirements of MIL-P-116. Lot formation and sampling procedures shall be as specified therein.

4.19.2.3 Packing inspection. - Inspection of packing and the marking for shipment and storage shall consist of the examinations specified in Table VII, "PACKING INSPECTION PROVISIONS". Lot formation shall consist of all packs made of the same materials during an identifiable period and submitted at one time for acceptance. Sampling procedures shall be in accordance with MIL-STD-105, using a single sampling plan and Acceptable Quality level of 4.0 percent defective.



Source: https://assist.dla.mil -- Downloaded: 2026l0-22T19:54Z
Check the source to verify that this is the currentversion before use.

TABLE VII PACKING INSPECTION PROVISIONS.

| No. | CHARACTERISTIC | METHOD OF INSPECTION |
|---|---|---|
| 101 | Intermediate container not as specifed | Visual |
| 102 | Improper closure of intermediate container | Visual |
| 103 | Shipping containers not in accordance with specification | Visual |
| 104 | Excessive cube | Visual |
| 105 | Improper blocking and bracing | Visual |
| 106 | Closure not in accordance with specification | Visual |
| 107 | Weight and size exceed container limitations | Weight & measure |
| 108 | Strapping not in accordance with specification, incorrectly applied, omitted | Visual |
| 109 | Marking omitted, incorrect, or illegible | Visual |

Paragraph 4.20 - Delete- "(Preparation for delivery)" and substitute "(packaging)."



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:54Z
Check the source to verify that this is the currentversion before use.

PAGE 56

Paragraph 5.1 - Delete - MIL-P-55507 "and substitute "MIL-S-55507.

Paragraph 6.2 Add the following paragraphs: "6.2.e Level A or B preservation and packing (see section 5)."

"6.2f. When first article inspection rough handling tests are not required.

"6.2g. When first article packaging inspection reports require acquisition activity approval prior to production unit packing".

PAGE 57

Paragraph 6.8, 6.9 Add the following paragraphs "6.8 Level B Preservation. When Level B Preservation is specified, this level of protection will only be used under known favorable conditions during transportation, storage and handling.

6.9 Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or preparing activity for recommended disposability methods."

Preparing Activity - Army - CR



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:54Z
Check the source to verify that this is the current version before use.