MILITARY SPECIFICATION

TRAILER, LIFT, AIRCRAFT ENGINE ETU-92/E;
TF-39 TURBOFAN ENGINE

This amendment forms a part of Military Specification
MIL-T-83317 (USAF) dated 23 April 1971.

Pages 1 and 2, paragraph 2.1:

(1) Military specifications: Delete "MIL-R-83232" and substitute:

"MIL-R-83232/2 Reel, Static Discharge, Grounding RMU-25/E, 50 Foot With Connector"

(2) Military standards: Delete "MS27610".

Page 13, paragraph 3.8, seventh sentence: Delete and substitute "The lift shall be designed to raise and lower a 12,000-pound load and shall be capable of lifting a proof load of 24,000 pounds. The lift shall be capable of withstanding a side load of 1,200 pounds at the load centerline while the proof load is held at the extended position."

Page 15: Add:

"3.9.1.2 Manual operation. A backup capability shall be provided to manually operate all positioning mechanism adjustments, loaded or unloaded, in the event of power system failure."

Page 17, paragraph 3.16: Delete and substitute:

"3.16 Static discharge grounding reel. An RMU-25/E reel conforming to MIL-R-83232/2 shall be mounted on the forward or rear chassis structure. The reel shall be bolted to the trailer, and the resistance between the reel and the chassis shall not exceed 0.5 ohm."

FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

Page 18: Add:

"3.20.2.3 Load restriction. The trailer shall be marked as follows:

THIS TRAILER IS NOT TO BE TRANSPORTED
BY AIR, RAIL, OR FLATBED TRUCK-TRAILER
WHEN LOADED WITH THE TF-39 ENGINE."

Custodian:
Air Force - 11

Reviewer:
Air Force - 82

Preparing activity:
Air Force - 11

Project No. 1730-F146

☆U.S. GOVERNMENT PRINTING OFFICE:1972-714-166/6932

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.