

FED. SUP CLASS
5305





Thread
Per Handbook H28 Screw Thread Standards for Federal Services 1957

THREAD	D DIA MAX	F		H DIA		SELF-LOCKING DESIGN DATA P(d)	T HEX DEPTH
		MAX	MIN	MAX	MIN	50° MAX.	MIN
#4-40NC-3A	.112	.0510	.0500	.061	.051	.062	.040
#6-32NC-3A	.138	.0635	.0625	.074	.064	.076	.050
#8-32NC-3A	.164	.0791	.0781	.087	.076	.085	.062
#10-32NF-3A	.190	.0947	.0937	.102	.088	.093	.075
1/4-28UNF-3A	.250	.1270	.1250	.132	.118	.116	.100
5/16-24UNF-3A	.3125	.1582	.1562	.172	.156	.136	.125
3/8-24UNF-3A	.375	.1895	.1875	.212	.194	.151	.150
1/2-20UNF-3A	.500	.2520	.2500	.291	.270	.188	.200

L LENGTH	TOLERANCE	DASH NUMBERS (a)							
		#4-40	#6-32	#8-32	#10-32	1/4-28	5/16-24	3/8-24	1/2-20
1/8	±.010	1	2	3	4				
3/16		5	6	7	8	9			
1/4		10	11	12	13	14	15		
5/16		16	17	18	19	20	21		
3/8		22	23	24	25	26	27	91	92
7/16		89	90	30	31	32			
1/2		33	34	35	36	37	38	39	40
9/16		41	42	43	44	45			
5/8		46	47	48	49	50	51	52	53
3/4	±.015		54	55	56	57	58	59	60
7/8			61	62		63	64	65	66
1				67	68	69	70	71	72
1-1/4						73	74	75	76
1-1/2						77	78	79	80
1-3/4	±.020	For lengths above heavy line see note (g).					81	82	83
2							84	85	86
2-1/2	±.031								87
3									88

This Standard takes precedence over documents referenced herein.
Reference documents shall be of the issue in effect on the date of invitation for bid.

User: Army - GL

Reviewers: Army - EL, MI, MO, MU, WC
USAF - 69

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 4 Jun 63 REVISED ▲ 22 Dec 64

P.A. Navy - WP Other Cust Army - WC USAF - 69	TITLE SETSCREW, HEXAGON SOCKET, FLAT POINT, 250°F, SELF LOCKING ELEMENT, CORROSION RESISTING STEEL, PASSIVATED	MILITARY STANDARD MS18066	
PROCUREMENT SPECIFICATION FF-S-200 & MIL-F-18240	SUPERSEDES:	SHEET 1 OF 2	

DD FORM 1 SEP 57 672-1 coordination PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:14Z
Check the source to verify that this is the current version before use.

(a) Unassigned dash numbers shall not be used.

(b) Socket end of screw shall be flat and chamfered. The chamfer shall extend to the minor diameter of the thread and the edge between flat and chamfer shall be slightly rounded

(c) Location of effective locking area "X" shall be in accordance with MS 15981 except as noted herein.

(d) $P_{Max.}$ = Maximum point plus minimum of 1 thread pitch. For ease in starting, locking element shall not be effective within this area.

(e) Maximum major thread diameter plus .010 = Maximum ring gage diameter that locking region of part must pass thru freely or with finger pressure.

(f) See MS251029, MS51031 and MS51032 for set screws without self-locking feature.

(g) As MIL-F-18240 doesn't establish torque requirements for items above the heavy line, only a positive indication of torque is required.

MATERIAL: Steel corrosion resisting; Federal Standard 66, numbers 302, 303, 304, 316 or equal to or interchangeable with 16:18 Chromium Nickel-Alloy Steel.

LOCKING ELEMENT: In accordance with specification MIL-F-18240.

DESIGN AND USAGE LIMITATIONS: See MS 15981.

TREATMENT: Passivated (See Procurement Specification).

MAGNETIC PERMEABILITY: These screws have a magnetic permeability of 2.0 maximum (air = 1.0) for a field of H = 200 orsteds using a magnetic indicator per MIL-I 17214.

EXAMPLE OF PART NUMBER: MS-18066 -57 = 1/4-28UNF-3A x 3/4 long corrosion resisting steel flat point self-locking set screw.

APPROVED 4 Jun 63 REVISED (A) 22 Dec 64

User: Army - GL

Reviewers: Army - EL, MI, MO, MU, WC
USAF - 69

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. Navy - WP Other Cust Army - WC USAF - 69	TITLE SETSCREW, HEXAGON SOCKET, FLAT POINT 250°F, SELF LOCKING ELEMENT, CORROSION RESISTING STEEL, PASSIVATED	MILITARY STANDARD MS18066
PROCUREMENT SPECIFICATION FF-S-200 & MIL-F-18240	SUPERSEDES:	SHEET 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:14Z
Check the source to verify that this is the current version before use.