MIL-C-50062D
30 September 1964
SUPERSEDING
MIL-C-50062C(MU)
4 June 1964

MILITARY SPECIFICATION

CARRIER, FIELD PROTECTIVE MASK, M15

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of protective mask carrier.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids, or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

CCC-C-419 - Cloth, Cotton, Duck, Unbleached, Plied-Yarns, (Army and Numbered).

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:15Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

EDGEWOOD ARSENAL

DL5-4-1039 - Carrier, Field Protective Mask, M15.

(All drawings referenced in this specification are listed on Drawing DL5-4-1039.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM Standards

D638 - Tensile Properties of Plastics.

D648 - Deflection Temperature of Plastics Under Load.

D747 - Stiffness of Plastics by Means of a Cantilever Beam.

D792 - Specific Gravity and Density of Plastics.

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia 3, Pennsylvania.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Materials and components. All materials and components shall conform to the specifications and drawings forming a part of this specification.

3.1.1 Reinforcing strip (Dwg A5-4-1024). When rubber-coated duck is used for the reinforcing strip, it shall consist of duck, weighing 8.25 ounces per square yard and conforming to type III of CCC-C-419, which has been evenly coated on both sides with a cured natural or synthetic rubber compound.

3.1.2 Stiffeners. The polypropylene material used for stiffeners shall conform to the requirements in table I when tested as specified therein.

Table I. Physical properties

Property	Requirement (minimum)	Test method
Specific gravity	0.903	ASTM D792
Tensile strength, pounds per square inch	4500	ASTM D638
Stiffness modulus, pounds per square inch	190,000	ASTM D747
Distortion (deflection temperature), degrees F	220	ASTM D648

3.2 Manufacture and assembly. The components and subassemblies of the carrier shall be manufactured and assembled as specified on Drawing E5-4-1039.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

3.2.1 Stitching. All rows of stitching shall be straight or regular lines, free from loose stitches or thread loops. When stitching is not of continuous thread, each thread end or break shall be backstitched for not less than 2 inches. All seams and hems shall be backstitched at the ends.

3.2.2 Fastener attachment. The male and female components of all fasteners shall be securely attached to the carrier. The pressure used in attaching the fastener components shall be applied in such a manner that the fabric will not be weakened or injured. The attached fasteners shall function smoothly and efficiently.

3.3 Marking. The finished carrier shall be legibly and indelibly marked as specified on Drawing D5-4-1036.

3.4 Workmanship. The carrier shall be free from damage, such as tears, cuts and holes. It shall be free from foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.2 Special provisions.

4.2.1 Alternative inspection. The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

4.2.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2.3 Inspection substation. If the supplier elects to establish substations for the purpose of conducting inspection for certain listed defects, the Acceptable Quality Levels (AQL's) for each inspection substation shall be equal to the AQL which is the next numerically lower value than the AQL specified for the total listed defects. The requirements of MIL-STD-105 are applicable to each substation and to the end item.

4.3 Preproduction sample inspection.

4.3.1 Preproduction sample. Prior to the start of regular production, a preproduction sample, the number specified in the contract or purchase order, shall be produced using the same materials, methods, and equipment as will be used in regular production.

4.3.2 Examination and tests. The preproduction sample shall be examined and tested for all the requirements of this specification.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with all the requirements of this specification to be acceptable.

4.4 Regular production.

4.4.1 Lotting. A lot shall consist of the carriers produced by one manufacturer, at one plant, from the same type of material, under essentially the same manufacturing conditions, and offered for acceptance at one time.

4.4.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:15Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection provisions.

4.4.3.1 For examination. The sample carriers shall be examined in accordance with the classification of defects and with MIL-STD-105.

4.4.3.2 Classification of defects.

4.4.3.2.1 Carrier, field protective mask, M15 - assembly (Dwg E5-4-1039).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing or incorrectly assembled
102	Inability of carrier to properly contain all specified contents
103	Hardware nonfunctioning
104	Marking incorrect
105	Workmanship (see 3.4)
106	Stiffeners not free from cracks or sharp corners
107	Stitching run off or stitches broken more than 1/2 inch
108	Seams or hems not backstitched at the ends
Minor:	AQL 2.5 percent defective
201	Stitching margin incorrect
202	Stitching tension loose causing exposed loops
203	Stitching tension tight causing pleating
204	Stitching run off or broken more than 1/4 inch but less than 1/2 inch
205	Stitches per inch incorrect by ± 2 or more
206	Tie-in stitches incorrect
207	Hardware coating missing
208	Marking missing or illegible

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:15Z
Check the source to verify that this is the currentversion before use.

5. PREPARATION FOR DELIVERY (For repair parts packaging, see 6.3.)

5.1 Packaging, level C. The carrier shall be packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

5.2 Packing, level C. Carriers, with the same mask-size marking, packaged as specified in 5.1, shall be packed together to insure carrier acceptance and safe delivery at first destination. Containers shall comply with Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. This carrier is intended for use with the ABC-M17 Field Protective Mask.

6.2 Ordering data. Procurement documents should specify:

(a) Title, number, and date of this specification.

(b) Mask-size marking to be placed on carrier and also on container.

6.3 Repair parts packaging. When repair parts packaging and packing is required for items authorized for stocking as repair parts, the repair parts packaging data sheets covering the carrier should be used. (Copies of repair parts packaging data sheets may be obtained from the Director of Engineering and Industrial Services, ATTN: Chief, Design Branch, US Army Edgewood Arsenal, Edgewood Arsenal, Maryland - 21010.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

6.4 International interest. Certain provisions of this specification are the subject of ABC international standardization agreement. When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned.

Custodian:
Army - MU
Navy - SH
Air Force - 84

International interest (see 6.4)

Review activities:
Army - MD
Navy - SH

User activities:
Navy - MC
Air Force - 84

Preparing activity:
Army - MU (EA)

Project No. 4240-0057

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:15Z
Check the source to verify that this is the currentversion before use.