MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), RECEPTACLE, (WIDE FLANGE MOUNT, BAYONET COUPLING, SOLDER PIN CONTACT), (SERIES I, CLASS H)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Ⓑ The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-C-26482.

Ⓑ INACTIVE. SUPERSEDED BY MS3442 OF MIL-C-26482.




FIGURE 1

Ⓑ denotes changes

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.

TABLE I

CONNECTOR DIMENSIONS

SHELL SIZE	A	B	C	D	E	F	G	H	J	N	P	R
10	1.134	.934	.991 .565	.488	.462	.573 .567	.078 .046	.801	.598 .578	.125 .105	.545 .534	.680 .664
12	1.260	.936	.741 .745	.613	.588	.782 .776	.078 .046	.801	.598 .578	.125 .105	.694 .683	.859 .843
14	1.384	1.063	.870 .870	.737	.641	.907 .901	.078 .046	.801	.598 .578	.125 .105	.819 .808	.984 .968
16	1.446	1.125	1.001 .995	.862 .857	.797	1.032 1.026	.078 .046	.801	.598 .578	.125 .105	.944 .933	1.108 1.092
18	1.526	1.203	1.126 1.120	.987 .981	.865	1.157 1.151	.078 .046	.801	.598 .578	.125 .105	1.044 1.033	1.233 1.217
20	1.682	1.297	1.251 1.245	1.092 1.086	.940	1.251 1.245	.110 .078	.803	.660 .640	.093 .073	1.169 1.158	1.358 1.342
22	1.700	1.375	1.376 1.370	1.217 1.211	1.105	1.376 1.370	.110 .078	.895	.660 .640	.125 .105	1.294 1.283	1.483 1.467
24	1.884	1.500	1.501 1.495	1.342 1.336	1.229	1.501 1.495	.110 .078	.895	.660 .640	.125 .105	1.419 1.408	1.610 1.594


SIZE	S	T	U	V	PANEL CUTOUT DIA.
10	.120	.178 .118	.248 .188	.515	.680
12	.120	.178 .118	.248 .188	.630	.789
14	.120	.178 .118	.248 .188	.755	.914
16	.120	.178 .118	.248 .188	.880	1.039
18	.120	.178 .118	.248 .188	.980	1.164
20	.120	.178 .118	.248 .188	1.105	1.258
22	.120	.146 .086	.216 .156	1.230	1.383
24	.147	.146 .086	.216 .156	1.385	1.508

TABLE II

CONTACT DIMENSIONS

CONT SIZE	X	Y	Z	AA	BB
20	.041 .039	.088 .061	.048 .042	.188 .109	.110 .068
16	.0635 .0615	.116 .096	.075 .069	.251 .172	.141 .109
12	.095 .093	.150 .130	.122 .112	.251 .172	.141 .109

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.



(AS VIEWED FROM ENGAGING END)
INSERT POSITION

▽ INDICATES ℄ OF SHELL

FIGURE 2




FIGURE 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.

ENGAGING END OF CONTACTS




FIGURE 4

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.

TABLE III. Insert arrangements requiring reduced diameters for raised seal barriers on outer row of contact cavities as indicated.

Shell	Insert arrangements	Contact cavities
12	10	C and G
14	12	A,B,C,D,E,F,G, and H
14	18	A,C,E,G,J, and L
14	19	B,D,F,H,K, and M
16	26	A,B,C,D,E,F,G,H,J, K,L,M,N,P, and R
18	32	A,B,C,D,E,F,G,H,J, K,L,M,N,P,R,S, and T
22	41	A,B,C,D,E,F,G,H,J, K,L,M,N,P,R,S,T,U, V,W,X, and Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.

NOTES: (NOTES 1 THRU 6 APPLICABLE TO CONTACTS ONLY).

1. CONTACT FINISH: GOLD PLATE .000050 INCH MIN. IN ACCORDANCE WITH MIL-G-45204. A SUITABLE UNDERPLATING SHALL BE USED. FINISH IS APPLIED AFTER SEALING.
2. DIMENSIONS IN INCHES. DIMENSIONS APPLY AFTER PLATING.
3. 63√ALL OVER PER ANSI B46.1-62 UNLESS OTHERWISE SPECIFIED
4. REMOVE ALL BURRS AND SHARP EDGES .003 TO .005 R.
5. DIAMETERS TO BE CONCENTRIC WITHIN .004 TIR.
6. DIAMETERS IN THE SAME CROSS-SECTIONAL PLANE TO BE CONCENTRIC WITH EACH OTHER WITHIN .003 TIR.
7. FOR ALTERNATE POLARIZING POSITIONS, THE CONNECTOR INSERT IS ROTATED IN RESPECT TO THE SHELL.
8. IN "NORMAL POSITION" (POSITION "N") THE INSERT VERTICAL CENTERLINE COINCIDES WITH THE CENTERLINE OF THE MASTER KEYWAY OF THE SHELL.
9. IN "ALTERNATE POSITIONS" (POSITIONS "W", "X", "Y" AND "Z") THE PIN INSERT IS ROTATED ∝ DEGREES CLOCKWISE RELATIVE TO ℄ OF THE MASTER KEYWAY OF SHELL. SEE REQUIREMENT 4.
10. POLARIZING STRIPE SHALL BE COLOR CODED BLUE.
11. THREE (3) PROJECTIONS LOCATED WITHIN .005 R (TP) AT (MMC) RELATIVE TO "C" DIA (MMC) AND SHELL FRONT, AND WITHIN .010 EITHER SIDE OF (TP) AT (MMC) RELATIVE TO MASTER POLARIZING KEYWAY.
12. FOUR KEYWAYS (MMC) AND INSERT SHALL BE LOCATED WITHIN .0035 EITHER SIDE OF (TP) RELATIVE TO MASTER KEYWAY (MMC) AND SHELL I.D. (MMC).
13. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED TOLERANCE SHALL BE .XX ±.010 AND .XXX ± .005; ANGULAR TOLERANCE X° ±1 -0' AND 'X°X' ±30'.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.

TABLE IV WIRE DATA

CONTACT SIZE	WIRE SIZE AWG	INSULATION O.D. IN INCHES / WIRE SPECIFICATION 3/			
		MIL-W-22759/4	MIL-W-16878/4	MIL-W-81381/-	
				LIGHT WT -/1	MEDIUM WT -/3
20	24	...	.040/.048 1/	.037/.043	.047/.054
	22	.071/.077	.046/.054	.043/.050	.053/.060
	20	.079/.085 2/	.054/.062	.051/.058	.061/.068
16	20	.079/.085	.054/.062 1/	.051/.058	.061/.068
	18	.092/.098	.064/.074	.060/.067	.071/.079
	16	.099/.107 2/	.073/.087	.066/.074	.079/.087
12	14	.112/.120 1/	.087/.101	.080/.089	.091/.099
	12	.129/.137 2/	.106/.120	.098/.108	.107/.117

1/ WIRE TO BE USED FOR CONNECTOR QUALIFICATION.

2/ WIRE TO BE USED FOR CONTACT QUALIFICATION.

3/ LISTED WIRE SPECIFICATIONS ARE NOT ALL INCLUSIVE. WIRE WITH SMOOTH EXTERIOR SURFACE, WHICH FALLS WITHIN THE SPECIFIED RANGE AND MEETS THE DESIGNERS CRITERIA, MAY BE USED IN APPLICATION.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figures.


This connector mates with MIL-C-83723/13(USAF).

(B) For insert arrangements see MIL-STD-1669.

Shell material: Cold rolled steel per QQ-S-637.

(B) Connector identification marking shall be in accordance with MIL-C-26482. Example: MS3442L----, M83723/10R----.

Part number example:



Custodian:
Air Force - 85

Review activities:
Air Force - 11, 17, 70, 71, 80, 82, 84
DSA - ES

Preparing activity:
Air Force - 85

(Project 5935-F964-10)

★ U.S. GOVERNMENT PRINTING OFFICE: 1975-683-764/1381

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:17Z
Check the source to verify that this is the current version before use.