MIL-P- 50841 (AR)
7 July 1977
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

PACKAGES 1, 2, AND 3 OF 3 FOR ADAPTION KIT, ATOMIC WARHEAD TO GUIDED MISSILE: XM248

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, packing, and marking of Packages 1, 2 and 3 of 3 for the Adaption Kit, Atomic Warhead to Guided Missile: XM248.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for propsoals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A- 45899	- Adaption Kit, Sub-Assembly.
MIL-A- 45897	- Arm Safe Device: XM134E1.
MIL-C- 48014	- Cable Assemblies, Special Purpose Electrical: 5W6E1 and 5W7.
MIL-C- 45895	- Cable Assembly, Special Purpose Electrical Branched: 5W5.
MIL-S- 48893	- Shipping and Storage Container: XM543E1.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	- Lot Numbering of Ammunition.

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 1135

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:40Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

9233270 - Adaption Kit, Atomic Warhead to Guided Missile: XM248.
9257234 - Shipping and Storage Container, XM543E1, Packing and Marking, Package 1 of 3, for Adaption Kit, Atomic Warhead to Guided Missile.
9275835 - Packing and Marking for Box, Fiberboard, Packing, Outer Pack 2 of 3 for Adaption Kit, Atomic Warhead to Guided Missile.
9275836 - Packing and Marking for Box, Fiberboard, Packing, Pack 3 of 3 for Adaption Kit, Atomic Warhead to Guided Missile.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The packing and marking of the adaption kit shall comply with all requirements specified on the drawing (dwg) 9233270, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Major components. For major components to be used in the adaption kit, objective evidence (see 6.2) indicating that the following components conform to their respective specifications and or drawings shall be made available to the Government representative:

a. Adaption Kit, Sub-Assembly - MIL-A-45899.
b. Shipping and Storage Container: XM5431, MIL-S-48893.
c. Arm Safe Device: XM134E1, MIL-A-45897.
d. Cable Assemblies, Special Purpose Electrical: 5W6E1 and 5W7, MIL-C-48014.
e. Cable Assembly, Special Purpose Electrical Branched: 5W5, MIL-C-45895.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Lot formation.

4.2.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.2.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.2.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor defects/characteristics table (see Table I and Table II), and inspected for all defects/characteristics in the applicable classification. Any defects/characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of defects/characteristics in each classification need not be followed as long as all defects/characteristics inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

Table I
Major Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.2.2.1 Classification of defects/characteristics (see 3.2). Critical, major and minor defects/characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Screw, cap, socket head (see dwg 8888397).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Objective evidence that item complies with drawing	Visual
	102. Length of thread	Gage
	103. Thread damaged	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.4)	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:40Z
Check the source to verify that this is the current version before use.

4.2.2.1.2 Washer flat, special purpose (see dwg 9272819).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Objective evidence that part complies with drawing	Visual
	102. Outside diameter incorrect	Gage
	103. Inside diameter incorrect	Gage
Minor:		
	201. Evidence of poor workmanship (see 3.4)	Visual

4.2.2.1.3 Bolt, twelve point, external wrenching (MS 21250-04018), washer countersunk (MS 20002-C4), washer, flat (MS 9321-09), screw, self locking, pan head, full thread (NAS 1190-3P10L) screw, cap, socket head (MS 16998-26) and washer, flat, for wood (AN 970-3), prior to packing.

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Objective evidence that components comply with applicable Government standards	Visual
Minor:	None defined.	

4.2.2.1.4 Packing of screw, cap, socket head (see dwg 8888397), washer, flat, special purpose (see dwg 9272819), bolt, twelve point, external wrenching (MS 21250-0418), washer countersunk (MS 20002-C4), screw, cap, socket head (MS 16998-26), washer, flat (MS 9321-09), screw, self-locking, pan head, full thread (NAS 1190-3P10L) and washer flat, for wood (AN 970-3) (see dwgs 9257234, 9275835 and 9275836 as applicable).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Improper amount of hardware in envelopes (see dwg 9233270)	Visual
	102. Improper number (4) of envelopes in barrier bag (prior to sealing barrier bag)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
	103. Barrier bag improperly sealed	Visual
	104. Marking on envelopes missing, illegible, or does not correspond to hardware in envelope	Visual
	105. Marking on barrier bag missing, improper or illegible	Visual

Minor: None defined.

4.2.2.1.5 Packing of package 1 of 3 (see dwg 9257234).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Talc missing from rubber surfaces of frame assembly and retaining plate	Visual
	102. Adaption Kit Sub-Assembly improperly seated in frame assembly	Visual
	103. Desiccant missing (4 bags)	Visual
	104. Barrier bags with mounting hardware not secured to retaining plate with tape	Visual
	105. Nuts holding retaining plate not torqued sufficiently	Gage
	106. Ground cable not secured to Adaption Kit Sub-Assembly	Visual
	107. Cables, improperly placed and secured in container	Visual
	108. Swing latches secured improperly	Visual/Manual
	109. Metallic seal missing or improperly crimped	Visual
	110. Marking missing, illegible or improper	Visual
	111. Evidence of poor workmanship (see 3.4)	Visual
	112. Packing or cushioning material missing	Visual

Minor: None defined.

4.2.2.1.6 Packages 2 of 3 and 3 of 3 (see dwg 9275835 and 9275836 respectively).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

Major:

101. Packages improperly sealed.....Visual
102. Marking improper, missing or illegible.....Visual
103. Barrier bags with mounting hardware missing or not secured as specified on drawings.....Visual

Minor: None defined.

4.2.3 Acceptance inspection equipment.

4.2.3.1 Major and Minor defects/characteristics and tests. Inspection and testing shall be performed with the acceptance test equipment, operating instructions and calibration instructions prepared by the contractor. The contractor shall obtain approval of such designs, operating instructions and special calibration instructions as specified in 6.3 prior to use on the contract.

4.3 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging of Packages 1, 2, and 3 of 3 shall be in accordance with dwg 9257234, 9275835 or 9275836 respectively (see 6.1).

5.2 Packing.

5.2.1 Adaption kit. Components Packages 1, 2 and 3 of 3 shall be packed in accordance with dwg 9257234, 9275835 or 9275836 respectively.

5.3 Marking. Marking shall be in accordance with dwg 9257234, 9275835 or 9275836 as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:40Z
Check the source to verify that this is the current version before use.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2227 dated 3 December 1973, SCN No. 1 dated 23 September 1974 and SCN No. 2 dated 6 February 1975.

Custodian:
Army - (AR)

Preparing activity:
Army - (AR)

Project No. 1135-A226

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.