MIL-S-82605 (OS)
9 March 1972
SUPERSEDING
OS 1257
9 December 1941

MILITARY SPECIFICATION

# STRAP ASSEMBLY, CHIN (FOR STEEL HELMET MARK 2)

*This specification has been approved by the Naval Ordnance Systems Command, Department of the Navy.*

## 1. SCOPE

1.1 This specification covers the chin strap assembly designed for use with the Steel Helmet Mk 2.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

| | |
|---|---|
| V-T-291 | Thread, Linen |
| V-T-295 | Thread, Nylon |
| QQ-N-281 | Nickel-Copper-Alloy (Monel and R-Monel) Bars, Plates, Rods, Sheets, Strips, Wire, Forgings, and Structural and Special Shaped Sections) |
| UU-P-268 | Paper, Kraft, Untreated, Wrapping |
| PPP-B-636 | Box, Fiberboard |

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

Military

| | |
|---|---|
| MIL-S-7720 | Steel, Corrosion Resistant (18-8) Bars, Wire, and Forging Stock (Aircraft Quality) |
| MIL-L-40074 | Leather, Calfskin, For Headbands |

STANDARDS

Federal

| | |
|---|---|
| FED-STD-311 | Leather, Methods of Sampling and Testing |
| FED-STD-751 | Stitch, Seam and Stitching |

Military

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | Marking for Shipment and Storage |

DRAWINGS

Naval Ordnance Systems Command (Code Ident 10001)

| | |
|---|---|
| 300969 | Steel Helmet Mk 2 (For use with Telephone Headsets) |

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Attn: Tariff Order Section, 1616 P Street, N. W., Washington, D. C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Ill. 60606.)

## 3. REQUIREMENTS

3.1 Guide sample. Samples, when furnished, are solely for guidance and information to the supplier (see 6.2). Variations from the specification may appear in the sample, in which case, the specification shall govern.

3.2 First article. When specified, (see 6.2) the supplier shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

3.3 Materials.

3.3.1 Leather. The chin straps, linings, slides, and slings shall be of a high grade vegetable tanned calfskin headband leather conforming to MIL-L-40074. The color shall be a uniform chocolate brown and shall show no signs of crocking or color transfer when rubbed with a dry white cloth. Defects that affect serviceability or comfort, such as scars, cuts, and holes, are prohibited, and the use of sewn, mended, or otherwise repaired leather is prohibited. Grain side shall have a smooth finish.

3.3.1.1 Thickness. The chin straps, linings, and slides shall be 3 to 4 ounces in thickness. (Note: 1 ounce equals 1/64 inch.)

3.3.1.2 Tolerances. Unless otherwise specified on the drawings, the tolerances shall be as follows:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

Width, ±1/32 inch
Length, +1/8 inch, -0

3.3.2 Links. The links shall be of nickel-copper alloy wire conforming to QQ-N-281, class B, form 2, and of the size and shape specified on the drawing. The diameter of the wire shall be 0.057 ± 0.003 inch.

3.3.3 Buckles. The buckles shall be of corrosion resistant steel conforming to MIL-S-7720, composition 316, condition G. Buckles shall be the friction lock type and of a size to suit the chin strap. The design shall be such that the chin strap may be shortened by a gentle pull on the loop of the strap passing through the buckle.

3.3.4 Thread. All stitching shall be done with linen thread in accordance with type A, class 2, of V-T-291, natural, with S twist. Nylon thread conforming to type I, class 1, size E, 3 ply, of V-T-295, may be substituted for linen. Color shall be compatible with leather.

3.4 Seams, stitches, and stitching. All seams, stitches, and stitching shall be in accordance with FED-STD-751. Stitch type shall be 301, having no less than nine nor more than eleven stitches per inch. Thread breaks in stitch type 301 stitching shall be stitched back of the break not less than one-half inch. Ends of all seams and stitchings when not caught in other seams or stitchings shall be back stitched not less than three-eighths inch.

3.5 Patterns. Standard patterns shall be furnished by the Government. The standard patterns shall not be altered in any way and are to be used as a guide for making the supplier's working patterns or dies. The working pattern or dies shall be identical to the standard patterns.

3.6 Construction. The chin strap assembly shall consist of a chin strap, chin strap lining, buckles, slides, slings, and links. The assembly shall be manufactured and assembled in accordance with NAVORD Drawing 300969.

3.6.1 Chin strap lining. The lining shall be cemented and/or stitched to the chin strap, and, when secured, shall be a smooth, close fit.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

3.6.2 Slings. The contact surfaces between the slides and slings shall be smooth and, when assembled, the slide shall move freely along its sling.

3.7 Workmanship. Workmanship shall be that required by the best commercial practices governing quantity production of similar material, maintaining the dimensions, tolerances, and quality specified herein and on the applicable drawings and specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 First article inspection. When required, the sample submitted in accordance with 3.2 shall be inspected as specified in 4.3.3 for compliance with design, construction, workmanship, and dimensional requirements.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Inspection of components and materials. In accordance with 4.1 above, components and materials shall be tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 Inprocess inspection. Inspection shall be made during manufacture of the chin strap assembly to ascertain that cutting and construction details which cannot be examined in the finished product are in



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance any material or service for which inprocess inspection has indicated nonconformance.

4.3.3 Examination of the end item. The defects found during examination shall be classified in accordance with the list shown in 4.3.3.1 and 4.3.3.2. The applicable inspection levels and acceptance quality levels (AQL's) expressed in defects per hundred units shall be as follows:

| Examination | Inspection level | AQL's Major | AQL's Total |
|---|---|---|---|
| Visual characteristics (4.3.3.1) | II | 2.5 | 6.5 |
| Dimensional characteristics (4.3.3.2) | S-3 | - | 4.0 (one class) |

4.3.3.1 Visual examination. The chin straps shall be visually examine for defects in color, design, construction, material, and workmanship as listed below:

| Examine | Defect | Classification Major | Classification Minor |
|---|---|---|---|
| Design | Not as specified, that is, does not conform to configuration shown on drawing | X | |
| Material (leather) | | | |
| Color | Color not as specified | | X |
| Finish | Grain side does not have a smooth finish | X | |
| | Finish applied to grain surface | X | |
| Quality of leather | Any hole, tear, cut or rip | X | |
| | Not full grain | X | |
| | Not calf skin | X | |


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

| | | | |
|---|---|---|---|
| | Any grain damage or imperfection; deep open scratch; deep wrinkles; any scar or abraded area; brittle bony area or thin spot: | | |
| | Seriously affecting serviceability | X | |
| | Affecting serviceability but not seriously | | X |
| | Loose or spongy leather | X | |
| | Flanky leather: | | |
| | Seriously affecting serviceability | X | |
| | Affecting serviceability but not seriously | | X |
| | Flesh side of leather not buffed smooth or contains loose flesh in excess of 1 square inch in total area | | X |
| Hardware | Not specified type | X | |
| Buckles and Links | Missing, broken, or malformed; finish not as specified; corroded area, burr, or sharp edge | X | |
| Seams and stitching | Any open seam | X | |
| | NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped stitches or runoffs occur. | | |
| | Wrong stitch type | X | |
| | Loose stitch tension resulting in a loose top or bobbin stitch | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

| | | | |
|---|---|---|---|
| | Tight stitch tension resulting in cutting of leather | X | |
| | Ends of stitching not back-stitched or backstitched less than 3/8 inch | | X |
| Stitches per inch | One or two stitches less than minimum specified | | X |
| | Three or more stitches less than minimum specified | X | |
| | One or more stitches in excess of maximum specified: | | |
| | Cutting or damaging leather | X | |
| | Not damaging leather | | X |
| Components and assembly | Any component or required operation omitted (unless otherwise classified herein) | X | |
| | Any required row of stitching omitted | X | |
| | Any workmanship damage, that is, scissor or knife cuts; needle chews likely to develop into a hole | X | |
| | Buckle reversed on strap | X | |
| | Buckle fails to function properly | X | |
| | Contact surfaces between the slides and slings not smooth, that is, slide does not move freely along its sling | X | |
| | Not properly trimmed or finished, which will cause discomfort to user | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| Cleanliness | Spots or stains affecting appearance | X |
| | Thread ends not trimmed throughout | X |

4.3.3.2 Dimensional examination. The chinstraps shall be examined for dimensional defects. Any dimension that is not within the established tolerances shall be classified as a major defect. Thickness shall be determined in accordance with method 1011 of FED-STD-311.

4.3.3.3 Examination of preparation for delivery requirements. An examination shall be made to determine that packing and marking requirements of the specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery, except that it need not be sealed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 2.5 defects per hundred units.

| Examine | Defect |
|---|---|
| Marking | Omitted, incorrect, illegible, of improper size, location, sequence, or method of application. |
| Materials | Any component missing. |
| | Any component damaged, affecting serviceability. |
| Workmanship | Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling. |
| | Bulging or distortion of containers. |
| Content | Number of items more or less than required. |

## 5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Twenty-five chinstraps shall be neatly stacked to form a bundle and securely tied with cotton tape or twine.

5.1.2 Level C. Chin strap assemblies shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A or C as specified (see 6.2).

5.2.1 Level A. Five-hundred chinstraps, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V3c or V3s of PPP-B-636. Each fiberboard container shall have the contents completely covered, top and bottom, with a sheet of 20-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each container shall be waterproofed in accordance with the appendix of PPP-B-636. Each shipping container shall be closed and reinforced with flat steel strapping or tape banding in accordance with the appendix of the applicable container specification.

5.2.2 Level C. Chin strap assemblies shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The Strap Assembly, Chin, is intended for use with telephone headsets on Steel Helmet Mark 2.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification
(b) Applicable levels of packaging and packing (see 5.1 and 5.2)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

(c) Special marking, if required (see 5.3).
(d) Whether first article is required (see 3.2).
(e) Availability of guide sample (see 3.1).

6.3 Supersession data. This specification includes the requirements of Ordnance Specification 1257, dated 9 December 1941.

Custodian:
Navy (OS)

Preparing activity:
Navy (OS)
(Project No. 8415-N740)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R357

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, associated with the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this sheet will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-S-82605 (OS), Strap Assembly, Chin (For Steel Helmet Mark 2)

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Naval Ordnance Station
Attn: Standardization Division (FS6)
Indian Head, Maryland 20640

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:17Z
Check the source to verify that this is the current version before use.