MIL-T-55069C
19 April 1988
SUPERSEDING
MIL-T-55069B
29 July 1975

MILITARY SPECIFICATION

TRAINING AID, MODEL BRIDGE: BRIDGE, FLOATING, ALUMINUM, HIGHWAY-TYPE, DECK BALK SUPERSTRUCTURE ON PNEUMATIC FLOATS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 1-to-12 scale model of a floating bridge together with the chests for storage of the components when disassembled. The floating bridge consists of the M4 floating bridge superstructure, mounted on the saddles and pneumatic floats of the Class 60 floating bridge, together with necessary adapters.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6910
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:20Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-P-416	- Plating, Cadmium (Electrodeposited).
RR-C-271	- Chains and Attachments, Welded and Weldless.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-T-3530	- Thread and Twine; Mildew Resistant or Water Repellent Treated.
MIL-C-12044	- Chests, Plywood.

STANDARDS

FEDERAL

FED-STD-H28	- Screw Thread Standards for Federal Services.
FED-STD-595	- Colors.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.

2.1.2 Other Government drawings. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

ME

D7569-3 to -12 inclusive, -14, and -29	- Training Aid, Bridge Model Kit M4 and M4A2 Floating Bridge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

D7891-3 to -7, inclusive, -14, -15, -18, and -24	- Training Aid, Bridge Model Kit, Steel Superstructure - Class 60 Pneumatic Float Floating Bridge.
D7921-1 to -4, inclusive	- Training Aid, Model Bridge M4T6 Floating Bridge.
D7985-1 and -2	- Training Aid, Model Bridge M4T6 Floating Bridge Chests.

(Copies of the specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. Components of the M4 model bridge training aid (hereafter called "training aid") and pneumatic float, class 60, shall be in accordance with the drawing part numbers listed in table I and as specified herein. The training aids shall be furnished disassembled and packed in the chests specified in 3.5. All sets furnished shall be assembled without selective fitting or alteration. The parts and spares furnished for one complete training aid shall be as shown on assembly Drawing D7921-1, and components as shown on Drawing D7921-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. Model bridge training aid components.

Item	Applicable drawing part number
M4 and M4A2 Floating Bridge Components	
Adapter, curb	7569-12-1
Balk, deck, normal	7569-8-1
Balk, deck, short	7569-8-2
Balk, deck, tapered	7569-9-1
Hook, cotter pin, w/washer	7569-29-6 and -29-9
Pin, medium length	7569-14-8
Pin, ramp, horizontal	7569-12-3
Pin, ramp, vertical	7569-12-8
Plate, cover, long	7569-10-2
Plate, cover, short	7569-10-3
Post, handrail	7569-11-1
Ramp, raft	7569-12-2
Rope, handrail	7569-11-7
Trestle assembly, w/hoists	7569-3, 7569-4-1 to -4-8, inclusive; 7569-5-1 to -5-5, inclusive; 7569-7-A, 7569-7-1 to -7-5, inclusive; 7569-7-8 and -7-9
Trestle bracing clamp	7569-6A, 7569-6-2 to -6-5, inclusive; 7569-6-8 and -6-9
Trestle bracing strut (One tapered cotter pin, Part No. 7569-6-10, to be furnished with each strut.)	7569-6-1 and 7569-6-10
Trestle bracing screw point	7569-6-7
Class 60, pneumatic float, floating bridge components bar, connecting	7891-5-3
Floats, half, 12-ton, pneumatic (Quantities shown on Drawings D7891-3 and -4 will form four complete pneumatic half-floats; floats shall be fully assembled by the contractor, including necessary lacing (see lacing diagram Drawing D7891-5).)	7891-3-1, 7891-4-1 to -4-5, inclusive; 7891-5-1 to 7891-5-18, inclusive
Sponge rubber	7891-24-1 and -24-2; 7891-5-4 to -5-8, inclusive; 7891-5-17 and -5-18

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. Model bridge training aid components. (Cont'd)

Item	Applicable drawing part number
Pin, saddle beam	7891-15-7
Pin, safety	7891-15-5
Pump	7891-18-5
Saddle, 24-ton:	
beam, center section w/sliding retainer, sliding retainer rivet, and permanent pin	7891-6-1, 7891-6-4, 7891-14-15, 7891-14-17
beam, end section w/permanent pin	7891-6-2, 7891-6-4
beam, outrigger	7891-6-3
end panels	7891-7-2
interior panels	7891-7-1
Spring clip, panel	7891-15-6
Mounting adapters plate, bearing	7921-4-2
Saddle, 24-ton:	
adapter, normal	7921-3-1
adapter, offset	7921-3-2
Stiffener, balk connecting	7921-4-1

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the training aid. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or deviations of training aids from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnished training aids conforming to this specification.

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.4 Chain. Chain shall conform to RR-C-271, type II, class 7, brass, 0.048-inch-diameter wire.

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:20Z
Check the source to verify that this is the current version before use.

3.5 Chests. Chests shall conform to MIL-C-12044 and to Drawings D7985-1 and -2.

3.6 Straps. Straps shall be fabricated cotton tape 3/8 inch wide having a minimum warp strength of 30 pounds, shall be dyed olive drab No. 7, and shall be mildew-resistant treated as specified in MIL-W-530, type IIa, class 4.

3.7 Twine. Twine shall be cotton having a minimum breaking strength of 30 pounds and shall be mildew-resistant treated as specified in MIL-T-3530, type I, class 1.

3.8 Bolts, nuts, screws, and rivets. Bolts, nuts, screws, and rivets shall be standard commercial items. Screw threads shall conform to FED-STD-H28.

3.9 Identification marking. Each chest shall be identified in accordance with MIL-STD-130. The marking shall be applied to the chests on identification plates conforming to MIL-P-514, type I, style 3, composition C, of type I, grade A, class 1 material. The identification plates shall include the number of the chest and shall be affixed on the outside lid of the chest.

3.10 Treatment and painting. All metal parts of the training aid, except nuts, screws, pins, and threads, shall be treated and painted in accordance with MIL-T-704, type A. The color numbers listed in table II shall match the specified color number of FED-STD-595.

TABLE II. Special colors.

Item (Drawing part No.)	Quantity to be painted in each bridge model	Color No.
7569-4-1	1	36373
7569-8-1	1	35109
7569-8-2	1	35231
7569-9-1	1	34325

3.10.1 Cadmium plating. Cadmium plating shall conform to QQ-P-416, type I, class 1, dull finish.

3.11 Government-furnished property. The following property in the quantities indicated will be furnished by the Government (see 6.4):

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:20Z
Check the source to verify that this is the current version before use.

Item No.	Description	Identification	Quantity for Each Unit
1	Technical manual	TM-267K	2
2	Pliers, long nose, without cutter, 6-inch nominal size	NSN 5120-00-268-3579	1

3.12 Workmanship.

3.12.1 Tolerances. Tolerances and gages for metal fits shall conform to the limitations shown on the drawings. Where not specifically shown, the tolerances shall be such as to permit correct assembly of the training aid.

3.12.2 Castings. All surfaces and projections of castings shall be filled out to the drawing requirements. There shall be no shrinkage defects, cracks, thin sections, cold or poor bonds, internal defects, or any evidence of poor flow characteristics. All gates, vents, and flash shall be removed and castings polished to eliminate projections and sharp edges. Holes shall be in alinement and there shall be no warpage which would affect the use of the part.

3.12.3 Cement. The aprons and flaps on pneumatic floats shall be securely cemented to the float.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission to known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T22:20Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. Inspections shall be classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article training aid shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Test. The first article training aid shall be tested as specified in 4.5.2. Failure of this test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination test shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 1.0 percent defective for major defects and 2.5 percent defective for minor defects.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The training aid shall be examined as specified herein for the following defects:

Major

101. Material not as specified.
102. Members not in accordance with the drawings or not true to dimensions and line containing twists, bends, or open joints.
103. Members not having sharp edges, burrs, or flash removed.
104. Holes out of position or of incorrect size.
105. Castings containing blowholes, porosity, shrinkage defects, cracks, thin sections, or poor bonds.
106. Aprons or flaps on pneumatic floats loose or improperly cemented.
107. Chains, chests, straps, twine, and identification marking not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

Minor

201. Castings not cleaned or having projections and sharp edges.
202. Castings improperly cleaned for painting or having paint blisters, spots, lumps, scratches, runs, or sags.
203. Parts requiring painting not painted.
204. White circle missing on Part No. 7569-11-1 (see table I).
205. Parts requiring cadmium plating not so placed.

4.5.2 Assembly test. The training aid shall be assembled from the components listed in 3.1. Inability to assemble the training aid or nonconformance to 3.1 shall constitute failure of the test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Examination. Each packaged training aid shall be examined for the following defects. Any defects sound shall be corrected prior to shipment.

108. Surfaces of components requiring a contact preservative in accordance with referenced document not coated for level A.
109. Components not placed and secured in the appropriate chest, and chest lid not closed and secured for level A or C.
110. Skids not applied to shipping container for level A or B.
111. Strapping not as specified for levels A and B.
112. Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Components requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall then be placed and secured in the appropriate chest and the chest lid closed and secured.

5.1.2 Level C. The components shall be placed and secured in the appropriate chest and the chest lid closed and secured.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. The chests containing a complete training aid shall be packed together in close-fitting boxes conforming to PPP-B-621, class 2, or PPP-B-601, overseas type, grade B. The boxes shall be modified by the installation of skids

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

in accordance with the applicable box specification. Strapping shall be in accordance with the box specification; strapping shall be flat with finish B.

5.2.2 Level B. Packing shall be as specified in 5.2.1 for level A, except that boxes shall be domestic type or class, as applicable. Strapping shall be finish A.

5.2.3 Level C. The chests containing one complete training aid shall be palletized or shall be consolidated in a single, sturdy container having strength characteristics appropriate for the size and weight of the chests contained. The chest shall be blocked to prevent movement within the container. If palletized, the chests shall be secured to the pallet with flat steel strapping.

5.3 Marking. Marking of all containers shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The training aid bridge model is intended as an instructional aid for the training of troops in the erection of the prototype.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. When a first article is not required for inspection and approval, and the number of units required (see 3.2).
c. Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the items should be an initial production item. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the first article.

6.4 Government-furnished property. The contracting officer should arrange to furnish the property specified in 3.11.

6.5 Subject term (key word).

Deck balk
Floats
M4T6 floating bridge
Model bridge
Pneumatic
Saddle
Training aid
Trestle

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 6910-0011

☆U.S. GOVERNMENT PRINTING OFFICE: 1988 - 505-033/91554

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:20Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Belvoir RD&E Center
ATTN: STRBE-TSE
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-55069C	Training Aid, Model Bridge: Bridge, Floating, Aluminum, Highway-Type, Deck Balk Superstructure on Pneumatic Floats

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.