MILITARY SPECIFICATION SHEET

ELECTRON TUBE, NUMERICAL INDICATOR

TYPE 7009

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Gas filled, cold cathode

See figure 1

Mounting position: See note 1

Weight: 0.2-ounce nominal

ABSOLUTE RATINGS:

Parameter:	Ebb	Ik (individual)	Rp	TA	Barometric pressure, reduced
Unit:	Vdc	mA	Ohms	°C	mmHg
Maximum:	---	2.0	---	+85	---
Minimum:	170	---	---	-65	35
TEST CONDITIONS:	170	---	68,000 ±1%	---	---

GENERAL:

Qualification - Required

Ⓑ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:50Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	SYMBOL	LIMITS		UNIT
					MINIMUM	MAXIMUM	
	Quality conformance inspection, part 1						
3347	Ionization voltage (1) (with illumination)	-	Ambient illumination = 5 to 50 ftC	Ebb	---	170	Vdc
3333	Uniformity of cathode glow	10	Ambient illumination = 5 to 50 ftC	---	---	---	---
1256	Electrode current (cathode)	10	Individual cathodes	Ik	0.7	1.2	mA
	Quality conformance inspection, part 2						
1002	Barometric pressure, reduced	2	eb = 170; Rp = 68,000 ohms; pressure = 35 mmHg	---	---	---	---
1031	Variable-frequency vibration	3,4		---	---	---	---
---	Light output	5,10,11	Light individual cathodes	---	0.15	---	ftC
---	Alinement, digits	6		---	---	±5	Degrees
---	Shock	3,7	250 G; duration = 1.0 ±0.5 ms	---	---	---	---
(B) 1105	Permanence of marking	-		---	---	---	---
	Quality conformance inspection, part 3						
---	Life test (1)	8	Group C; sequential counting, 1 Hz, t = 1,000 hours (min)	---	---	---	---
---	Life-test (1) end points:						
3333	Uniformity of cathode glow	10		---	---	---	---
1256	Electrode current (cathode)	10		Ik	0.5	1.7	mA
---	Light output	-		---	0.1	---	ftC
---	Life test (2)	9	Group C; one numeral cathode glowing steadily; t = 500 hours (min)	---	---	---	---
---	Life-test (2) end points:						
3333	Uniformity of cathode glow	10	Numeral under test	---	---	---	---
1256	Electrode current (cathode)	10	Numeral under test	Ik	0.5	1.7	mA
---	Light output	-	Numeral under test	---	0.1	---	ftC
(B) ---	Cathode	12	Glow discharge (neon)	---	---	---	---

NOTES:

1. The tube socket is mounted with respect to the viewing position so that a line intersecting pins 1 and 7 is vertical with pin 7 on top. This orients the numbers in the correct-viewing position. The numbers are viewed through the top of the tube.
2. The tube shall be tested by using a 60 Hz sine wave, full-wave rectified and unfiltered, having the indicated peak value.
3. No permanent shorts or open circuits shall be permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:50Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

4. On each plane the 10 cathodes shall be sequentially energized at the test conditions.

5. Light output of each numeral is measured with a footcandle (ftC) meter and an eye-corrected Phontronic cell, or equivalent. The entire cell area shall be illuminated and shall be coupled to the tube by a light-tight cylinder so that the face of the cell is 1-1/2 inches (38.10 mm) from the tube base.

6. Centerline of numerals, drawn through the top of the numeral support posts, shall be within the tolerance specified herein in relation to line drawn on the base of the tube through pins 1 and 7.

7. Shock test shall be made on any shock machine capable of producing a half-sine wave shock waveform of the specified duration and amplitude. No voltages shall be applied during this test. Each tube shall be subjected to a total of 20 shocks; five shocks in each of positions X, Y, and Z, in any sequence. This is a destructive test. Tubes subjected to destructive tests shall not be delivered on the contract or order.

8. The tube shall be energized with a duty cycle greater than 90 percent.

9. Group C, life-test sampling plan, and Group C, establishment of prerelease eligibility (MIL-E-1 paragraphs) should be used with the following exceptions:

   (a) Group C life-test sampling plan.

   (1) The first sample size = 3.
   (2) The first cumulative sample size = 3.
   (3) The second sample size = 3.
   (4) The second cumulative sample size = 6.

   (b) Group C, establishment of prerelease eligibility.

   (1) A minimum of 15 tubes shall-------etc.
   (2) Replace all reference to the current 4-tube sample with current 3-tube sample. Replace all reference to the last 16 with the last 15.

   (c) One tube shall have the top numeral cathode glowing steadily. One tube shall have the bottom numeral cathode glowing steadily. One tube shall have the "0" numeral cathode glowing steadily.

10. No glow shall be permitted on any tube part other than the numeral under test.

11. After a quiescent state of two or more weeks, the numerals, if required, shall be given a 90-second warmup prior to checking for full glow.

(B) 12. This test shall be performed during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of one. In the event of failure, the test will be made as a part of quality conformance inspection, part 2, code level D, with an AQL of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 17, 80
DSA - ES


User activities:
Army - MU
Navy - AS, OS, MC, CG
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-3054)

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:50Z
Check the source to verify that this is the current version before use.



PIN CONNECTIONS	
Pin No.	Element
1	k1
2	k2
3	k3
4	k4
5	k5
6	k6
7	k7
8	k8
9	k9
10	k0
11	a

Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
Quality conformance inspection, part 2		
A	- - -	1.175 (29.85)
B	- - -	.650 (16.51)
C	.840 (21.34)	.925 (23.50)
D	- - -	.064 (1.63)
E	.295 (7.49)	.315 (8.00)

FIGURE 1. Outline drawing of electron tube type 7009.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:50Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*.

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:50Z
Check the source to verify that this is the current version before use.