MILITARY SPECIFICATION

INDICATOR, HORIZONTAL SITUATION,
AQU-2/A

This amendment forms a part of MIL-I-26689C(USAF), dated 10 June 1981, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Delete title and first sentence and add: "Government documents."

Add: "2.1.1 Specifications and standards. The following specifications, and standards, form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under SPECIFICATION, Military, delete "MIL-E-5272" and title.

Delete "Add the following boxed paragraph to the bottom center of page."

Delete address on lines 3 and 4 of beneficial comments block and add: "Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990."

Under STANDARDS, Military, add: "MIL-STD-810C Environmental Test Methods" and "MIL-STD-2073-1 DOD Material Procedures For Development And Application of Packaging Requirements."

Add: "2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

American Society For Testing And Materials (ASTM)

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:07Z
Check the source to verify that this is the current version before use.

Add: "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

PAGE 7

3.9.2 Line 4 change to read "It shall be flat and free from discolorations (except as induced by glare reducing coatings), scratches and striae which interfere with the reading of the instrument."

3.9.4.2 Line 3 delete "100" and add: "10."

PAGE 9

3.14.2 Line 3 delete "or" and add: "of".

PAGE 15

3.17.1 Line 10 delete "The course bar mechanism shall have a resistance of 1000 ohm ±3p pins of figure 3 shall cause a deflection on the right when course arrow is on top. The course bar sensitivity shall be 75 ua per dot and range of displacement shall be +2 dots."

PAGE 21

Delete "4.1" entirety and add:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Add: "4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

4.2.a Add: "(see 4.4)."

4.2.b Add: (see 4.5)."

4.3 Delete "Test conditions." and add: "Inspection conditions. Unless otherwise specified all inspection shall be performed in accordance with the test conditions specified in 4.3.1 of this specification."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:07Z
Check the source to verify that this is the current version before use.

PAGE 24

4.5.2.2,h Delete "spray" and add: "fog".

4.5.2.2,i Delete "Sand and dust" and add: "Dust (fine sand)."

PAGE 25

Under Group II Delete "spray" and add: "fog".

Under Group II Delete "sand and dust" and add: "dust (fine sand)."

PAGE 28

4.6.18 Delete existing paragraph and add: "Vibration error. The indicator shall be mounted, in its normal operating position, on a vibration fixture, and properly connected for operation. While being operated, the indicator shall be vibrated with circular motion in a plane inclined 45 degrees to the horizontal with a total vibration amplitude between 0.003 and 0.005 inches. The frequency of applied vibration shall be varied slowly from 5 to 50 cycles per second. While being vibrated, the indicator shall meet the following requirements."

PAGE 29

4.6.23 Line 1 delete "sample required in 3.26.1" and add: "cover glass and wedge."

4.6.25 Line 3 delete "MIL-E-5272" and add: "MIL-STD-810C."

4.6.25.1 Line 3 delete "procedures II" and add: "Method 501.1 Procedure I."

PAGE 30

4.6.25.2 Delete entire paragraph and add: "Temperature altitude. The indicator shall be subjected to a temperature altitude test in accordance with Method 504.1 of MIL-STD-810C for equipment category 6. There shall be no binding or sticking at any possible indication. After the indicator has returned to room temperature, it shall meet all individual tests. There shall be a 5 minute warm-up after the application of power before data is taken."

4.6.25.3 Line 2 add: "Method 503.1" before "procedure I."

4.6.25.4 Line 2 add: "Method 507.1" before "procedure I."

4.6.25.6 Line 1 delete "salt spray" and add: "salt fog" (2 places).

4.6.25.6 Line 2 add: "Method 509.1" before procedure I."

4.6.25.7 Line 1 delete "sand and dust" and add: "Dust (fine sand)" (2 places).

4.6.25.7 Line 2 add: "Method 510.1" before procedure I."

4.6.25.8 Line 2 delete "procedure V and add: "Method 514.2, procedure I, part 1 curve C and part 2 curve B."

PAGE 32

Delete "4.8" entirely.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:07Z
Check the source to verify that this is the current version before use.

4.8.1 Change title "Quality conformance." to "Inspection of packaging."

Delete "4.8.2" entirely.

Delete Section 5 in its entirety and add:

"5. PACKAGING

5.1 Preservation. Preservation shall be level A, C, or Industrial, IAW MIL-STD-2073-1, as specified (see 6.2)

5.1.1 Level A.

5.1.1.1 Cleaning. Indicator shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.3 Preservation application. Preservative shall not be used.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity unit packs of one each in accordance with Method IC-1 of MIL-P-116. Each indicator shall be placed in a PPP-B-636 Fiberboard container weather resistant, with sufficient cushioning material between bag and unit container of a type, density, and thickness to insure indicator does not exceed peak values in G's established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each indicator shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of indicator shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Indicator packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Indicator packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:07Z
Check the source to verify that this is the current version before use.

5.2.4 Industrial. The packaged indicator shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

Custodian:
AIR FORCE -99

Preparing activity:
AIR FORCE -71

Review Activity:
AIR FORCE -11

Project number:
6610-F208

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:07Z
Check the source to verify that this is the current version before use.