MIL-L-26598A(USAF)
11 May 1959
Superseding
MIL-L-26598 (USAF)
17 February 1959

MILITARY SPECIFICATION

LANTERN, ELECTRIC LEU-2/E

1. SCOPE

1.1 This specification covers one type of electric lantern designated LEU-2/E.

1.2 Lanterns shall be of the following classes as specified (see 6.2):

Class 1 - Spread-beam lens for flood illumination
Class 2 - Clear lens for spot illumination.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

Federal

QQ-P-416	Plating, Cadmium (Electrodeposited)
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-585	Boxes, Wood, Wirebound
PPP-B-591	Boxes, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Boxes, Fiber
PPP-B-665	Boxes: Paperboard, Metal Stayed (Including Stay Material)
PPP-B-676	Boxes, Set-Up, Paperboard
PPP-T-60	Tape, Pressure Sensitive Adhesive, Waterproof - For Packaging and Sealing

Military

MIL-B-18	Batteries, Dry
JAN-P-100	Packaging and Packing For Overseas Shipment, General Specification
MIL-P-116	Preservation, Methods of
MIL-B-138	Boxes, Wood, Fiberboard-Lined For Overseas Shipment (For Weight Contents Not Exceeding 500 Pounds)

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 20261O-20T09:59Z
Check the source to verify that this is the current version before use.

MIL-D-5028	Drawings and Data Lists; Preparation Of Manufacturers' (For Production Aeronautical and Associated Equipment)
MIL-E-5272	Environmental Testing, Aeronautical and Associated Equipment, General Specification For
MIL-C-5541	Chemical Films For Aluminum And Aluminum Alloys
MIL-J-5624	Jet Fuel, Grades JP-3, JP-4, and JP-5
MIL-A-8625	Anodic Coatings, For Aluminum and Aluminum Alloys
MIL-B-10377	Box, Wood, Cleated, Veneer, Paper Overlaid
MIL-L-10547	Liners, Case, Waterproof

STANDARDS

Federal

595	Colors

Military

MIL-STD-129	Marking For Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property
MS35058	Switches, Toggle, Single Pole, One-Hole Mounting (Sealed Toggle Bushing)

PUBLICATION

Air Force-Navy Aeronautical Bulletin

143	Specifications and Standards; Use of

Air Force Bulletin

F49	Codes for Ground Equipment in Finishing Schemes

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 PREPRODUCTION.- This specification makes provisions for preproduction testing.

Source: https://assist.dla.mil -- Downloaded: 20260-20T09:59Z
Check the source to verify that this is the current version before use.

3.2 COMPONENTS.- The lantern shall consist of:

Item No.	Quantity	Description	Class Component Use With	See Requirement
1	1	Battery case	1 and 2	3.7
2	1	Handle	1 and 2	3.8
3	1	Reflector head		
		With spread lens	1	3.9
		With clear lens	2	3.9
4	1	Switch	1 and 2	3.10
5	1	Mounting bracket	2	3.11

3.3 SELECTION OF SPECIFICATIONS AND STANDARDS.- Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with Bulletin 143 except as provided in 3.3.1 and 3.3.2.

3.3.1 COMMERCIAL PARTS.- Commercial parts having suitable properties may be used where, on the date of invitation for bids, there are no suitable standard parts. In any case, commercial utility parts, such as screws, bolts, nuts, and cotter pins, having suitable properties may be used provided:

a. They can be replaced by the standard parts (MS or AN) without alteration

b. The corresponding standard part numbers are referenced in the parts list and, if practical, on the contractor's drawings.

3.3.2 STANDARD PARTS.- With the exception in 3.3.1, MS and AN standard parts shall be used where they suit the purpose. They shall be identified on the drawings by their part numbers.

3.4 MATERIALS

3.4.1 FUNGUS-PROOF MATERIALS.- Materials that are nutrients for fungi shall not be used where it is practical to avoid them. When used and not hermetically sealed, they shall be treated with a fungicidal agent acceptable to the procuring activity.

3.4.2 NONFERROUS MATERIALS.- All materials used in the external construction of the lantern shall be nonferrous. This shall include all parts of the case, handle, reflector head, and all bolts, rivets, screws or other fasteners.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T09:59Z
Check the source to verify that this is the current version before use.

3.5 DESIGN AND CONSTRUCTION.- The lantern shall be designed and constructed so that no parts will work loose in service. It shall be built to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, and service.

3.5.1 MAINTENANCE.- The lantern shall be so constructed that adjustment and repairs (including replacement of lamp and batteries) can be easily made by the personnel of operating units, with tools normally available commercially.

3.5.2 LANTERNS OF DIFFERENT CONSTRUCTION.- Lanterns of slightly different construction will be considered acceptable providing all requirements specified herein are met and the design is approved by the procuring activity.

3.5.3 WIRING.- In so far as practicable, wiring designed to carry current from the batteries to the reflector head shall be adequately insulated and enclosed. Flexible cable utilized to permit positioning of the reflector head shall be shielded to prevent accidental damage to the insulation. The cable shall be provided with strain relief terminals inside the battery case and inside the reflector head.

3.5.4 RELIABILITY.- The lantern shall be so designed as to provide reliable operation throughout its normal life under conditions as specified herein.

3.6 PERFORMANCE.- The lantern shall operate satisfactorily under the following conditions:

a. Ambient temperatures ranging from 32° to 120° F

b. Relative humidity of 95 percent

c. In an explosive vapor within or surrounding the equipment

d. Rough handling as anticipated in service use.

3.6.1 FUEL AND WATER RESISTANCE.- After the lantern has been used extensively in the presence of water and fuel vapors, its components shall not swell, its adhesives shall not dissolve, and other deterioration that would affect the ability of the lantern to comply with other requirements of the specification shall not be evident.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T09:59Z
Check the source to verify that this is the current version before use.

3.6.2 ILLUMINATION.- Illumination design goals shall be as specified in table I.

TABLE I. ILLUMINATION REQUIREMENTS

Class	Beam Width	Minimum Candlepower
1	8°	320
1	35°	32
2	1°	6,000
2	4°	2,000

3.7 BATTERY CASE.- The battery case shall provide a convenient enclosure for the batteries. The battery case shall be accessible without the use of special tools. The case, in general, shall provide a mounting base for the lantern and shall provide support for the reflector assembly.

3.8 HANDLE.- A handle shall be provided for the lantern. It shall be affixed to the top of the assembly in such a way as to facilitate carrying and positioning of the lantern. The handle shall not interfere with operation of the switch, vertical positioning of the lamp head, or access to the battery housing. The handle shall be covered with a vinyl plastic sheath to insulate it against heat or cold.

3.9 REFLECTOR HEAD.- The reflector head shall be so adjustable that the beam may be maintained in any position from 20° below to 45° above the horizontal plane. The following components shall be included:

a. A corrosion-resistant reflector and socket with spring-supported center contact

b. A shatter-resistant plastic lens. For class 1 lanterns, the lens may be formed or treated so as to obtain the illumination specified in table I. For class 2 lanterns, the lens shall be transparent.

c. A metal guard located so as not to interfere with the light distribution shall protect the lens from breaking

d. An ASA No. 157 lamp

e. A retaining device to hold the lamp in position by exerting force on the glass envelope of the lamp in such a way as to compress the spring that supports the center socket contact.

Source: https://assist.dla.mil -- Downloaded: 202610-20T09:59Z
Check the source to verify that this is the currentversion before use.

3.10 SWITCH.- An explosion-proof switch conforming to MS35058 or an equivalent commercial switch shall be provided with the lantern.

3.11 MOUNTING BRACKET (CLASS 2).- A quick-release bracket shall be provided to hold securely the lantern when it is mounted either on a horizontal or vertical surface. The bracket shall withstand the shock and vibration encountered in normal service of emergency vehicles without being jammed and without accidently releasing the lantern. The design of the device shall be approved by the procuring activity.

3.12 BATTERIES.- The lantern shall accommodate three BA-200/U batteries conforming to MIL-B-18. The lantern also shall be able to accommodate three rechargeable batteries that are each interchangeable with the BA-200/U dry battery. Unless so specified by the procuring activity, batteries shall not be furnished with the lantern.

3.13 INTERCHANGEABILITY.- All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The drawing number requirements of MIL-D-5028 shall govern changes in the manufacturer's part numbers.

3.14 WEIGHT.- The weight of the lantern, without batteries, shall not exceed 4-1/2 pounds.

3.15 FINISHES AND PROTECTIVE COATINGS

3.15.1 ALUMINUM-ALLOY PARTS.- Aluminum-alloy parts shall be covered with an anodic film conforming to MIL-A-8625, except as follows:

a. Small holes need not be anodized

b. Aluminum alloys that do not anodize satisfactorily shall be coated with a chemical film conforming to MIL-C-5541

c. Where the primary purpose of the treatment is to afford a suitable paint base, chemical treatments conforming to MIL-C-5541 may be used in lieu of anodizing

d. Castings containing no aluminum-alloy integral inserts may be treated with a chemical film conforming to MIL-C-5541

e. When abrasion resistance is a factor, chemical films conforming to MIL-C-5541 shall be used in lieu of anodizing.

Source: https://assist.dla.mil -- Downloaded: 202640-20T09:59Z
Check the source to verify that this is the currenversion before use.

3.15.2 Except for latches, lens guard, lens retainer, or other incidental parts that are suitably anodized, the exterior of the lantern shall be finished in accordance with Bulletin F49, code F49A-4. The color shall be red, color 11136, conforming to Standard 595.

3.15.3 STEEL PARTS.- Where practicable, steel parts shall be cadmium plated in accordance with QQ-P-416, type II or III, and of a class that is adequate to achieve the degree of protection required.

3.16 OPERATION MARKINGS.- Instruction plates containing operating instructions such as ON, OFF, et cetera, shall be permanently affixed to the lantern. The lettering shall be clearly legible and permanently marked. Where practicable, a diagram showing the proper method for inserting the batteries shall be permanently attached to the interior of the housing or other surface. The diagram shall be legible and protected against destruction.

3.17 IDENTIFICATION OF PRODUCT.- Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130, except that serial numbers are not required.

3.18 WORKMANSHIP.- The lantern, including all parts and accessories, shall be fabricated in a thorough and workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies, thoroughness of soldering, welding, brazing, painting, wiring, and riveting; alignment of parts and tightness of assembly screws and bolts; et cetera.

3.19 RIVETING.- Riveting operations shall be carefully performed to insure that the rivets are tight and satisfactorily headed.

3.20 CLEANING.- The lantern shall be thoroughly cleaned. Excess solder, metal chips, and other foreign material shall be removed during and after final assembly.

3.21 HAZARDOUS LOCATIONS.- The lantern shall conform to the Underwriters' Laboratories, Inc., standards for operation in class I, group D, hazardous locations.

Source: https://assist.dla.mil -- Downloaded: 202610-20T09:59Z
Check the source to verify that this is the current version before use.

3.22 WARNING PLATE.- Each lantern shall have the following information molded into it or provided on a plate securely attached in a convenient and conspicuous location:

C A U T I O N

Do not disassemble lantern for repairs or for replacement of lamps or batteries in areas where explosive vapors are present.

4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified herein, the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 CLASSIFICATION OF TESTS.- The inspection and testing of the lantern shall be classified as follows:

a. Acceptance tests	see 4.3
b. Preproduction testing	see 4.6.

4.3 ACCEPTANCE TESTS.- Acceptance tests shall consist of the individual test.

4.3.1 INDIVIDUAL TESTS.- Each lantern shall be subjected to the following tests, as described under 4.5:

a. Examination of product

b. Operation.

4.4 TEST CONDITIONS

4.4.1 ATMOSPHERIC CONDITIONS.- Unless otherwise specified, the tests shall be made at an atmospheric pressure of approximately 29.92 inches Hg and at room temperature of approximately 25° C. Where tests are made with atmospheric pressure or temperature differing materially from these values, proper allowance shall be made for the difference from the specified condition.

4.4.2 TEST SPECIMEN.- The test specimen shall be equipped with lamp and batteries.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

4.5 TEST METHODS

4.5.1 EXAMINATION OF PRODUCT.- The lantern shall be inspected to determine compliance with the requirements specified herein with respect to materials, workmanship, and marking.

4.5.2 OPERATION.- The lantern, with lamp and batteries installed, shall be turned on. Illumination of the lamp shall be satisfactory evidence of compliance with this requirement.

4.5.3 ENVIRONMENTAL TESTS.- The lantern shall be subjected to the following tests in accordance with the specified procedures of MIL-E-5272.

4.5.3.1 LOW TEMPERATURE.- The lantern shall be subjected to the low temperature test in accordance with procedure I, except that the lantern shall be placed in an ambient temperature of 32° ± 2° F for a period of 4 hours.

4.5.3.2 HUMIDITY.- The lantern, with batteries installed, shall be subjected to humidity in accordance with procedure III, except that the test conditions shall be maintained for an 80-hour period. At the conclusion of this test, the assembly shall operate satisfactorily and no parts of the assembly shall show damage as a result of the test. The lamp shall not be turned on during the soak period, but it shall be turned on at the end of the test to check proper operation.

4.5.3.3 EXPLOSION PROOF.- The lantern shall be subjected to an explosion-proof test in accordance with procedure I, except that the test shall be conducted only at a pressure simulating an altitude of 5,000 feet. The switch shall be operated 50 times. The highest ambient temperature maintained shall be 125° F.

4.5.4 DROP TEST.- The lantern, with batteries installed, shall be allowed to drop in free fall to a concrete surface from a height of 3 feet. The lantern shall be dropped three times. The point of initial contact in each drop shall be the lens or as nearly thereto as construction of the lantern will permit.

4.5.5 FUEL RESISTANCE.- The lantern, assembled and without batteries, shall be immersed in JP-4 fuel conforming to MIL-J-5624 for 24 hours at a temperature of 77° ± 5° F. The lantern shall be removed from the test fluid and allowed to drain for 1 hour at room temperature. There shall be no swelling of seals, gaskets, or of similar components; there shall be no separation of components, dissolving of adhesives, nor other deterioration that would cause the lantern to fail during subsequent tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

4.5.6 WATER RESISTANCE.- The lantern, assembled and with batteries installed, shall be immersed in water for a period of 30 minutes at a temperature of 77° ± 5° F. The lantern shall then be removed from the water and checked immediately for proper operation. Upon completion of the operational test, the lantern shall again be immersed in the water. After a 24-hour immersion period, the lantern shall be removed and allowed to drain for 1 hour at room temperature. There shall be no swelling of seals, gaskets, or of similar components; there shall be no separation of components, dissolving of adhesives, or other deterioration that would cause the lantern to fail during subsequent tests.

4.5.7 ILLUMINATION (PHOTOMETRIC).- The lantern shall be subjected to a photometric test to determine compliance with the light distribution specified in 3.6.2. During the test, the lamp shall be operated at the design voltage from a regulated external power source. The test shall be made to determine the candlepower distribution in an initial plane (selected at random) that contains the focal axis of the light. Tests shall then be made successively to obtain the light distribution in planes that contain the focal axis and that intersect the initial plane at angles of 30°, 60°, 90°, 120°, and 150°.

4.6 PREPRODUCTION TESTING

4.6.1 PREPRODUCTION TEST SAMPLES.- Test samples shall consist of two lanterns representative of the production. They shall be tested in a laboratory designated by the procuring activity or, when so stated in the contract, at the contractor's plant under the supervision of the procuring activity.

4.6.2 PREPRODUCTION TESTS.- Preproduction tests shall consist of all tests described under 4.5 and shall be tested in the order shown in table II. If the sample is furnished with proof that it conforms to Underwriters' Laboratories, Inc., standards as suitable for use in class 1, group D, hazardous locations, the explosion-proof and drop tests need not be conducted.

TABLE II. PREPRODUCTION TEST SEQUENCE

Test Sequence Sample No. 1	Test Sequence Sample No. 2
Examination Illumination	Examination Drop test Humidity Fuel resistance Water resistance Explosion proof

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

4.7 INSPECTION OF THE PRESERVATION, PACKAGING, AND PACKING.- The inspection of the preservation, packaging, and packing shall be in accordance with the instructions in section 5, or the specifications referenced therein.

5. PREPARATION FOR DELIVERY

5.1 PRESERVATION AND PACKAGING

5.1.1 LEVEL A.- The lanterns shall be preserved in accordance with MIL-P-116, method II, and packaged in containers conforming to PPP-B-566, PPP-B-636, PPP-B-665, or PPP-B-676. For domestic shipment, containers conforming to PPP-B-636 may be used. Unit quantities shall be as specified by the procuring activity.

5.1.2 LEVEL C.- The lanterns shall be preserved and packaged in accordance with the manufacturer's commercial practice.

5.2 PACKING

5.2.1 LEVEL A.- Lanterns preserved and packaged to meet 5.1.1 shall be packed in exterior-type shipping containers conforming to PPP-B-585, PPP-B-591, PPP-B-601, PPP-B-621, PPP-B-636, type I, class 3, or type II, class 3, MIL-B-138, or MIL-B-10377. In so far as practicable, exterior containers shall be of uniform shape and size, be of minimum cube and tare consistent with the protection required, and contain identical quantities. The gross weight of each pack shall be limited to approximately 200 pounds. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto. Containers shall be provided with a case liner conforming to MIL-L-10547 and shall be sealed in accordance with the appendix thereto. The case liner will not be required when the unit, intermediate, or exterior container conforms to PPP-B-636, type I, class 3, or type II, class 3, and is sealed at all joints and seams, including the manufacturer's joint, with tape conforming to PPP-T-60.

5.2.2 LEVEL B.- Lanterns preserved and packaged to meet 5.1.1 shall be packed in domestic-type exterior containers conforming to PPP-B-585, PPP-B-591, PPP-B-601, PPP-B-621, PPP-B-636, or MIL-B-10377. Exterior containers shall be of minimum cube and tare consistent with the protection required. Insofar as practicable, exterior containers shall be of uniform shape and size and contain identical quantities. The gross weight of each pack shall be limited to approximately 500 pounds. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto. When fiberboard containers are used, the fiberboard shall meet the special requirements table of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

5.2.3 LEVEL C.- Packages which require overpacking for acceptance by the carrier shall be packed in exterior-type shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall meet Consolidated Freight Classification rules or regulations of other common carriers as applicable to the mode of transportation.

5.3 PHYSICAL PROTECTION.- Cushioning, blocking, bracing, and bolting as required shall be in accordance with JAN-P-100, except that for domestic shipments waterproofing requirements for cushioning materials and containers shall be waived. The drop tests of JAN-P-100 shall be waived when preservation, packaging, and packing of the item are for immediate use or when drop tests of MIL-P-116 are applicable.

5.4 MARKING.- Interior and exterior containers shall be marked in accordance with MIL-STD-129. The nomenclature shall be:

Lantern, Electric LEU-2/E, Class___ (insert class 1 or 2, as applicable).

6. NOTES

6.1 INTENDED USE.- The LEU-2/E electric lantern is intended for use as follows:

a. For class 1, as a portable work light for use in repair and maintenance of aircraft fuel cells

b. For class 2, as a portable utility spotlight for use on fire trucks or similar emergency vehicles.

6.2 ORDERING DATA.- Procurement documents should specify the following:

a. Title, number, and date of specification

b. Whether class 1 lanterns, class 2 lanterns, or some of each type are to be furnished

c. Whether batteries are to be supplied (see 3.12)

d. Unit quantities required (see 5.1.1)

e. The number of preproduction samples and the point of inspection

f. Levels of preservation and packaging and packing desired (see section 5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

6.3 HAZARDS GUARANTEE.- The bidder will submit proof to the procuring activity that the lantern which he proposes to supply under this specification conforms to the standards of the Underwriters' Laboratories, Inc. The label or listing of Underwriters' Laboratories, Inc., will be accepted as evidence of conforming to the explosion proof and drop test requirements.

6.3.1 In lieu of the label or listing, the bidder may submit independent proof satisfactory to the procuring activity that the lantern conforms to the published standards, including methods of tests, of Underwriters' Laboratories, Inc., for class 1, group D, hazardous locations. Compliance with the fire and casualty hazard requirements does not absolve the bidder from complete compliance with the other requirements of this specification.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

PWK/MLB/mt
WCLE

Source: https://assist.dla.mil -- Downloaded: 20240-20T09:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AFLC CASO/LODS
Federal Center
Battle Creek, MI 49016

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-20T09:59Z
Check the source to verify that this is the current version before use.