MIL-L-26598A(USAF)
AMENDMENT 4
4 August 1978

SUPERSEDING
AMENDMENT 3
1 April 1968

MILITARY SPECIFICATION

LANTERN, ELECTRIC LEU-2/E

This amendment forms a part of Military Specification MIL-L-26598A(USAF), dated 11 May 1959, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: Under SPECIFICATIONS, Federal add:

"TT-E-489 Enamel Alkyd, Gloss, (For Exterior And Interior Surfaces)"

PAGE 2

2.1: Under SPECIFICATIONS, Military add:

"MIL-P-8585 Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity"

2.1: Under STANDARDS delete:

"Federal

595 Colors"

2.1: Under PUBLICATION, Air Force-Navy Aeronautical Bulletin add:

"166 Colors, List of Standard Aircraft Glossy"

2.1: Under PUBLICATION delete:

"Air Force Bulletin

F49 Codes for Ground Equipment in Finishing Schemes"

Following 2.1, add:

"2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNDERWRITERS' LABORATORIES, INCORPORATED

Methods of Tests Class 1, Group D, Hazardous Locations

(Application for copies should be addressed to the Underwriters' laboratories, Inc., 161 Sixth Avenue, New York, NY 10003; 207 East Ohio Street, Chicago IL 60611; or 1655 Scott Lane, Santa Clara CA 95050.)"

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 20260-20T09:59Z
Check the source to verify that this is the current version before use.

3.1, line 2: Following the word "testing" add "on new and unapproved items only."

After 3.1 add: "3.1.1 General requirements. The requirements of Underwriters' Laboratories, Inc., for Class 1, Group D, hazardous locations shall apply."

PAGE 4

3.5.2: Delete and substitute:

"3.5.2 Lanterns of varying construction. Lanterns of varying construction and housings and brackets of plastic will be acceptable provided all of the requirements of this specification are complied with."

PAGE 5

TABLE I: Delete and substitute:

TABLE I. Illumination requirements.

Class	Beam Width	Minimum Candlepower
1	10°	80
1	16°	40
2	0.5°	5,000
2	3°	1,000

After TABLE I, add 3.6.3 and 3.6.4:

"3.6.3 Operating life. The operating life of the lantern shall be as follows:

a. Eight hours of continuous operation without undue heating.

b. After eight hours of continuous operation, the lantern shall give an illumination of at least 25 percent of its design illumination.

3.6.4 Hazardous locations. The lamp shall conform to Underwriters' Laboratories, Inc. for operation in Class 1, Group D hazardous locations. (See 6.3)"

PAGE 5

3.9d: Delete and substitute:

"d. A lamp that is compatible with illumination design goals (3.6.2) and satisfactory for use in hazardous locations (3.2.1)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:59Z
Check the source to verify that this is the current version before use.

PAGE 6

3.12, lines 1 and 3: Delete the word "three."

3.14, line 2: Delete "4-1/2" and substitute "6-1/4."

PAGE 7

3.15.2: Delete and substitute:

"3.15.2 Except for latches, lens guard, lens retainer or other incidental parts that are anodized metal, all portions of the exterior of the lantern shall be finished with one coat of zinc-chromate primer in accordance with MIL-P-8585 followed by two coats of enamel conforming to TT-E-489. The color shall be insignia red, color 509, conforming to Bulletin 166."

3.17: Add: "Each lantern shall bear the label of the Underwirters' Laboratories, Inc. for use in Class 1, Group D, hazardous locations."

3.21: Delete in its entirety.

PAGE 9

4.5.3.3: Delete in its entirety.

4.5.4: Delete in its entirety.

PAGE 10

4.5.7, last two sentences: Delete and substitute:

"Tests shall be made to determine the candlepower distribution in an initial plane (selected at random) that passes through the peak of the beam, and the candlepower distribution in a plane which intersects the initial plane at an angle of 90°."

4.6.2: Delete and substitute:

"4.6.2 Preproduction tests. Preproduction tests shall consist of all tests described under 4.5."

TABLE II: Delete in its entirety.

PAGE 11

4.7: Delete and substitute:

"4.7 Inspection of the preservation, packaging, packing and marking for shipment and storage. Sample items or packs and the inspection of the preservation, packaging, packing and marking for shipment and storage shall be in accordance with the requirements of Section 5, or the documents specified therein."

Source: https://assist.dla.mil -- Downloaded: 202640-20T09:59Z
Check the source to verify that this is the currentversion before use.

* 6.3: Delete and substitute:

"6.3 Certification of conformance. A certificate of conformance shall be furnished SA-ALC/MMEDO, Kelly AFB TX 78241, and will certify that the light has been tested and has been approved by the Underwriters' Laboratories, Inc. for use in Class 1, Group D, hazardous locations. On new and unapproved items, this approval shall be obtained before preproduction tests are performed."

* 6.3.1: Delete in its entirety.

After 6.3 add: "6.4 Reclaimed materiels. The use of reclaimed materiels shall be encouraged to the maximum extent possible."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

* Concluding material: Delete and substitute as follows:

Custodian:
Air Force - 99

Preparing activity:
Air Force - 99

(Project 6230-F207)

Source: https://assist.dla.mil -- Downloaded: 202640-20T09:59Z
Check the source to verify that this is the currentversion before use.