INCH-POUND

MIL-T-26639C
AMENDMENT 4
17 November 1989
SUPERSEDING
AMENDMENT 3
17 May 1984

MILITARY SPECIFICATION

TESTER, TORQUE WRENCH

This amendment forms a part of MIL-T-26639C, dated 14 March 1969, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Change "TESTERS" to "TESTER" in title of MIL-T-26639C.

Add the following DD Form 1426 note to bottom of page 1:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Support Division, San Antonio ALC/MMDEMM, Kelly AFB TX 78241-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

2.1: Delete MIL-D-1000 and substitute DOD-D-1000.
Delete MIL-H-4034.
Delete MIL-E-4970 and substitute MIL-STD-810.
Delete MIL-H-26497 and substitute MIL-W-26497.

PAGE 3

* Delete MIL-STD-167 and substitute MIL-STD-167/1 and MIL-STD-167/2.

PAGE 4

3.5, third line: Delete MIL-H-4034. Delete MIL-H-26497 and substitute MIL-W-26497.

3.5.1, second line: Delete MIL-H-4034.

3.6.3, last line: Delete "or Type I of MIL-H-4034."

AMSC N/A FSC 6635

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:05Z
Check the source to verify that this is the current version before use..

3.9.1: Delete second sentence and substitute "The space between graduations shall not be less than 0.020 inch."

PAGE 8

3.12: Delete MIL-D-1000 and substitute DOD-D-1000.

PAGE 9

* 3.17, last sentence: Delete MIL-H-4034 and delete MIL-H-26497 and substitute with MIL-W-26497.

PAGE 13

* 4.6.3.1: Delete and substitute:

"4.6.3.1 Low temperature operation and storage. The tester shall be subjected to low temperature in accordance with MIL-STD-810, Method 502.2, Procedures I and II, modified as follows:

a. Procedure I, step 2. Adjust the chamber temperature to -80° F (-62° C).

b. Procedure I, step 3. Maintain the test item -80° F for 48 hours.

c. Procedure I, step 4. Conduct a visual examination of the test item for conformance with 3.9.1.

d. Procedure I, step 5. Proceed to Procedure II.

e. Procedure II, step 1. The low operating temperature is 32° F (0° C).

f. Procedure II, step 4. Conduct an operational checkout of the test item for compliance with 4.6.1 and 4.6.2.

g. Procedure II, step 6. Proceed to step 7.

h. Procedure II, step 8. Conduct a complete visual examination of the test item for compliance with 3.9.1.

i. Procedure II, step 10. Conduct an operational checkout of the test item for compliance with 4.6.1 and 4.6.2."

* 4.6.3.2: Delete and substitute.

"4.6.3.2 High temperature operation and storage. The tester shall be subjected to high temperature in accordance with MIL-STD-810, Method 501.2, Procedures I and II, modified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:05Z
Check the source to verify that this is the current version before use.

a. Procedure I, step 4. Expose the test item to 160° F (71° C) for a total of 48 hours.

b. Procedure I, step 5. At the end of the 48 hours exposure of high temperature, adjust the chamber air temperature to control ambient conditions and allow the unit to stabilize at this temperature.

c. Procedure I, step 6. Conduct a complete visual examination and an operational checkout of the test item for compliance with 3.9.1, 4.6.1 and 4.6.2.

d. Procedure II, step 2. The operational temperature is 120° F (49° C). Proceed to step 7 for constant temperature exposure.

e. Procedure II, step 10. Operate the test item until temperature stabilization of the test item has been achieved. Conduct an operational checkout of the test item for compliance with 4.6.1 and 4.6.2.

f. Procedure II, step 16. Conduct a complete visual examination and an operational checkout of the test item for compliance with 3.9.1, 4.6.1 and 4.6.2."

4.6.6: Delete MIL-H-4034 and substitute GGG-W-686.

PAGE 15

6.3a, b, c, d and e: Delete and substitute:

a. Type I, size 6 replaces size 3 of MIL-T-26639B.

b. Type I, size 7 replaces testers previously covered in MIL-T-26210.

c. Type IA, size 1 replaces testers previously covered in MIL-T-26556.

d. Type I, size 5 replaces size 1 of MIL-T-26639B.

e. Type IA, size 3 replaces size 2 of MIL-T-26639B.

* 6.4: NOTE:

"The margins of this amendment are marked with an asterick or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:05Z
Check the source to verify that this is the current version before use.

Custodians:
Army - GL
Navy - AS
Air Force - 99

Review activity:
Army - AV

User activities:
Army - CE
Navy - MC, OS

Preparing activity:
Air Force - 82

(Project 6635-0136)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:05Z
Check the source to verify that this is the current version before use.