MILITARY SPECIFICATION SHEET

(B) CABLE ASSEMBLY, RADIO FREQUENCY (AIRCRAFT AUDIO), CX-13017/AR

This specification sheet is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the cable described herein shall consist of this document and the latest issue of specification MIL-C-22442.




FIGURE 1 CABLE ASSEMBLY CX-13017/AR

TABLE I

DIMENSION A	PART NUMBER	WEIGHT MAX
2 FT -4 IN MIN	M22442/24-1	2 OUNCES
2FT - 8 IN "	M22442/24-2	2 "
3FT - 4 IN "	M22442/24-3	3 "
7FT - 0 IN "	M22442/24-4	4 "




FIGURE 2 CABLE ASSEMBLY CX-13017/AR
SCHEMATIC DIAGRAM

AMSC N/A FSC 5995

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:28Z
Check the source to verify that this is the current version before use.

APPLICABLE DOCUMENTS:

MIL-C-10392	Cord Electrical (Audio, Miniature)
MIL-J-641/22	Jacks, Telephone, General Specification for
MIL-P-642/14	Plugs, Telephone, and Accessory Screws, General Specification for

REQUIREMENTS:

1. The cable (cord) shall be in accordance with MIL-C-10392 Type WM-59A/U.

2. The weight of the cable assembly shall be in accordance with Table I.

3. The stay cord shall be firmly attached to the connectors.

(B) 4. The DC resistance shall be less than 2 ohms between the following contacts when tested with a suitable ohmmeter.

   (a) Contact 5 of P/N M641/22-01 (U-385/U) and contact 5 of P/N M642/14-01 (U-384/U).

   (b) Contact 4 of P/N M641/22-01 (U-385/U) and contact 4 of P/N M642/14-01 (U-384/U).

   (c) Contact 3 of P/N M641/22-01 (U-385/U) and contact 3 of P/N M641/14-01 (U-384/U).

   (d) Contact 2 of P/N M641/22-01 (U-385/U) and contact 2 of P/N M641/14-01 (U-384/U).

   (e) Contact 1 of P/N M641/22-01 (U-385/U) and contact 1 of P/N M641/14-01 (U-384/U).

5. The cable assembly shall be tested in accordance with the tests listed in Table II.

NOTES:

1. All dimensions are in inches.

2. Tolerances are metal parts $\pm$.005, molded sections $\pm$.05 inches unless otherwise specified.

3. MIL-C-81866 is superseded by MIL-C-22442/24.

Preparing Activity:
Navy - AS
Project No. 5995-N120-11

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:28Z
Check the source to verify that this is the current version before use.

(B) TABLE II.

Inspection	Requirement Paragraph	Test Paragraph	Group I Qualification Tests	Group II Quality Conformance Test 100%	Group III Sample Testing Per 4.5.1
GROUP A (ALL SAMPLE UNITS) 1/					
Visual & Mechanical Inspection	3.1 & 3.4	4.6.2	X	X	
Soldering	3.4.24	4.6.2.1	X	X	
Continuity	3.5.3	4.6.5	X	X	
GROUP B					
Dielectric Withstanding Voltage	3.5.5	4.6.7	X		X
Pull Test 1/	3.5.7	4.6.9	X		X
GROUP C					
Durability 1/	3.5.13	4.6.15	X		X
Ozone Resistance 1/	3.5.14	4.6.16	X		X
Jacket Elongation	3.5.15	4.6.17	X		X
GROUP D 1/					
Temperature-Altitude 2/	3.6.1	4.7	X		
Salt Fog	3.6.2	4.7	X		
Shock	3.6.6	4.7	X		
Humidity	3.6.6	4.7	X		
Thermal Shock	3.6.6	4.7	X		

1/ Minimum tests for QPL retention (see paragraph 4.4.4).
2/ Steps 3 and 12 only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:28Z
Check the source to verify that this is the current version before use.