INCH-POUND
MIL-DTL-22442/29B(AS)
5 January 1998
SUPERSEDING
MIL-C-22442/29A(AS)
2 September 1988

DETAIL SPECIFICATION SHEET

CABLE ASSEMBLY, RADIO FREQUENCY AIRCRAFT AUDIO, CX-13154/A

This specification sheet is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-22442 listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation



FIGURE l. Cable assembly CX-13154/A P/N M22442/29-1.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:31Z
Check the source to verify that this is the current version before use.



FIGURE 2. Cable assembly CX-13154/A schematic diagram P/N M22442/29-1.

APPLICABLE DOCUMENTS:

MIL-C-55668 - Cord, Electrical, Audio Subminiature (Retractile and Straight)

MIL-C-l0392 - Cord, Electrical (Audio, Miniature)

APPLICABLE DRAWINGS:

AIR FORCE

57Bl662 - Connector, Plug Electrical U-l72/U

57Bl664 - Tip - Electrical, Plug Connector

REQUIREMENTS:

*1. The cable (cord) shall be in accordance with the requirements of MIL-C-10392 Type WM-27A/U, or MIL-C-55668 Type III 2 conductor or equal

2. The stay cord shall be firmly attached to the connectors.

3. The DC resistance shall be less than 2 ohms between the following contacts:

(a) Contact l of U-l79A/U and contact l of U-l73/U.

(b) Contact 2 of U-l79A/U and contact 2 of U-l73/U.

4. The cable assembly shall be tested in accordance with the tests listed in Table I.

5. The weight of the cable assembly shall not be greater than l ounce.

6. The U-173/U connector shall be made in accordance with Air Force drawings 57Bl662 and 57Bl664.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:31Z
Check the source to verify that this is the current version before use.

NOTES:

l. All dimensions are in inches.

2. Tolerances are metal parts ±.005, molded sections ±.05 inches unless otherwise specified.

3. This specification supersedes Naval Air Systems Command Drawing 765AS380.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing activity:
Navy - AS
(Project No. 5995-0l28-11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:31Z
Check the source to verify that this is the current version before use.

TABLE I. Tests

Inspection	Requirement Paragraph	Test Paragraph	Group I Qualification Tests	Group II Quality Conformance Test 100%	Group III Sample Testing Per 4.4.1
GROUP A (ALL SAMPLE UNITS) 1/					
Visual & Mechanical Inspection	3.1 & 3.4	4.5.2	X	X	
Soldering	3.4.18	4.5.2.1	X	X	
Continuity	3.5.1	4.5.3	X	X	
GROUP B					
Dielectric Withstanding Voltage	3.5.2	4.5.4	X		X
Pull and Twist Test 1/	3.5.4	4.5.6	X		X
GROUP C					
Durability 1/	3.5.7	4.5.9	X		X
Ozone Resistance 1/	3.5.8	4.5.10	X		X
Jacket Elongation	3.5.9	4.5.11	X		X
GROUP D 1/					
Salt Fog	3.6.2	4.6.2	X		
Humidity	3.6.5	4.6.5	X		
Thermal Shock	3.6.5	4.6.6	X		

l/ Minimum tests for QPL retention (see paragraph 4.3.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:31Z
Check the source to verify that this is the current version before use.