MIL-D-36242 A

20 September 1966

SUPERSEDING
MIL-D-36242 (DM)
21 July 1964

MILITARY SPECIFICATION

DISPENSER, DENTAL FLOSS, METAL

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a dental floss dispenser suitable for accommodating two spools of dental floss or flat tape.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-Z-363	Zinc-Base Alloy; Die Castings.
PPP-B-566	Boxes, Folding, Paperboard.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Boxes, Set-up, Paperboard.

Military

MIL-C-3133	Cellular Elastomeric Materials, Fabricated Parts.
MIL-L-10547	Liners, Case, and Sheet Overwrap; Water-Vaporproof or Waterproof, Flexible.

FSC 6520

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:16Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-66	Steel, Chemical Composition and Hardenability.
FED-STD-151	Metals, Test Methods.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

DRAWING

Defense Medical Supply Center

20738 Dispenser, Dental Floss.

(Copies of specifications, standards and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material

3.1.1 Base. The base of the dispenser shall be fabricated of a zinc-base alloy die casting conforming to chemical composition Alloy AG40A of QQ-Z-363, except that the copper content shall be a maximum of 0.1 percent.

3.1.2 Cover plate. The cover plate shall be die-formed and fabricated of AISI 304 corrosion-resisting steel in conformance with chemical composition of Standard No. 66.

3.1.3 Rubber pad. The rubber pad shall be fabricated of black non-skid sponge rubber conforming to MIL-C-3133 for grade SC 41.

3.1.4 Rods. Rods (see 3.2)shall be fabricated of rigid material suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:16Z
Check the source to verify that this is the current version before use.

3.1.5 Adhesive. The adhesive used for cementing the sponge rubber shall be high quality commercial pressure-sensitive cement, suitable for the purpose intended, and shall not separate readily from the metal.

3.2 Style, design, and dimensions. The floss dispenser shall consist of a plated die-cast zinc alloy base, a corrosion-resisting steel cover plate, and a non-skid sponge rubber pad bonded to the base. The dispenser shall be suitable for accommodating two spools of waxed or unwaxed floss or waxed flat tape so that the floss can be withdrawn and cut to desired length in a one hand operation. The cutoff slots shall be sufficiently sharp to provide a clean cut of floss and tape. The dispenser shall conform to Defense Medical Supply Center Drawing No. 20738 for style, design, and dimensions. In addition, two rods, (2 3/4 ± 1/16 inches long by 13/64 ± 1/64 inch in diameter), shall be furnished with each floss dispenser for use with floss or tape, having short core insert or without insert (see 3.1.4).

3.3 Base die-castings. Die castings shall be free from blowholes, porosity, hard spots, shrinkage defects, cracks, and other defects that may affect the structural strength of the designed serviceability of the castings involved. Die castings shall not be repaired in any manner.

3.4 Finish. All exterior surfaces of the base shall be chromium over nickel over copper plated. The cover plate shall have a No. 3 satin commercial stainless steel finish. The rubber pad shall have a smooth, trimmed, flat, non-skid surface. The rods shall have a smooth surface.

3.5 Identification marking. The dispenser shall be permanently and legibly marked with name or registered trademark of the manufacturer. In addition, the following instructions shall also appear:

"DENTAL FLOSS -UNWIND FROM BOTTOM"

All markings and instructions shall be an integral part of the die-cast and shall appear on the top surface of the base.

3.6 Instructions for use. Adequate and accurate instructions for use of the floss dispenser and rods shall be supplied with each unit. Instructions shall include the following minimum requirements:

1. Method of loading spools of tape or floss when dispenser base is secured by screws or bolts to top of, or inside of, a drawer of a dental cabinet.

2. Purpose and use of rods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:16Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Workmansnip shall be first class throughout. Parts shall be free from such defects as rough edges, sink marks, blemishes, cracks or flaking, which may detract from their appearance or impair their serviceability. The parts shall fit with ease.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties).

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105.

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, and as indicated in table I.

Table I. Sampling Criteria

Component	Characteristic	Reqmt.	Test Procedure	Unit of Product	Insp. level	AQL (Percent defective)
Base Cover plate	Chemical analysis	3.1.1 3.1.2	4.4.1 4.4.1	1-Dispenser 1-Dispenser	N.A	N.A.
Dimension		3.2	S.M.I.	1-Dispenser	S2	4.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:16Z
Check the source to verify that this is the current version before use.

4.2.3 Raw materials. Sufficient quantities of each lot of (each) metal used in the construction of the floss dispenser shall be selected for chemical analysis.

4.2.4 Sample Unit. Where feasible, the same sample unit shall be used for the determination of two or more test characteristics.

4.3 Examination. The dispenser components and rods shall be examined to determine compliance with all requirements contained in this specification.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.4.1 Chemical analysis of the metals. In the absence of certificates of quality for the raw material, the samples selected in accordance with 4.2.3 shall be analyzed in conformance with methods 111 or 112 of Test Method Standard No. 151. In case of dispute, method 111 shall be used for referee analysis.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One (1) dispenser, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table II shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table II. Packaging Quantities

Unit package	Intermediate package	Exterior container
1 unit	12 units	36 units

5.1.2.1 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:16Z
Check the source to verify that this is the currentversion before use.

5.1.3 Level A.

5.1.3.1 Unit package. Unit package shall be a carton of appropriate size constructed in accordance with PPP-B-566 or PPP-B-676, except that commercial colors will be acceptable, or PPP-B-636. Closure shall be adequate to prevent spilling of contents under normal handling.

5.1.3.2 Intermediate package. Intermediate package shall be a carton of appropriate size constructed in accordance with PPP-B-636. Closure shall be adequate to prevent spilling of contents under normal handling.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type III, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather-resistant.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.3 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix, and waterproofing shall conform with 30.4, of PPP-B-636.

5.2.1.4 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:16Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall conform to PPP-B-601, table I, using type III, class 1 plywood; or shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 2 use; PPP-B-621, table I; or PPP-B-636, type CF, class domestic and method I closure shall be utilized.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package and each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

Custodians:
Army. - MD
Navy. - BuMed
Air Force. - AFMSC

Preparing activity:
Defense Supply Agency-DM

Review activities:
Army. - MD
Navy. - BuMed
Air Force. - AFMSG

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

CATEGORY M.

Source: https://assist.dla.mil -- Downloaded: 202640-21T08:16Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

MIL-D-36242 A

ORGANIZATION (Of submitter)	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity)	DATE

DD FORM 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:16Z
Check the source to verify that this is the current version before use.